

GNAT Reference Manual

GNAT, The GNU Ada Compiler
For GCC version 4.6.3

(GCC)

Copyright © 1995-2008, Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, with the Front-Cover Texts being “GNAT Reference Manual”, and with no Back-Cover Texts. A copy of the license is included in the section entitled “GNU Free Documentation License”.

About This Guide

This manual contains useful information in writing programs using the GNAT compiler. It includes information on implementation dependent characteristics of GNAT, including all the information required by Annex M of the Ada language standard.

GNAT implements Ada 95 and Ada 2005, and it may also be invoked in Ada 83 compatibility mode. By default, GNAT assumes Ada 2005, but you can override with a compiler switch to explicitly specify the language version. (Please refer to [Section “Compiling Different Versions of Ada” in *GNAT User’s Guide*](#), for details on these switches.) Throughout this manual, references to “Ada” without a year suffix apply to both the Ada 95 and Ada 2005 versions of the language.

Ada is designed to be highly portable. In general, a program will have the same effect even when compiled by different compilers on different platforms. However, since Ada is designed to be used in a wide variety of applications, it also contains a number of system dependent features to be used in interfacing to the external world.

Note: Any program that makes use of implementation-dependent features may be non-portable. You should follow good programming practice and isolate and clearly document any sections of your program that make use of these features in a non-portable manner.

What This Reference Manual Contains

This reference manual contains the following chapters:

- [Chapter 1 \[Implementation Defined Pragmas\]](#), [page 3](#), lists GNAT implementation-dependent pragmas, which can be used to extend and enhance the functionality of the compiler.
- [Chapter 2 \[Implementation Defined Attributes\]](#), [page 57](#), lists GNAT implementation-dependent attributes which can be used to extend and enhance the functionality of the compiler.
- [Chapter 3 \[Implementation Advice\]](#), [page 67](#), provides information on generally desirable behavior which are not requirements that all compilers must follow since it cannot be provided on all systems, or which may be undesirable on some systems.
- [Chapter 4 \[Implementation Defined Characteristics\]](#), [page 91](#), provides a guide to minimizing implementation dependent features.
- [Chapter 5 \[Intrinsic Subprograms\]](#), [page 117](#), describes the intrinsic subprograms implemented by GNAT, and how they can be imported into user application programs.
- [Chapter 6 \[Representation Clauses and Pragmas\]](#), [page 121](#), describes in detail the way that GNAT represents data, and in particular the exact set of representation clauses and pragmas that is accepted.
- [Chapter 7 \[Standard Library Routines\]](#), [page 143](#), provides a listing of packages and a brief description of the functionality that is provided by Ada’s extensive set of standard library routines as implemented by GNAT.
- [Chapter 8 \[The Implementation of Standard I/O\]](#), [page 151](#), details how the GNAT implementation of the input-output facilities.
- [Chapter 9 \[The GNAT Library\]](#), [page 165](#), is a catalog of packages that complement the Ada predefined library.
- [Chapter 10 \[Interfacing to Other Languages\]](#), [page 179](#), describes how programs written in Ada using GNAT can be interfaced to other programming languages.
- [Chapter 11 \[Specialized Needs Annexes\]](#), [page 181](#), describes the GNAT implementation of all of the specialized needs annexes.

- [Chapter 12 \[Implementation of Specific Ada Features\]](#), [page 183](#), discusses issues related to GNAT's implementation of machine code insertions, tasking, and several other features.
- [Chapter 13 \[Implementation of Ada 2012 Features\]](#), [page 191](#), describes the status of the GNAT implementation of the Ada 2012 language standard.
- [Chapter 14 \[Obsolescent Features\]](#), [page 205](#) documents implementation dependent features, including pragmas and attributes, which are considered obsolescent, since there are other preferred ways of achieving the same results. These obsolescent forms are retained for backwards compatibility.

This reference manual assumes a basic familiarity with the Ada 95 language, as described in the International Standard ANSI/ISO/IEC-8652:1995, January 1995. It does not require knowledge of the new features introduced by Ada 2005, (officially known as ISO/IEC 8652:1995 with Technical Corrigendum 1 and Amendment 1). Both reference manuals are included in the GNAT documentation package.

Conventions

Following are examples of the typographical and graphic conventions used in this guide:

- Functions, utility program names, standard names, and classes.
- Option flags
- 'File names', 'button names', and 'field names'.
- Variables, environment variables, and *metasyntactic variables*.
- *Emphasis*.
- [optional information or parameters]
- Examples are described by text
and then shown this way.

Commands that are entered by the user are preceded in this manual by the characters '\$ ' (dollar sign followed by space). If your system uses this sequence as a prompt, then the commands will appear exactly as you see them in the manual. If your system uses some other prompt, then the command will appear with the '\$' replaced by whatever prompt character you are using.

Related Information

See the following documents for further information on GNAT:

- See [Section "About This Guide" in *GNAT User's Guide*](#), which provides information on how to use the GNAT compiler system.
- *Ada 95 Reference Manual*, which contains all reference material for the Ada 95 programming language.
- *Ada 95 Annotated Reference Manual*, which is an annotated version of the Ada 95 standard. The annotations describe detailed aspects of the design decision, and in particular contain useful sections on Ada 83 compatibility.
- *Ada 2005 Reference Manual*, which contains all reference material for the Ada 2005 programming language.
- *Ada 2005 Annotated Reference Manual*, which is an annotated version of the Ada 2005 standard. The annotations describe detailed aspects of the design decision, and in particular contain useful sections on Ada 83 and Ada 95 compatibility.
- *DEC Ada, Technical Overview and Comparison on DIGITAL Platforms*, which contains specific information on compatibility between GNAT and DEC Ada 83 systems.
- *DEC Ada, Language Reference Manual, part number AA-PYZAB-TK* which describes in detail the pragmas and attributes provided by the DEC Ada 83 compiler system.

1 Implementation Defined Pragmas

Ada defines a set of pragmas that can be used to supply additional information to the compiler. These language defined pragmas are implemented in GNAT and work as described in the Ada Reference Manual.

In addition, Ada allows implementations to define additional pragmas whose meaning is defined by the implementation. GNAT provides a number of these implementation-defined pragmas, which can be used to extend and enhance the functionality of the compiler. This section of the GNAT Reference Manual describes these additional pragmas.

Note that any program using these pragmas might not be portable to other compilers (although GNAT implements this set of pragmas on all platforms). Therefore if portability to other compilers is an important consideration, the use of these pragmas should be minimized.

Pragma Abort_Defer

Syntax:

```
pragma Abort_Defer;
```

This pragma must appear at the start of the statement sequence of a handled sequence of statements (right after the **begin**). It has the effect of deferring aborts for the sequence of statements (but not for the declarations or handlers, if any, associated with this statement sequence).

Pragma Ada_83

Syntax:

```
pragma Ada_83;
```

A configuration pragma that establishes Ada 83 mode for the unit to which it applies, regardless of the mode set by the command line switches. In Ada 83 mode, GNAT attempts to be as compatible with the syntax and semantics of Ada 83, as defined in the original Ada 83 Reference Manual as possible. In particular, the keywords added by Ada 95 and Ada 2005 are not recognized, optional package bodies are allowed, and generics may name types with unknown discriminants without using the (<>) notation. In addition, some but not all of the additional restrictions of Ada 83 are enforced.

Ada 83 mode is intended for two purposes. Firstly, it allows existing Ada 83 code to be compiled and adapted to GNAT with less effort. Secondly, it aids in keeping code backwards compatible with Ada 83. However, there is no guarantee that code that is processed correctly by GNAT in Ada 83 mode will in fact compile and execute with an Ada 83 compiler, since GNAT does not enforce all the additional checks required by Ada 83.

Pragma Ada_95

Syntax:

```
pragma Ada_95;
```

A configuration pragma that establishes Ada 95 mode for the unit to which it applies, regardless of the mode set by the command line switches. This mode is set automatically for the **Ada** and **System** packages and their children, so you need not specify it in these contexts. This pragma is useful when writing a reusable component that itself uses Ada 95 features, but which is intended to be usable from either Ada 83 or Ada 95 programs.

Pragma Ada_05

Syntax:

```
pragma Ada_05;
```

A configuration pragma that establishes Ada 2005 mode for the unit to which it applies, regardless of the mode set by the command line switches. This pragma is useful when writing a reusable component that itself uses Ada 2005 features, but which is intended to be usable from either Ada 83 or Ada 95 programs.

Pragma Ada_2005

Syntax:

```
pragma Ada_2005;
```

This configuration pragma is a synonym for pragma Ada_05 and has the same syntax and effect.

Pragma Ada_12

Syntax:

```
pragma Ada_12;
```

A configuration pragma that establishes Ada 2012 mode for the unit to which it applies, regardless of the mode set by the command line switches. This mode is set automatically for the **Ada** and **System** packages and their children, so you need not specify it in these contexts. This pragma is useful when writing a reusable component that itself uses Ada 2012 features, but which is intended to be usable from Ada 83, Ada 95, or Ada 2005 programs.

Pragma Ada_2012

Syntax:

```
pragma Ada_2012;
```

This configuration pragma is a synonym for pragma Ada_12 and has the same syntax and effect.

Pragma Annotate

Syntax:

```
pragma Annotate (IDENTIFIER [,IDENTIFIER] {, ARG});
```

```
ARG ::= NAME | EXPRESSION
```

This pragma is used to annotate programs. *identifier* identifies the type of annotation. GNAT verifies that it is an identifier, but does not otherwise analyze it. The second optional identifier is also left unanalyzed, and by convention is used to control the action of the tool to which the annotation is addressed. The remaining *arg* arguments can be either string literals or more generally expressions. String literals are assumed to be either of type **Standard.String** or else **Wide_String** or **Wide_Wide_String** depending on the character literals they contain. All other kinds of arguments are analyzed as expressions, and must be unambiguous.

The analyzed pragma is retained in the tree, but not otherwise processed by any part of the GNAT compiler. This pragma is intended for use by external tools, including ASIS.

Pragma Assert

Syntax:

```
pragma Assert (
  boolean_EXPRESSION
  [, string_EXPRESSION]);
```

The effect of this pragma depends on whether the corresponding command line switch is set to activate assertions. The pragma expands into code equivalent to the following:

```

if assertions-enabled then
  if not boolean_EXPRESSION then
    System.Assertions.Raise_Assert_Failure
      (string_EXPRESSION);
  end if;
end if;

```

The string argument, if given, is the message that will be associated with the exception occurrence if the exception is raised. If no second argument is given, the default message is `'file:nnn'`, where *file* is the name of the source file containing the assert, and *nnn* is the line number of the assert. A pragma is not a statement, so if a statement sequence contains nothing but a pragma assert, then a null statement is required in addition, as in:

```

...
if J > 3 then
  pragma Assert (K > 3, "Bad value for K");
  null;
end if;

```

Note that, as with the `if` statement to which it is equivalent, the type of the expression is either `Standard.Boolean`, or any type derived from this standard type.

If assertions are disabled (switch `'-gnata'` not used), then there is no run-time effect (and in particular, any side effects from the expression will not occur at run time). (The expression is still analyzed at compile time, and may cause types to be frozen if they are mentioned here for the first time).

If assertions are enabled, then the given expression is tested, and if it is `False` then `System.Assertions.Raise_Assert_Failure` is called which results in the raising of `Assert_Failure` with the given message.

You should generally avoid side effects in the expression arguments of this pragma, because these side effects will turn on and off with the setting of the assertions mode, resulting in assertions that have an effect on the program. However, the expressions are analyzed for semantic correctness whether or not assertions are enabled, so turning assertions on and off cannot affect the legality of a program.

Pragma Assume_No_Invalid_Values

Syntax:

```
pragma Assume_No_Invalid_Values (On | Off);
```

This is a configuration pragma that controls the assumptions made by the compiler about the occurrence of invalid representations (invalid values) in the code.

The default behavior (corresponding to an `Off` argument for this pragma), is to assume that values may in general be invalid unless the compiler can prove they are valid. Consider the following example:

```

V1 : Integer range 1 .. 10;
V2 : Integer range 11 .. 20;
...
for J in V2 .. V1 loop
  ...
end loop;

```

if `V1` and `V2` have valid values, then the loop is known at compile time not to execute since the lower bound must be greater than the upper bound. However in default mode, no such assumption is made, and the loop may execute. If `Assume_No_Invalid_Values (On)` is given, the compiler will assume that any occurrence of a variable other than in an explicit `'Valid` test always has a valid value, and the loop above will be optimized away.

The use of `Assume_No_Invalid_Values (On)` is appropriate if you know your code is free of uninitialized variables and other possible sources of invalid representations, and may result

in more efficient code. A program that accesses an invalid representation with this pragma in effect is erroneous, so no guarantees can be made about its behavior.

It is peculiar though permissible to use this pragma in conjunction with validity checking (-gnatVa). In such cases, accessing invalid values will generally give an exception, though formally the program is erroneous so there are no guarantees that this will always be the case, and it is recommended that these two options not be used together.

Pragma Ast_Entry

Syntax:

```
pragma AST_Entry (entry_IDENTIFIER);
```

This pragma is implemented only in the OpenVMS implementation of GNAT. The argument is the simple name of a single entry; at most one `AST_Entry` pragma is allowed for any given entry. This pragma must be used in conjunction with the `AST_Entry` attribute, and is only allowed after the entry declaration and in the same task type specification or single task as the entry to which it applies. This pragma specifies that the given entry may be used to handle an OpenVMS asynchronous system trap (AST) resulting from an OpenVMS system service call. The pragma does not affect normal use of the entry. For further details on this pragma, see the DEC Ada Language Reference Manual, section 9.12a.

Pragma C_Pass_By_Copy

Syntax:

```
pragma C_Pass_By_Copy
  ([Max_Size =>] static_integer_EXPRESSION);
```

Normally the default mechanism for passing C convention records to C convention subprograms is to pass them by reference, as suggested by RM B.3(69). Use the configuration pragma `C_Pass_By_Copy` to change this default, by requiring that record formal parameters be passed by copy if all of the following conditions are met:

- The size of the record type does not exceed the value specified for `Max_Size`.
- The record type has `Convention C`.
- The formal parameter has this record type, and the subprogram has a foreign (non-Ada) convention.

If these conditions are met the argument is passed by copy, i.e. in a manner consistent with what C expects if the corresponding formal in the C prototype is a struct (rather than a pointer to a struct).

You can also pass records by copy by specifying the convention `C_Pass_By_Copy` for the record type, or by using the extended `Import` and `Export` pragmas, which allow specification of passing mechanisms on a parameter by parameter basis.

Pragma Check

Syntax:

```
pragma Check (
  [Name    =>] Identifier,
  [Check   =>] Boolean_EXPRESSION
  [, [Message =>] string_EXPRESSION] );
```

This pragma is similar to the predefined pragma `Assert` except that an extra identifier argument is present. In conjunction with pragma `Check_Policy`, this can be used to define groups of assertions that can be independently controlled. The identifier `Assertion` is special, it refers to the normal set of pragma `Assert` statements. The identifiers `Precondition` and `Postcondition`

correspond to the pragmas of these names, so these three names would normally not be used directly in a pragma **Check**.

Checks introduced by this pragma are normally deactivated by default. They can be activated either by the command line option ‘-gnata’, which turns on all checks, or individually controlled using pragma **Check_Policy**.

Pragma Check_Name

Syntax:

```
pragma Check_Name (check_name_IDENTIFIER);
```

This is a configuration pragma that defines a new implementation defined check name (unless IDENTIFIER matches one of the predefined check names, in which case the pragma has no effect). Check names are global to a partition, so if two or more configuration pragmas are present in a partition mentioning the same name, only one new check name is introduced.

An implementation defined check name introduced with this pragma may be used in only three contexts: **pragma Suppress**, **pragma Unsuppress**, and as the prefix of a **Check_Name’Enabled** attribute reference. For any of these three cases, the check name must be visible. A check name is visible if it is in the configuration pragmas applying to the current unit, or if it appears at the start of any unit that is part of the dependency set of the current unit (e.g., units that are mentioned in **with** clauses).

Pragma Check_Policy

Syntax:

```
pragma Check_Policy
  ([Name =>] Identifier,
   [Policy =>] POLICY_IDENTIFIER);

POLICY_IDENTIFIER ::= On | Off | Check | Ignore
```

This pragma is similar to the predefined pragma **Assertion_Policy**, except that it controls sets of named assertions introduced using the **Check** pragmas. It can be used as a configuration pragma or (unlike **Assertion_Policy**) can be used within a declarative part, in which case it controls the status to the end of the corresponding construct (in a manner identical to pragma **Suppress**).

The identifier given as the first argument corresponds to a name used in associated **Check** pragmas. For example, if the pragma:

```
pragma Check_Policy (Critical_Error, Off);
```

is given, then subsequent **Check** pragmas whose first argument is also **Critical_Error** will be disabled. The special identifier **Assertion** controls the behavior of normal **Assert** pragmas (thus a pragma **Check_Policy** with this identifier is similar to the normal **Assertion_Policy** pragma except that it can appear within a declarative part).

The special identifiers **Precondition** and **Postcondition** control the status of preconditions and postconditions. If a **Precondition** pragma is encountered, it is ignored if turned off by a **Check_Policy** specifying that **Precondition** checks are **Off** or **Ignored**. Similarly use of the name **Postcondition** controls whether **Postcondition** pragmas are recognized.

The check policy is **Off** to turn off corresponding checks, and **On** to turn on corresponding checks. The default for a set of checks for which no **Check_Policy** is given is **Off** unless the compiler switch ‘-gnata’ is given, which turns on all checks by default.

The check policy settings **Check** and **Ignore** are also recognized as synonyms for **On** and **Off**. These synonyms are provided for compatibility with the standard **Assertion_Policy** pragma.

Pragma Comment

Syntax:

```
pragma Comment (static_string_EXPRESSION);
```

This is almost identical in effect to pragma `Ident`. It allows the placement of a comment into the object file and hence into the executable file if the operating system permits such usage. The difference is that `Comment`, unlike `Ident`, has no limitations on placement of the pragma (it can be placed anywhere in the main source unit), and if more than one pragma is used, all comments are retained.

Pragma Common_Object

Syntax:

```
pragma Common_Object (
    [Internal =>] LOCAL_NAME
    [, [External =>] EXTERNAL_SYMBOL]
    [, [Size    =>] EXTERNAL_SYMBOL] );

EXTERNAL_SYMBOL ::=
    IDENTIFIER
    | static_string_EXPRESSION
```

This pragma enables the shared use of variables stored in overlaid linker areas corresponding to the use of `COMMON` in Fortran. The single object `LOCAL_NAME` is assigned to the area designated by the *External* argument. You may define a record to correspond to a series of fields. The *Size* argument is syntax checked in GNAT, but otherwise ignored.

`Common_Object` is not supported on all platforms. If no support is available, then the code generator will issue a message indicating that the necessary attribute for implementation of this pragma is not available.

Pragma Compile_Time_Error

Syntax:

```
pragma Compile_Time_Error
    (boolean_EXPRESSION, static_string_EXPRESSION);
```

This pragma can be used to generate additional compile time error messages. It is particularly useful in generics, where errors can be issued for specific problematic instantiations. The first parameter is a boolean expression. The pragma is effective only if the value of this expression is known at compile time, and has the value `True`. The set of expressions whose values are known at compile time includes all static boolean expressions, and also other values which the compiler can determine at compile time (e.g., the size of a record type set by an explicit size representation clause, or the value of a variable which was initialized to a constant and is known not to have been modified). If these conditions are met, an error message is generated using the value given as the second argument. This string value may contain embedded ASCII.LF characters to break the message into multiple lines.

Pragma Compile_Time_Warning

Syntax:

```
pragma Compile_Time_Warning
    (boolean_EXPRESSION, static_string_EXPRESSION);
```

Same as pragma `Compile_Time_Error`, except a warning is issued instead of an error message. Note that if this pragma is used in a package that is with'ed by a client, the client will get the warning even though it is issued by a with'ed package (normally warnings in with'ed units are suppressed, but this is a special exception to that rule).

One typical use is within a generic where compile time known characteristics of formal parameters are tested, and warnings given appropriately. Another use with a first parameter of `True` is to warn a client about use of a package, for example that it is not fully implemented.

Pragma `Compiler_Unit`

Syntax:

```
pragma Compiler_Unit;
```

This pragma is intended only for internal use in the GNAT run-time library. It indicates that the unit is used as part of the compiler build. The effect is to disallow constructs (raise with message, conditional expressions etc) that would cause trouble when bootstrapping using an older version of GNAT. For the exact list of restrictions, see the compiler sources and references to `Is_Compiler_Unit`.

Pragma `Complete_Representation`

Syntax:

```
pragma Complete_Representation;
```

This pragma must appear immediately within a record representation clause. Typical placements are before the first component clause or after the last component clause. The effect is to give an error message if any component is missing a component clause. This pragma may be used to ensure that a record representation clause is complete, and that this invariant is maintained if fields are added to the record in the future.

Pragma `Complex_Representation`

Syntax:

```
pragma Complex_Representation
  ([Entity =>] LOCAL_NAME);
```

The *Entity* argument must be the name of a record type which has two fields of the same floating-point type. The effect of this pragma is to force gcc to use the special internal complex representation form for this record, which may be more efficient. Note that this may result in the code for this type not conforming to standard ABI (application binary interface) requirements for the handling of record types. For example, in some environments, there is a requirement for passing records by pointer, and the use of this pragma may result in passing this type in floating-point registers.

Pragma `Component_Alignment`

Syntax:

```
pragma Component_Alignment (
  [Form =>] ALIGNMENT_CHOICE
  [, [Name =>] type_LOCAL_NAME]);

ALIGNMENT_CHOICE ::=
  Component_Size
| Component_Size_4
| Storage_Unit
| Default
```

Specifies the alignment of components in array or record types. The meaning of the *Form* argument is as follows:

`Component_Size`

Aligns scalar components and subcomponents of the array or record type on boundaries appropriate to their inherent size (naturally aligned). For example, 1-byte

components are aligned on byte boundaries, 2-byte integer components are aligned on 2-byte boundaries, 4-byte integer components are aligned on 4-byte boundaries and so on. These alignment rules correspond to the normal rules for C compilers on all machines except the VAX.

Component_Size_4

Naturally aligns components with a size of four or fewer bytes. Components that are larger than 4 bytes are placed on the next 4-byte boundary.

Storage_Unit

Specifies that array or record components are byte aligned, i.e. aligned on boundaries determined by the value of the constant `System.Storage_Unit`.

Default Specifies that array or record components are aligned on default boundaries, appropriate to the underlying hardware or operating system or both. For OpenVMS VAX systems, the **Default** choice is the same as the **Storage_Unit** choice (byte alignment). For all other systems, the **Default** choice is the same as **Component_Size** (natural alignment).

If the **Name** parameter is present, *type.LOCAL_NAME* must refer to a local record or array type, and the specified alignment choice applies to the specified type. The use of **Component_Alignment** together with a pragma **Pack** causes the **Component_Alignment** pragma to be ignored. The use of **Component_Alignment** together with a record representation clause is only effective for fields not specified by the representation clause.

If the **Name** parameter is absent, the pragma can be used as either a configuration pragma, in which case it applies to one or more units in accordance with the normal rules for configuration pragmas, or it can be used within a declarative part, in which case it applies to types that are declared within this declarative part, or within any nested scope within this declarative part. In either case it specifies the alignment to be applied to any record or array type which has otherwise standard representation.

If the alignment for a record or array type is not specified (using pragma **Pack**, pragma **Component_Alignment**, or a record rep clause), the GNAT uses the default alignment as described previously.

Pragma Convention_Identifier

Syntax:

```
pragma Convention_Identifier (
    [Name =>]      IDENTIFIER,
    [Convention =>] convention_IDENTIFIER);
```

This pragma provides a mechanism for supplying synonyms for existing convention identifiers. The **Name** identifier can subsequently be used as a synonym for the given convention in other pragmas (including for example pragma **Import** or another **Convention_Identifier** pragma). As an example of the use of this, suppose you had legacy code which used **Fortran77** as the identifier for Fortran. Then the pragma:

```
pragma Convention_Identifier (Fortran77, Fortran);
```

would allow the use of the convention identifier **Fortran77** in subsequent code, avoiding the need to modify the sources. As another example, you could use this to parameterize convention requirements according to systems. Suppose you needed to use **Stdcall** on windows systems, and **C** on some other system, then you could define a convention identifier **Library** and use a single **Convention_Identifier** pragma to specify which convention would be used system-wide.

Pragma CPP_Class

Syntax:

```
pragma CPP_Class ([Entity =>] LOCAL_NAME);
```

The argument denotes an entity in the current declarative region that is declared as a record type. It indicates that the type corresponds to an externally declared C++ class type, and is to be laid out the same way that C++ would lay out the type. If the C++ class has virtual primitives then the record must be declared as a tagged record type.

Types for which `CPP_Class` is specified do not have assignment or equality operators defined (such operations can be imported or declared as subprograms as required). Initialization is allowed only by constructor functions (see `pragma CPP_Constructor`). Such types are implicitly limited if not explicitly declared as limited or derived from a limited type, and an error is issued in that case.

Pragma `CPP_Class` is intended primarily for automatic generation using an automatic binding generator tool. See [Section 10.2 \[Interfacing to C++\]](#), page 180 for related information.

Note: Pragma `CPP_Class` is currently obsolete. It is supported for backward compatibility but its functionality is available using `pragma Import` with `Convention = CPP`.

Pragma CPP_Constructor

Syntax:

```
pragma CPP_Constructor ([Entity =>] LOCAL_NAME
  [, [External_Name =>] static_string_EXPRESSION ]
  [, [Link_Name      =>] static_string_EXPRESSION ]);
```

This pragma identifies an imported function (imported in the usual way with `pragma Import`) as corresponding to a C++ constructor. If `External_Name` and `Link_Name` are not specified then the `Entity` argument is a name that must have been previously mentioned in a `pragma Import` with `Convention = CPP`. Such name must be of one of the following forms:

- `function Fname return T`
 - `function Fname return T'Class`
 - `function Fname (...) return T`
- `function Fname (...) return T'Class`

where *T* is a limited record type imported from C++ with `pragma Import` and `Convention = CPP`.

The first two forms import the default constructor, used when an object of type *T* is created on the Ada side with no explicit constructor. The latter two forms cover all the non-default constructors of the type. See the GNAT users guide for details.

If no constructors are imported, it is impossible to create any objects on the Ada side and the type is implicitly declared abstract.

Pragma `CPP_Constructor` is intended primarily for automatic generation using an automatic binding generator tool. See [Section 10.2 \[Interfacing to C++\]](#), page 180 for more related information.

Note: The use of functions returning class-wide types for constructors is currently obsolete. They are supported for backward compatibility. The use of functions returning the type *T* leave the Ada sources more clear because the imported C++ constructors always return an object of type *T*; that is, they never return an object whose type is a descendant of type *T*.

Pragma CPP_Virtual

This pragma is now obsolete has no effect because GNAT generates the same object layout than the G++ compiler.

See [Section 10.2 \[Interfacing to C++\]](#), page 180 for related information.

Pragma CPP_Vtable

This pragma is now obsolete has no effect because GNAT generates the same object layout than the G++ compiler.

See [Section 10.2 \[Interfacing to C++\]](#), page 180 for related information.

Pragma Debug

Syntax:

```
pragma Debug ([CONDITION, ]PROCEDURE_CALL_WITHOUT_SEMICOLON);

PROCEDURE_CALL_WITHOUT_SEMICOLON ::=
  PROCEDURE_NAME
  | PROCEDURE_PREFIX ACTUAL_PARAMETER_PART
```

The procedure call argument has the syntactic form of an expression, meeting the syntactic requirements for pragmas.

If debug pragmas are not enabled or if the condition is present and evaluates to False, this pragma has no effect. If debug pragmas are enabled, the semantics of the pragma is exactly equivalent to the procedure call statement corresponding to the argument with a terminating semicolon. Pragmas are permitted in sequences of declarations, so you can use pragma `Debug` to intersperse calls to debug procedures in the middle of declarations. Debug pragmas can be enabled either by use of the command line switch ‘-gnata’ or by use of the configuration pragma `Debug_Policy`.

Pragma Debug_Policy

Syntax:

```
pragma Debug_Policy (CHECK | IGNORE);
```

If the argument is `CHECK`, then pragma `DEBUG` is enabled. If the argument is `IGNORE`, then pragma `DEBUG` is ignored. This pragma overrides the effect of the ‘-gnata’ switch on the command line.

Pragma Detect_Blocking

Syntax:

```
pragma Detect_Blocking;
```

This is a configuration pragma that forces the detection of potentially blocking operations within a protected operation, and to raise `Program_Error` if that happens.

Pragma Elaboration_Checks

Syntax:

```
pragma Elaboration_Checks (Dynamic | Static);
```

This is a configuration pragma that provides control over the elaboration model used by the compilation affected by the pragma. If the parameter is `Dynamic`, then the dynamic elaboration model described in the Ada Reference Manual is used, as though the ‘-gnatE’ switch had been specified on the command line. If the parameter is `Static`, then the default GNAT static model is used. This configuration pragma overrides the setting of the command line. For full details on the elaboration models used by the GNAT compiler, see [Section “Elaboration Order Handling in GNAT”](#) in *GNAT User’s Guide*.

Pragma Eliminate

Syntax:

```
pragma Eliminate (UNIT_NAME, ENTITY, Source_Location => SOURCE_TRACE)

UNIT_NAME      ::= IDENTIFIER |
                  SELECTED_COMPONENT,

ENTITY         ::= IDENTIFIER |
                  SELECTED_COMPONENT,

SOURCE_TRACE   ::= SOURCE_REFERENCE |
                  SOURCE_REFERENCE LBRACKET SOURCE_TRACE RBRACKET

LBRACKET       ::= [
RBRACKET       ::= ]

SOURCE_REFERENCE ::= FILE_NAME : LINE_NUMBER

FILE_NAME      ::= STRING_LITERAL
LINE_NUMBER    ::= INTEGER_LITERAL
```

This pragma indicates that the given entity is not used in the program to be compiled and built. The entity must be an explicitly declared subprogram; this includes generic subprogram instances and subprograms declared in generic package instances. **Unit_Name** must be the name of the compilation unit in which the entity is declared.

The **Source_Location** argument is used to resolve overloading in case more than one callable entity with the same name is declared in the given compilation unit. Each file name must be the short name of the source file (with no directory information). If an entity is not declared in a generic instantiation (this includes generic subprogram instances), the source trace includes only one source reference. If an entity is declared inside a generic instantiation, its source trace starts from the source location in the instantiation and ends with the source location of the declaration of the corresponding entity in the generic unit. This approach is recursively used in case of nested instantiations: the leftmost element of the source trace is the location of the outermost instantiation, the next element is the location of the next (first nested) instantiation in the code of the corresponding generic unit, and so on.

The effect of the pragma is to allow the compiler to eliminate the code or data associated with the named entity. Any reference to an eliminated entity outside the compilation unit where it is defined causes a compile-time or link-time error.

The intention of pragma **Eliminate** is to allow a program to be compiled in a system-independent manner, with unused entities eliminated, without needing to modify the source text. Normally the required set of **Eliminate** pragmas is constructed automatically using the gnatelim tool. Elimination of unused entities local to a compilation unit is automatic, without requiring the use of pragma **Eliminate**.

Any source file change that removes, splits, or adds lines may make the set of **Eliminate** pragmas invalid because their **Source_Location** argument values may get out of date.

Pragma **Eliminate** may be used where the referenced entity is a dispatching operation. In this case all the subprograms to which the given operation can dispatch are considered to be unused (are never called as a result of a direct or a dispatching call).

Pragma Export_Exception

Syntax:

```
pragma Export_Exception (
    [Internal =>] LOCAL_NAME
    [, [External =>] EXTERNAL_SYMBOL]
```



```

[, [Form      =>] Ada | VMS]
[, [Code      =>] static_integer_EXPRESSION]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
| static_string_EXPRESSION

```

This pragma is implemented only in the OpenVMS implementation of GNAT. It causes the specified exception to be propagated outside of the Ada program, so that it can be handled by programs written in other OpenVMS languages. This pragma establishes an external name for an Ada exception and makes the name available to the OpenVMS Linker as a global symbol. For further details on this pragma, see the DEC Ada Language Reference Manual, section 13.9a3.2.

Pragma Export_Function

Syntax:

```

pragma Export_Function (
  [Internal      =>] LOCAL_NAME
[, [External     =>] EXTERNAL_SYMBOL]
[, [Parameter_Types =>] PARAMETER_TYPES]
[, [Result_Type   =>] result_SUBTYPE_MARK]
[, [Mechanism     =>] MECHANISM]
[, [Result_Mechanism =>] MECHANISM_NAME]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
| static_string_EXPRESSION
| ""

PARAMETER_TYPES ::=
  null
| TYPE_DESIGNATOR {, TYPE_DESIGNATOR}

TYPE_DESIGNATOR ::=
  subtype_NAME
| subtype_Name ' Access

MECHANISM ::=
  MECHANISM_NAME
| (MECHANISM_ASSOCIATION {, MECHANISM_ASSOCIATION})

MECHANISM_ASSOCIATION ::=
  [formal_parameter_NAME =>] MECHANISM_NAME

MECHANISM_NAME ::=
  Value
| Reference
| Descriptor [([Class =>] CLASS_NAME)]
| Short_Descriptor [([Class =>] CLASS_NAME)]

CLASS_NAME ::= ubs | ubsb | uba | s | sb | a

```

Use this pragma to make a function externally callable and optionally provide information on mechanisms to be used for passing parameter and result values. We recommend, for the purposes of improving portability, this pragma always be used in conjunction with a separate pragma `Export`, which must precede the pragma `Export_Function`. GNAT does not require a separate pragma `Export`, but if none is present, `Convention Ada` is assumed, which is usually not what is wanted, so it is usually appropriate to use this pragma in conjunction with a `Export` or `Convention` pragma that specifies the desired foreign convention. Pragma `Export_Function` (and `Export`, if present) must appear in the same declarative region as the function to which they apply.

internal_name must uniquely designate the function to which the pragma applies. If more than one function name exists of this name in the declarative part you must use the **Parameter_Types** and **Result_Type** parameters is mandatory to achieve the required unique designation. *subtype_marks* in these parameters must exactly match the subtypes in the corresponding function specification, using positional notation to match parameters with subtype marks. The form with an **'Access** attribute can be used to match an anonymous access parameter.

Passing by descriptor is supported only on the OpenVMS ports of GNAT. The default behavior for **Export_Function** is to accept either 64bit or 32bit descriptors unless **short_descriptor** is specified, then only 32bit descriptors are accepted.

Special treatment is given if the **EXTERNAL** is an explicit null string or a static string expressions that evaluates to the null string. In this case, no external name is generated. This form still allows the specification of parameter mechanisms.

Pragma Export_Object

Syntax:

```
pragma Export_Object
  [Internal =>] LOCAL_NAME
  [, [External =>] EXTERNAL_SYMBOL]
  [, [Size      =>] EXTERNAL_SYMBOL]

EXTERNAL_SYMBOL ::=
  IDENTIFIER
| static_string_EXPRESSION
```

This pragma designates an object as exported, and apart from the extended rules for external symbols, is identical in effect to the use of the normal **Export** pragma applied to an object. You may use a separate **Export** pragma (and you probably should from the point of view of portability), but it is not required. *Size* is syntax checked, but otherwise ignored by GNAT.

Pragma Export_Procedure

Syntax:

```
pragma Export_Procedure (
  [Internal      =>] LOCAL_NAME
  [, [External    =>] EXTERNAL_SYMBOL]
  [, [Parameter_Types =>] PARAMETER_TYPES]
  [, [Mechanism    =>] MECHANISM]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
| static_string_EXPRESSION
| ""

PARAMETER_TYPES ::=
  null
| TYPE_DESIGNATOR {, TYPE_DESIGNATOR}

TYPE_DESIGNATOR ::=
  subtype_NAME
| subtype_Name ' Access

MECHANISM ::=
  MECHANISM_NAME
| (MECHANISM_ASSOCIATION {, MECHANISM_ASSOCIATION})

MECHANISM_ASSOCIATION ::=
  [formal_parameter_NAME =>] MECHANISM_NAME

MECHANISM_NAME ::=
```

```

    Value
  | Reference
  | Descriptor [[([Class =>] CLASS_NAME)]
  | Short_Descriptor [[([Class =>] CLASS_NAME)]

```

```

CLASS_NAME ::= ubs | ubsb | uba | s | sb | a

```

This pragma is identical to `Export_Function` except that it applies to a procedure rather than a function and the parameters `Result_Type` and `Result_Mechanism` are not permitted. GNAT does not require a separate pragma `Export`, but if none is present, `Convention Ada` is assumed, which is usually not what is wanted, so it is usually appropriate to use this pragma in conjunction with a `Export` or `Convention` pragma that specifies the desired foreign convention.

Passing by descriptor is supported only on the OpenVMS ports of GNAT. The default behavior for `Export_Procedure` is to accept either 64bit or 32bit descriptors unless `short_descriptor` is specified, then only 32bit descriptors are accepted.

Special treatment is given if the `EXTERNAL` is an explicit null string or a static string expressions that evaluates to the null string. In this case, no external name is generated. This form still allows the specification of parameter mechanisms.

Pragma Export_Value

Syntax:

```

pragma Export_Value (
  [Value      =>] static_integer_EXPRESSION,
  [Link_Name =>] static_string_EXPRESSION);

```

This pragma serves to export a static integer value for external use. The first argument specifies the value to be exported. The `Link_Name` argument specifies the symbolic name to be associated with the integer value. This pragma is useful for defining a named static value in Ada that can be referenced in assembly language units to be linked with the application. This pragma is currently supported only for the AAMP target and is ignored for other targets.

Pragma Export_Valued_Procedure

Syntax:

```

pragma Export_Valued_Procedure (
  [Internal      =>] LOCAL_NAME
  [, [External   =>] EXTERNAL_SYMBOL]
  [, [Parameter_Types =>] PARAMETER_TYPES]
  [, [Mechanism   =>] MECHANISM]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
| static_string_EXPRESSION
| ""

PARAMETER_TYPES ::=
  null
| TYPE_DESIGNATOR {, TYPE_DESIGNATOR}

TYPE_DESIGNATOR ::=
  subtype_NAME
| subtype_Name ' Access

MECHANISM ::=
  MECHANISM_NAME
| (MECHANISM_ASSOCIATION {, MECHANISM_ASSOCIATION})

MECHANISM_ASSOCIATION ::=
  [formal_parameter_NAME =>] MECHANISM_NAME

```

```

MECHANISM_NAME ::=
  Value
| Reference
| Descriptor [[([Class =>] CLASS_NAME)]
| Short_Descriptor [[([Class =>] CLASS_NAME)]

CLASS_NAME ::= ubs | ubsb | uba | s | sb | a

```

This pragma is identical to `Export_Procedure` except that the first parameter of `LOCAL_NAME`, which must be present, must be of mode `OUT`, and externally the subprogram is treated as a function with this parameter as the result of the function. GNAT provides for this capability to allow the use of `OUT` and `IN OUT` parameters in interfacing to external functions (which are not permitted in Ada functions). GNAT does not require a separate pragma `Export`, but if none is present, `Convention Ada` is assumed, which is almost certainly not what is wanted since the whole point of this pragma is to interface with foreign language functions, so it is usually appropriate to use this pragma in conjunction with a `Export` or `Convention` pragma that specifies the desired foreign convention.

Passing by descriptor is supported only on the OpenVMS ports of GNAT. The default behavior for `Export_Valued_Procedure` is to accept either 64bit or 32bit descriptors unless `short_descriptor` is specified, then only 32bit descriptors are accepted.

Special treatment is given if the `EXTERNAL` is an explicit null string or a static string expressions that evaluates to the null string. In this case, no external name is generated. This form still allows the specification of parameter mechanisms.

Pragma Extend_System

Syntax:

```
pragma Extend_System ([Name =>] IDENTIFIER);
```

This pragma is used to provide backwards compatibility with other implementations that extend the facilities of package `System`. In GNAT, `System` contains only the definitions that are present in the Ada RM. However, other implementations, notably the DEC Ada 83 implementation, provide many extensions to package `System`.

For each such implementation accommodated by this pragma, GNAT provides a package `Aux_xxx`, e.g. `Aux_DEC` for the DEC Ada 83 implementation, which provides the required additional definitions. You can use this package in two ways. You can `with` it in the normal way and access entities either by selection or using a `use` clause. In this case no special processing is required.

However, if existing code contains references such as `System.xxx` where `xxx` is an entity in the extended definitions provided in package `System`, you may use this pragma to extend visibility in `System` in a non-standard way that provides greater compatibility with the existing code. Pragma `Extend_System` is a configuration pragma whose single argument is the name of the package containing the extended definition (e.g. `Aux_DEC` for the DEC Ada case). A unit compiled under control of this pragma will be processed using special visibility processing that looks in package `System.Aux_xxx` where `Aux_xxx` is the pragma argument for any entity referenced in package `System`, but not found in package `System`.

You can use this pragma either to access a predefined `System` extension supplied with the compiler, for example `Aux_DEC` or you can construct your own extension unit following the above definition. Note that such a package is a child of `System` and thus is considered part of the implementation. To compile it you will have to use the appropriate switch for compiling system units. See [Section “About This Guide” in GNAT User’s Guide](#), for details.

Pragma Extensions_Allowed

Syntax:

```
pragma Extensions_Allowed (On | Off);
```

This configuration pragma enables or disables the implementation extension mode (the use of Off as a parameter cancels the effect of the ‘-gnatX’ command switch).

In extension mode, the latest version of the Ada language is implemented (currently Ada 2012), and in addition a small number of GNAT specific extensions are recognized as follows:

Constrained attribute for generic objects

The **Constrained** attribute is permitted for objects of generic types. The result indicates if the corresponding actual is constrained.

Pragma External

Syntax:

```
pragma External (
  [ Convention    =>] convention_IDENTIFIER,
  [ Entity        =>] LOCAL_NAME
  [, [External_Name =>] static_string_EXPRESSION ]
  [, [Link_Name    =>] static_string_EXPRESSION ]);
```

This pragma is identical in syntax and semantics to pragma **Export** as defined in the Ada Reference Manual. It is provided for compatibility with some Ada 83 compilers that used this pragma for exactly the same purposes as pragma **Export** before the latter was standardized.

Pragma External_Name_Casing

Syntax:

```
pragma External_Name_Casing (
  Uppercase | Lowercase
  [, Uppercase | Lowercase | As_Is]);
```

This pragma provides control over the casing of external names associated with Import and Export pragmas. There are two cases to consider:

Implicit external names

Implicit external names are derived from identifiers. The most common case arises when a standard Ada Import or Export pragma is used with only two arguments, as in:

```
pragma Import (C, C_Routine);
```

Since Ada is a case-insensitive language, the spelling of the identifier in the Ada source program does not provide any information on the desired casing of the external name, and so a convention is needed. In GNAT the default treatment is that such names are converted to all lower case letters. This corresponds to the normal C style in many environments. The first argument of pragma **External_Name_Casing** can be used to control this treatment. If **Uppercase** is specified, then the name will be forced to all uppercase letters. If **Lowercase** is specified, then the normal default of all lower case letters will be used.

This same implicit treatment is also used in the case of extended DEC Ada 83 compatible Import and Export pragmas where an external name is explicitly specified using an identifier rather than a string.

Explicit external names

Explicit external names are given as string literals. The most common case arises when a standard Ada Import or Export pragma is used with three arguments, as in:

```
pragma Import (C, C_Routine, "C_routine");
```

In this case, the string literal normally provides the exact casing required for the external name. The second argument of pragma **External_Name_Casing** may be used to modify this behavior. If **Uppercase** is specified, then the name will be forced to all uppercase letters. If **Lowercase** is specified, then the name will be forced to all lowercase letters. A specification of **As_Is** provides the normal default behavior in which the casing is taken from the string provided.

This pragma may appear anywhere that a pragma is valid. In particular, it can be used as a configuration pragma in the ‘**gnat.adc**’ file, in which case it applies to all subsequent compilations, or it can be used as a program unit pragma, in which case it only applies to the current unit, or it can be used more locally to control individual Import/Export pragmas.

It is primarily intended for use with OpenVMS systems, where many compilers convert all symbols to upper case by default. For interfacing to such compilers (e.g. the DEC C compiler), it may be convenient to use the pragma:

```
pragma External_Name_Casing (Uppercase, Uppercase);
```

to enforce the upper casing of all external symbols.

Pragma Fast_Math

Syntax:

```
pragma Fast_Math;
```

This is a configuration pragma which activates a mode in which speed is considered more important for floating-point operations than absolutely accurate adherence to the requirements of the standard. Currently the following operations are affected:

Complex Multiplication

The normal simple formula for complex multiplication can result in intermediate overflows for numbers near the end of the range. The Ada standard requires that this situation be detected and corrected by scaling, but in **Fast_Math** mode such cases will simply result in overflow. Note that to take advantage of this you must instantiate your own version of **Ada.Numerics.Generic_Complex_Types** under control of the pragma, rather than use the preinstantiated versions.

Pragma Favor_Top_Level

Syntax:

```
pragma Favor_Top_Level (type_NAME);
```

The named type must be an access-to-subprogram type. This pragma is an efficiency hint to the compiler, regarding the use of ‘**Access**’ or ‘**Unrestricted_Access**’ on nested (non-library-level) subprograms. The pragma means that nested subprograms are not used with this type, or are rare, so that the generated code should be efficient in the top-level case. When this pragma is used, dynamically generated trampolines may be used on some targets for nested subprograms. See also the **No_Implicit_Dynamic_Code** restriction.

Pragma Finalize_Storage_Only

Syntax:

```
pragma Finalize_Storage_Only (first_subtype_LOCAL_NAME);
```

This pragma allows the compiler not to emit a **Finalize** call for objects defined at the library level. This is mostly useful for types where finalization is only used to deal with storage reclamation since in most environments it is not necessary to reclaim memory just before terminating execution, hence the name.

Pragma Float_Representation

Syntax:

```
pragma Float_Representation (FLOAT_REP[, float_type_LOCAL_NAME]);

FLOAT_REP ::= VAX_Float | IEEE_Float
```

In the one argument form, this pragma is a configuration pragma which allows control over the internal representation chosen for the predefined floating point types declared in the packages **Standard** and **System**. On all systems other than OpenVMS, the argument must be **IEEE_Float** and the pragma has no effect. On OpenVMS, the argument may be **VAX_Float** to specify the use of the VAX float format for the floating-point types in **Standard**. This requires that the standard runtime libraries be recompiled.

The two argument form specifies the representation to be used for the specified floating-point type. On all systems other than OpenVMS, the argument must be **IEEE_Float** and the pragma has no effect. On OpenVMS, the argument may be **VAX_Float** to specify the use of the VAX float format, as follows:

- For digits values up to 6, F float format will be used.
- For digits values from 7 to 9, D float format will be used.
- For digits values from 10 to 15, G float format will be used.
- Digits values above 15 are not allowed.

Pragma Ident

Syntax:

```
pragma Ident (static_string_EXPRESSION);
```

This pragma provides a string identification in the generated object file, if the system supports the concept of this kind of identification string. This pragma is allowed only in the outermost declarative part or declarative items of a compilation unit. If more than one **Ident** pragma is given, only the last one processed is effective. On OpenVMS systems, the effect of the pragma is identical to the effect of the DEC Ada 83 pragma of the same name. Note that in DEC Ada 83, the maximum allowed length is 31 characters, so if it is important to maintain compatibility with this compiler, you should obey this length limit.

Pragma Implemented

Syntax:

```
pragma Implemented (procedure_LOCAL_NAME, implementation_kind);

implementation_kind ::= By_Entry | By_Protected_Procedure | By_Any
```

This is an Ada 2012 representation pragma which applies to protected, task and synchronized interface primitives. The use of pragma **Implemented** provides a way to impose a static requirement on the overriding operation by adhering to one of the three implementation kinds: entry, protected procedure or any of the above.

```
type Synch_Iface is synchronized interface;
procedure Prim_Op (Obj : in out Iface) is abstract;
pragma Implemented (Prim_Op, By_Protected_Procedure);

protected type Prot_1 is new Synch_Iface with
  procedure Prim_Op; -- Legal
end Prot_1;

protected type Prot_2 is new Synch_Iface with
  entry Prim_Op;     -- Illegal
end Prot_2;
```

```

task type Task_Typ is new Synch_Iface with
  entry Prim_Op;      -- Illegal
end Task_Typ;

```

When applied to the `procedure_or_entry_NAME` of a `requeue` statement, pragma `Implemented` determines the runtime behavior of the `requeue`. Implementation kind `By_Entry` guarantees that the action of `requeueing` will proceed from an entry to another entry. Implementation kind `By_Protected_Procedure` transforms the `requeue` into a dispatching call, thus eliminating the chance of blocking. Kind `By_Any` shares the behavior of `By_Entry` and `By_Protected_Procedure` depending on the target's overriding subprogram kind.

Pragma `Implicit_Packing`

Syntax:

```
pragma Implicit_Packing;
```

This is a configuration pragma that requests implicit packing for packed arrays for which a size clause is given but no explicit pragma `Pack` or specification of `Component_Size` is present. It also applies to records where no record representation clause is present. Consider this example:

```

type R is array (0 .. 7) of Boolean;
for R'Size use 8;

```

In accordance with the recommendation in the RM (RM 13.3(53)), a `Size` clause does not change the layout of a composite object. So the `Size` clause in the above example is normally rejected, since the default layout of the array uses 8-bit components, and thus the array requires a minimum of 64 bits.

If this declaration is compiled in a region of code covered by an occurrence of the configuration pragma `Implicit_Packing`, then the `Size` clause in this and similar examples will cause implicit packing and thus be accepted. For this implicit packing to occur, the type in question must be an array of small components whose size is known at compile time, and the `Size` clause must specify the exact size that corresponds to the length of the array multiplied by the size in bits of the component type.

Similarly, the following example shows the use in the record case

```

type r is record
  a, b, c, d, e, f, g, h : boolean;
  chr                    : character;
end record;
for r'size use 16;

```

Without a pragma `Pack`, each Boolean field requires 8 bits, so the minimum size is 72 bits, but with a pragma `Pack`, 16 bits would be sufficient. The use of pragma `Implicit_Packing` allows this record declaration to compile without an explicit pragma `Pack`.

Pragma `Import_Exception`

Syntax:

```

pragma Import_Exception (
  [Internal =>] LOCAL_NAME
  [, [External =>] EXTERNAL_SYMBOL]
  [, [Form    =>] Ada | VMS]
  [, [Code    =>] static_integer_EXPRESSION]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
  | static_string_EXPRESSION

```

This pragma is implemented only in the OpenVMS implementation of GNAT. It allows OpenVMS conditions (for example, from OpenVMS system services or other OpenVMS languages)

to be propagated to Ada programs as Ada exceptions. The pragma specifies that the exception associated with an exception declaration in an Ada program be defined externally (in non-Ada code). For further details on this pragma, see the DEC Ada Language Reference Manual, section 13.9a.3.1.

Pragma `Import_Function`

Syntax:

```
pragma Import_Function (
    [Internal                =>] LOCAL_NAME,
    [, [External             =>] EXTERNAL_SYMBOL]
    [, [Parameter_Types      =>] PARAMETER_TYPES]
    [, [Result_Type          =>] SUBTYPE_MARK]
    [, [Mechanism            =>] MECHANISM]
    [, [Result_Mechanism     =>] MECHANISM_NAME]
    [, [First_Optional_Parameter =>] IDENTIFIER]);

EXTERNAL_SYMBOL ::=
    IDENTIFIER
| static_string_EXPRESSION

PARAMETER_TYPES ::=
    null
| TYPE_DESIGNATOR {, TYPE_DESIGNATOR}

TYPE_DESIGNATOR ::=
    subtype_NAME
| subtype_Name ' Access

MECHANISM ::=
    MECHANISM_NAME
| (MECHANISM_ASSOCIATION {, MECHANISM_ASSOCIATION})

MECHANISM_ASSOCIATION ::=
    [formal_parameter_NAME =>] MECHANISM_NAME

MECHANISM_NAME ::=
    Value
| Reference
| Descriptor [[([Class =>] CLASS_NAME)]
| Short_Descriptor [[([Class =>] CLASS_NAME)]

CLASS_NAME ::= ubs | ubsb | uba | s | sb | a | nca
```

This pragma is used in conjunction with a pragma `Import` to specify additional information for an imported function. The pragma `Import` (or equivalent pragma `Interface`) must precede the `Import_Function` pragma and both must appear in the same declarative part as the function specification.

The *Internal* argument must uniquely designate the function to which the pragma applies. If more than one function name exists of this name in the declarative part you must use the *Parameter_Types* and *Result_Type* parameters to achieve the required unique designation. Subtype marks in these parameters must exactly match the subtypes in the corresponding function specification, using positional notation to match parameters with subtype marks. The form with an *'Access* attribute can be used to match an anonymous access parameter.

You may optionally use the *Mechanism* and *Result_Mechanism* parameters to specify passing mechanisms for the parameters and result. If you specify a single mechanism name, it applies to all parameters. Otherwise you may specify a mechanism on a parameter by parameter basis using either positional or named notation. If the mechanism is not specified, the default mechanism is used.

Passing by descriptor is supported only on the OpenVMS ports of GNAT. The default behavior for `Import_Function` is to pass a 64bit descriptor unless `short_descriptor` is specified, then a 32bit descriptor is passed.

`First_Optional_Parameter` applies only to OpenVMS ports of GNAT. It specifies that the designated parameter and all following parameters are optional, meaning that they are not passed at the generated code level (this is distinct from the notion of optional parameters in Ada where the parameters are passed anyway with the designated optional parameters). All optional parameters must be of mode `IN` and have default parameter values that are either known at compile time expressions, or uses of the `'Null_Parameter` attribute.

Pragma Import_Object

Syntax:

```
pragma Import_Object
  [Internal =>] LOCAL_NAME
  [, [External =>] EXTERNAL_SYMBOL]
  [, [Size      =>] EXTERNAL_SYMBOL]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
  | static_string_EXPRESSION
```

This pragma designates an object as imported, and apart from the extended rules for external symbols, is identical in effect to the use of the normal `Import` pragma applied to an object. Unlike the subprogram case, you need not use a separate `Import` pragma, although you may do so (and probably should do so from a portability point of view). `size` is syntax checked, but otherwise ignored by GNAT.

Pragma Import_Procedure

Syntax:

```
pragma Import_Procedure (
  [Internal      =>] LOCAL_NAME
  [, [External    =>] EXTERNAL_SYMBOL]
  [, [Parameter_Types =>] PARAMETER_TYPES]
  [, [Mechanism    =>] MECHANISM]
  [, [First_Optional_Parameter =>] IDENTIFIER]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
  | static_string_EXPRESSION

PARAMETER_TYPES ::=
  null
  | TYPE_DESIGNATOR {, TYPE_DESIGNATOR}

TYPE_DESIGNATOR ::=
  subtype_NAME
  | subtype_Name ' Access

MECHANISM ::=
  MECHANISM_NAME
  | (MECHANISM_ASSOCIATION {, MECHANISM_ASSOCIATION})

MECHANISM_ASSOCIATION ::=
  [formal_parameter_NAME =>] MECHANISM_NAME

MECHANISM_NAME ::=
  Value
  | Reference
  | Descriptor [([Class =>] CLASS_NAME)]
```

```
| Short_Descriptor [(Class =>] CLASS_NAME)]
```

```
CLASS_NAME ::= ubs | ubsb | uba | s | sb | a | nca
```

This pragma is identical to `Import_Function` except that it applies to a procedure rather than a function and the parameters `Result_Type` and `Result_Mechanism` are not permitted.

Pragma `Import_Valued_Procedure`

Syntax:

```
pragma Import_Valued_Procedure (
  [Internal                =>] LOCAL_NAME
  [, [External              =>] EXTERNAL_SYMBOL]
  [, [Parameter_Types       =>] PARAMETER_TYPES]
  [, [Mechanism             =>] MECHANISM]
  [, [First_Optional_Parameter =>] IDENTIFIER]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
| static_string_EXPRESSION

PARAMETER_TYPES ::=
  null
| TYPE_DESIGNATOR {, TYPE_DESIGNATOR}

TYPE_DESIGNATOR ::=
  subtype_NAME
| subtype_Name ' Access

MECHANISM ::=
  MECHANISM_NAME
| (MECHANISM_ASSOCIATION {, MECHANISM_ASSOCIATION})

MECHANISM_ASSOCIATION ::=
  [formal_parameter_NAME =>] MECHANISM_NAME

MECHANISM_NAME ::=
  Value
| Reference
| Descriptor [(Class =>] CLASS_NAME)]
| Short_Descriptor [(Class =>] CLASS_NAME)]

CLASS_NAME ::= ubs | ubsb | uba | s | sb | a | nca
```

This pragma is identical to `Import_Procedure` except that the first parameter of *LOCAL_NAME*, which must be present, must be of mode `OUT`, and externally the subprogram is treated as a function with this parameter as the result of the function. The purpose of this capability is to allow the use of `OUT` and `IN OUT` parameters in interfacing to external functions (which are not permitted in Ada functions). You may optionally use the `Mechanism` parameters to specify passing mechanisms for the parameters. If you specify a single mechanism name, it applies to all parameters. Otherwise you may specify a mechanism on a parameter by parameter basis using either positional or named notation. If the mechanism is not specified, the default mechanism is used.

Note that it is important to use this pragma in conjunction with a separate pragma `Import` that specifies the desired convention, since otherwise the default convention is `Ada`, which is almost certainly not what is required.

Pragma `InitializeScalars`

Syntax:

```
pragma InitializeScalars;
```

This pragma is similar to `Normalize_Scalars` conceptually but has two important differences. First, there is no requirement for the pragma to be used uniformly in all units of a partition, in particular, it is fine to use this just for some or all of the application units of a partition, without needing to recompile the run-time library.

In the case where some units are compiled with the pragma, and some without, then a declaration of a variable where the type is defined in package `Standard` or is locally declared will always be subject to initialization, as will any declaration of a scalar variable. For composite variables, whether the variable is initialized may also depend on whether the package in which the type of the variable is declared is compiled with the pragma.

The other important difference is that you can control the value used for initializing scalar objects. At bind time, you can select several options for initialization. You can initialize with invalid values (similar to `Normalize_Scalars`, though for `Initialize_Scalars` it is not always possible to determine the invalid values in complex cases like signed component fields with non-standard sizes). You can also initialize with high or low values, or with a specified bit pattern. See the users guide for binder options for specifying these cases.

This means that you can compile a program, and then without having to recompile the program, you can run it with different values being used for initializing otherwise uninitialized values, to test if your program behavior depends on the choice. Of course the behavior should not change, and if it does, then most likely you have an erroneous reference to an uninitialized value.

It is even possible to change the value at execution time eliminating even the need to rebind with a different switch using an environment variable. See the GNAT users guide for details.

Note that pragma `Initialize_Scalars` is particularly useful in conjunction with the enhanced validity checking that is now provided in GNAT, which checks for invalid values under more conditions. Using this feature (see description of the ‘-gnatV’ flag in the users guide) in conjunction with pragma `Initialize_Scalars` provides a powerful new tool to assist in the detection of problems caused by uninitialized variables.

Note: the use of `Initialize_Scalars` has a fairly extensive effect on the generated code. This may cause your code to be substantially larger. It may also cause an increase in the amount of stack required, so it is probably a good idea to turn on stack checking (see description of stack checking in the GNAT users guide) when using this pragma.

Pragma `Inline_Always`

Syntax:

```
pragma Inline_Always (NAME [, NAME]);
```

Similar to pragma `Inline` except that inlining is not subject to the use of option ‘-gnatn’ and the inlining happens regardless of whether this option is used.

Pragma `Inline_Generic`

Syntax:

```
pragma Inline_Generic (generic_package_NAME);
```

This is implemented for compatibility with DEC Ada 83 and is recognized, but otherwise ignored, by GNAT. All generic instantiations are inlined by default when using GNAT.

Pragma `Interface`

Syntax:

```
pragma Interface (
  [Convention    =>] convention_identifier,
  [Entity        =>] local_NAME
```

```
[, [External_Name =>] static_string_expression]
[, [Link_Name      =>] static_string_expression]);
```

This pragma is identical in syntax and semantics to the standard Ada pragma `Import`. It is provided for compatibility with Ada 83. The definition is upwards compatible both with pragma `Interface` as defined in the Ada 83 Reference Manual, and also with some extended implementations of this pragma in certain Ada 83 implementations. The only difference between pragma `Interface` and pragma `Import` is that there is special circuitry to allow both pragmas to appear for the same subprogram entity (normally it is illegal to have multiple `Import` pragmas. This is useful in maintaining Ada 83/Ada 95 compatibility and is compatible with other Ada 83 compilers.

Pragma Interface_Name

Syntax:

```
pragma Interface_Name (
  [Entity      =>] LOCAL_NAME
  [, [External_Name =>] static_string_EXPRESSION]
  [, [Link_Name   =>] static_string_EXPRESSION]);
```

This pragma provides an alternative way of specifying the interface name for an interfaced subprogram, and is provided for compatibility with Ada 83 compilers that use the pragma for this purpose. You must provide at least one of *External_Name* or *Link_Name*.

Pragma Interrupt_Handler

Syntax:

```
pragma Interrupt_Handler (procedure_LOCAL_NAME);
```

This program unit pragma is supported for parameterless protected procedures as described in Annex C of the Ada Reference Manual. On the AAMP target the pragma can also be specified for nonprotected parameterless procedures that are declared at the library level (which includes procedures declared at the top level of a library package). In the case of AAMP, when this pragma is applied to a nonprotected procedure, the instruction `IERET` is generated for returns from the procedure, enabling maskable interrupts, in place of the normal return instruction.

Pragma Interrupt_State

Syntax:

```
pragma Interrupt_State
  ([Name =>] value,
   [State =>] SYSTEM | RUNTIME | USER);
```

Normally certain interrupts are reserved to the implementation. Any attempt to attach an interrupt causes `Program_Error` to be raised, as described in RM C.3.2(22). A typical example is the `SIGINT` interrupt used in many systems for an *Ctrl-C* interrupt. Normally this interrupt is reserved to the implementation, so that *Ctrl-C* can be used to interrupt execution. Additionally, signals such as `SIGSEGV`, `SIGABRT`, `SIGFPE` and `SIGILL` are often mapped to specific Ada exceptions, or used to implement run-time functions such as the `abort` statement and stack overflow checking.

Pragma `Interrupt_State` provides a general mechanism for overriding such uses of interrupts. It subsumes the functionality of pragma `Unreserve_All_Interrupts`. Pragma `Interrupt_State` is not available on Windows or VMS. On all other platforms than VxWorks, it applies to signals; on VxWorks, it applies to vectored hardware interrupts and may be used to mark interrupts required by the board support package as reserved.

Interrupts can be in one of three states:

- System

The interrupt is reserved (no Ada handler can be installed), and the Ada run-time may not install a handler. As a result you are guaranteed standard system default action if this interrupt is raised.

- Runtime

The interrupt is reserved (no Ada handler can be installed). The run time is allowed to install a handler for internal control purposes, but is not required to do so.

- User

The interrupt is unreserved. The user may install a handler to provide some other action.

These states are the allowed values of the `State` parameter of the pragma. The `Name` parameter is a value of the type `Ada.Interrupts.Interrupt_ID`. Typically, it is a name declared in `Ada.Interrupts.Names`.

This is a configuration pragma, and the binder will check that there are no inconsistencies between different units in a partition in how a given interrupt is specified. It may appear anywhere a pragma is legal.

The effect is to move the interrupt to the specified state.

By declaring interrupts to be `SYSTEM`, you guarantee the standard system action, such as a core dump.

By declaring interrupts to be `USER`, you guarantee that you can install a handler.

Note that certain signals on many operating systems cannot be caught and handled by applications. In such cases, the pragma is ignored. See the operating system documentation, or the value of the array `Reserved` declared in the spec of package `System.OS_Interface`.

Overriding the default state of signals used by the Ada runtime may interfere with an application's runtime behavior in the cases of the synchronous signals, and in the case of the signal used to implement the `abort` statement.

Pragma Invariant

Syntax:

```
pragma Invariant
  ([Entity =>]    private_type_LOCAL_NAME,
   [Check  =>]    EXPRESSION
   [, [Message =>] String_Expression]);
```

This pragma provides exactly the same capabilities as the Invariant aspect defined in AI05-0146-1, and in the Ada 2012 Reference Manual. The Invariant aspect is fully implemented in Ada 2012 mode, but since it requires the use of the aspect syntax, which is not available exception in 2012 mode, it is not possible to use the Invariant aspect in earlier versions of Ada. However the Invariant pragma may be used in any version of Ada.

The pragma must appear within the visible part of the package specification, after the type to which its Entity argument appears. As with the Invariant aspect, the Check expression is not analyzed until the end of the visible part of the package, so it may contain forward references. The Message argument, if present, provides the exception message used if the invariant is violated. If no Message parameter is provided, a default message that identifies the line on which the pragma appears is used.

It is permissible to have multiple Invariants for the same type entity, in which case they are and'ed together. It is permissible to use this pragma in Ada 2012 mode, but you cannot have both an invariant aspect and an invariant pragma for the same entity.

For further details on the use of this pragma, see the Ada 2012 documentation of the Invariant aspect.

Pragma `Keep_Names`

Syntax:

```
pragma Keep_Names ([On =>] enumeration_first_subtype_LOCAL_NAME);
```

The *LOCAL_NAME* argument must refer to an enumeration first subtype in the current declarative part. The effect is to retain the enumeration literal names for use by `Image` and `Value` even if a global `Discard_Names` pragma applies. This is useful when you want to generally suppress enumeration literal names and for example you therefore use a `Discard_Names` pragma in the ‘gnat.adc’ file, but you want to retain the names for specific enumeration types.

Pragma `License`

Syntax:

```
pragma License (Unrestricted | GPL | Modified_GPL | Restricted);
```

This pragma is provided to allow automated checking for appropriate license conditions with respect to the standard and modified GPL. A pragma `License`, which is a configuration pragma that typically appears at the start of a source file or in a separate ‘gnat.adc’ file, specifies the licensing conditions of a unit as follows:

- **Unrestricted** This is used for a unit that can be freely used with no license restrictions. Examples of such units are public domain units, and units from the Ada Reference Manual.
- **GPL** This is used for a unit that is licensed under the unmodified GPL, and which therefore cannot be `with`’ed by a restricted unit.
- **Modified_GPL** This is used for a unit licensed under the GNAT modified GPL that includes a special exception paragraph that specifically permits the inclusion of the unit in programs without requiring the entire program to be released under the GPL.
- **Restricted** This is used for a unit that is restricted in that it is not permitted to depend on units that are licensed under the GPL. Typical examples are proprietary code that is to be released under more restrictive license conditions. Note that restricted units are permitted to `with` units which are licensed under the modified GPL (this is the whole point of the modified GPL).

Normally a unit with no `License` pragma is considered to have an unknown license, and no checking is done. However, standard GNAT headers are recognized, and license information is derived from them as follows.

A GNAT license header starts with a line containing 78 hyphens. The following comment text is searched for the appearance of any of the following strings.

If the string “GNU General Public License” is found, then the unit is assumed to have GPL license, unless the string “As a special exception” follows, in which case the license is assumed to be modified GPL.

If one of the strings “This specification is adapted from the Ada Semantic Interface” or “This specification is derived from the Ada Reference Manual” is found then the unit is assumed to be unrestricted.

These default actions means that a program with a restricted license pragma will automatically get warnings if a GPL unit is inappropriately `with`’ed. For example, the program:

```
with Sem_Ch3;
with GNAT.Sockets;
procedure Secret_Stuff is
...
end Secret_Stuff
```

if compiled with pragma `License (Restricted)` in a ‘gnat.adc’ file will generate the warning:


```

1.  with Sem_Ch3;
    |
    >>> license of withed unit "Sem_Ch3" is incompatible

2.  with GNAT.Sockets;
3.  procedure Secret_Stuff is

```

Here we get a warning on `Sem_Ch3` since it is part of the GNAT compiler and is licensed under the GPL, but no warning for `GNAT.Sockets` which is part of the GNAT run time, and is therefore licensed under the modified GPL.

Pragma Link_With

Syntax:

```
pragma Link_With (static_string_EXPRESSION {,static_string_EXPRESSION});
```

This pragma is provided for compatibility with certain Ada 83 compilers. It has exactly the same effect as pragma `Linker_Options` except that spaces occurring within one of the string expressions are treated as separators. For example, in the following case:

```
pragma Link_With ("-labc -ldef");
```

results in passing the strings `-labc` and `-ldef` as two separate arguments to the linker. In addition pragma `Link_With` allows multiple arguments, with the same effect as successive pragmas.

Pragma Linker_Alias

Syntax:

```
pragma Linker_Alias (
  [Entity =>] LOCAL_NAME,
  [Target =>] static_string_EXPRESSION);
```

LOCAL_NAME must refer to an object that is declared at the library level. This pragma establishes the given entity as a linker alias for the given target. It is equivalent to `__attribute__((alias))` in GNU C and causes *LOCAL_NAME* to be emitted as an alias for the symbol *static_string_EXPRESSION* in the object file, that is to say no space is reserved for *LOCAL_NAME* by the assembler and it will be resolved to the same address as *static_string_EXPRESSION* by the linker.

The actual linker name for the target must be used (e.g. the fully encoded name with qualification in Ada, or the mangled name in C++), or it must be declared using the C convention with pragma `Import` or pragma `Export`.

Not all target machines support this pragma. On some of them it is accepted only if pragma `Weak_External` has been applied to *LOCAL_NAME*.

```

-- Example of the use of pragma Linker_Alias

package p is
  i : Integer := 1;
  pragma Export (C, i);

  new_name_for_i : Integer;
  pragma Linker_Alias (new_name_for_i, "i");
end p;

```

Pragma Linker_Constructor

Syntax:

```
pragma Linker_Constructor (procedure_LOCAL_NAME);
```

procedure_LOCAL_NAME must refer to a parameterless procedure that is declared at the library level. A procedure to which this pragma is applied will be treated as an initialization routine by the linker. It is equivalent to `__attribute__((constructor))` in GNU C and causes

procedure_LOCAL_NAME to be invoked before the entry point of the executable is called (or immediately after the shared library is loaded if the procedure is linked in a shared library), in particular before the Ada run-time environment is set up.

Because of these specific contexts, the set of operations such a procedure can perform is very limited and the type of objects it can manipulate is essentially restricted to the elementary types. In particular, it must only contain code to which pragma Restrictions (No_Elaboration_Code) applies.

This pragma is used by GNAT to implement auto-initialization of shared Stand Alone Libraries, which provides a related capability without the restrictions listed above. Where possible, the use of Stand Alone Libraries is preferable to the use of this pragma.

Pragma Linker_Destructor

Syntax:

```
pragma Linker_Destructor (procedure_LOCAL_NAME);
```

procedure_LOCAL_NAME must refer to a parameterless procedure that is declared at the library level. A procedure to which this pragma is applied will be treated as a finalization routine by the linker. It is equivalent to `__attribute__((destructor))` in GNU C and causes *procedure_LOCAL_NAME* to be invoked after the entry point of the executable has exited (or immediately before the shared library is unloaded if the procedure is linked in a shared library), in particular after the Ada run-time environment is shut down.

See pragma Linker_Constructor for the set of restrictions that apply because of these specific contexts.

Pragma Linker_Section

Syntax:

```
pragma Linker_Section (
  [Entity =>] LOCAL_NAME,
  [Section =>] static_string_EXPRESSION);
```

LOCAL_NAME must refer to an object that is declared at the library level. This pragma specifies the name of the linker section for the given entity. It is equivalent to `__attribute__((section))` in GNU C and causes *LOCAL_NAME* to be placed in the *static_string_EXPRESSION* section of the executable (assuming the linker doesn't rename the section).

The compiler normally places library-level objects in standard sections depending on their type: procedures and functions generally go in the `.text` section, initialized variables in the `.data` section and uninitialized variables in the `.bss` section.

Other, special sections may exist on given target machines to map special hardware, for example I/O ports or flash memory. This pragma is a means to defer the final layout of the executable to the linker, thus fully working at the symbolic level with the compiler.

Some file formats do not support arbitrary sections so not all target machines support this pragma. The use of this pragma may cause a program execution to be erroneous if it is used to place an entity into an inappropriate section (e.g. a modified variable into the `.text` section). See also pragma Persistent_BSS.

```
-- Example of the use of pragma Linker_Section
```

```
package IO_Card is
  Port_A : Integer;
  pragma Volatile (Port_A);
  pragma Linker_Section (Port_A, ".bss.port_a");

  Port_B : Integer;
```

```
pragma Volatile (Port_B);
pragma Linker_Section (Port_B, ".bss.port_b");
end IO_Card;
```

Pragma Long_Float

Syntax:

```
pragma Long_Float (FLOAT_FORMAT);

FLOAT_FORMAT ::= D_Float | G_Float
```

This pragma is implemented only in the OpenVMS implementation of GNAT. It allows control over the internal representation chosen for the predefined type `Long_Float` and for floating point type representations with `digits` specified in the range 7 through 15. For further details on this pragma, see the *DEC Ada Language Reference Manual*, section 3.5.7b. Note that to use this pragma, the standard runtime libraries must be recompiled.

Pragma Machine_Attribute

Syntax:

```
pragma Machine_Attribute (
  [Entity      =>] LOCAL_NAME,
  [Attribute_Name =>] static_string_EXPRESSION
  [, [Info      =>] static_EXPRESSION] );
```

Machine-dependent attributes can be specified for types and/or declarations. This pragma is semantically equivalent to `__attribute__((attribute_name))` (if *info* is not specified) or `__attribute__((attribute_name(info)))` in GNU C, where *attribute_name* is recognized by the compiler middle-end or the `TARGET_ATTRIBUTE_TABLE` machine specific macro. A string literal for the optional parameter *info* is transformed into an identifier, which may make this pragma unusable for some attributes. See [Section “Defining target-specific uses of `\_\_attribute\_`” in *GNU Compiler Collection \(GCC\) Internals*](#), further information.

Pragma Main

Syntax:

```
pragma Main
  (MAIN_OPTION [, MAIN_OPTION]);

MAIN_OPTION ::=
  [Stack_Size      =>] static_integer_EXPRESSION
  | [Task_Stack_Size_Default =>] static_integer_EXPRESSION
  | [Time_Slicing_Enabled   =>] static_boolean_EXPRESSION
```

This pragma is provided for compatibility with OpenVMS VAX Systems. It has no effect in GNAT, other than being syntax checked.

Pragma Main_Storage

Syntax:

```
pragma Main_Storage
  (MAIN_STORAGE_OPTION [, MAIN_STORAGE_OPTION]);

MAIN_STORAGE_OPTION ::=
  [WORKING_STORAGE =>] static_SIMPLE_EXPRESSION
  | [TOP_GUARD      =>] static_SIMPLE_EXPRESSION
```

This pragma is provided for compatibility with OpenVMS VAX Systems. It has no effect in GNAT, other than being syntax checked. Note that the pragma also has no effect in DEC Ada 83 for OpenVMS Alpha Systems.

Pragma No_Body

Syntax:

```
pragma No_Body;
```

There are a number of cases in which a package spec does not require a body, and in fact a body is not permitted. GNAT will not permit the spec to be compiled if there is a body around. The pragma `No_Body` allows you to provide a body file, even in a case where no body is allowed. The body file must contain only comments and a single `No_Body` pragma. This is recognized by the compiler as indicating that no body is logically present.

This is particularly useful during maintenance when a package is modified in such a way that a body needed before is no longer needed. The provision of a dummy body with a `No_Body` pragma ensures that there is no interference from earlier versions of the package body.

Pragma No_Return

Syntax:

```
pragma No_Return (procedure_LOCAL_NAME {, procedure_LOCAL_NAME});
```

Each *procedure_LOCAL_NAME* argument must refer to one or more procedure declarations in the current declarative part. A procedure to which this pragma is applied may not contain any explicit `return` statements. In addition, if the procedure contains any implicit returns from falling off the end of a statement sequence, then execution of that implicit return will cause `Program_Error` to be raised.

One use of this pragma is to identify procedures whose only purpose is to raise an exception. Another use of this pragma is to suppress incorrect warnings about missing returns in functions, where the last statement of a function statement sequence is a call to such a procedure.

Note that in Ada 2005 mode, this pragma is part of the language, and is identical in effect to the pragma as implemented in Ada 95 mode.

Pragma No_Strict_Aliasing

Syntax:

```
pragma No_Strict_Aliasing [(Entity =>] type_LOCAL_NAME);
```

type_LOCAL_NAME must refer to an access type declaration in the current declarative part. The effect is to inhibit strict aliasing optimization for the given type. The form with no arguments is a configuration pragma which applies to all access types declared in units to which the pragma applies. For a detailed description of the strict aliasing optimization, and the situations in which it must be suppressed, see [Section “Optimization and Strict Aliasing” in *GNAT User’s Guide*](#).

Pragma Normalize_Scalars

Syntax:

```
pragma Normalize_Scalars;
```

This is a language defined pragma which is fully implemented in GNAT. The effect is to cause all scalar objects that are not otherwise initialized to be initialized. The initial values are implementation dependent and are as follows:

Standard.Character

Objects whose root type is `Standard.Character` are initialized to `Character’Last` unless the subtype range excludes `NUL` (in which case `NUL` is used). This choice will always generate an invalid value if one exists.

Standard.Wide_Character

Objects whose root type is `Standard.Wide_Character` are initialized to `Wide_Character'Last` unless the subtype range excludes NUL (in which case NUL is used). This choice will always generate an invalid value if one exists.

Standard.Wide_Wide_Character

Objects whose root type is `Standard.Wide_Wide_Character` are initialized to the invalid value `16#FFFF_FFFF#` unless the subtype range excludes NUL (in which case NUL is used). This choice will always generate an invalid value if one exists.

Integer types

Objects of an integer type are treated differently depending on whether negative values are present in the subtype. If no negative values are present, then all one bits is used as the initial value except in the special case where zero is excluded from the subtype, in which case all zero bits are used. This choice will always generate an invalid value if one exists.

For subtypes with negative values present, the largest negative number is used, except in the unusual case where this largest negative number is in the subtype, and the largest positive number is not, in which case the largest positive value is used. This choice will always generate an invalid value if one exists.

Floating-Point Types

Objects of all floating-point types are initialized to all 1-bits. For standard IEEE format, this corresponds to a NaN (not a number) which is indeed an invalid value.

Fixed-Point Types

Objects of all fixed-point types are treated as described above for integers, with the rules applying to the underlying integer value used to represent the fixed-point value.

Modular types

Objects of a modular type are initialized to all one bits, except in the special case where zero is excluded from the subtype, in which case all zero bits are used. This choice will always generate an invalid value if one exists.

Enumeration types

Objects of an enumeration type are initialized to all one-bits, i.e. to the value `2 ** typ'Size - 1` unless the subtype excludes the literal whose Pos value is zero, in which case a code of zero is used. This choice will always generate an invalid value if one exists.

Pragma Obsolescent

Syntax:

```
pragma Obsolescent;

pragma Obsolescent (
  [Message =>] static_string_EXPRESSION
  [, [Version =>] Ada_05]);

pragma Obsolescent (
  [Entity =>] NAME
  [, [Message =>] static_string_EXPRESSION
  [, [Version =>] Ada_05]] );
```

This pragma can occur immediately following a declaration of an entity, including the case of a record component. If no Entity argument is present, then this declaration is the one to which the pragma applies. If an Entity parameter is present, it must either match the name of the

entity in this declaration, or alternatively, the pragma can immediately follow an enumeration type declaration, where the Entity argument names one of the enumeration literals.

This pragma is used to indicate that the named entity is considered obsolescent and should not be used. Typically this is used when an API must be modified by eventually removing or modifying existing subprograms or other entities. The pragma can be used at an intermediate stage when the entity is still present, but will be removed later.

The effect of this pragma is to output a warning message on a reference to an entity thus marked that the subprogram is obsolescent if the appropriate warning option in the compiler is activated. If the Message parameter is present, then a second warning message is given containing this text. In addition, a reference to the entity is considered to be a violation of pragma Restrictions (No_Obsolescent_Features).

This pragma can also be used as a program unit pragma for a package, in which case the entity name is the name of the package, and the pragma indicates that the entire package is considered obsolescent. In this case a client `with`'ing such a package violates the restriction, and the `with` statement is flagged with warnings if the warning option is set.

If the Version parameter is present (which must be exactly the identifier Ada_05, no other argument is allowed), then the indication of obsolescence applies only when compiling in Ada 2005 mode. This is primarily intended for dealing with the situations in the predefined library where subprograms or packages have become defined as obsolescent in Ada 2005 (e.g. in Ada.Characters.Handling), but may be used anywhere.

The following examples show typical uses of this pragma:

```
package p is
  pragma Obsolescent (p, Message => "use pp instead of p");
end p;

package q is
  procedure q2;
  pragma Obsolescent ("use q2new instead");

  type R is new integer;
  pragma Obsolescent
    (Entity => R,
     Message => "use RR in Ada 2005",
     Version => Ada_05);

  type M is record
    F1 : Integer;
    F2 : Integer;
    pragma Obsolescent;
    F3 : Integer;
  end record;

  type E is (a, bc, 'd', quack);
  pragma Obsolescent (Entity => bc)
  pragma Obsolescent (Entity => 'd')

  function "+"
    (a, b : character) return character;
  pragma Obsolescent (Entity => "+");
end;
```

Note that, as for all pragmas, if you use a pragma argument identifier, then all subsequent parameters must also use a pragma argument identifier. So if you specify "Entity =>" for the Entity argument, and a Message argument is present, it must be preceded by "Message =>".

Pragma Optimize_Alignment

Syntax:

```
pragma Optimize_Alignment (TIME | SPACE | OFF);
```

This is a configuration pragma which affects the choice of default alignments for types where no alignment is explicitly specified. There is a time/space trade-off in the selection of these values. Large alignments result in more efficient code, at the expense of larger data space, since sizes have to be increased to match these alignments. Smaller alignments save space, but the access code is slower. The normal choice of default alignments (which is what you get if you do not use this pragma, or if you use an argument of OFF), tries to balance these two requirements.

Specifying SPACE causes smaller default alignments to be chosen in two cases. First any packed record is given an alignment of 1. Second, if a size is given for the type, then the alignment is chosen to avoid increasing this size. For example, consider:

```
type R is record
  X : Integer;
  Y : Character;
end record;

for R'Size use 5*8;
```

In the default mode, this type gets an alignment of 4, so that access to the Integer field X are efficient. But this means that objects of the type end up with a size of 8 bytes. This is a valid choice, since sizes of objects are allowed to be bigger than the size of the type, but it can waste space if for example fields of type R appear in an enclosing record. If the above type is compiled in `Optimize_Alignment (Space)` mode, the alignment is set to 1.

Specifying TIME causes larger default alignments to be chosen in the case of small types with sizes that are not a power of 2. For example, consider:

```
type R is record
  A : Character;
  B : Character;
  C : Boolean;
end record;

pragma Pack (R);
for R'Size use 17;
```

The default alignment for this record is normally 1, but if this type is compiled in `Optimize_Alignment (Time)` mode, then the alignment is set to 4, which wastes space for objects of the type, since they are now 4 bytes long, but results in more efficient access when the whole record is referenced.

As noted above, this is a configuration pragma, and there is a requirement that all units in a partition be compiled with a consistent setting of the optimization setting. This would normally be achieved by use of a configuration pragma file containing the appropriate setting. The exception to this rule is that units with an explicit configuration pragma in the same file as the source unit are excluded from the consistency check, as are all predefined units. The latter are compiled by default in pragma `Optimize_Alignment (Off)` mode if no pragma appears at the start of the file.

Pragma Ordered

Syntax:

```
pragma Ordered (enumeration_first_subtype_LOCAL_NAME);
```

Most enumeration types are from a conceptual point of view unordered. For example, consider:

```
type Color is (Red, Blue, Green, Yellow);
```

By Ada semantics `Blue > Red` and `Green > Blue`, but really these relations make no sense; the enumeration type merely specifies a set of possible colors, and the order is unimportant.

For unordered enumeration types, it is generally a good idea if clients avoid comparisons (other than equality or inequality) and explicit ranges. (A *client* is a unit where the type is

referenced, other than the unit where the type is declared, its body, and its subunits.) For example, if code buried in some client says:

```
if Current_Color < Yellow then ...
if Current_Color in Blue .. Green then ...
```

then the client code is relying on the order, which is undesirable. It makes the code hard to read and creates maintenance difficulties if entries have to be added to the enumeration type. Instead, the code in the client should list the possibilities, or an appropriate subtype should be declared in the unit that declares the original enumeration type. E.g., the following subtype could be declared along with the type `Color`:

```
subtype RGB is Color range Red .. Green;
```

and then the client could write:

```
if Current_Color in RGB then ...
if Current_Color = Blue or Current_Color = Green then ...
```

However, some enumeration types are legitimately ordered from a conceptual point of view. For example, if you declare:

```
type Day is (Mon, Tue, Wed, Thu, Fri, Sat, Sun);
```

then the ordering imposed by the language is reasonable, and clients can depend on it, writing for example:

```
if D in Mon .. Fri then ...
if D < Wed then ...
```

The pragma `'Ordered'` is provided to mark enumeration types that are conceptually ordered, alerting the reader that clients may depend on the ordering. GNAT provides a pragma to mark enumerations as ordered rather than one to mark them as unordered, since in our experience, the great majority of enumeration types are conceptually unordered.

The types `Boolean`, `Character`, `Wide_Character`, and `Wide_Wide_Character` are considered to be ordered types, so each is declared with a pragma `Ordered` in package `Standard`.

Normally pragma `Ordered` serves only as documentation and a guide for coding standards, but GNAT provides a warning switch `'-gnatw.u'` that requests warnings for inappropriate uses (comparisons and explicit subranges) for unordered types. If this switch is used, then any enumeration type not marked with pragma `Ordered` will be considered as unordered, and will generate warnings for inappropriate uses.

For additional information please refer to the description of the `'-gnatw.u'` switch in the GNAT User's Guide.

Pragma Passive

Syntax:

```
pragma Passive [(Semaphore | No)];
```

Syntax checked, but otherwise ignored by GNAT. This is recognized for compatibility with DEC Ada 83 implementations, where it is used within a task definition to request that a task be made passive. If the argument `Semaphore` is present, or the argument is omitted, then DEC Ada 83 treats the pragma as an assertion that the containing task is passive and that optimization of context switch with this task is permitted and desired. If the argument `No` is present, the task must not be optimized. GNAT does not attempt to optimize any tasks in this manner (since protected objects are available in place of passive tasks).

Pragma Persistent_BSS

Syntax:

```
pragma Persistent_BSS [(LOCAL_NAME)]
```

This pragma allows selected objects to be placed in the `.persistent_bss` section. On some targets the linker and loader provide for special treatment of this section, allowing a program to be reloaded without affecting the contents of this data (hence the name persistent).

There are two forms of usage. If an argument is given, it must be the local name of a library level object, with no explicit initialization and whose type is potentially persistent. If no argument is given, then the pragma is a configuration pragma, and applies to all library level objects with no explicit initialization of potentially persistent types.

A potentially persistent type is a scalar type, or a non-tagged, non-discriminated record, all of whose components have no explicit initialization and are themselves of a potentially persistent type, or an array, all of whose constraints are static, and whose component type is potentially persistent.

If this pragma is used on a target where this feature is not supported, then the pragma will be ignored. See also `pragma Linker_Section`.

Pragma Polling

Syntax:

```
pragma Polling (ON | OFF);
```

This pragma controls the generation of polling code. This is normally off. If `pragma Polling (ON)` is used then periodic calls are generated to the routine `Ada.Exceptions.Poll`. This routine is a separate unit in the runtime library, and can be found in file `'a-excpol.adb'`.

`Pragma Polling` can appear as a configuration pragma (for example it can be placed in the `'gnat.adc'` file) to enable polling globally, or it can be used in the statement or declaration sequence to control polling more locally.

A call to the polling routine is generated at the start of every loop and at the start of every subprogram call. This guarantees that the `Poll` routine is called frequently, and places an upper bound (determined by the complexity of the code) on the period between two `Poll` calls.

The primary purpose of the polling interface is to enable asynchronous aborts on targets that cannot otherwise support it (for example Windows NT), but it may be used for any other purpose requiring periodic polling. The standard version is null, and can be replaced by a user program. This will require re-compilation of the `Ada.Exceptions` package that can be found in files `'a-except.ads'` and `'a-except.adb'`.

A standard alternative unit (in file `'4wexcpol.adb'` in the standard GNAT distribution) is used to enable the asynchronous abort capability on targets that do not normally support the capability. The version of `Poll` in this file makes a call to the appropriate runtime routine to test for an abort condition.

Note that polling can also be enabled by use of the `'-gnatP'` switch. See [Section “Switches for gcc” in *GNAT User's Guide*](#), for details.

Pragma Postcondition

Syntax:

```
pragma Postcondition (
  [Check =>] Boolean_Expression
  [, [Message =>] String_Expression]);
```

The `Postcondition` pragma allows specification of automatic postcondition checks for subprograms. These checks are similar to assertions, but are automatically inserted just prior to the return statements of the subprogram with which they are associated (including implicit returns at the end of procedure bodies and associated exception handlers).

In addition, the boolean expression which is the condition which must be true may contain references to function'Result in the case of a function to refer to the returned value.

Postcondition pragmas may appear either immediately following the (separate) declaration of a subprogram, or at the start of the declarations of a subprogram body. Only other pragmas may intervene (that is appear between the subprogram declaration and its postconditions, or appear before the postcondition in the declaration sequence in a subprogram body). In the case of a postcondition appearing after a subprogram declaration, the formal arguments of the subprogram are visible, and can be referenced in the postcondition expressions.

The postconditions are collected and automatically tested just before any return (implicit or explicit) in the subprogram body. A postcondition is only recognized if postconditions are active at the time the pragma is encountered. The compiler switch '**gnata**' turns on all postconditions by default, and pragma **Check_Policy** with an identifier of **Postcondition** can also be used to control whether postconditions are active.

The general approach is that postconditions are placed in the spec if they represent functional aspects which make sense to the client. For example we might have:

```
function Direction return Integer;
pragma Postcondition
  (Direction'Result = +1
   or else
    Direction'Result = -1);
```

which serves to document that the result must be +1 or -1, and will test that this is the case at run time if postcondition checking is active.

Postconditions within the subprogram body can be used to check that some internal aspect of the implementation, not visible to the client, is operating as expected. For instance if a square root routine keeps an internal counter of the number of times it is called, then we might have the following postcondition:

```
Sqrt_Calls : Natural := 0;

function Sqrt (Arg : Float) return Float is
  pragma Postcondition
    (Sqrt_Calls = Sqrt_Calls'Old + 1);
  ...
end Sqrt
```

As this example, shows, the use of the **Old** attribute is often useful in postconditions to refer to the state on entry to the subprogram.

Note that postconditions are only checked on normal returns from the subprogram. If an abnormal return results from raising an exception, then the postconditions are not checked.

If a postcondition fails, then the exception **System.Assertions.Assert_Failure** is raised. If a message argument was supplied, then the given string will be used as the exception message. If no message argument was supplied, then the default message has the form "Postcondition failed at file:line". The exception is raised in the context of the subprogram body, so it is possible to catch postcondition failures within the subprogram body itself.

Within a package spec, normal visibility rules in Ada would prevent forward references within a postcondition pragma to functions defined later in the same package. This would introduce undesirable ordering constraints. To avoid this problem, all postcondition pragmas are analyzed at the end of the package spec, allowing forward references.

The following example shows that this even allows mutually recursive postconditions as in:

```
package Parity_Functions is
  function Odd (X : Natural) return Boolean;
  pragma Postcondition
    (Odd'Result =
     (x = 1
      or else
       (x /= 0 and then Even (X - 1))));
```

```

function Even (X : Natural) return Boolean;
pragma Postcondition
  (Even'Result =
    (x = 0
     or else
     (x /= 1 and then Odd (X - 1))));

end Parity_Functions;

```

There are no restrictions on the complexity or form of conditions used within `Postcondition` pragmas. The following example shows that it is even possible to verify performance behavior.

```

package Sort is

  Performance : constant Float;
  -- Performance constant set by implementation
  -- to match target architecture behavior.

  procedure Treesort (Arg : String);
  -- Sorts characters of argument using N*logN sort
  pragma Postcondition
    (Float (Clock - Clock'Old) <=
     Float (Arg'Length) *
     log (Float (Arg'Length)) *
     Performance);
end Sort;

```

Note: postcondition pragmas associated with subprograms that are marked as `Inline_Always`, or those marked as `Inline` with front-end inlining (`-gnatN` option set) are accepted and legality-checked by the compiler, but are ignored at run-time even if postcondition checking is enabled.

Pragma Precondition

Syntax:

```

pragma Precondition (
  [Check =>] Boolean_Expression
  [, [Message =>] String_Expression]);

```

The `Precondition` pragma is similar to `Postcondition` except that the corresponding checks take place immediately upon entry to the subprogram, and if a precondition fails, the exception is raised in the context of the caller, and the attribute `'Result` cannot be used within the precondition expression.

Otherwise, the placement and visibility rules are identical to those described for postconditions. The following is an example of use within a package spec:

```

package Math_Functions is
  ...
  function Sqrt (Arg : Float) return Float;
  pragma Precondition (Arg >= 0.0)
  ...
end Math_Functions;

```

`Precondition` pragmas may appear either immediately following the (separate) declaration of a subprogram, or at the start of the declarations of a subprogram body. Only other pragmas may intervene (that is appear between the subprogram declaration and its postconditions, or appear before the postcondition in the declaration sequence in a subprogram body).

Note: postcondition pragmas associated with subprograms that are marked as `Inline_Always`, or those marked as `Inline` with front-end inlining (`-gnatN` option set) are accepted and legality-checked by the compiler, but are ignored at run-time even if postcondition checking is enabled.

Pragma Profile (Ravenscar)

Syntax:

```
pragma Profile (Ravenscar);
```

A configuration pragma that establishes the following set of configuration pragmas:

Task_Dispatching_Policy (FIFO_Within_Priorities)

[RM D.2.2] Tasks are dispatched following a preemptive priority-ordered scheduling policy.

Locking_Policy (Ceiling_Locking)

[RM D.3] While tasks and interrupts execute a protected action, they inherit the ceiling priority of the corresponding protected object.

plus the following set of restrictions:

Max_Entry_Queue_Length = 1

Defines the maximum number of calls that are queued on a (protected) entry. Note that this restriction is checked at run time. Violation of this restriction results in the raising of Program_Error exception at the point of the call. For the Profile (Ravenscar) the value of Max_Entry_Queue_Length is always 1 and hence no task can be queued on a protected entry.

Max_Protected_Entries = 1

[RM D.7] Specifies the maximum number of entries per protected type. The bounds of every entry family of a protected unit shall be static, or shall be defined by a discriminant of a subtype whose corresponding bound is static. For the Profile (Ravenscar) the value of Max_Protected_Entries is always 1.

Max_Task_Entries = 0

[RM D.7] Specifies the maximum number of entries per task. The bounds of every entry family of a task unit shall be static, or shall be defined by a discriminant of a subtype whose corresponding bound is static. A value of zero indicates that no rendezvous are possible. For the Profile (Ravenscar), the value of Max_Task_Entries is always 0 (zero).

No_Abort_Statements

[RM D.7] There are no abort_statements, and there are no calls to Task_Identification.Abort_Task.

No_Asynchronous_Control

There are no semantic dependences on the package Asynchronous_Task_Control.

No_Calendar

There are no semantic dependencies on the package Ada.Calendar.

No_Dynamic_Attachment

There is no call to any of the operations defined in package Ada.Interrupts (Is_Reserved, Is_Attached, Current_Handler, Attach_Handler, Exchange_Handler, Detach_Handler, and Reference).

No_Dynamic_Priorities

[RM D.7] There are no semantic dependencies on the package Dynamic_Priorities.

No_Implicit_Heap_Allocations

[RM D.7] No constructs are allowed to cause implicit heap allocation.

No_Local_Protected_Objects

Protected objects and access types that designate such objects shall be declared only at library level.

No_Local_Timing_Events

[RM D.7] All objects of type `Ada.Timing_Events.Timing_Event` are declared at the library level.

No_Protected_Type_Allocators

There are no allocators for protected types or types containing protected subcomponents.

No_Relative_Delay

There are no `delay_relative` statements.

No_Requeue_Statements

Requeue statements are not allowed.

No_Select_Statements

There are no `select` statements.

No_Specific_Termination_Handlers

[RM D.7] There are no calls to `Ada.Task_Termination.Set_Specific_Handler` or to `Ada.Task_Termination.Specific_Handler`.

No_Task_Allocators

[RM D.7] There are no allocators for task types or types containing task subcomponents.

No_Task_Attributes_Package

There are no semantic dependencies on the `Ada.Task_Attributes` package.

No_Task_Hierarchy

[RM D.7] All (non-environment) tasks depend directly on the environment task of the partition.

No_Task_Termination

Tasks which terminate are erroneous.

No_Unchecked_Conversion

There are no semantic dependencies on the `Ada.Unchecked_Conversion` package.

No_Unchecked_Deallocation

There are no semantic dependencies on the `Ada.Unchecked_Deallocation` package.

Simple_Barriers

Entry barrier condition expressions shall be either static boolean expressions or boolean objects which are declared in the protected type which contains the entry.

This set of configuration pragmas and restrictions correspond to the definition of the “Ravenscar Profile” for limited tasking, devised and published by the *International Real-Time Ada Workshop*, 1997, and whose most recent description is available at <http://www-users.cs.york.ac.uk/~burns/ravenscar.ps>.

The original definition of the profile was revised at subsequent IRTAW meetings. It has been included in the ISO *Guide for the Use of the Ada Programming Language in High Integrity Systems*, and has been approved by ISO/IEC/SC22/WG9 for inclusion in the next revision of the standard. The formal definition given by the Ada Rapporteur Group (ARG) can be found in two Ada Issues (AI-249 and AI-305) available at <http://www.ada-auth.org/cgi-bin/cvsweb.cgi/AIs/AI-00249.TXT> and <http://www.ada-auth.org/cgi-bin/cvsweb.cgi/AIs/AI-00305.TXT> respectively.

The above set is a superset of the restrictions provided by pragma `Profile (Restricted)`, it includes six additional restrictions (`Simple_Barriers`, `No_Select_Statements`, `No_Calendar`, `No_Implicit_Heap_Allocations`, `No_Relative_Delay` and `No_Task_Termination`). This

means that `pragma Profile (Ravenscar)`, like the `pragma Profile (Restricted)`, automatically causes the use of a simplified, more efficient version of the tasking run-time system.

Pragma Profile (Restricted)

Syntax:

```
pragma Profile (Restricted);
```

A configuration pragma that establishes the following set of restrictions:

- No_Abort_Statements
- No_Entry_Queue
- No_Task_Hierarchy
- No_Task_Allocators
- No_Dynamic_Priorities
- No_Terminate_Alternatives
- No_Dynamic_Attachment
- No_Protected_Type_Allocators
- No_Local_Protected_Objects
- No_Requeue_Statements
- No_Task_Attributes_Package
- Max_Asynchronous_Select_Nesting = 0
- Max_Task_Entries = 0
- Max_Protected_Entries = 1
- Max_Select_Alternatives = 0

This set of restrictions causes the automatic selection of a simplified version of the run time that provides improved performance for the limited set of tasking functionality permitted by this set of restrictions.

Pragma Psect_Object

Syntax:

```
pragma Psect_Object (
  [Internal =>] LOCAL_NAME,
  [, [External =>] EXTERNAL_SYMBOL]
  [, [Size      =>] EXTERNAL_SYMBOL]);

EXTERNAL_SYMBOL ::=
  IDENTIFIER
  | static_string_EXPRESSION
```

This pragma is identical in effect to `pragma Common_Object`.

Pragma Pure_Function

Syntax:

```
pragma Pure_Function ([Entity =>] function_LOCAL_NAME);
```

This pragma appears in the same declarative part as a function declaration (or a set of function declarations if more than one overloaded declaration exists, in which case the pragma applies to all entities). It specifies that the function `Entity` is to be considered pure for the purposes of code generation. This means that the compiler can assume that there are no side effects, and in

particular that two calls with identical arguments produce the same result. It also means that the function can be used in an address clause.

Note that, quite deliberately, there are no static checks to try to ensure that this promise is met, so `Pure_Function` can be used with functions that are conceptually pure, even if they do modify global variables. For example, a square root function that is instrumented to count the number of times it is called is still conceptually pure, and can still be optimized, even though it modifies a global variable (the count). Memo functions are another example (where a table of previous calls is kept and consulted to avoid re-computation).

Note also that the normal rules excluding optimization of subprograms in pure units (when parameter types are descended from `System.Address`, or when the full view of a parameter type is limited), do not apply for the `Pure_Function` case. If you explicitly specify `Pure_Function`, the compiler may optimize away calls with identical arguments, and if that results in unexpected behavior, the proper action is not to use the pragma for subprograms that are not (conceptually) pure.

Note: Most functions in a `Pure` package are automatically pure, and there is no need to use pragma `Pure_Function` for such functions. One exception is any function that has at least one formal of type `System.Address` or a type derived from it. Such functions are not considered pure by default, since the compiler assumes that the `Address` parameter may be functioning as a pointer and that the referenced data may change even if the address value does not. Similarly, imported functions are not considered to be pure by default, since there is no way of checking that they are in fact pure. The use of pragma `Pure_Function` for such a function will override these default assumption, and cause the compiler to treat a designated subprogram as pure in these cases.

Note: If pragma `Pure_Function` is applied to a renamed function, it applies to the underlying renamed function. This can be used to disambiguate cases of overloading where some but not all functions in a set of overloaded functions are to be designated as pure.

If pragma `Pure_Function` is applied to a library level function, the function is also considered pure from an optimization point of view, but the unit is not a `Pure` unit in the categorization sense. So for example, a function thus marked is free to `with` non-pure units.

Pragma `Restriction_Warnings`

Syntax:

```
pragma Restriction_Warnings
  (restriction_IDENTIFIER {, restriction_IDENTIFIER});
```

This pragma allows a series of restriction identifiers to be specified (the list of allowed identifiers is the same as for pragma `Restrictions`). For each of these identifiers the compiler checks for violations of the restriction, but generates a warning message rather than an error message if the restriction is violated.

Pragma `Shared`

This pragma is provided for compatibility with Ada 83. The syntax and semantics are identical to pragma `Atomic`.

Pragma `Short_Circuit_And_Or`

This configuration pragma causes any occurrence of the `AND` operator applied to operands of type `Standard.Boolean` to be short-circuited (i.e. the `AND` operator is treated as if it were `AND THEN`). Or is similarly treated as `OR ELSE`. This may be useful in the context of certification protocols requiring the use of short-circuited logical operators. If this configuration pragma occurs locally within the file being compiled, it applies only to the file being compiled. There is no requirement that all units in a partition use this option.

Pragma Short_Descriptors

Syntax:

```
pragma Short_Descriptors
```

In VMS versions of the compiler, this configuration pragma causes all occurrences of the mechanism types `Descriptor[_xxx]` to be treated as `Short_Descriptor[_xxx]`. This is helpful in porting legacy applications from a 32-bit environment to a 64-bit environment. This pragma is ignored for non-VMS versions.

Pragma Source_File_Name

Syntax:

```
pragma Source_File_Name (
  [Unit_Name =>] unit_NAME,
  Spec_File_Name => STRING_LITERAL,
  [Index => INTEGER_LITERAL]);

pragma Source_File_Name (
  [Unit_Name =>] unit_NAME,
  Body_File_Name => STRING_LITERAL,
  [Index => INTEGER_LITERAL]);
```

Use this to override the normal naming convention. It is a configuration pragma, and so has the usual applicability of configuration pragmas (i.e. it applies to either an entire partition, or to all units in a compilation, or to a single unit, depending on how it is used. *unit_name* is mapped to *file_name_literal*. The identifier for the second argument is required, and indicates whether this is the file name for the spec or for the body.

The optional `Index` argument should be used when a file contains multiple units, and when you do not want to use `gnatchop` to separate them into multiple files (which is the recommended procedure to limit the number of recompilations that are needed when some sources change). For instance, if the source file ‘`source.adb`’ contains

```
package B is
...
end B;

with B;
procedure A is
begin
..
end A;
```

you could use the following configuration pragmas:

```
pragma Source_File_Name
  (B, Spec_File_Name => "source.adb", Index => 1);
pragma Source_File_Name
  (A, Body_File_Name => "source.adb", Index => 2);
```

Note that the `gnatname` utility can also be used to generate those configuration pragmas.

Another form of the `Source_File_Name` pragma allows the specification of patterns defining alternative file naming schemes to apply to all files.

```
pragma Source_File_Name
  ( [Spec_File_Name =>] STRING_LITERAL
    [, [Casing      =>] CASING_SPEC]
    [, [Dot_Replacement =>] STRING_LITERAL]);

pragma Source_File_Name
  ( [Body_File_Name =>] STRING_LITERAL
    [, [Casing      =>] CASING_SPEC]
    [, [Dot_Replacement =>] STRING_LITERAL]);
```

```
pragma Source_File_Name
( [Subunit_File_Name =>] STRING_LITERAL
  [, [Casing          =>] CASING_SPEC]
  [, [Dot_Replacement =>] STRING_LITERAL]);

CASING_SPEC ::= Lowercase | Uppercase | Mixedcase
```

The first argument is a pattern that contains a single asterisk indicating the point at which the unit name is to be inserted in the pattern string to form the file name. The second argument is optional. If present it specifies the casing of the unit name in the resulting file name string. The default is lower case. Finally the third argument allows for systematic replacement of any dots in the unit name by the specified string literal.

A pragma `Source_File_Name` cannot appear after a [\[Pragma Source_File_Name_Project\]](#), [page 45](#).

For more details on the use of the `Source_File_Name` pragma, See [Section “Using Other File Names” in *GNAT User’s Guide*](#), and [Section “Alternative File Naming Schemes” in *GNAT User’s Guide*](#).

Pragma Source_File_Name_Project

This pragma has the same syntax and semantics as pragma `Source_File_Name`. It is only allowed as a stand alone configuration pragma. It cannot appear after a [\[Pragma Source_File_Name\]](#), [page 44](#), and most importantly, once pragma `Source_File_Name_Project` appears, no further `Source_File_Name` pragmas are allowed.

The intention is that `Source_File_Name_Project` pragmas are always generated by the Project Manager in a manner consistent with the naming specified in a project file, and when naming is controlled in this manner, it is not permissible to attempt to modify this naming scheme using `Source_File_Name` pragmas (which would not be known to the project manager).

Pragma Source_Reference

Syntax:

```
pragma Source_Reference (INTEGER_LITERAL, STRING_LITERAL);
```

This pragma must appear as the first line of a source file. *integer_literal* is the logical line number of the line following the pragma line (for use in error messages and debugging information). *string_literal* is a static string constant that specifies the file name to be used in error messages and debugging information. This is most notably used for the output of `gnatchop` with the ‘-r’ switch, to make sure that the original unchopped source file is the one referred to.

The second argument must be a string literal, it cannot be a static string expression other than a string literal. This is because its value is needed for error messages issued by all phases of the compiler.

Pragma Stream_Convert

Syntax:

```
pragma Stream_Convert (
  [Entity =>] type_LOCAL_NAME,
  [Read   =>] function_NAME,
  [Write  =>] function_NAME);
```

This pragma provides an efficient way of providing stream functions for types defined in packages. Not only is it simpler to use than declaring the necessary functions with attribute representation clauses, but more significantly, it allows the declaration to be made in such a way that the stream packages are not loaded unless they are needed. The use of the `Stream_Convert` pragma adds no overhead at all, unless the stream attributes are actually used on the designated type.

The first argument specifies the type for which stream functions are provided. The second parameter provides a function used to read values of this type. It must name a function whose argument type may be any subtype, and whose returned type must be the type given as the first argument to the pragma.

The meaning of the *Read* parameter is that if a stream attribute directly or indirectly specifies reading of the type given as the first parameter, then a value of the type given as the argument to the Read function is read from the stream, and then the Read function is used to convert this to the required target type.

Similarly the *Write* parameter specifies how to treat write attributes that directly or indirectly apply to the type given as the first parameter. It must have an input parameter of the type specified by the first parameter, and the return type must be the same as the input type of the Read function. The effect is to first call the Write function to convert to the given stream type, and then write the result type to the stream.

The Read and Write functions must not be overloaded subprograms. If necessary renamings can be supplied to meet this requirement. The usage of this attribute is best illustrated by a simple example, taken from the GNAT implementation of package Ada.Strings.Unbounded:

```
function To_Unbounded (S : String)
    return Unbounded_String
renames To_Unbounded_String;

pragma Stream_Convert
(Unbounded_String, To_Unbounded, To_String);
```

The specifications of the referenced functions, as given in the Ada Reference Manual are:

```
function To_Unbounded_String (Source : String)
    return Unbounded_String;

function To_String (Source : Unbounded_String)
    return String;
```

The effect is that if the value of an unbounded string is written to a stream, then the representation of the item in the stream is in the same format that would be used for `Standard.String'Output`, and this same representation is expected when a value of this type is read from the stream. Note that the value written always includes the bounds, even for `Unbounded_String'Write`, since `Unbounded_String` is not an array type.

Pragma Style_Checks

Syntax:

```
pragma Style_Checks (string_LITERAL | ALL_CHECKS |
    On | Off [, LOCAL_NAME]);
```

This pragma is used in conjunction with compiler switches to control the built in style checking provided by GNAT. The compiler switches, if set, provide an initial setting for the switches, and this pragma may be used to modify these settings, or the settings may be provided entirely by the use of the pragma. This pragma can be used anywhere that a pragma is legal, including use as a configuration pragma (including use in the `'gnat.adc'` file).

The form with a string literal specifies which style options are to be activated. These are additive, so they apply in addition to any previously set style check options. The codes for the options are the same as those used in the `'-gnaty'` switch to `gcc` or `gnatmake`. For example the following two methods can be used to enable layout checking:

- ```
pragma Style_Checks ("l");
```
- ```
gcc -c -gnatyl ...
```

The form `ALL_CHECKS` activates all standard checks (its use is equivalent to the use of the `gnaty` switch with no options. See [Section “About This Guide” in *GNAT User’s Guide*](#), for details.)

Note: the behavior is slightly different in GNAT mode (`-gnatg` used). In this case, `ALL_CHECKS` implies the standard set of GNAT mode style check options (i.e. equivalent to `-gnatyg`).

The forms with `Off` and `On` can be used to temporarily disable style checks as shown in the following example:

```
pragma Style_Checks ("k"); -- requires keywords in lower case
pragma Style_Checks (Off); -- turn off style checks
NULL;                      -- this will not generate an error message
pragma Style_Checks (On);  -- turn style checks back on
NULL;                      -- this will generate an error message
```

Finally the two argument form is allowed only if the first argument is `On` or `Off`. The effect is to turn of semantic style checks for the specified entity, as shown in the following example:

```
pragma Style_Checks ("r"); -- require consistency of identifier casing
Arg : Integer;
Rf1 : Integer := ARG;      -- incorrect, wrong case
pragma Style_Checks (Off, Arg);
Rf2 : Integer := ARG;      -- OK, no error
```

Pragma Subtitle

Syntax:

```
pragma Subtitle ([Subtitle =>] STRING_LITERAL);
```

This pragma is recognized for compatibility with other Ada compilers but is ignored by GNAT.

Pragma Suppress

Syntax:

```
pragma Suppress (Identifier [, [On =>] Name]);
```

This is a standard pragma, and supports all the check names required in the RM. It is included here because GNAT recognizes one additional check name: `Alignment_Check` which can be used to suppress alignment checks on addresses used in address clauses. Such checks can also be suppressed by suppressing range checks, but the specific use of `Alignment_Check` allows suppression of alignment checks without suppressing other range checks.

Note that pragma `Suppress` gives the compiler permission to omit checks, but does not require the compiler to omit checks. The compiler will generate checks if they are essentially free, even when they are suppressed. In particular, if the compiler can prove that a certain check will necessarily fail, it will generate code to do an unconditional “raise”, even if checks are suppressed. The compiler warns in this case.

Of course, run-time checks are omitted whenever the compiler can prove that they will not fail, whether or not checks are suppressed.

Pragma Suppress_All

Syntax:

```
pragma Suppress_All;
```

This pragma can appear anywhere within a unit. The effect is to apply `Suppress (All_Checks)` to the unit in which it appears. This pragma is implemented for compatibility with DEC Ada

83 usage where it appears at the end of a unit, and for compatibility with Rational Ada, where it appears as a program unit pragma. The use of the standard Ada pragma `Suppress (All_Checks)` as a normal configuration pragma is the preferred usage in GNAT.

Pragma `Suppress_Exception_Locations`

Syntax:

```
pragma Suppress_Exception_Locations;
```

In normal mode, a raise statement for an exception by default generates an exception message giving the file name and line number for the location of the raise. This is useful for debugging and logging purposes, but this entails extra space for the strings for the messages. The configuration pragma `Suppress_Exception_Locations` can be used to suppress the generation of these strings, with the result that space is saved, but the exception message for such raises is null. This configuration pragma may appear in a global configuration pragma file, or in a specific unit as usual. It is not required that this pragma be used consistently within a partition, so it is fine to have some units within a partition compiled with this pragma and others compiled in normal mode without it.

Pragma `Suppress_Initialization`

Syntax:

```
pragma Suppress_Initialization ([Entity =>] type_Name);
```

This pragma suppresses any implicit or explicit initialization associated with the given type name for all variables of this type.

Pragma `Task_Info`

Syntax

```
pragma Task_Info (EXPRESSION);
```

This pragma appears within a task definition (like pragma `Priority`) and applies to the task in which it appears. The argument must be of type `System.Task_Info.Task_Info_Type`. The `Task_Info` pragma provides system dependent control over aspects of tasking implementation, for example, the ability to map tasks to specific processors. For details on the facilities available for the version of GNAT that you are using, see the documentation in the spec of package `System.Task_Info` in the runtime library.

Pragma `Task_Name`

Syntax

```
pragma Task_Name (string_EXPRESSION);
```

This pragma appears within a task definition (like pragma `Priority`) and applies to the task in which it appears. The argument must be of type `String`, and provides a name to be used for the task instance when the task is created. Note that this expression is not required to be static, and in particular, it can contain references to task discriminants. This facility can be used to provide different names for different tasks as they are created, as illustrated in the example below.

The task name is recorded internally in the run-time structures and is accessible to tools like the debugger. In addition the routine `Ada.Task_Identification.Image` will return this string, with a unique task address appended.

```
-- Example of the use of pragma Task_Name

with Ada.Task_Identification;
use Ada.Task_Identification;
```

```

with Text_IO; use Text_IO;
procedure t3 is

  type Astring is access String;

  task type Task_Typ (Name : access String) is
    pragma Task_Name (Name.all);
  end Task_Typ;

  task body Task_Typ is
    Nam : constant String := Image (Current_Task);
  begin
    Put_Line ("-->" & Nam (1 .. 14) & "<--");
  end Task_Typ;

  type Ptr_Task is access Task_Typ;
  Task_Var : Ptr_Task;

begin
  Task_Var :=
    new Task_Typ (new String'("This is task 1"));
  Task_Var :=
    new Task_Typ (new String'("This is task 2"));
end;

```

Pragma Task_Storage

Syntax:

```

pragma Task_Storage (
  [Task_Type =>] LOCAL_NAME,
  [Top_Guard =>] static_integer_EXPRESSION);

```

This pragma specifies the length of the guard area for tasks. The guard area is an additional storage area allocated to a task. A value of zero means that either no guard area is created or a minimal guard area is created, depending on the target. This pragma can appear anywhere a `Storage_Size` attribute definition clause is allowed for a task type.

Pragma Thread_Local_Storage

Syntax:

```

pragma Thread_Local_Storage ([Entity =>] LOCAL_NAME);

```

This pragma specifies that the specified entity, which must be a variable declared in a library level package, is to be marked as "Thread Local Storage" (TLS). On systems supporting this (which include Solaris, GNU/Linux and VxWorks 6), this causes each thread (and hence each Ada task) to see a distinct copy of the variable.

The variable may not have default initialization, and if there is an explicit initialization, it must be either `null` for an access variable, or a static expression for a scalar variable. This provides a low level mechanism similar to that provided by the `Ada.Task_Attributes` package, but much more efficient and is also useful in writing interface code that will interact with foreign threads.

If this pragma is used on a system where TLS is not supported, then an error message will be generated and the program will be rejected.

Pragma Time_Slice

Syntax:

```

pragma Time_Slice (static_duration_EXPRESSION);

```

For implementations of GNAT on operating systems where it is possible to supply a time slice value, this pragma may be used for this purpose. It is ignored if it is used in a system that does

not allow this control, or if it appears in other than the main program unit. Note that the effect of this pragma is identical to the effect of the DEC Ada 83 pragma of the same name when operating under OpenVMS systems.

Pragma Title

Syntax:

```
pragma Title (TITLING_OPTION [, TITLING_OPTION]);

TITLING_OPTION ::=
  [Title    =>] STRING_LITERAL,
  | [Subtitle =>] STRING_LITERAL
```

Syntax checked but otherwise ignored by GNAT. This is a listing control pragma used in DEC Ada 83 implementations to provide a title and/or subtitle for the program listing. The program listing generated by GNAT does not have titles or subtitles.

Unlike other pragmas, the full flexibility of named notation is allowed for this pragma, i.e. the parameters may be given in any order if named notation is used, and named and positional notation can be mixed following the normal rules for procedure calls in Ada.

Pragma Unchecked_Union

Syntax:

```
pragma Unchecked_Union (first_subtype_LOCAL_NAME);
```

This pragma is used to specify a representation of a record type that is equivalent to a C union. It was introduced as a GNAT implementation defined pragma in the GNAT Ada 95 mode. Ada 2005 includes an extended version of this pragma, making it language defined, and GNAT fully implements this extended version in all language modes (Ada 83, Ada 95, and Ada 2005). For full details, consult the Ada 2005 Reference Manual, section B.3.3.

Pragma Unimplemented_Unit

Syntax:

```
pragma Unimplemented_Unit;
```

If this pragma occurs in a unit that is processed by the compiler, GNAT aborts with the message ‘xxx not implemented’, where xxx is the name of the current compilation unit. This pragma is intended to allow the compiler to handle unimplemented library units in a clean manner.

The abort only happens if code is being generated. Thus you can use specs of unimplemented packages in syntax or semantic checking mode.

Pragma Universal_Aliasing

Syntax:

```
pragma Universal_Aliasing [(Entity =>] type_LOCAL_NAME];
```

type_LOCAL_NAME must refer to a type declaration in the current declarative part. The effect is to inhibit strict type-based aliasing optimization for the given type. In other words, the effect is as though access types designating this type were subject to pragma No_Strict_Aliasing. For a detailed description of the strict aliasing optimization, and the situations in which it must be suppressed, See [Section “Optimization and Strict Aliasing” in *GNAT User’s Guide*](#).

Pragma `Universal_Data`

Syntax:

```
pragma Universal_Data [(library_unit_Name)];
```

This pragma is supported only for the AAMP target and is ignored for other targets. The pragma specifies that all library-level objects (Counter 0 data) associated with the library unit are to be accessed and updated using universal addressing (24-bit addresses for AAMP5) rather than the default of 16-bit Data Environment (DENV) addressing. Use of this pragma will generally result in less efficient code for references to global data associated with the library unit, but allows such data to be located anywhere in memory. This pragma is a library unit pragma, but can also be used as a configuration pragma (including use in the `gnat.adc` file). The functionality of this pragma is also available by applying the `-univ` switch on the compilations of units where universal addressing of the data is desired.

Pragma `Unmodified`

Syntax:

```
pragma Unmodified (LOCAL_NAME {, LOCAL_NAME});
```

This pragma signals that the assignable entities (variables, `out` parameters, `in out` parameters) whose names are listed are deliberately not assigned in the current source unit. This suppresses warnings about the entities being referenced but not assigned, and in addition a warning will be generated if one of these entities is in fact assigned in the same unit as the pragma (or in the corresponding body, or one of its subunits).

This is particularly useful for clearly signaling that a particular parameter is not modified, even though the spec suggests that it might be.

Pragma `Unreferenced`

Syntax:

```
pragma Unreferenced (LOCAL_NAME {, LOCAL_NAME});
pragma Unreferenced (library_unit_NAME {, library_unit_NAME});
```

This pragma signals that the entities whose names are listed are deliberately not referenced in the current source unit. This suppresses warnings about the entities being unreferenced, and in addition a warning will be generated if one of these entities is in fact referenced in the same unit as the pragma (or in the corresponding body, or one of its subunits).

This is particularly useful for clearly signaling that a particular parameter is not referenced in some particular subprogram implementation and that this is deliberate. It can also be useful in the case of objects declared only for their initialization or finalization side effects.

If `LOCAL_NAME` identifies more than one matching homonym in the current scope, then the entity most recently declared is the one to which the pragma applies. Note that in the case of accept formals, the pragma `Unreferenced` may appear immediately after the keyword `do` which allows the indication of whether or not accept formals are referenced or not to be given individually for each accept statement.

The left hand side of an assignment does not count as a reference for the purpose of this pragma. Thus it is fine to assign to an entity for which pragma `Unreferenced` is given.

Note that if a warning is desired for all calls to a given subprogram, regardless of whether they occur in the same unit as the subprogram declaration, then this pragma should not be used (calls from another unit would not be flagged); pragma `Obsolescent` can be used instead for this purpose, see See [\[Pragma Obsolescent\]](#), page 33.

The second form of pragma `Unreferenced` is used within a context clause. In this case the arguments must be unit names of units previously mentioned in `with` clauses (similar to the

usage of pragma `Elaborate_All`. The effect is to suppress warnings about unreferenced units and unreferenced entities within these units.

Pragma Unreferenced_Objects

Syntax:

```
pragma Unreferenced_Objects (local_subtype_NAME {, local_subtype_NAME});
```

This pragma signals that for the types or subtypes whose names are listed, objects which are declared with one of these types or subtypes may not be referenced, and if no references appear, no warnings are given.

This is particularly useful for objects which are declared solely for their initialization and finalization effect. Such variables are sometimes referred to as RAII variables (Resource Acquisition Is Initialization). Using this pragma on the relevant type (most typically a limited controlled type), the compiler will automatically suppress unwanted warnings about these variables not being referenced.

Pragma Unreserve_All_Interrupts

Syntax:

```
pragma Unreserve_All_Interrupts;
```

Normally certain interrupts are reserved to the implementation. Any attempt to attach an interrupt causes `Program_Error` to be raised, as described in RM C.3.2(22). A typical example is the `SIGINT` interrupt used in many systems for a `Ctrl-C` interrupt. Normally this interrupt is reserved to the implementation, so that `Ctrl-C` can be used to interrupt execution.

If the pragma `Unreserve_All_Interrupts` appears anywhere in any unit in a program, then all such interrupts are unreserved. This allows the program to handle these interrupts, but disables their standard functions. For example, if this pragma is used, then pressing `Ctrl-C` will not automatically interrupt execution. However, a program can then handle the `SIGINT` interrupt as it chooses.

For a full list of the interrupts handled in a specific implementation, see the source code for the spec of `Ada.Interrupts.Names` in file `'a-intnam.ads'`. This is a target dependent file that contains the list of interrupts recognized for a given target. The documentation in this file also specifies what interrupts are affected by the use of the `Unreserve_All_Interrupts` pragma.

For a more general facility for controlling what interrupts can be handled, see pragma `Interrupt_State`, which subsumes the functionality of the `Unreserve_All_Interrupts` pragma.

Pragma Unsuppress

Syntax:

```
pragma Unsuppress (IDENTIFIER [, [On =>] NAME]);
```

This pragma undoes the effect of a previous pragma `Suppress`. If there is no corresponding pragma `Suppress` in effect, it has no effect. The range of the effect is the same as for pragma `Suppress`. The meaning of the arguments is identical to that used in pragma `Suppress`.

One important application is to ensure that checks are on in cases where code depends on the checks for its correct functioning, so that the code will compile correctly even if the compiler switches are set to suppress checks.

Pragma Use_VADS_Size

Syntax:

```
pragma Use_VADS_Size;
```

This is a configuration pragma. In a unit to which it applies, any use of the 'Size attribute is automatically interpreted as a use of the 'VADS_Size attribute. Note that this may result in incorrect semantic processing of valid Ada 95 or Ada 2005 programs. This is intended to aid in the handling of existing code which depends on the interpretation of Size as implemented in the VADS compiler. See description of the VADS_Size attribute for further details.

Pragma Validity_Checks

Syntax:

```
pragma Validity_Checks (string_LITERAL | ALL_CHECKS | On | Off);
```

This pragma is used in conjunction with compiler switches to control the built-in validity checking provided by GNAT. The compiler switches, if set provide an initial setting for the switches, and this pragma may be used to modify these settings, or the settings may be provided entirely by the use of the pragma. This pragma can be used anywhere that a pragma is legal, including use as a configuration pragma (including use in the 'gnat.adc' file).

The form with a string literal specifies which validity options are to be activated. The validity checks are first set to include only the default reference manual settings, and then a string of letters in the string specifies the exact set of options required. The form of this string is exactly as described for the '-gnatVx' compiler switch (see the GNAT users guide for details). For example the following two methods can be used to enable validity checking for mode `in` and `in out` subprogram parameters:

- ```
pragma Validity_Checks ("im");
```
- ```
gcc -c -gnatVim ...
```

The form `ALL_CHECKS` activates all standard checks (its use is equivalent to the use of the `gnatva` switch).

The forms with `Off` and `On` can be used to temporarily disable validity checks as shown in the following example:

```
pragma Validity_Checks ("c"); -- validity checks for copies
pragma Validity_Checks (Off); -- turn off validity checks
A := B;                       -- B will not be validity checked
pragma Validity_Checks (On);  -- turn validity checks back on
A := C;                       -- C will be validity checked
```

Pragma Volatile

Syntax:

```
pragma Volatile (LOCAL_NAME);
```

This pragma is defined by the Ada Reference Manual, and the GNAT implementation is fully conformant with this definition. The reason it is mentioned in this section is that a pragma of the same name was supplied in some Ada 83 compilers, including DEC Ada 83. The Ada 95 / Ada 2005 implementation of pragma Volatile is upwards compatible with the implementation in DEC Ada 83.

Pragma Warnings

Syntax:

```
pragma Warnings (On | Off);
pragma Warnings (On | Off, LOCAL_NAME);
pragma Warnings (static_string_EXPRESSION);
pragma Warnings (On | Off, static_string_EXPRESSION);
```

Normally warnings are enabled, with the output being controlled by the command line switch. `Warnings (Off)` turns off generation of warnings until a `Warnings (On)` is encountered or the end of the current unit. If generation of warnings is turned off using this pragma, then no warning messages are output, regardless of the setting of the command line switches.

The form with a single argument may be used as a configuration pragma.

If the `LOCAL_NAME` parameter is present, warnings are suppressed for the specified entity. This suppression is effective from the point where it occurs till the end of the extended scope of the variable (similar to the scope of `Suppress`).

The form with a single `static_string_EXPRESSION` argument provides more precise control over which warnings are active. The string is a list of letters specifying which warnings are to be activated and which deactivated. The code for these letters is the same as the string used in the command line switch controlling warnings. For a brief summary, use the `gnatmake` command with no arguments, which will generate usage information containing the list of warnings switches supported. For full details see [Section “Warning Message Control” in *GNAT User’s Guide*](#).

The specified warnings will be in effect until the end of the program or another pragma `Warnings` is encountered. The effect of the pragma is cumulative. Initially the set of warnings is the standard default set as possibly modified by compiler switches. Then each pragma `Warning` modifies this set of warnings as specified. This form of the pragma may also be used as a configuration pragma.

The fourth form, with an `On|Off` parameter and a string, is used to control individual messages, based on their text. The string argument is a pattern that is used to match against the text of individual warning messages (not including the initial “warning: ” tag).

The pattern may contain asterisks, which match zero or more characters in the message. For example, you can use `pragma Warnings (Off, “*bits of*unused”)` to suppress the warning message `warning: 960 bits of “a” unused`. No other regular expression notations are permitted. All characters other than asterisk in these three specific cases are treated as literal characters in the match.

There are two ways to use this pragma. The `OFF` form can be used as a configuration pragma. The effect is to suppress all warnings (if any) that match the pattern string throughout the compilation.

The second usage is to suppress a warning locally, and in this case, two pragmas must appear in sequence:

```
pragma Warnings (Off, Pattern);
... code where given warning is to be suppressed
pragma Warnings (On, Pattern);
```

In this usage, the pattern string must match in the `Off` and `On` pragmas, and at least one matching warning must be suppressed.

Note: the debug flag `-gnatd.i (/NOWARNINGS_PRAGMAS` in VMS) can be used to cause the compiler to entirely ignore all `WARNINGS` pragmas. This can be useful in checking whether obsolete pragmas in existing programs are hiding real problems.

Note: pragma `Warnings` does not affect the processing of style messages. See separate entry for pragma `Style_Checks` for control of style messages.

Pragma Weak_External

Syntax:

```
pragma Weak_External ([Entity =>] LOCAL_NAME);
```

LOCAL_NAME must refer to an object that is declared at the library level. This pragma specifies that the given entity should be marked as a weak symbol for the linker. It is equivalent to `__attribute__((weak))` in GNU C and causes *LOCAL_NAME* to be emitted as a weak symbol instead of a regular symbol, that is to say a symbol that does not have to be resolved by the linker if used in conjunction with a pragma Import.

When a weak symbol is not resolved by the linker, its address is set to zero. This is useful in writing interfaces to external modules that may or may not be linked in the final executable, for example depending on configuration settings.

If a program references at run time an entity to which this pragma has been applied, and the corresponding symbol was not resolved at link time, then the execution of the program is erroneous. It is not erroneous to take the Address of such an entity, for example to guard potential references, as shown in the example below.

Some file formats do not support weak symbols so not all target machines support this pragma.

```
-- Example of the use of pragma Weak_External

package External_Module is
  key : Integer;
  pragma Import (C, key);
  pragma Weak_External (key);
  function Present return boolean;
end External_Module;

with System; use System;
package body External_Module is
  function Present return boolean is
  begin
    return key'Address /= System.Null_Address;
  end Present;
end External_Module;
```

Pragma Wide_Character-Encoding

Syntax:

```
pragma Wide_Character-Encoding (IDENTIFIER | CHARACTER_LITERAL);
```

This pragma specifies the wide character encoding to be used in program source text appearing subsequently. It is a configuration pragma, but may also be used at any point that a pragma is allowed, and it is permissible to have more than one such pragma in a file, allowing multiple encodings to appear within the same file.

The argument can be an identifier or a character literal. In the identifier case, it is one of `HEX`, `UPPER`, `SHIFT_JIS`, `EUC`, `UTF8`, or `BRACKETS`. In the character literal case it is correspondingly one of the characters `'h'`, `'u'`, `'s'`, `'e'`, `'8'`, or `'b'`.

Note that when the pragma is used within a file, it affects only the encoding within that file, and does not affect withed units, specs, or subunits.

2 Implementation Defined Attributes

Ada defines (throughout the Ada reference manual, summarized in Annex K), a set of attributes that provide useful additional functionality in all areas of the language. These language defined attributes are implemented in GNAT and work as described in the Ada Reference Manual.

In addition, Ada allows implementations to define additional attributes whose meaning is defined by the implementation. GNAT provides a number of these implementation-dependent attributes which can be used to extend and enhance the functionality of the compiler. This section of the GNAT reference manual describes these additional attributes.

Note that any program using these attributes may not be portable to other compilers (although GNAT implements this set of attributes on all platforms). Therefore if portability to other compilers is an important consideration, you should minimize the use of these attributes.

Abort_Signal

`Standard'Abort_Signal` (`Standard` is the only allowed prefix) provides the entity for the special exception used to signal task abort or asynchronous transfer of control. Normally this attribute should only be used in the tasking runtime (it is highly peculiar, and completely outside the normal semantics of Ada, for a user program to intercept the abort exception).

Address_Size

`Standard'Address_Size` (`Standard` is the only allowed prefix) is a static constant giving the number of bits in an `Address`. It is the same value as `System.Address'Size`, but has the advantage of being static, while a direct reference to `System.Address'Size` is non-static because `Address` is a private type.

Asm_Input

The `Asm_Input` attribute denotes a function that takes two parameters. The first is a string, the second is an expression of the type designated by the prefix. The first (string) argument is required to be a static expression, and is the constraint for the parameter, (e.g. what kind of register is required). The second argument is the value to be used as the input argument. The possible values for the constant are the same as those used in the RTL, and are dependent on the configuration file used to build the GCC back end. [Section 12.1 \[Machine Code Insertions\], page 183](#)

Asm_Output

The `Asm_Output` attribute denotes a function that takes two parameters. The first is a string, the second is the name of a variable of the type designated by the attribute prefix. The first (string) argument is required to be a static expression and designates the constraint for the parameter (e.g. what kind of register is required). The second argument is the variable to be updated with the result. The possible values for constraint are the same as those used in the RTL, and are dependent on the configuration file used to build the GCC back end. If there are no output operands, then this argument may either be omitted, or explicitly given as `No_Output_Operands`. [Section 12.1 \[Machine Code Insertions\], page 183](#)

AST_Entry

This attribute is implemented only in OpenVMS versions of GNAT. Applied to the name of an entry, it yields a value of the predefined type `AST_Handler` (declared in the predefined package `System`, as extended by the use of `pragma Extend_System (Aux_DEC)`). This value enables

the given entry to be called when an AST occurs. For further details, refer to the *DEC Ada Language Reference Manual*, section 9.12a.

Bit

obj'**Bit**, where *obj* is any object, yields the bit offset within the storage unit (byte) that contains the first bit of storage allocated for the object. The value of this attribute is of the type **Universal_Integer**, and is always a non-negative number not exceeding the value of **System.Storage_Unit**.

For an object that is a variable or a constant allocated in a register, the value is zero. (The use of this attribute does not force the allocation of a variable to memory).

For an object that is a formal parameter, this attribute applies to either the matching actual parameter or to a copy of the matching actual parameter.

For an access object the value is zero. Note that *obj.all*'**Bit** is subject to an **Access_Check** for the designated object. Similarly for a record component *X.C*'**Bit** is subject to a discriminant check and *X(I1..I2)*'**Bit** are subject to index checks.

This attribute is designed to be compatible with the DEC Ada 83 definition and implementation of the **Bit** attribute.

Bit_Position

R.C'**Bit_Position**, where *R* is a record object and *C* is one of the fields of the record type, yields the bit offset within the record contains the first bit of storage allocated for the object. The value of this attribute is of the type **Universal_Integer**. The value depends only on the field *C* and is independent of the alignment of the containing record *R*.

Compiler_Version

Standard'**Compiler_Version** (**Standard** is the only allowed prefix) yields a static string identifying the version of the compiler being used to compile the unit containing the attribute reference. A typical result would be something like "GNAT Pro 6.3.0w (20090221)".

Code_Address

The '**Address** attribute may be applied to subprograms in Ada 95 and Ada 2005, but the intended effect seems to be to provide an address value which can be used to call the subprogram by means of an address clause as in the following example:

```
procedure K is ...

procedure L;
for L'Address use K'Address;
pragma Import (Ada, L);
```

A call to *L* is then expected to result in a call to *K*. In Ada 83, where there were no access-to-subprogram values, this was a common work-around for getting the effect of an indirect call. GNAT implements the above use of **Address** and the technique illustrated by the example code works correctly.

However, for some purposes, it is useful to have the address of the start of the generated code for the subprogram. On some architectures, this is not necessarily the same as the **Address** value described above. For example, the **Address** value may reference a subprogram descriptor rather than the subprogram itself.

The '**Code_Address** attribute, which can only be applied to subprogram entities, always returns the address of the start of the generated code of the specified subprogram, which may or may not be the same value as is returned by the corresponding '**Address** attribute.

Default_Bit_Order

`Standard'Default_Bit_Order` (`Standard` is the only permissible prefix), provides the value `System.Default_Bit_Order` as a `Pos` value (0 for `High_Order_First`, 1 for `Low_Order_First`). This is used to construct the definition of `Default_Bit_Order` in package `System`.

Elaborated

The prefix of the `'Elaborated` attribute must be a unit name. The value is a Boolean which indicates whether or not the given unit has been elaborated. This attribute is primarily intended for internal use by the generated code for dynamic elaboration checking, but it can also be used in user programs. The value will always be `True` once elaboration of all units has been completed. An exception is for units which need no elaboration, the value is always `False` for such units.

Elab_Body

This attribute can only be applied to a program unit name. It returns the entity for the corresponding elaboration procedure for elaborating the body of the referenced unit. This is used in the main generated elaboration procedure by the binder and is not normally used in any other context. However, there may be specialized situations in which it is useful to be able to call this elaboration procedure from Ada code, e.g. if it is necessary to do selective re-elaboration to fix some error.

Elab_Spec

This attribute can only be applied to a program unit name. It returns the entity for the corresponding elaboration procedure for elaborating the spec of the referenced unit. This is used in the main generated elaboration procedure by the binder and is not normally used in any other context. However, there may be specialized situations in which it is useful to be able to call this elaboration procedure from Ada code, e.g. if it is necessary to do selective re-elaboration to fix some error.

Emax

The `Emax` attribute is provided for compatibility with Ada 83. See the Ada 83 reference manual for an exact description of the semantics of this attribute.

Enabled

The `Enabled` attribute allows an application program to check at compile time to see if the designated check is currently enabled. The prefix is a simple identifier, referencing any predefined check name (other than `All_Checks`) or a check name introduced by `pragma Check_Name`. If no argument is given for the attribute, the check is for the general state of the check, if an argument is given, then it is an entity name, and the check indicates whether an `Suppress` or `Unsuppress` has been given naming the entity (if not, then the argument is ignored).

Note that instantiations inherit the check status at the point of the instantiation, so a useful idiom is to have a library package that introduces a check name with `pragma Check_Name`, and then contains generic packages or subprograms which use the `Enabled` attribute to see if the check is enabled. A user of this package can then issue a `pragma Suppress` or `pragma Unsuppress` before instantiating the package or subprogram, controlling whether the check will be present.

Enum_Rep

For every enumeration subtype `S`, `S'Enum_Rep` denotes a function with the following spec:

```
function S'Enum_Rep (Arg : S'Base)
  return Universal_Integer;
```

It is also allowable to apply `Enum_Rep` directly to an object of an enumeration type or to a non-overloaded enumeration literal. In this case `S'Enum_Rep` is equivalent to `typ'Enum_Rep(S)` where `typ` is the type of the enumeration literal or object.

The function returns the representation value for the given enumeration value. This will be equal to value of the `Pos` attribute in the absence of an enumeration representation clause. This is a static attribute (i.e. the result is static if the argument is static).

`S'Enum_Rep` can also be used with integer types and objects, in which case it simply returns the integer value. The reason for this is to allow it to be used for (<>) discrete formal arguments in a generic unit that can be instantiated with either enumeration types or integer types. Note that if `Enum_Rep` is used on a modular type whose upper bound exceeds the upper bound of the largest signed integer type, and the argument is a variable, so that the universal integer calculation is done at run time, then the call to `Enum_Rep` may raise `Constraint_Error`.

Enum_Val

For every enumeration subtype `S`, `S'Enum_Val` denotes a function with the following spec:

```
function S'Enum_Val (Arg : Universal_Integer)
  return S'Base;
```

The function returns the enumeration value whose representation matches the argument, or raises `Constraint_Error` if no enumeration literal of the type has the matching value. This will be equal to value of the `Val` attribute in the absence of an enumeration representation clause. This is a static attribute (i.e. the result is static if the argument is static).

Epsilon

The `Epsilon` attribute is provided for compatibility with Ada 83. See the Ada 83 reference manual for an exact description of the semantics of this attribute.

Fixed_Value

For every fixed-point type `S`, `S'Fixed_Value` denotes a function with the following specification:

```
function S'Fixed_Value (Arg : Universal_Integer)
  return S;
```

The value returned is the fixed-point value `V` such that

$$V = \text{Arg} * S'\text{Small}$$

The effect is thus similar to first converting the argument to the integer type used to represent `S`, and then doing an unchecked conversion to the fixed-point type. The difference is that there are full range checks, to ensure that the result is in range. This attribute is primarily intended for use in implementation of the input-output functions for fixed-point values.

Has_Access_Values

The prefix of the `Has_Access_Values` attribute is a type. The result is a Boolean value which is `True` if the is an access type, or is a composite type with a component (at any nesting depth) that is an access type, and is `False` otherwise. The intended use of this attribute is in conjunction with generic definitions. If the attribute is applied to a generic private type, it indicates whether or not the corresponding actual type has access values.

Has_Discriminants

The prefix of the `Has_Discriminants` attribute is a type. The result is a Boolean value which is `True` if the type has discriminants, and `False` otherwise. The intended use of this attribute is in conjunction with generic definitions. If the attribute is applied to a generic private type, it indicates whether or not the corresponding actual type has discriminants.

Img

The `Img` attribute differs from `Image` in that it may be applied to objects as well as types, in which case it gives the `Image` for the subtype of the object. This is convenient for debugging:

```
Put_Line ("X = " & X'Img);
```

has the same meaning as the more verbose:

```
Put_Line ("X = " & T'Image (X));
```

where T is the (sub)type of the object X .

Integer_Value

For every integer type S , S' `Integer_Value` denotes a function with the following spec:

```
function S'Integer_Value (Arg : Universal_Fixed)
  return S;
```

The value returned is the integer value V , such that

```
Arg = V * T'Small
```

where T is the type of `Arg`. The effect is thus similar to first doing an unchecked conversion from the fixed-point type to its corresponding implementation type, and then converting the result to the target integer type. The difference is that there are full range checks, to ensure that the result is in range. This attribute is primarily intended for use in implementation of the standard input-output functions for fixed-point values.

Invalid_Value

For every scalar type S , S' `Invalid_Value` returns an undefined value of the type. If possible this value is an invalid representation for the type. The value returned is identical to the value used to initialize an otherwise uninitialized value of the type if `pragma Initialize_Scalars` is used, including the ability to modify the value with the binder `-Sxx` flag and relevant environment variables at run time.

Large

The `Large` attribute is provided for compatibility with Ada 83. See the Ada 83 reference manual for an exact description of the semantics of this attribute.

Machine_Size

This attribute is identical to the `Object_Size` attribute. It is provided for compatibility with the DEC Ada 83 attribute of this name.

Mantissa

The `Mantissa` attribute is provided for compatibility with Ada 83. See the Ada 83 reference manual for an exact description of the semantics of this attribute.

Max_Interrupt_Priority

`Standard'Max_Interrupt_Priority` (`Standard` is the only permissible prefix), provides the same value as `System.Max_Interrupt_Priority`.

Max_Priority

`Standard'Max_Priority` (`Standard` is the only permissible prefix) provides the same value as `System.Max_Priority`.

Maximum_Alignment

`Standard'Maximum_Alignment` (`Standard` is the only permissible prefix) provides the maximum useful alignment value for the target. This is a static value that can be used to specify the alignment for an object, guaranteeing that it is properly aligned in all cases.

Mechanism_Code

`function'Mechanism_Code` yields an integer code for the mechanism used for the result of function, and `subprogram'Mechanism_Code (n)` yields the mechanism used for formal parameter number *n* (a static integer value with 1 meaning the first parameter) of *subprogram*. The code returned is:

- 1 by copy (value)
- 2 by reference
- 3 by descriptor (default descriptor class)
- 4 by descriptor (UBS: unaligned bit string)
- 5 by descriptor (UBSB: aligned bit string with arbitrary bounds)
- 6 by descriptor (UBA: unaligned bit array)
- 7 by descriptor (S: string, also scalar access type parameter)
- 8 by descriptor (SB: string with arbitrary bounds)
- 9 by descriptor (A: contiguous array)
- 10 by descriptor (NCA: non-contiguous array)

Values from 3 through 10 are only relevant to Digital OpenVMS implementations.

Null_Parameter

A reference `T'Null_Parameter` denotes an imaginary object of type or subtype *T* allocated at machine address zero. The attribute is allowed only as the default expression of a formal parameter, or as an actual expression of a subprogram call. In either case, the subprogram must be imported.

The identity of the object is represented by the address zero in the argument list, independent of the passing mechanism (explicit or default).

This capability is needed to specify that a zero address should be passed for a record or other composite object passed by reference. There is no way of indicating this without the `Null_Parameter` attribute.

Object_Size

The size of an object is not necessarily the same as the size of the type of an object. This is because by default object sizes are increased to be a multiple of the alignment of the object. For example, `Natural'Size` is 31, but by default objects of type `Natural` will have a size of 32 bits. Similarly, a record containing an integer and a character:

```

type Rec is record
  I : Integer;
  C : Character;
end record;

```

will have a size of 40 (that is `Rec'Size` will be 40). The alignment will be 4, because of the integer field, and so the default size of record objects for this type will be 64 (8 bytes).

Old

The attribute `Prefix'Old` can be used within a subprogram body or within a precondition or postcondition pragma. The effect is to refer to the value of the prefix on entry. So for example if you have an argument of a record type `X` called `Arg1`, you can refer to `Arg1.Field'Old` which yields the value of `Arg1.Field` on entry. The implementation simply involves generating an object declaration which captures the value on entry. Any prefix is allowed except one of a limited type (since limited types cannot be copied to capture their values) or an expression which references a local variable (since local variables do not exist at subprogram entry time).

The following example shows the use of `'Old` to implement a test of a postcondition:

```

with Old_Pkg;
procedure Old is
begin
  Old_Pkg.Incr;
end Old;

package Old_Pkg is
  procedure Incr;
end Old_Pkg;

package body Old_Pkg is
  Count : Natural := 0;

  procedure Incr is
  begin
    ... code manipulating the value of Count

    pragma Assert (Count = Count'Old + 1);
  end Incr;
end Old_Pkg;

```

Note that it is allowed to apply `'Old` to a constant entity, but this will result in a warning, since the old and new values will always be the same.

Passed_By_Reference

`type 'Passed_By_Reference` for any subtype `type` returns a value of type `Boolean` value that is `True` if the type is normally passed by reference and `False` if the type is normally passed by copy in calls. For scalar types, the result is always `False` and is static. For non-scalar types, the result is non-static.

Pool_Address

`X'Pool_Address` for any object `X` returns the address of `X` within its storage pool. This is the same as `X'Address`, except that for an unconstrained array whose bounds are allocated just before the first component, `X'Pool_Address` returns the address of those bounds, whereas `X'Address` returns the address of the first component.

Here, we are interpreting “storage pool” broadly to mean “wherever the object is allocated”, which could be a user-defined storage pool, the global heap, on the stack, or in a static memory area. For an object created by `new`, `Ptr.all'Pool_Address` is what is passed to `Allocate` and returned from `Deallocate`.

Range_Length

type 'Range_Length for any discrete type *type* yields the number of values represented by the subtype (zero for a null range). The result is static for static subtypes. Range_Length applied to the index subtype of a one dimensional array always gives the same result as Range applied to the array itself.

Ref

The `System.Address'Ref` (`System.Address` is the only permissible prefix) denotes a function identical to `System.Storage_Elements.To_Address` except that it is a static attribute. See [\[To_Address\]](#), page 65 for more details.

Result

function 'Result can only be used with in a Postcondition pragma for a function. The prefix must be the name of the corresponding function. This is used to refer to the result of the function in the postcondition expression. For a further discussion of the use of this attribute and examples of its use, see the description of pragma Postcondition.

Safe_Emax

The `Safe_Emax` attribute is provided for compatibility with Ada 83. See the Ada 83 reference manual for an exact description of the semantics of this attribute.

Safe_Large

The `Safe_Large` attribute is provided for compatibility with Ada 83. See the Ada 83 reference manual for an exact description of the semantics of this attribute.

Small

The `Small` attribute is defined in Ada 95 (and Ada 2005) only for fixed-point types. GNAT also allows this attribute to be applied to floating-point types for compatibility with Ada 83. See the Ada 83 reference manual for an exact description of the semantics of this attribute when applied to floating-point types.

Storage_Unit

`Standard'Storage_Unit` (`Standard` is the only permissible prefix) provides the same value as `System.Storage_Unit`.

Stub_Type

The GNAT implementation of remote access-to-classwide types is organized as described in AARM section E.4 (20.t): a value of an RACW type (designating a remote object) is represented as a normal access value, pointing to a "stub" object which in turn contains the necessary information to contact the designated remote object. A call on any dispatching operation of such a stub object does the remote call, if necessary, using the information in the stub object to locate the target partition, etc.

For a prefix *T* that denotes a remote access-to-classwide type, *T'Stub_Type* denotes the type of the corresponding stub objects.

By construction, the layout of *T'Stub_Type* is identical to that of type `RACW_Stub_Type` declared in the internal implementation-defined unit `System.Partition_Interface`. Use of this attribute will create an implicit dependency on this unit.

Target_Name

`Standard'Target_Name` (`Standard` is the only permissible prefix) provides a static string value that identifies the target for the current compilation. For GCC implementations, this is the standard gcc target name without the terminating slash (for example, GNAT 5.0 on windows yields "i586-pc-mingw32msv").

Tick

`Standard'Tick` (`Standard` is the only permissible prefix) provides the same value as `System.Tick`,

To_Address

The `System'To_Address` (`System` is the only permissible prefix) denotes a function identical to `System.Storage_Elements.To_Address` except that it is a static attribute. This means that if its argument is a static expression, then the result of the attribute is a static expression. The result is that such an expression can be used in contexts (e.g. preelaborable packages) which require a static expression and where the function call could not be used (since the function call is always non-static, even if its argument is static).

Type_Class

`type'Type_Class` for any type or subtype *type* yields the value of the type class for the full type of *type*. If *type* is a generic formal type, the value is the value for the corresponding actual subtype. The value of this attribute is of type `System.Aux_DEC.Type_Class`, which has the following definition:

```
type Type_Class is
  (Type_Class_Enumeration,
   Type_Class_Integer,
   Type_Class_Fixed_Point,
   Type_Class_Floating_Point,
   Type_Class_Array,
   Type_Class_Record,
   Type_Class_Access,
   Type_Class_Task,
   Type_Class_Address);
```

Protected types yield the value `Type_Class_Task`, which thus applies to all concurrent types. This attribute is designed to be compatible with the DEC Ada 83 attribute of the same name.

UET_Address

The `UET_Address` attribute can only be used for a prefix which denotes a library package. It yields the address of the unit exception table when zero cost exception handling is used. This attribute is intended only for use within the GNAT implementation. See the unit `Ada.Exceptions` in files 'a-except.ads' and 'a-except.adb' for details on how this attribute is used in the implementation.

Unconstrained_Array

The `Unconstrained_Array` attribute can be used with a prefix that denotes any type or subtype. It is a static attribute that yields `True` if the prefix designates an unconstrained array, and `False` otherwise. In a generic instance, the result is still static, and yields the result of applying this test to the generic actual.

Universal_Literal_String

The prefix of `Universal_Literal_String` must be a named number. The static result is the string consisting of the characters of the number as defined in the original source. This allows the user program to access the actual text of named numbers without intermediate conversions and without the need to enclose the strings in quotes (which would preclude their use as numbers).

For example, the following program prints the first 50 digits of pi:

```
with Text_IO; use Text_IO;
with Ada.Numerics;
procedure Pi is
begin
  Put (Ada.Numerics.Pi'Universal_Literal_String);
end;
```

Unrestricted_Access

The `Unrestricted_Access` attribute is similar to `Access` except that all accessibility and aliased view checks are omitted. This is a user-beware attribute. It is similar to `Address`, for which it is a desirable replacement where the value desired is an access type. In other words, its effect is identical to first applying the `Address` attribute and then doing an unchecked conversion to a desired access type. In GNAT, but not necessarily in other implementations, the use of static chains for inner level subprograms means that `Unrestricted_Access` applied to a subprogram yields a value that can be called as long as the subprogram is in scope (normal Ada accessibility rules restrict this usage).

It is possible to use `Unrestricted_Access` for any type, but care must be exercised if it is used to create pointers to unconstrained objects. In this case, the resulting pointer has the same scope as the context of the attribute, and may not be returned to some enclosing scope. For instance, a function cannot use `Unrestricted_Access` to create a unconstrained pointer and then return that value to the caller.

VADS_Size

The `'VADS_Size` attribute is intended to make it easier to port legacy code which relies on the semantics of `'Size` as implemented by the VADS Ada 83 compiler. GNAT makes a best effort at duplicating the same semantic interpretation. In particular, `'VADS_Size` applied to a predefined or other primitive type with no `Size` clause yields the `Object_Size` (for example, `Natural'Size` is 32 rather than 31 on typical machines). In addition `'VADS_Size` applied to an object gives the result that would be obtained by applying the attribute to the corresponding type.

Value_Size

type `'Value_Size` is the number of bits required to represent a value of the given subtype. It is the same as *type* `'Size`, but, unlike `Size`, may be set for non-first subtypes.

Wchar_T_Size

`Standard'wchar_T_Size` (`Standard` is the only permissible prefix) provides the size in bits of the C `wchar_t` type primarily for constructing the definition of this type in package `Interfaces.C`.

Word_Size

`Standard'Word_Size` (`Standard` is the only permissible prefix) provides the value `System.Word_Size`.

3 Implementation Advice

The main text of the Ada Reference Manual describes the required behavior of all Ada compilers, and the GNAT compiler conforms to these requirements.

In addition, there are sections throughout the Ada Reference Manual headed by the phrase “Implementation advice”. These sections are not normative, i.e., they do not specify requirements that all compilers must follow. Rather they provide advice on generally desirable behavior. You may wonder why they are not requirements. The most typical answer is that they describe behavior that seems generally desirable, but cannot be provided on all systems, or which may be undesirable on some systems.

As far as practical, GNAT follows the implementation advice sections in the Ada Reference Manual. This chapter contains a table giving the reference manual section number, paragraph number and several keywords for each advice. Each entry consists of the text of the advice followed by the GNAT interpretation of this advice. Most often, this simply says “followed”, which means that GNAT follows the advice. However, in a number of cases, GNAT deliberately deviates from this advice, in which case the text describes what GNAT does and why.

1.1.3(20): Error Detection

If an implementation detects the use of an unsupported Specialized Needs Annex feature at run time, it should raise `Program_Error` if feasible.

Not relevant. All specialized needs annex features are either supported, or diagnosed at compile time.

1.1.3(31): Child Units

If an implementation wishes to provide implementation-defined extensions to the functionality of a language-defined library unit, it should normally do so by adding children to the library unit.

Followed.

1.1.5(12): Bounded Errors

If an implementation detects a bounded error or erroneous execution, it should raise `Program_Error`.

Followed in all cases in which the implementation detects a bounded error or erroneous execution. Not all such situations are detected at runtime.

2.8(16): Pragmas

Normally, implementation-defined pragmas should have no semantic effect for error-free programs; that is, if the implementation-defined pragmas are removed from a working program, the program should still be legal, and should still have the same semantics.

The following implementation defined pragmas are exceptions to this rule:

<code>Abort_Defer</code>	Affects semantics
<code>Ada_83</code>	Affects legality
<code>Assert</code>	Affects semantics
<code>CPP_Class</code>	Affects semantics
<code>CPP_Constructor</code>	Affects semantics
<code>Debug</code>	Affects semantics
<code>Interface_Name</code>	Affects semantics
<code>Machine_Attribute</code>	Affects semantics
<code>Unimplemented_Unit</code>	Affects legality
<code>Unchecked_Union</code>	Affects semantics

In each of the above cases, it is essential to the purpose of the pragma that this advice not be followed. For details see the separate section on implementation defined pragmas.

2.8(17-19): Pragmas

Normally, an implementation should not define pragmas that can make an illegal program legal, except as follows:

A pragma used to complete a declaration, such as a pragma `Import`;

A pragma used to configure the environment by adding, removing, or replacing `library_items`.

See response to paragraph 16 of this same section.

3.5.2(5): Alternative Character Sets

If an implementation supports a mode with alternative interpretations for `Character` and `Wide_Character`, the set of graphic characters of `Character` should nevertheless remain a proper subset of the set of graphic characters of `Wide_Character`. Any character set “localizations” should be reflected in the results of the subprograms defined in the language-defined package `Characters.Handling` (see A.3) available in such a mode. In a mode with an alternative interpretation of `Character`, the implementation should also support a corresponding change in what is a legal `identifier_letter`.

Not all wide character modes follow this advice, in particular the JIS and IEC modes reflect standard usage in Japan, and in these encoding, the upper half of the Latin-1 set is not part of the wide-character subset, since the most significant bit is used for wide character encoding. However, this only applies to the external forms. Internally there is no such restriction.

3.5.4(28): Integer Types

An implementation should support `Long_Integer` in addition to `Integer` if the target machine supports 32-bit (or longer) arithmetic. No other named integer subtypes are recommended for package `Standard`. Instead, appropriate named integer subtypes should be provided in the library package `Interfaces` (see B.2).

`Long_Integer` is supported. Other standard integer types are supported so this advice is not fully followed. These types are supported for convenient interface to C, and so that all hardware types of the machine are easily available.

3.5.4(29): Integer Types

An implementation for a two’s complement machine should support modular types with a binary modulus up to `System.Max_Int*2+2`. An implementation should support a non-binary modules up to `Integer’Last`.

Followed.

3.5.5(8): Enumeration Values

For the evaluation of a call on `S’Pos` for an enumeration subtype, if the value of the operand does not correspond to the internal code for any enumeration literal of its type (perhaps due to an un-initialized variable), then the implementation should raise `Program_Error`. This is particularly important for enumeration types with noncontiguous internal codes specified by an `enumeration_representation_clause`.

Followed.

3.5.7(17): Float Types

An implementation should support `Long_Float` in addition to `Float` if the target machine supports 11 or more digits of precision. No other named floating point subtypes are recommended for package `Standard`. Instead, appropriate named floating point subtypes should be provided in the library package `Interfaces` (see B.2).

`Short_Float` and `Long_Long_Float` are also provided. The former provides improved compatibility with other implementations supporting this type. The latter corresponds to the highest precision floating-point type supported by the hardware. On most machines, this will be the same as `Long_Float`, but on some machines, it will correspond to the IEEE extended form. The notable case is all ia32 (x86) implementations, where `Long_Long_Float` corresponds to the 80-bit extended precision format supported in hardware on this processor. Note that the 128-bit format on SPARC is not supported, since this is a software rather than a hardware format.

3.6.2(11): Multidimensional Arrays

An implementation should normally represent multidimensional arrays in row-major order, consistent with the notation used for multidimensional array aggregates (see 4.3.3). However, if a pragma `Convention (Fortran, ...)` applies to a multidimensional array type, then column-major order should be used instead (see B.5, “Interfacing with Fortran”).

Followed.

9.6(30-31): Duration'Small

Whenever possible in an implementation, the value of `Duration'Small` should be no greater than 100 microseconds.

Followed. (`Duration'Small = 10**(-9)`).

The time base for `delay_relative_statements` should be monotonic; it need not be the same time base as used for `Calendar.Clock`.

Followed.

10.2.1(12): Consistent Representation

In an implementation, a type declared in a pre-elaborated package should have the same representation in every elaboration of a given version of the package, whether the elaborations occur in distinct executions of the same program, or in executions of distinct programs or partitions that include the given version.

Followed, except in the case of tagged types. Tagged types involve implicit pointers to a local copy of a dispatch table, and these pointers have representations which thus depend on a

particular elaboration of the package. It is not easy to see how it would be possible to follow this advice without severely impacting efficiency of execution.

11.4.1(19): Exception Information

`Exception_Message` by default and `Exception_Information` should produce information useful for debugging. `Exception_Message` should be short, about one line. `Exception_Information` can be long. `Exception_Message` should not include the `Exception_Name`. `Exception_Information` should include both the `Exception_Name` and the `Exception_Message`.

Followed. For each exception that doesn't have a specified `Exception_Message`, the compiler generates one containing the location of the raise statement. This location has the form "file:line", where file is the short file name (without path information) and line is the line number in the file. Note that in the case of the Zero Cost Exception mechanism, these messages become redundant with the `Exception_Information` that contains a full backtrace of the calling sequence, so they are disabled. To disable explicitly the generation of the source location message, use the `Pragma Discard_Names`.

11.5(28): Suppression of Checks

The implementation should minimize the code executed for checks that have been suppressed.

Followed.

13.1 (21-24): Representation Clauses

The recommended level of support for all representation items is qualified as follows:

An implementation need not support representation items containing non-static expressions, except that an implementation should support a representation item for a given entity if each non-static expression in the representation item is a name that statically denotes a constant declared before the entity.

Followed. In fact, GNAT goes beyond the recommended level of support by allowing nonstatic expressions in some representation clauses even without the need to declare constants initialized with the values of such expressions. For example:

```
X : Integer;
Y : Float;
for Y'Address use X'Address;>>
```

An implementation need not support a specification for the `Size` for a given composite subtype, nor the size or storage place for an object (including a component) of a given composite subtype, unless the constraints on the subtype and its composite subcomponents (if any) are all static constraints.

Followed. Size Clauses are not permitted on non-static components, as described above.

An aliased component, or a component whose type is by-reference, should always be allocated at an addressable location.

Followed.

13.2(6-8): Packed Types

If a type is packed, then the implementation should try to minimize storage allocated to objects of the type, possibly at the expense of speed of accessing components, subject to reasonable complexity in addressing calculations.

The recommended level of support pragma **Pack** is:

For a packed record type, the components should be packed as tightly as possible subject to the Sizes of the component subtypes, and subject to any **record_representation_clause** that applies to the type; the implementation may, but need not, reorder components or cross aligned word boundaries to improve the packing. A component whose **Size** is greater than the word size may be allocated an integral number of words.

Followed. Tight packing of arrays is supported for all component sizes up to 64-bits. If the array component size is 1 (that is to say, if the component is a boolean type or an enumeration type with two values) then values of the type are implicitly initialized to zero. This happens both for objects of the packed type, and for objects that have a subcomponent of the packed type.

An implementation should support Address clauses for imported subprograms.

Followed.

13.3(14-19): Address Clauses

For an array *X*, *X'Address* should point at the first component of the array, and not at the array bounds.

Followed.

The recommended level of support for the **Address** attribute is:

X'Address should produce a useful result if *X* is an object that is aliased or of a by-reference type, or is an entity whose **Address** has been specified.

Followed. A valid address will be produced even if none of those conditions have been met. If necessary, the object is forced into memory to ensure the address is valid.

An implementation should support **Address** clauses for imported subprograms.

Followed.

Objects (including subcomponents) that are aliased or of a by-reference type should be allocated on storage element boundaries.

Followed.

If the **Address** of an object is specified, or it is imported or exported, then the implementation should not perform optimizations based on assumptions of no aliases.

Followed.

13.3(29-35): Alignment Clauses

The recommended level of support for the **Alignment** attribute for subtypes is:

An implementation should support specified **Alignments** that are factors and multiples of the number of storage elements per word, subject to the following:

Followed.

An implementation need not support specified **Alignments** for combinations of **Sizes** and **Alignments** that cannot be easily loaded and stored by available machine instructions.

Followed.

An implementation need not support specified **Alignments** that are greater than the maximum **Alignment** the implementation ever returns by default.

Followed.

The recommended level of support for the **Alignment** attribute for objects is:
Same as above, for subtypes, but in addition:

Followed.

For stand-alone library-level objects of statically constrained subtypes, the implementation should support all **Alignments** supported by the target linker. For example, page alignment is likely to be supported for such objects, but not for subtypes.

Followed.

13.3(42-43): Size Clauses

The recommended level of support for the **Size** attribute of objects is:

A **Size** clause should be supported for an object if the specified **Size** is at least as large as its subtype's **Size**, and corresponds to a size in storage elements that is a multiple of the object's **Alignment** (if the **Alignment** is nonzero).

Followed.

13.3(50-56): Size Clauses

If the **Size** of a subtype is specified, and allows for efficient independent addressability (see 9.10) on the target architecture, then the **Size** of the following objects of the subtype should equal the **Size** of the subtype:

Aliased objects (including components).

Followed.

Size clause on a composite subtype should not affect the internal layout of components.

Followed. But note that this can be overridden by use of the implementation pragma `Implicit_Packing` in the case of packed arrays.

The recommended level of support for the **Size** attribute of subtypes is:

The **Size** (if not specified) of a static discrete or fixed point subtype should be the number of bits needed to represent each value belonging to the subtype using an unbiased representation, leaving space for a sign bit only if the subtype contains negative values. If such a subtype is a first subtype, then an implementation should support a specified **Size** for it that reflects this representation.

Followed.

For a subtype implemented with levels of indirection, the **Size** should include the size of the pointers, but not the size of what they point at.

Followed.

13.3(71-73): Component Size Clauses

The recommended level of support for the **Component_Size** attribute is:

An implementation need not support specified `Component_Sizes` that are less than the `Size` of the component subtype.

Followed.

An implementation should support specified `Component_Sizes` that are factors and multiples of the word size. For such `Component_Sizes`, the array should contain no gaps between components. For other `Component_Sizes` (if supported), the array should contain no gaps between components when packing is also specified; the implementation should forbid this combination in cases where it cannot support a no-gaps representation.

Followed.

13.4(9-10): Enumeration Representation Clauses

The recommended level of support for enumeration representation clauses is:

An implementation need not support enumeration representation clauses for boolean types, but should at minimum support the internal codes in the range `System.Min_Int..System.Max_Int`.

Followed.

13.5.1(17-22): Record Representation Clauses

The recommended level of support for `record_representation_clauses` is:

An implementation should support storage places that can be extracted with a load, mask, shift sequence of machine code, and set with a load, shift, mask, store sequence, given the available machine instructions and run-time model.

Followed.

A storage place should be supported if its size is equal to the `Size` of the component subtype, and it starts and ends on a boundary that obeys the `Alignment` of the component subtype.

Followed.

If the default bit ordering applies to the declaration of a given type, then for a component whose subtype's `Size` is less than the word size, any storage place that does not cross an aligned word boundary should be supported.

Followed.

An implementation may reserve a storage place for the tag field of a tagged type, and disallow other components from overlapping that place.

Followed. The storage place for the tag field is the beginning of the tagged record, and its size is `Address'Size`. GNAT will reject an explicit component clause for the tag field.

An implementation need not support a `component_clause` for a component of an extension part if the storage place is not after the storage places of all components of the parent type, whether or not those storage places had been specified.

Followed. The above advice on record representation clauses is followed, and all mentioned features are implemented.

13.5.2(5): Storage Place Attributes

If a component is represented using some form of pointer (such as an offset) to the actual data of the component, and this data is contiguous with the rest of the object, then the storage place attributes should reflect the place of the actual data, not the pointer. If a component is allocated discontinuously from the rest of the object, then a warning should be generated upon reference to one of its storage place attributes.

Followed. There are no such components in GNAT.

13.5.3(7-8): Bit Ordering

The recommended level of support for the non-default bit ordering is:

If `Word_Size = Storage_Unit`, then the implementation should support the non-default bit ordering in addition to the default bit ordering.

Followed. Word size does not equal storage size in this implementation. Thus non-default bit ordering is not supported.

13.7(37): Address as Private

`Address` should be of a private type.

Followed.

13.7.1(16): Address Operations

Operations in `System` and its children should reflect the target environment semantics as closely as is reasonable. For example, on most machines, it makes sense for address arithmetic to “wrap around”. Operations that do not make sense should raise `Program_Error`.

Followed. Address arithmetic is modular arithmetic that wraps around. No operation raises `Program_Error`, since all operations make sense.

13.9(14-17): Unchecked Conversion

The **Size** of an array object should not include its bounds; hence, the bounds should not be part of the converted data.

Followed.

The implementation should not generate unnecessary run-time checks to ensure that the representation of S is a representation of the target type. It should take advantage of the permission to return by reference when possible. Restrictions on unchecked conversions should be avoided unless required by the target environment.

Followed. There are no restrictions on unchecked conversion. A warning is generated if the source and target types do not have the same size since the semantics in this case may be target dependent.

The recommended level of support for unchecked conversions is:

Unchecked conversions should be supported and should be reversible in the cases where this clause defines the result. To enable meaningful use of unchecked conversion, a contiguous representation should be used for elementary subtypes, for statically constrained array subtypes whose component subtype is one of the subtypes described in this paragraph, and for record subtypes without discriminants whose component subtypes are described in this paragraph.

Followed.

13.11(23-25): Implicit Heap Usage

An implementation should document any cases in which it dynamically allocates heap storage for a purpose other than the evaluation of an allocator.

Followed, the only other points at which heap storage is dynamically allocated are as follows:

- At initial elaboration time, to allocate dynamically sized global objects.
- To allocate space for a task when a task is created.
- To extend the secondary stack dynamically when needed. The secondary stack is used for returning variable length results.

A default (implementation-provided) storage pool for an access-to-constant type should not have overhead to support deallocation of individual objects.

Followed.

A storage pool for an anonymous access type should be created at the point of an allocator for the type, and be reclaimed when the designated object becomes inaccessible.

Followed.

13.11.2(17): Unchecked De-allocation

For a standard storage pool, `Free` should actually reclaim the storage.

Followed.

13.13.2(17): Stream Oriented Attributes

If a stream element is the same size as a storage element, then the normal in-memory representation should be used by `Read` and `Write` for scalar objects. Otherwise, `Read` and `Write` should use the smallest number of stream elements needed to represent all values in the base range of the scalar type.

Followed. By default, GNAT uses the interpretation suggested by AI-195, which specifies using the size of the first subtype. However, such an implementation is based on direct binary representations and is therefore target- and endianness-dependent. To address this issue, GNAT also supplies an alternate implementation of the stream attributes `Read` and `Write`, which uses the target-independent XDR standard representation for scalar types. The XDR implementation is provided as an alternative body of the `System.Stream_Attributes` package, in the file ‘`s-stratt-xdr.adb`’ in the GNAT library. There is no ‘`s-stratt-xdr.ads`’ file. In order to install the XDR implementation, do the following:

1. Replace the default implementation of the `System.Stream_Attributes` package with the XDR implementation. For example on a Unix platform issue the commands:

```
$ mv s-stratt.adb s-stratt-default.adb
$ mv s-stratt-xdr.adb s-stratt.adb
```

2. Rebuild the GNAT run-time library as documented in [Section “GNAT and Libraries” in *GNAT User’s Guide*](#).

A.1(52): Names of Predefined Numeric Types

If an implementation provides additional named predefined integer types, then the names should end with ‘`Integer`’ as in ‘`Long_Integer`’. If an implementation provides additional named predefined floating point types, then the names should end with ‘`Float`’ as in ‘`Long_Float`’.

Followed.

A.3.2(49): Ada.Characters.Handling

If an implementation provides a localized definition of `Character` or `Wide_Character`, then the effects of the subprograms in `Characters.Handling` should reflect the localizations. See also 3.5.2.

Followed. GNAT provides no such localized definitions.

A.4.4(106): Bounded-Length String Handling

Bounded string objects should not be implemented by implicit pointers and dynamic allocation.

Followed. No implicit pointers or dynamic allocation are used.

A.5.2(46-47): Random Number Generation

Any storage associated with an object of type `Generator` should be reclaimed on exit from the scope of the object.

Followed.

If the generator period is sufficiently long in relation to the number of distinct initiator values, then each possible value of `Initiator` passed to `Reset` should initiate a sequence of random numbers that does not, in a practical sense, overlap the sequence initiated by any other value. If this is not possible, then the mapping between initiator values and generator states should be a rapidly varying function of the initiator value.

Followed. The generator period is sufficiently long for the first condition here to hold true.

A.10.7(23): Get_Immediate

The `Get_Immediate` procedures should be implemented with unbuffered input. For a device such as a keyboard, input should be *available* if a key has already been typed, whereas for a disk file, input should always be available except at end of file. For a file associated with a keyboard-like device, any line-editing features of the underlying operating system should be disabled during the execution of `Get_Immediate`.

Followed on all targets except VxWorks. For VxWorks, there is no way to provide this functionality that does not result in the input buffer being flushed before the `Get_Immediate` call. A special unit `Interfaces.Vxworks.IO` is provided that contains routines to enable this functionality.

B.1(39-41): Pragma Export

If an implementation supports pragma **Export** to a given language, then it should also allow the main subprogram to be written in that language. It should support some mechanism for invoking the elaboration of the Ada library units included in the system, and for invoking the finalization of the environment task. On typical systems, the recommended mechanism is to provide two subprograms whose link names are **adainit** and **adafinal**. **adainit** should contain the elaboration code for library units. **adafinal** should contain the finalization code. These subprograms should have no effect the second and subsequent time they are called.

Followed.

Automatic elaboration of pre-elaborated packages should be provided when pragma **Export** is supported.

Followed when the main program is in Ada. If the main program is in a foreign language, then **adainit** must be called to elaborate pre-elaborated packages.

For each supported convention *L* other than **Intrinsic**, an implementation should support **Import** and **Export** pragmas for objects of *L*-compatible types and for subprograms, and pragma **Convention** for *L*-eligible types and for subprograms, presuming the other language has corresponding features. Pragma **Convention** need not be supported for scalar types.

Followed.

B.2(12-13): Package Interfaces

For each implementation-defined convention identifier, there should be a child package of package **Interfaces** with the corresponding name. This package should contain any declarations that would be useful for interfacing to the language (implementation) represented by the convention. Any declarations useful for interfacing to any language on the given hardware architecture should be provided directly in **Interfaces**.

Followed. An additional package not defined in the Ada Reference Manual is **Interfaces.CPP**, used for interfacing to C++.

An implementation supporting an interface to C, COBOL, or Fortran should provide the corresponding package or packages described in the following clauses.

Followed. GNAT provides all the packages described in this section.

B.3(63-71): Interfacing with C

An implementation should support the following interface correspondences between Ada and C.

Followed.

An Ada procedure corresponds to a void-returning C function.

Followed.

An Ada function corresponds to a non-void C function.

Followed.

An Ada `in` scalar parameter is passed as a scalar argument to a C function.

Followed.

An Ada `in` parameter of an access-to-object type with designated type T is passed as a t^* argument to a C function, where t is the C type corresponding to the Ada type T .

Followed.

An Ada access T parameter, or an Ada `out` or `in out` parameter of an elementary type T , is passed as a t^* argument to a C function, where t is the C type corresponding to the Ada type T . In the case of an elementary `out` or `in out` parameter, a pointer to a temporary copy is used to preserve by-copy semantics.

Followed.

An Ada parameter of a record type T , of any mode, is passed as a t^* argument to a C function, where t is the C structure corresponding to the Ada type T .

Followed. This convention may be overridden by the use of the `C_Pass_By_Copy` pragma, or Convention, or by explicitly specifying the mechanism for a given call using an extended import or export pragma.

An Ada parameter of an array type with component type T , of any mode, is passed as a t^* argument to a C function, where t is the C type corresponding to the Ada type T .

Followed.

An Ada parameter of an access-to-subprogram type is passed as a pointer to a C function whose prototype corresponds to the designated subprogram's specification.

Followed.

B.4(95-98): Interfacing with COBOL

An Ada implementation should support the following interface correspondences between Ada and COBOL.

Followed.

An Ada access T parameter is passed as a 'BY REFERENCE' data item of the COBOL type corresponding to T .

Followed.

An Ada in scalar parameter is passed as a 'BY CONTENT' data item of the corresponding COBOL type.

Followed.

Any other Ada parameter is passed as a 'BY REFERENCE' data item of the COBOL type corresponding to the Ada parameter type; for scalars, a local copy is used if necessary to ensure by-copy semantics.

Followed.

B.5(22-26): Interfacing with Fortran

An Ada implementation should support the following interface correspondences between Ada and Fortran:

Followed.

An Ada procedure corresponds to a Fortran subroutine.

Followed.

An Ada function corresponds to a Fortran function.

Followed.

An Ada parameter of an elementary, array, or record type T is passed as a T argument to a Fortran procedure, where T is the Fortran type corresponding to the Ada type T , and where the `INTENT` attribute of the corresponding dummy argument matches the Ada formal parameter mode; the Fortran implementation's parameter passing conventions are used. For elementary types, a local copy is used if necessary to ensure by-copy semantics.

Followed.

An Ada parameter of an access-to-subprogram type is passed as a reference to a Fortran procedure whose interface corresponds to the designated subprogram's specification.

Followed.

C.1(3-5): Access to Machine Operations

The machine code or intrinsic support should allow access to all operations normally available to assembly language programmers for the target environment, including privileged instructions, if any.

Followed.

The interfacing pragmas (see Annex B) should support interface to assembler; the default assembler should be associated with the convention identifier `Assembler`.

Followed.

If an entity is exported to assembly language, then the implementation should allocate it at an addressable location, and should ensure that it is retained by the linking process, even if not otherwise referenced from the Ada code. The implementation should assume that any call to a machine code or assembler subprogram is allowed to read or update every object that is specified as exported.

Followed.

C.1(10-16): Access to Machine Operations

The implementation should ensure that little or no overhead is associated with calling intrinsic and machine-code subprograms.

Followed for both intrinsics and machine-code subprograms.

It is recommended that intrinsic subprograms be provided for convenient access to any machine operations that provide special capabilities or efficiency and that are not otherwise available through the language constructs.

Followed. A full set of machine operation intrinsic subprograms is provided.

Atomic read-modify-write operations—e.g., test and set, compare and swap, decrement and test, enqueue/dequeue.

Followed on any target supporting such operations.

Standard numeric functions—e.g., sin, log.

Followed on any target supporting such operations.

String manipulation operations—e.g., translate and test.

Followed on any target supporting such operations.

Vector operations—e.g., compare vector against thresholds.

Followed on any target supporting such operations.

Direct operations on I/O ports.

Followed on any target supporting such operations.

C.3(28): Interrupt Support

If the `Ceiling_Locking` policy is not in effect, the implementation should provide means for the application to specify which interrupts are to be blocked during protected actions, if the underlying system allows for a finer-grain control of interrupt blocking.

Followed. The underlying system does not allow for finer-grain control of interrupt blocking.

C.3.1(20-21): Protected Procedure Handlers

Whenever possible, the implementation should allow interrupt handlers to be called directly by the hardware.

Followed on any target where the underlying operating system permits such direct calls.

Whenever practical, violations of any implementation-defined restrictions should be detected before run time.

Followed. Compile time warnings are given when possible.

C.3.2(25): Package Interrupts

If implementation-defined forms of interrupt handler procedures are supported, such as protected procedures with parameters, then for each such form of a handler, a type analogous to `Parameterless_Handler` should be specified in a child package of `Interrupts`, with the same operations as in the predefined package `Interrupts`.

Followed.

C.4(14): Pre-elaboration Requirements

It is recommended that pre-elaborated packages be implemented in such a way that there should be little or no code executed at run time for the elaboration of entities not already covered by the Implementation Requirements.

Followed. Executable code is generated in some cases, e.g. loops to initialize large arrays.

C.5(8): Pragma Discard_Names

If the pragma applies to an entity, then the implementation should reduce the amount of storage used for storing names associated with that entity.

Followed.

C.7.2(30): The Package Task_Attributes

Some implementations are targeted to domains in which memory use at run time must be completely deterministic. For such implementations, it is recommended that the storage for task attributes will be pre-allocated statically and not from the heap. This can be accomplished by either placing restrictions on the number and the size of the task's attributes, or by using the pre-allocated storage for the first N attribute objects, and the heap for the others. In the latter case, N should be documented.

Not followed. This implementation is not targeted to such a domain.

D.3(17): Locking Policies

The implementation should use names that end with ‘`_Locking`’ for locking policies defined by the implementation.

Followed. A single implementation-defined locking policy is defined, whose name (`Inheritance_Locking`) follows this suggestion.

D.4(16): Entry Queuing Policies

Names that end with ‘_Queuing’ should be used for all implementation-defined queuing policies.

Followed. No such implementation-defined queuing policies exist.

D.6(9-10): Preemptive Abort

Even though the `abort_statement` is included in the list of potentially blocking operations (see 9.5.1), it is recommended that this statement be implemented in a way that never requires the task executing the `abort_statement` to block.

Followed.

On a multi-processor, the delay associated with aborting a task on another processor should be bounded; the implementation should use periodic polling, if necessary, to achieve this.

Followed.

D.7(21): Tasking Restrictions

When feasible, the implementation should take advantage of the specified restrictions to produce a more efficient implementation.

GNAT currently takes advantage of these restrictions by providing an optimized run time when the Ravenscar profile and the GNAT restricted run time set of restrictions are specified. See `pragma Profile (Ravenscar)` and `pragma Profile (Restricted)` for more details.

D.8(47-49): Monotonic Time

When appropriate, implementations should provide configuration mechanisms to change the value of `Tick`.

Such configuration mechanisms are not appropriate to this implementation and are thus not supported.

It is recommended that `Calendar.Clock` and `Real_Time.Clock` be implemented as transformations of the same time base.

Followed.

It is recommended that the *best* time base which exists in the underlying system be available to the application through `Clock`. *Best* may mean highest accuracy or largest range.

Followed.

E.5(28-29): Partition Communication Subsystem

Whenever possible, the PCS on the called partition should allow for multiple tasks to call the RPC-receiver with different messages and should allow them to block until the corresponding subprogram body returns.

Followed by GLADE, a separately supplied PCS that can be used with GNAT.

The `Write` operation on a stream of type `Params_Stream_Type` should raise `Storage_Error` if it runs out of space trying to write the `Item` into the stream.

Followed by GLADE, a separately supplied PCS that can be used with GNAT.

F(7): COBOL Support

If COBOL (respectively, C) is widely supported in the target environment, implementations supporting the Information Systems Annex should provide the child package `Interfaces.COBOL` (respectively, `Interfaces.C`) specified in Annex B and should support a `convention_identifier` of COBOL (respectively, C) in the interfacing pragmas (see Annex B), thus allowing Ada programs to interface with programs written in that language.

Followed.

F.1(2): Decimal Radix Support

Packed decimal should be used as the internal representation for objects of subtype `S` when `S'Machine_Radix = 10`.

Not followed. GNAT ignores `S'Machine_Radix` and always uses binary representations.

G: Numerics

If Fortran (respectively, C) is widely supported in the target environment, implementations supporting the Numerics Annex should provide the child package `Interfaces.Fortran` (respectively, `Interfaces.C`) specified in Annex B and should support a `convention_identifier` of Fortran (respectively, C) in the interfacing pragmas (see Annex B), thus allowing Ada programs to interface with programs written in that language.

Followed.

G.1.1(56-58): Complex Types

Because the usual mathematical meaning of multiplication of a complex operand and a real operand is that of the scaling of both components of the former by the latter, an implementation should not perform this operation by first promoting the real operand to complex type and then performing a full complex multiplication. In systems that, in the future, support an Ada binding to IEC 559:1989, the latter technique will not generate the required result when one of the components of the complex operand is infinite. (Explicit multiplication of the infinite component by the zero component obtained during promotion yields a NaN that propagates into the final result.) Analogous advice applies in the case of multiplication of a complex operand and a pure-imaginary operand, and in the case of division of a complex operand by a real or pure-imaginary operand.

Not followed.

Similarly, because the usual mathematical meaning of addition of a complex operand and a real operand is that the imaginary operand remains unchanged, an implementation should not perform this operation by first promoting the real operand to complex type and then performing a full complex addition. In implementations in which the **Signed_Zeros** attribute of the component type is **True** (and which therefore conform to IEC 559:1989 in regard to the handling of the sign of zero in predefined arithmetic operations), the latter technique will not generate the required result when the imaginary component of the complex operand is a negatively signed zero. (Explicit addition of the negative zero to the zero obtained during promotion yields a positive zero.) Analogous advice applies in the case of addition of a complex operand and a pure-imaginary operand, and in the case of subtraction of a complex operand and a real or pure-imaginary operand.

Not followed.

Implementations in which **Real'Signed_Zeros** is **True** should attempt to provide a rational treatment of the signs of zero results and result components. As one example, the result of the **Argument** function should have the sign of the imaginary component of the parameter **X** when the point represented by that parameter lies on the positive real axis; as another, the sign of the imaginary component of the **Compose_From_Polar** function should be the same as (respectively, the opposite of) that of the **Argument** parameter when that parameter has a value of zero and the **Modulus** parameter has a nonnegative (respectively, negative) value.

Followed.

G.1.2(49): Complex Elementary Functions

Implementations in which `Complex_Types.Real'Signed_Zeros` is `True` should attempt to provide a rational treatment of the signs of zero results and result components. For example, many of the complex elementary functions have components that are odd functions of one of the parameter components; in these cases, the result component should have the sign of the parameter component at the origin. Other complex elementary functions have zero components whose sign is opposite that of a parameter component at the origin, or is always positive or always negative.

Followed.

G.2.4(19): Accuracy Requirements

The versions of the forward trigonometric functions without a `Cycle` parameter should not be implemented by calling the corresponding version with a `Cycle` parameter of `2.0*Numerics.Pi`, since this will not provide the required accuracy in some portions of the domain. For the same reason, the version of `Log` without a `Base` parameter should not be implemented by calling the corresponding version with a `Base` parameter of `Numerics.e`.

Followed.

G.2.6(15): Complex Arithmetic Accuracy

The version of the `Compose_From_Polar` function without a `Cycle` parameter should not be implemented by calling the corresponding version with a `Cycle` parameter of `2.0*Numerics.Pi`, since this will not provide the required accuracy in some portions of the domain.

Followed.

4 Implementation Defined Characteristics

In addition to the implementation dependent pragmas and attributes, and the implementation advice, there are a number of other Ada features that are potentially implementation dependent and are designated as implementation-defined. These are mentioned throughout the Ada Reference Manual, and are summarized in Annex M.

A requirement for conforming Ada compilers is that they provide documentation describing how the implementation deals with each of these issues. In this chapter, you will find each point in Annex M listed followed by a description in *italic font* of how GNAT handles the implementation dependence.

You can use this chapter as a guide to minimizing implementation dependent features in your programs if portability to other compilers and other operating systems is an important consideration. The numbers in each section below correspond to the paragraph number in the Ada Reference Manual.

2. Whether or not each recommendation given in Implementation Advice is followed. See 1.1.2(37).

See [Chapter 3 \[Implementation Advice\]](#), page 67.

3. Capacity limitations of the implementation. See 1.1.3(3).

The complexity of programs that can be processed is limited only by the total amount of available virtual memory, and disk space for the generated object files.

4. Variations from the standard that are impractical to avoid given the implementation's execution environment. See 1.1.3(6).

There are no variations from the standard.

5. Which `code_statements` cause external interactions. See 1.1.3(10).

Any `code_statement` can potentially cause external interactions.

6. The coded representation for the text of an Ada program. See 2.1(4).

See separate section on source representation.

7. The control functions allowed in comments. See 2.1(14).

See separate section on source representation.

8. The representation for an end of line. See 2.2(2).

See separate section on source representation.

9. Maximum supported line length and lexical element length. See 2.2(15).

The maximum line length is 255 characters and the maximum length of a lexical element is also 255 characters.

10. Implementation defined pragmas. See 2.8(14).

See [Chapter 1 \[Implementation Defined Pragmas\]](#), page 3.

11. Effect of pragma `Optimize`. See 2.8(27).

Pragma `Optimize`, if given with a `Time` or `Space` parameter, checks that the optimization flag is set, and aborts if it is not.

12. The sequence of characters of the value returned by `S'Image` when some of the graphic characters of `S'Wide_Image` are not defined in `Character`. See 3.5(37).

The sequence of characters is as defined by the wide character encoding method used for the source. See section on source representation for further details.

13. The predefined integer types declared in `Standard`. See 3.5.4(25).

`Short_Short_Integer`
8 bit signed

`Short_Integer`
(Short) 16 bit signed

`Integer` 32 bit signed

`Long_Integer`
64 bit signed (Alpha OpenVMS only) 32 bit signed (all other targets)

`Long_Long_Integer`
64 bit signed

14. Any nonstandard integer types and the operators defined for them. See 3.5.4(26).

There are no nonstandard integer types.

15. Any nonstandard real types and the operators defined for them. See 3.5.6(8).

There are no nonstandard real types.

16. What combinations of requested decimal precision and range are supported for floating point types. See 3.5.7(7).

The precision and range is as defined by the IEEE standard.

17. The predefined floating point types declared in **Standard**. See 3.5.7(16).

Short_Float

32 bit IEEE short

Float (Short) 32 bit IEEE short

Long_Float

64 bit IEEE long

Long_Long_Float

64 bit IEEE long (80 bit IEEE long on x86 processors)

18. The small of an ordinary fixed point type. See 3.5.9(8).

Fine_Delta is $2^{*(-63)}$

19. What combinations of small, range, and digits are supported for fixed point types. See 3.5.9(10).

Any combinations are permitted that do not result in a small less than **Fine_Delta** and do not result in a mantissa larger than 63 bits. If the mantissa is larger than 53 bits on machines where **Long_Long_Float** is 64 bits (true of all architectures except ia32), then the output from **Text_IO** is accurate to only 53 bits, rather than the full mantissa. This is because floating-point conversions are used to convert fixed point.

20. The result of **Tags.Expanded_Name** for types declared within an unnamed **block_statement**. See 3.9(10).

Block numbers of the form **Bnnn**, where *nnn* is a decimal integer are allocated.

21. Implementation-defined attributes. See 4.1.4(12).

See [Chapter 2 \[Implementation Defined Attributes\]](#), page 57.

22. Any implementation-defined time types. See 9.6(6).

There are no implementation-defined time types.

23. The time base associated with relative delays.

See 9.6(20). The time base used is that provided by the C library function `gettimeofday`.

24. The time base of the type `Calendar.Time`. See 9.6(23).

The time base used is that provided by the C library function `gettimeofday`.

25. The time zone used for package `Calendar` operations. See 9.6(24).

The time zone used by package `Calendar` is the current system time zone setting for local time, as accessed by the C library function `localtime`.

26. Any limit on `delay_until_statements` of `select_statements`. See 9.6(29).

There are no such limits.

27. Whether or not two non-overlapping parts of a composite object are independently addressable, in the case where packing, record layout, or `Component_Size` is specified for the object. See 9.10(1).

Separate components are independently addressable if they do not share overlapping storage units.

28. The representation for a compilation. See 10.1(2).

A compilation is represented by a sequence of files presented to the compiler in a single invocation of the `gcc` command.

29. Any restrictions on compilations that contain multiple compilation_units. See 10.1(4).

No single file can contain more than one compilation unit, but any sequence of files can be presented to the compiler as a single compilation.

30. The mechanisms for creating an environment and for adding and replacing compilation units. See 10.1.4(3).

See separate section on compilation model.

31. The manner of explicitly assigning library units to a partition. See 10.2(2).

If a unit contains an Ada main program, then the Ada units for the partition are determined by recursive application of the rules in the Ada Reference Manual section 10.2(2-6). In other words, the Ada units will be those that are needed by the main program, and then this definition

of need is applied recursively to those units, and the partition contains the transitive closure determined by this relationship. In short, all the necessary units are included, with no need to explicitly specify the list. If additional units are required, e.g. by foreign language units, then all units must be mentioned in the context clause of one of the needed Ada units.

If the partition contains no main program, or if the main program is in a language other than Ada, then GNAT provides the binder options ‘-z’ and ‘-n’ respectively, and in this case a list of units can be explicitly supplied to the binder for inclusion in the partition (all units needed by these units will also be included automatically). For full details on the use of these options, refer to [Section “The GNAT Make Program gnatmake” in *GNAT User’s Guide*](#).

32. The implementation-defined means, if any, of specifying which compilation units are needed by a given compilation unit. See 10.2(2).

The units needed by a given compilation unit are as defined in the Ada Reference Manual section 10.2(2-6). There are no implementation-defined pragmas or other implementation-defined means for specifying needed units.

33. The manner of designating the main subprogram of a partition. See 10.2(7).

The main program is designated by providing the name of the corresponding ‘ALI’ file as the input parameter to the binder.

34. The order of elaboration of `library_items`. See 10.2(18).

The first constraint on ordering is that it meets the requirements of Chapter 10 of the Ada Reference Manual. This still leaves some implementation dependent choices, which are resolved by first elaborating bodies as early as possible (i.e., in preference to specs where there is a choice), and second by evaluating the immediate with clauses of a unit to determine the probably best choice, and third by elaborating in alphabetical order of unit names where a choice still remains.

35. Parameter passing and function return for the main subprogram. See 10.2(21).

The main program has no parameters. It may be a procedure, or a function returning an integer type. In the latter case, the returned integer value is the return code of the program (overriding any value that may have been set by a call to `Ada.Command_Line.Set_Exit_Status`).

36. The mechanisms for building and running partitions. See 10.2(24).

GNAT itself supports programs with only a single partition. The GNATDIST tool provided with the GLADE package (which also includes an implementation of the PCS) provides a completely flexible method for building and running programs consisting of multiple partitions. See the separate GLADE manual for details.

37. The details of program execution, including program termination. See 10.2(25).

See separate section on compilation model.

38. The semantics of any non-active partitions supported by the implementation. See 10.2(28).

Passive partitions are supported on targets where shared memory is provided by the operating system. See the GLADE reference manual for further details.

39. The information returned by `Exception_Message`. See 11.4.1(10).

Exception message returns the null string unless a specific message has been passed by the program.

40. The result of `Exceptions.Exception_Name` for types declared within an unnamed `block_statement`. See 11.4.1(12).

Blocks have implementation defined names of the form `Bnnn` where `nnn` is an integer.

41. The information returned by `Exception_Information`. See 11.4.1(13).

`Exception_Information` returns a string in the following format:

```
Exception_Name: nnnnn
Message: mmmmm
PID: ppp
Call stack traceback locations:
0xhhhh 0xhhhh 0xhhhh ... 0xhhh
```

where

- `nnnn` is the fully qualified name of the exception in all upper case letters. This line is always present.
- `mmmm` is the message (this line present only if message is non-null)
- `ppp` is the Process Id value as a decimal integer (this line is present only if the Process Id is nonzero). Currently we are not making use of this field.
- The Call stack traceback locations line and the following values are present only if at least one traceback location was recorded. The values are given in C style format, with lower case letters for a-f, and only as many digits present as are necessary.

The line terminator sequence at the end of each line, including the last line is a single LF character (16#0A#).

42. Implementation-defined check names. See 11.5(27).

The implementation defined check name `Alignment_Check` controls checking of address clause values for proper alignment (that is, the address supplied must be consistent with the alignment of the type).

In addition, a user program can add implementation-defined check names by means of the pragma `Check_Name`.

43. The interpretation of each aspect of representation. See 13.1(20).

See separate section on data representations.

44. Any restrictions placed upon representation items. See 13.1(20).

See separate section on data representations.

45. The meaning of **Size** for indefinite subtypes. See 13.3(48).

Size for an indefinite subtype is the maximum possible size, except that for the case of a sub-program parameter, the size of the parameter object is the actual size.

46. The default external representation for a type tag. See 13.3(75).

The default external representation for a type tag is the fully expanded name of the type in upper case letters.

47. What determines whether a compilation unit is the same in two different partitions. See 13.3(76).

A compilation unit is the same in two different partitions if and only if it derives from the same source file.

48. Implementation-defined components. See 13.5.1(15).

The only implementation defined component is the tag for a tagged type, which contains a pointer to the dispatching table.

49. If **Word_Size** = **Storage_Unit**, the default bit ordering. See 13.5.3(5).

Word_Size (32) is not the same as **Storage_Unit** (8) for this implementation, so no non-default bit ordering is supported. The default bit ordering corresponds to the natural endianness of the target architecture.

50. The contents of the visible part of package **System** and its language-defined children. See 13.7(2).

See the definition of these packages in files ‘**system.ads**’ and ‘**s-stoele.ads**’.

51. The contents of the visible part of package **System.Machine_Code**, and the meaning of **code_statements**. See 13.8(7).

See the definition and documentation in file ‘`s-maccod.ads`’.

52. The effect of unchecked conversion. See 13.9(11).

Unchecked conversion between types of the same size results in an uninterpreted transmission of the bits from one type to the other. If the types are of unequal sizes, then in the case of discrete types, a shorter source is first zero or sign extended as necessary, and a shorter target is simply truncated on the left. For all non-discrete types, the source is first copied if necessary to ensure that the alignment requirements of the target are met, then a pointer is constructed to the source value, and the result is obtained by dereferencing this pointer after converting it to be a pointer to the target type. Unchecked conversions where the target subtype is an unconstrained array are not permitted. If the target alignment is greater than the source alignment, then a copy of the result is made with appropriate alignment

53. The semantics of operations on invalid representations. See 13.9.2(10-11).

For assignments and other operations where the use of invalid values cannot result in erroneous behavior, the compiler ignores the possibility of invalid values. An exception is raised at the point where an invalid value would result in erroneous behavior. For example executing:

```
procedure invalidvals is
  X : Integer := -1;
  Y : Natural range 1 .. 10;
  for Y'Address use X'Address;
  Z : Natural range 1 .. 10;
  A : array (Natural range 1 .. 10) of Integer;
begin
  Z := Y;      -- no exception
  A (Z) := 3;  -- exception raised;
end;
```

As indicated, an exception is raised on the array assignment, but not on the simple assignment of the invalid negative value from Y to Z.

53. The manner of choosing a storage pool for an access type when `Storage_Pool` is not specified for the type. See 13.11(17).

There are 3 different standard pools used by the compiler when `Storage_Pool` is not specified depending whether the type is local to a subprogram or defined at the library level and whether `Storage_Size` is specified or not. See documentation in the runtime library units `System.Pool_Global`, `System.Pool_Size` and `System.Pool_Local` in files ‘`s-poosiz.ads`’, ‘`s-pooglo.ads`’ and ‘`s-pooloc.ads`’ for full details on the default pools used.

54. Whether or not the implementation provides user-accessible names for the standard pool type(s). See 13.11(17).

See documentation in the sources of the run time mentioned in paragraph **53** . All these pools are accessible by means of `with`’ing these units.

55. The meaning of `Storage_Size`. See 13.11(18).

`Storage_Size` is measured in storage units, and refers to the total space available for an access type collection, or to the primary stack space for a task.

56. Implementation-defined aspects of storage pools. See 13.11(22).

See documentation in the sources of the run time mentioned in paragraph **53** for details on GNAT-defined aspects of storage pools.

57. The set of restrictions allowed in a pragma `Restrictions`. See 13.12(7).

All RM defined Restriction identifiers are implemented. The following additional restriction identifiers are provided. There are two separate lists of implementation dependent restriction identifiers. The first set requires consistency throughout a partition (in other words, if the restriction identifier is used for any compilation unit in the partition, then all compilation units in the partition must obey the restriction).

`Simple_Barriers`

This restriction ensures at compile time that barriers in entry declarations for protected types are restricted to either static boolean expressions or references to simple boolean variables defined in the private part of the protected type. No other form of entry barriers is permitted. This is one of the restrictions of the Ravenscar profile for limited tasking (see also pragma `Profile (Ravenscar)`).

`Max_Entry_Queue_Length => Expr`

This restriction is a declaration that any protected entry compiled in the scope of the restriction has at most the specified number of tasks waiting on the entry at any one time, and so no queue is required. This restriction is not checked at compile time. A program execution is erroneous if an attempt is made to queue more than the specified number of tasks on such an entry.

`No_Calendar`

This restriction ensures at compile time that there is no implicit or explicit dependence on the package `Ada.Calendar`.

`No_Default_Initialization`

This restriction prohibits any instance of default initialization of variables. The binder implements a consistency rule which prevents any unit compiled without the restriction from with'ing a unit with the restriction (this allows the generation of initialization procedures to be skipped, since you can be sure that no call is ever generated to an initialization procedure in a unit with the restriction active). If used in conjunction with `Initialize_Scalars` or `Normalize_Scalars`, the effect is to prohibit all cases of variables declared without a specific initializer (including the case of OUT scalar parameters).

`No_Direct_Boolean_Operators`

This restriction ensures that no logical (and/or/xor) are used on operands of type Boolean (or any type derived from Boolean). This is intended for use in safety critical programs where the certification protocol requires the use of short-circuit (and then, or else) forms for all composite boolean operations.

No_Dispatching_Calls

This restriction ensures at compile time that the code generated by the compiler involves no dispatching calls. The use of this restriction allows the safe use of record extensions, classwide membership tests and other classwide features not involving implicit dispatching. This restriction ensures that the code contains no indirect calls through a dispatching mechanism. Note that this includes internally-generated calls created by the compiler, for example in the implementation of class-wide objects assignments. The membership test is allowed in the presence of this restriction, because its implementation requires no dispatching. This restriction is comparable to the official Ada restriction `No_Dispatch` except that it is a bit less restrictive in that it allows all classwide constructs that do not imply dispatching. The following example indicates constructs that violate this restriction.

```

package Pkg is
  type T is tagged record
    Data : Natural;
  end record;
  procedure P (X : T);

  type DT is new T with record
    More_Data : Natural;
  end record;
  procedure Q (X : DT);
end Pkg;

with Pkg; use Pkg;
procedure Example is
  procedure Test (O : T'Class) is
    N : Natural := O'Size;-- Error: Dispatching call
    C : T'Class := O;    -- Error: implicit Dispatching Call
  begin
    if O in DT'Class then -- OK : Membership test
      Q (DT (O));         -- OK : Type conversion plus direct call
    else
      P (O);              -- Error: Dispatching call
    end if;
  end Test;

  Obj : DT;
begin
  P (Obj);               -- OK : Direct call
  P (T (Obj));           -- OK : Type conversion plus direct call
  P (T'Class (Obj));     -- Error: Dispatching call

  Test (Obj);            -- OK : Type conversion

  if Obj in T'Class then -- OK : Membership test
    null;
  end if;
end Example;

```

No_Dynamic_Attachment

This restriction ensures that there is no call to any of the operations defined in package `Ada.Interrupts`.

No_Enumeration_Maps

This restriction ensures at compile time that no operations requiring enumeration maps are used (that is `Image` and `Value` attributes applied to enumeration types).

No_Entry_Calls_In_Elaboration_Code

This restriction ensures at compile time that no task or protected entry calls are made during elaboration code. As a result of the use of this restriction, the compiler

can assume that no code past an accept statement in a task can be executed at elaboration time.

No_Exception_Handlers

This restriction ensures at compile time that there are no explicit exception handlers. It also indicates that no exception propagation will be provided. In this mode, exceptions may be raised but will result in an immediate call to the last chance handler, a routine that the user must define with the following profile:

```
procedure Last_Chance_Handler
  (Source_Location : System.Address; Line : Integer);
pragma Export (C, Last_Chance_Handler,
  "__gnat_last_chance_handler");
```

The parameter is a C null-terminated string representing a message to be associated with the exception (typically the source location of the raise statement generated by the compiler). The Line parameter when nonzero represents the line number in the source program where the raise occurs.

No_Exception_Propagation

This restriction guarantees that exceptions are never propagated to an outer subprogram scope). The only case in which an exception may be raised is when the handler is statically in the same subprogram, so that the effect of a raise is essentially like a goto statement. Any other raise statement (implicit or explicit) will be considered unhandled. Exception handlers are allowed, but may not contain an exception occurrence identifier (exception choice). In addition use of the package GNAT.Current_Exception is not permitted, and reraise statements (raise with no operand) are not permitted.

No_Exception_Registration

This restriction ensures at compile time that no stream operations for types Exception_Id or Exception_Occurrence are used. This also makes it impossible to pass exceptions to or from a partition with this restriction in a distributed environment. If this exception is active, then the generated code is simplified by omitting the otherwise-required global registration of exceptions when they are declared.

No_Implicit_Conditionals

This restriction ensures that the generated code does not contain any implicit conditionals, either by modifying the generated code where possible, or by rejecting any construct that would otherwise generate an implicit conditional. Note that this check does not include run time constraint checks, which on some targets may generate implicit conditionals as well. To control the latter, constraint checks can be suppressed in the normal manner. Constructs generating implicit conditionals include comparisons of composite objects and the Max/Min attributes.

No_Implicit_Dynamic_Code

This restriction prevents the compiler from building “trampolines”. This is a structure that is built on the stack and contains dynamic code to be executed at run time. On some targets, a trampoline is built for the following features: **Access**, **Unrestricted_Access**, or **Address** of a nested subprogram; nested task bodies; primitive operations of nested tagged types. Trampolines do not work on machines that prevent execution of stack data. For example, on windows systems, enabling DEP (data execution protection) will cause trampolines to raise an exception. Trampolines are also quite slow at run time.

On many targets, trampolines have been largely eliminated. Look at the version of system.ads for your target — if it has Always-Compatible_Rep equal to False, then trampolines are largely eliminated. In particular, a trampoline is built for

the following features: **Address** of a nested subprogram; **Access** or **Unrestricted_Access** of a nested subprogram, but only if pragma **Favor_Top_Level** applies, or the access type has a foreign-language convention; primitive operations of nested tagged types.

No_Implicit_Loops

This restriction ensures that the generated code does not contain any implicit **for** loops, either by modifying the generated code where possible, or by rejecting any construct that would otherwise generate an implicit **for** loop. If this restriction is active, it is possible to build large array aggregates with all static components without generating an intermediate temporary, and without generating a loop to initialize individual components. Otherwise, a loop is created for arrays larger than about 5000 scalar components.

No_InitializeScalars

This restriction ensures that no unit in the partition is compiled with pragma **InitializeScalars**. This allows the generation of more efficient code, and in particular eliminates dummy null initialization routines that are otherwise generated for some record and array types.

No_Local_Protected_Objects

This restriction ensures at compile time that protected objects are only declared at the library level.

No_Protected_Type_Allocators

This restriction ensures at compile time that there are no allocator expressions that attempt to allocate protected objects.

No_Secondary_Stack

This restriction ensures at compile time that the generated code does not contain any reference to the secondary stack. The secondary stack is used to implement functions returning unconstrained objects (arrays or records) on some targets.

No_Select_Statements

This restriction ensures at compile time no select statements of any kind are permitted, that is the keyword **select** may not appear. This is one of the restrictions of the Ravenscar profile for limited tasking (see also pragma **Profile (Ravenscar)**).

No_Standard_Storage_Pools

This restriction ensures at compile time that no access types use the standard default storage pool. Any access type declared must have an explicit **Storage_Pool** attribute defined specifying a user-defined storage pool.

No_Streams

This restriction ensures at compile/bind time that there are no stream objects created and no use of stream attributes. This restriction does not forbid dependences on the package **Ada.Streams**. So it is permissible to with **Ada.Streams** (or another package that does so itself) as long as no actual stream objects are created and no stream attributes are used.

Note that the use of restriction allows optimization of tagged types, since they do not need to worry about dispatching stream operations. To take maximum advantage of this space-saving optimization, any unit declaring a tagged type should be compiled with the restriction, though this is not required.

No_Task_Attributes_Package

This restriction ensures at compile time that there are no implicit or explicit dependencies on the package **Ada.Task_Attributes**.

No_Task_Termination

This restriction ensures at compile time that no terminate alternatives appear in any task body.

No_Tasking

This restriction prevents the declaration of tasks or task types throughout the partition. It is similar in effect to the use of `Max_Tasks => 0` except that violations are caught at compile time and cause an error message to be output either by the compiler or binder.

Static_Priorities

This restriction ensures at compile time that all priority expressions are static, and that there are no dependencies on the package `Ada.Dynamic_Priorities`.

Static_Storage_Size

This restriction ensures at compile time that any expression appearing in a `Storage_Size` pragma or attribute definition clause is static.

The second set of implementation dependent restriction identifiers does not require partition-wide consistency. The restriction may be enforced for a single compilation unit without any effect on any of the other compilation units in the partition.

No_Elaboration_Code

This restriction ensures at compile time that no elaboration code is generated. Note that this is not the same condition as is enforced by pragma `Preelaborate`. There are cases in which pragma `Preelaborate` still permits code to be generated (e.g. code to initialize a large array to all zeroes), and there are cases of units which do not meet the requirements for pragma `Preelaborate`, but for which no elaboration code is generated. Generally, it is the case that preelaborable units will meet the restrictions, with the exception of large aggregates initialized with an `others_clause`, and exception declarations (which generate calls to a run-time registry procedure). This restriction is enforced on a unit by unit basis, it need not be obeyed consistently throughout a partition.

In the case of aggregates with `others`, if the aggregate has a dynamic size, there is no way to eliminate the elaboration code (such dynamic bounds would be incompatible with `Preelaborate` in any case). If the bounds are static, then use of this restriction actually modifies the code choice of the compiler to avoid generating a loop, and instead generate the aggregate statically if possible, no matter how many times the data for the `others` clause must be repeatedly generated.

It is not possible to precisely document the constructs which are compatible with this restriction, since, unlike most other restrictions, this is not a restriction on the source code, but a restriction on the generated object code. For example, if the source contains a declaration:

```
Val : constant Integer := X;
```

where X is not a static constant, it may be possible, depending on complex optimization circuitry, for the compiler to figure out the value of X at compile time, in which case this initialization can be done by the loader, and requires no initialization code. It is not possible to document the precise conditions under which the optimizer can figure this out.

Note that this the implementation of this restriction requires full code generation. If it is used in conjunction with "semantics only" checking, then some cases of violations may be missed.

No_Entry_Queue

This restriction is a declaration that any protected entry compiled in the scope of the restriction has at most one task waiting on the entry at any one time, and so no queue is required. This restriction is not checked at compile time. A program execution is erroneous if an attempt is made to queue a second task on such an entry.

No_Implementation_Attributes

This restriction checks at compile time that no GNAT-defined attributes are present. With this restriction, the only attributes that can be used are those defined in the Ada Reference Manual.

No_Implementation_Pragmas

This restriction checks at compile time that no GNAT-defined pragmas are present. With this restriction, the only pragmas that can be used are those defined in the Ada Reference Manual.

No_Implementation_Restrictions

This restriction checks at compile time that no GNAT-defined restriction identifiers (other than **No_Implementation_Restrictions** itself) are present. With this restriction, the only other restriction identifiers that can be used are those defined in the Ada Reference Manual.

No_Wide_Characters

This restriction ensures at compile time that no uses of the types **Wide_Character** or **Wide_String** or corresponding wide wide types appear, and that no wide or wide wide string or character literals appear in the program (that is literals representing characters not in type **Character**).

58. The consequences of violating limitations on **Restrictions** pragmas. See 13.12(9).

Restrictions that can be checked at compile time result in illegalities if violated. Currently there are no other consequences of violating restrictions.

59. The representation used by the **Read** and **Write** attributes of elementary types in terms of stream elements. See 13.13.2(9).

The representation is the in-memory representation of the base type of the type, using the number of bits corresponding to the **type'Size** value, and the natural ordering of the machine.

60. The names and characteristics of the numeric subtypes declared in the visible part of package **Standard**. See A.1(3).

See items describing the integer and floating-point types supported.

61. The accuracy actually achieved by the elementary functions. See A.5.1(1).

The elementary functions correspond to the functions available in the C library. Only fast math mode is implemented.

62. The sign of a zero result from some of the operators or functions in `Numerics.Generic_Elementary_Functions`, when `Float_Type'Signed_Zeros` is `True`. See A.5.1(46).

The sign of zeroes follows the requirements of the IEEE 754 standard on floating-point.

63. The value of `Numerics.Float_Random.Max_Image_Width`. See A.5.2(27).

Maximum image width is 6864, see library file `'s-rannum.ads'`.

64. The value of `Numerics.Discrete_Random.Max_Image_Width`. See A.5.2(27).

Maximum image width is 6864, see library file `'s-rannum.ads'`.

65. The algorithms for random number generation. See A.5.2(32).

The algorithm is the Mersenne Twister, as documented in the source file `'s-rannum.adb'`. This version of the algorithm has a period of $2^{19937}-1$.

66. The string representation of a random number generator's state. See A.5.2(38).

The value returned by the `Image` function is the concatenation of the fixed-width decimal representations of the 64 32-bit integers of the state vector.

67. The minimum time interval between calls to the time-dependent `Reset` procedure that are guaranteed to initiate different random number sequences. See A.5.2(45).

The minimum period between reset calls to guarantee distinct series of random numbers is one microsecond.

68. The values of the `Model_Mantissa`, `Model_Emin`, `Model_Epsilon`, `Model_Safe_First`, and `Safe_Last` attributes, if the Numerics Annex is not supported. See A.5.3(72).

Run the compiler with `'-gnatS'` to produce a listing of package `Standard`, has the values of all numeric attributes.

69. Any implementation-defined characteristics of the input-output packages. See A.7(14).

There are no special implementation defined characteristics for these packages.

70. The value of `Buffer_Size` in `Storage_IO`. See A.9(10).

All type representations are contiguous, and the `Buffer_Size` is the value of `type'Size` rounded up to the next storage unit boundary.

71. External files for standard input, standard output, and standard error See A.10(5).

These files are mapped onto the files provided by the C streams libraries. See source file ‘`i-cstrea.ads`’ for further details.

72. The accuracy of the value produced by `Put`. See A.10.9(36).

If more digits are requested in the output than are represented by the precision of the value, zeroes are output in the corresponding least significant digit positions.

73. The meaning of `Argument_Count`, `Argument`, and `Command_Name`. See A.15(1).

These are mapped onto the `argv` and `argc` parameters of the main program in the natural manner.

74. The interpretation of the `Form` parameter in procedure `Create_Directory`. See A.16(56).

The `Form` parameter is not used.

75. The interpretation of the `Form` parameter in procedure `Create_Path`. See A.16(60).

The `Form` parameter is not used.

76. The interpretation of the `Form` parameter in procedure `Copy_File`. See A.16(68).

The `Form` parameter is case-insensitive.

Two fields are recognized in the `Form` parameter:

`preserve=<value>`

`mode=<value>`

`<value>` starts immediately after the character ‘=’ and ends with the character immediately preceding the next comma (’,’) or with the last character of the parameter.

The only possible values for `preserve=` are:

`no_attributes`

Do not try to preserve any file attributes. This is the default if no `preserve=` is found in `Form`.

`all_attributes`

Try to preserve all file attributes (timestamps, access rights).

`timestamps`

Preserve the timestamp of the copied file, but not the other file attributes.

The only possible values for `mode=` are:

`copy`

Only do the copy if the destination file does not already exist. If it already exists, `Copy_File` fails.

overwrite

Copy the file in all cases. Overwrite an already existing destination file.

append

Append the original file to the destination file. If the destination file does not exist, the destination file is a copy of the source file. When mode=append, the field preserve=, if it exists, is not taken into account.

If the Form parameter includes one or both of the fields and the value or values are incorrect, Copy_file fails with Use_Error.

Examples of correct Forms:

```
Form => "preserve=no_attributes,mode=overwrite" (the default)
Form => "mode=append"
Form => "mode=copy, preserve=all_attributes"
```

Examples of incorrect Forms

```
Form => "preserve=junk"
Form => "mode=internal, preserve=timestamps"
```

77. Implementation-defined convention names. See B.1(11).

The following convention names are supported

Ada Ada

Assembler

Assembly language

Asm Synonym for Assembler

Assembly Synonym for Assembler

C C

C_Pass_By_Copy

Allowed only for record types, like C, but also notes that record is to be passed by copy rather than reference.

COBOL COBOL

C_Plus_Plus (or CPP)

C++

Default Treated the same as C

External Treated the same as C

Fortran Fortran

Intrinsic

For support of pragma **Import** with convention Intrinsic, see separate section on Intrinsic Subprograms.

Stdcall Stdcall (used for Windows implementations only). This convention correspond to the WINAPI (previously called Pascal convention) C/C++ convention under Windows. A function with this convention cleans the stack before exit.

DLL Synonym for Stdcall

Win32 Synonym for Stdcall

Stubbed Stubbed is a special convention used to indicate that the body of the subprogram will be entirely ignored. Any call to the subprogram is converted into a raise of the `Program_Error` exception. If a pragma `Import` specifies convention `stubbed` then no body need be present at all. This convention is useful during development for the inclusion of subprograms whose body has not yet been written.

In addition, all otherwise unrecognized convention names are also treated as being synonymous with convention `C`. In all implementations except for VMS, use of such other names results in a warning. In VMS implementations, these names are accepted silently.

78. The meaning of link names. See B.1(36).

Link names are the actual names used by the linker.

79. The manner of choosing link names when neither the link name nor the address of an imported or exported entity is specified. See B.1(36).

The default linker name is that which would be assigned by the relevant external language, interpreting the Ada name as being in all lower case letters.

80. The effect of pragma `Linker_Options`. See B.1(37).

The string passed to `Linker_Options` is presented uninterpreted as an argument to the link command, unless it contains ASCII.NUL characters. NUL characters if they appear act as argument separators, so for example

```
pragma Linker_Options ("-labc" & ASCII.NUL & "-ldef");
```

causes two separate arguments `-labc` and `-ldef` to be passed to the linker. The order of linker options is preserved for a given unit. The final list of options passed to the linker is in reverse order of the elaboration order. For example, linker options for a body always appear before the options from the corresponding package spec.

81. The contents of the visible part of package `Interfaces` and its language-defined descendants. See B.2(1).

See files with prefix `'i-'` in the distributed library.

82. Implementation-defined children of package `Interfaces`. The contents of the visible part of package `Interfaces`. See B.2(11).

See files with prefix `'i-'` in the distributed library.

83. The types `Floating`, `Long_Floating`, `Binary`, `Long_Binary`, `Decimal_Element`, and `COBOL_Character`; and the initialization of the variables `Ada_To_COBOL` and `COBOL_To_Ada`, in `Interfaces.COBOLE`. See B.4(50).

Floating Float

Long_Floating
(Floating) Long_Float

Binary Integer

Long_Binary
Long_Long_Integer

Decimal_Element
Character

COBOL_Character
Character

For initialization, see the file ‘`i-cobol.ads`’ in the distributed library.

84. Support for access to machine instructions. See C.1(1).

See documentation in file ‘`s-maccod.ads`’ in the distributed library.

85. Implementation-defined aspects of access to machine operations. See C.1(9).

See documentation in file ‘`s-maccod.ads`’ in the distributed library.

86. Implementation-defined aspects of interrupts. See C.3(2).

Interrupts are mapped to signals or conditions as appropriate. See definition of unit `Ada.Interrupt_Names` in source file ‘`a-intnam.ads`’ for details on the interrupts supported on a particular target.

87. Implementation-defined aspects of pre-elaboration. See C.4(13).

GNAT does not permit a partition to be restarted without reloading, except under control of the debugger.

88. The semantics of pragma `Discard_Names`. See C.5(7).

Pragma `Discard_Names` causes names of enumeration literals to be suppressed. In the presence of this pragma, the `Image` attribute provides the image of the `Pos` of the literal, and `Value` accepts `Pos` values.

89. The result of the `Task_Identification.Image` attribute. See C.7.1(7).

The result of this attribute is a string that identifies the object or component that denotes a given task. If a variable `Var` has a task type, the image for this task will have the form `Var_XXXXXXX`, where the suffix is the hexadecimal representation of the virtual address of the

corresponding task control block. If the variable is an array of tasks, the image of each task will have the form of an indexed component indicating the position of a given task in the array, e.g. `Group(5)_XXXXXX`. If the task is a component of a record, the image of the task will have the form of a selected component. These rules are fully recursive, so that the image of a task that is a subcomponent of a composite object corresponds to the expression that designates this task. If a task is created by an allocator, its image depends on the context. If the allocator is part of an object declaration, the rules described above are used to construct its image, and this image is not affected by subsequent assignments. If the allocator appears within an expression, the image includes only the name of the task type. If the configuration pragma `Discard_Names` is present, or if the restriction `No_Implicit_Heap_Allocation` is in effect, the image reduces to the numeric suffix, that is to say the hexadecimal representation of the virtual address of the control block of the task.

90. The value of `Current_Task` when in a protected entry or interrupt handler. See C.7.1(17).

Protected entries or interrupt handlers can be executed by any convenient thread, so the value of `Current_Task` is undefined.

91. The effect of calling `Current_Task` from an entry body or interrupt handler. See C.7.1(19).

The effect of calling `Current_Task` from an entry body or interrupt handler is to return the identification of the task currently executing the code.

92. Implementation-defined aspects of `Task_Attributes`. See C.7.2(19).

There are no implementation-defined aspects of `Task_Attributes`.

93. Values of all `Metrics`. See D(2).

The metrics information for GNAT depends on the performance of the underlying operating system. The sources of the run-time for tasking implementation, together with the output from `-gnatG` can be used to determine the exact sequence of operating systems calls made to implement various tasking constructs. Together with appropriate information on the performance of the underlying operating system, on the exact target in use, this information can be used to determine the required metrics.

94. The declarations of `Any_Priority` and `Priority`. See D.1(11).

See declarations in file `'system.ads'`.

95. Implementation-defined execution resources. See D.1(15).

There are no implementation-defined execution resources.

96. Whether, on a multiprocessor, a task that is waiting for access to a protected object keeps its processor busy. See D.2.1(3).

On a multi-processor, a task that is waiting for access to a protected object does not keep its processor busy.

97. The affect of implementation defined execution resources on task dispatching. See D.2.1(9).

Tasks map to threads in the threads package used by GNAT. Where possible and appropriate, these threads correspond to native threads of the underlying operating system.

98. Implementation-defined `policy_identifiers` allowed in a pragma `Task_Dispatching_Policy`. See D.2.2(3).

There are no implementation-defined policy-identifiers allowed in this pragma.

99. Implementation-defined aspects of priority inversion. See D.2.2(16).

Execution of a task cannot be preempted by the implementation processing of delay expirations for lower priority tasks.

100. Implementation defined task dispatching. See D.2.2(18).

The policy is the same as that of the underlying threads implementation.

101. Implementation-defined `policy_identifiers` allowed in a pragma `Locking_Policy`. See D.3(4).

The only implementation defined policy permitted in GNAT is `Inheritance_Locking`. On targets that support this policy, locking is implemented by inheritance, i.e. the task owning the lock operates at a priority equal to the highest priority of any task currently requesting the lock.

102. Default ceiling priorities. See D.3(10).

The ceiling priority of protected objects of the type `System.Interrupt_Priority'Last` as described in the Ada Reference Manual D.3(10),

103. The ceiling of any protected object used internally by the implementation. See D.3(16).

The ceiling priority of internal protected objects is `System.Priority'Last`.

104. Implementation-defined queuing policies. See D.4(1).

There are no implementation-defined queuing policies.

105. On a multiprocessor, any conditions that cause the completion of an aborted construct to be delayed later than what is specified for a single processor. See D.6(3).

The semantics for abort on a multi-processor is the same as on a single processor, there are no further delays.

106. Any operations that implicitly require heap storage allocation. See D.7(8).

The only operation that implicitly requires heap storage allocation is task creation.

107. Implementation-defined aspects of pragma `Restrictions`. See D.7(20).

There are no such implementation-defined aspects.

108. Implementation-defined aspects of package `Real_Time`. See D.8(17).

There are no implementation defined aspects of package `Real_Time`.

109. Implementation-defined aspects of `delay_statements`. See D.9(8).

Any difference greater than one microsecond will cause the task to be delayed (see D.9(7)).

110. The upper bound on the duration of interrupt blocking caused by the implementation. See D.12(5).

The upper bound is determined by the underlying operating system. In no cases is it more than 10 milliseconds.

111. The means for creating and executing distributed programs. See E(5).

The GLADE package provides a utility GNATDIST for creating and executing distributed programs. See the GLADE reference manual for further details.

112. Any events that can result in a partition becoming inaccessible. See E.1(7).

See the GLADE reference manual for full details on such events.

113. The scheduling policies, treatment of priorities, and management of shared resources between partitions in certain cases. See E.1(11).

See the GLADE reference manual for full details on these aspects of multi-partition execution.

114. Events that cause the version of a compilation unit to change. See E.3(5).

Editing the source file of a compilation unit, or the source files of any units on which it is dependent in a significant way cause the version to change. No other actions cause the version number to change. All changes are significant except those which affect only layout, capitalization or comments.

115. Whether the execution of the remote subprogram is immediately aborted as a result of cancellation. See E.4(13).

See the GLADE reference manual for details on the effect of abort in a distributed application.

116. Implementation-defined aspects of the PCS. See E.5(25).

See the GLADE reference manual for a full description of all implementation defined aspects of the PCS.

117. Implementation-defined interfaces in the PCS. See E.5(26).

See the GLADE reference manual for a full description of all implementation defined interfaces.

118. The values of named numbers in the package `Decimal`. See F.2(7).

```
Max_Scale
    +18
Min_Scale
    -18
Min_Delta
    1.0E-18
Max_Delta
    1.0E+18
Max_Decimal_Digits
    18
```

119. The value of `Max_Picture_Length` in the package `Text_IO Editing`. See F.3.3(16).

64

120. The value of `Max_Picture_Length` in the package `Wide_Text_IO Editing`. See F.3.4(5).

64

121. The accuracy actually achieved by the complex elementary functions and by other complex arithmetic operations. See G.1(1).

Standard library functions are used for the complex arithmetic operations. Only fast math mode is currently supported.

122. The sign of a zero result (or a component thereof) from any operator or function in `Numerics.Generic_Complex_Types`, when `Real'Signed_Zeros` is `True`. See G.1.1(53).

The signs of zero values are as recommended by the relevant implementation advice.

123. The sign of a zero result (or a component thereof) from any operator or function in `Numerics.Generic_Complex_Elementary_Functions`, when `Real'Signed_Zeros` is `True`. See G.1.2(45).

The signs of zero values are as recommended by the relevant implementation advice.

124. Whether the strict mode or the relaxed mode is the default. See G.2(2).

The strict mode is the default. There is no separate relaxed mode. GNAT provides a highly efficient implementation of strict mode.

125. The result interval in certain cases of fixed-to-float conversion. See G.2.1(10).

For cases where the result interval is implementation dependent, the accuracy is that provided by performing all operations in 64-bit IEEE floating-point format.

126. The result of a floating point arithmetic operation in overflow situations, when the `Machine_Overflows` attribute of the result type is `False`. See G.2.1(13).

Infinite and NaN values are produced as dictated by the IEEE floating-point standard.

Note that on machines that are not fully compliant with the IEEE floating-point standard, such as Alpha, the `'-mieee'` compiler flag must be used for achieving IEEE conforming behavior (although at the cost of a significant performance penalty), so infinite and NaN values are properly generated.

127. The result interval for division (or exponentiation by a negative exponent), when the floating point hardware implements division as multiplication by a reciprocal. See G.2.1(16).

Not relevant, division is IEEE exact.

128. The definition of close result set, which determines the accuracy of certain fixed point multiplications and divisions. See G.2.3(5).

Operations in the close result set are performed using IEEE long format floating-point arithmetic. The input operands are converted to floating-point, the operation is done in floating-point, and the result is converted to the target type.

129. Conditions on a `universal_real` operand of a fixed point multiplication or division for which the result shall be in the perfect result set. See G.2.3(22).

The result is only defined to be in the perfect result set if the result can be computed by a single scaling operation involving a scale factor representable in 64-bits.

130. The result of a fixed point arithmetic operation in overflow situations, when the `Machine_Overflows` attribute of the result type is `False`. See G.2.3(27).

Not relevant, `Machine_Overflows` is `True` for fixed-point types.

131. The result of an elementary function reference in overflow situations, when the `Machine_Overflows` attribute of the result type is `False`. See G.2.4(4).

IEEE infinite and Nan values are produced as appropriate.

132. The value of the angle threshold, within which certain elementary functions, complex arithmetic operations, and complex elementary functions yield results conforming to a maximum relative error bound. See G.2.4(10).

Information on this subject is not yet available.

133. The accuracy of certain elementary functions for parameters beyond the angle threshold. See G.2.4(10).

Information on this subject is not yet available.

134. The result of a complex arithmetic operation or complex elementary function reference in overflow situations, when the `Machine_Overflows` attribute of the corresponding real type is `False`. See G.2.6(5).

IEEE infinite and Nan values are produced as appropriate.

135. The accuracy of certain complex arithmetic operations and certain complex elementary functions for parameters (or components thereof) beyond the angle threshold. See G.2.6(8).

Information on those subjects is not yet available.

136. Information regarding bounded errors and erroneous execution. See H.2(1).

Information on this subject is not yet available.

137. Implementation-defined aspects of pragma `Inspection_Point`. See H.3.2(8).

Pragma `Inspection_Point` ensures that the variable is live and can be examined by the debugger at the inspection point.

138. Implementation-defined aspects of pragma `Restrictions`. See H.4(25).

There are no implementation-defined aspects of pragma `Restrictions`. The use of pragma `Restrictions` [`No_Exceptions`] has no effect on the generated code. Checks must be suppressed by use of pragma `Suppress`.

139. Any restrictions on pragma `Restrictions`. See H.4(27).

There are no restrictions on pragma `Restrictions`.

5 Intrinsic Subprograms

GNAT allows a user application program to write the declaration:

```
pragma Import (Intrinsic, name);
```

providing that the name corresponds to one of the implemented intrinsic subprograms in GNAT, and that the parameter profile of the referenced subprogram meets the requirements. This chapter describes the set of implemented intrinsic subprograms, and the requirements on parameter profiles. Note that no body is supplied; as with other uses of `pragma Import`, the body is supplied elsewhere (in this case by the compiler itself). Note that any use of this feature is potentially non-portable, since the Ada standard does not require Ada compilers to implement this feature.

5.1 Intrinsic Operators

All the predefined numeric operators in package `Standard` in `pragma Import (Intrinsic,...)` declarations. In the binary operator case, the operands must have the same size. The operand or operands must also be appropriate for the operator. For example, for addition, the operands must both be floating-point or both be fixed-point, and the right operand for `"**"` must have a root type of `Standard.Integer'Base`. You can use an intrinsic operator declaration as in the following example:

```
type Int1 is new Integer;
type Int2 is new Integer;

function "+" (X1 : Int1; X2 : Int2) return Int1;
function "+" (X1 : Int1; X2 : Int2) return Int2;
pragma Import (Intrinsic, "+");
```

This declaration would permit “mixed mode” arithmetic on items of the differing types `Int1` and `Int2`. It is also possible to specify such operators for private types, if the full views are appropriate arithmetic types.

5.2 Enclosing_Entity

This intrinsic subprogram is used in the implementation of the library routine `GNAT.Source_Info`. The only useful use of the intrinsic import in this case is the one in this unit, so an application program should simply call the function `GNAT.Source_Info.Enclosing_Entity` to obtain the name of the current subprogram, package, task, entry, or protected subprogram.

5.3 Exception_Information

This intrinsic subprogram is used in the implementation of the library routine `GNAT.Current_Exception`. The only useful use of the intrinsic import in this case is the one in this unit, so an application program should simply call the function `GNAT.Current_Exception.Exception_Information` to obtain the exception information associated with the current exception.

5.4 Exception_Message

This intrinsic subprogram is used in the implementation of the library routine `GNAT.Current_Exception`. The only useful use of the intrinsic import in this case is the one in this unit, so an application program should simply call the function `GNAT.Current_Exception.Exception_Message` to obtain the message associated with the current exception.

5.5 Exception_Name

This intrinsic subprogram is used in the implementation of the library routine `GNAT.Current_Exception`. The only useful use of the intrinsic import in this case is the one in this unit, so an application program should simply call the function `GNAT.Current_Exception.Exception_Name` to obtain the name of the current exception.

5.6 File

This intrinsic subprogram is used in the implementation of the library routine `GNAT.Source_Info`. The only useful use of the intrinsic import in this case is the one in this unit, so an application program should simply call the function `GNAT.Source_Info.File` to obtain the name of the current file.

5.7 Line

This intrinsic subprogram is used in the implementation of the library routine `GNAT.Source_Info`. The only useful use of the intrinsic import in this case is the one in this unit, so an application program should simply call the function `GNAT.Source_Info.Line` to obtain the number of the current source line.

5.8 Rotate_Left

In standard Ada, the `Rotate_Left` function is available only for the predefined modular types in package `Interfaces`. However, in GNAT it is possible to define a `Rotate_Left` function for a user defined modular type or any signed integer type as in this example:

```
function Shift_Left
  (Value  : My_Modular_Type;
   Amount : Natural)
  return My_Modular_Type;
```

The requirements are that the profile be exactly as in the example above. The only modifications allowed are in the formal parameter names, and in the type of `Value` and the return type, which must be the same, and must be either a signed integer type, or a modular integer type with a binary modulus, and the size must be 8, 16, 32 or 64 bits.

5.9 Rotate_Right

A `Rotate_Right` function can be defined for any user defined binary modular integer type, or signed integer type, as described above for `Rotate_Left`.

5.10 Shift_Left

A `Shift_Left` function can be defined for any user defined binary modular integer type, or signed integer type, as described above for `Rotate_Left`.

5.11 Shift_Right

A `Shift_Right` function can be defined for any user defined binary modular integer type, or signed integer type, as described above for `Rotate_Left`.

5.12 Shift_Right_Arithmetic

A `Shift_Right_Arithmetic` function can be defined for any user defined binary modular integer type, or signed integer type, as described above for `Rotate_Left`.

5.13 Source_Location

This intrinsic subprogram is used in the implementation of the library routine `GNAT.Source_Info`. The only useful use of the intrinsic import in this case is the one in this unit, so an application program should simply call the function `GNAT.Source_Info.Source_Location` to obtain the current source file location.

6 Representation Clauses and Pragmas

This section describes the representation clauses accepted by GNAT, and their effect on the representation of corresponding data objects.

GNAT fully implements Annex C (Systems Programming). This means that all the implementation advice sections in chapter 13 are fully implemented. However, these sections only require a minimal level of support for representation clauses. GNAT provides much more extensive capabilities, and this section describes the additional capabilities provided.

6.1 Alignment Clauses

GNAT requires that all alignment clauses specify a power of 2, and all default alignments are always a power of 2. The default alignment values are as follows:

- *Primitive Types.* For primitive types, the alignment is the minimum of the actual size of objects of the type divided by `Storage_Unit`, and the maximum alignment supported by the target. (This maximum alignment is given by the GNAT-specific attribute `Standard'Maximum_Alignment`; see [\[Maximum_Alignment\]](#), page 62.) For example, for type `Long_Float`, the object size is 8 bytes, and the default alignment will be 8 on any target that supports alignments this large, but on some targets, the maximum alignment may be smaller than 8, in which case objects of type `Long_Float` will be maximally aligned.
- *Arrays.* For arrays, the alignment is equal to the alignment of the component type for the normal case where no packing or component size is given. If the array is packed, and the packing is effective (see separate section on packed arrays), then the alignment will be one for long packed arrays, or arrays whose length is not known at compile time. For short packed arrays, which are handled internally as modular types, the alignment will be as described for primitive types, e.g. a packed array of length 31 bits will have an object size of four bytes, and an alignment of 4.
- *Records.* For the normal non-packed case, the alignment of a record is equal to the maximum alignment of any of its components. For tagged records, this includes the implicit access type used for the tag. If a pragma `Pack` is used and all components are packable (see separate section on pragma `Pack`), then the resulting alignment is 1, unless the layout of the record makes it profitable to increase it.

A special case is when:

- the size of the record is given explicitly, or a full record representation clause is given, and
- the size of the record is 2, 4, or 8 bytes.

In this case, an alignment is chosen to match the size of the record. For example, if we have:

```
type Small is record
  A, B : Character;
end record;
for Small'Size use 16;
```

then the default alignment of the record type `Small` is 2, not 1. This leads to more efficient code when the record is treated as a unit, and also allows the type to be specified as `Atomic` on architectures requiring strict alignment.

An alignment clause may specify a larger alignment than the default value up to some maximum value dependent on the target (obtainable by using the attribute reference `Standard'Maximum_Alignment`). It may also specify a smaller alignment than the default value for enumeration, integer and fixed point types, as well as for record types, for example

```

type V is record
  A : Integer;
end record;

for V'alignment use 1;

```

The default alignment for the type `V` is 4, as a result of the `Integer` field in the record, but it is permissible, as shown, to override the default alignment of the record with a smaller value.

6.2 Size Clauses

The default size for a type `T` is obtainable through the language-defined attribute `T'Size` and also through the equivalent GNAT-defined attribute `T'Value_Size`. For objects of type `T`, GNAT will generally increase the type size so that the object size (obtainable through the GNAT-defined attribute `T'Object_Size`) is a multiple of `T'Alignment * Storage_Unit`. For example

```

type Smallint is range 1 .. 6;

type Rec is record
  Y1 : integer;
  Y2 : boolean;
end record;

```

In this example, `Smallint'Size = Smallint'Value_Size = 3`, as specified by the RM rules, but objects of this type will have a size of 8 (`Smallint'Object_Size = 8`), since objects by default occupy an integral number of storage units. On some targets, notably older versions of the Digital Alpha, the size of stand alone objects of this type may be 32, reflecting the inability of the hardware to do byte load/stores.

Similarly, the size of type `Rec` is 40 bits (`Rec'Size = Rec'Value_Size = 40`), but the alignment is 4, so objects of this type will have their size increased to 64 bits so that it is a multiple of the alignment (in bits). This decision is in accordance with the specific Implementation Advice in RM 13.3(43):

A **Size** clause should be supported for an object if the specified **Size** is at least as large as its subtype's **Size**, and corresponds to a size in storage elements that is a multiple of the object's **Alignment** (if the **Alignment** is nonzero).

An explicit size clause may be used to override the default size by increasing it. For example, if we have:

```

type My_Boolean is new Boolean;
for My_Boolean'Size use 32;

```

then values of this type will always be 32 bits long. In the case of discrete types, the size can be increased up to 64 bits, with the effect that the entire specified field is used to hold the value, sign- or zero-extended as appropriate. If more than 64 bits is specified, then padding space is allocated after the value, and a warning is issued that there are unused bits.

Similarly the size of records and arrays may be increased, and the effect is to add padding bits after the value. This also causes a warning message to be generated.

The largest **Size** value permitted in GNAT is $2^{31}-1$. Since this is a **Size** in bits, this corresponds to an object of size 256 megabytes (minus one). This limitation is true on all targets. The reason for this limitation is that it improves the quality of the code in many cases if it is known that a **Size** value can be accommodated in an object of type `Integer`.

6.3 Storage_Size Clauses

For tasks, the **Storage_Size** clause specifies the amount of space to be allocated for the task stack. This cannot be extended, and if the stack is exhausted, then **Storage_Error** will be raised

(if stack checking is enabled). Use a `Storage_Size` attribute definition clause, or a `Storage_Size` pragma in the task definition to set the appropriate required size. A useful technique is to include in every task definition a pragma of the form:

```
pragma Storage_Size (Default_Stack_Size);
```

Then `Default_Stack_Size` can be defined in a global package, and modified as required. Any tasks requiring stack sizes different from the default can have an appropriate alternative reference in the pragma.

You can also use the ‘-d’ binder switch to modify the default stack size.

For access types, the `Storage_Size` clause specifies the maximum space available for allocation of objects of the type. If this space is exceeded then `Storage_Error` will be raised by an allocation attempt. In the case where the access type is declared local to a subprogram, the use of a `Storage_Size` clause triggers automatic use of a special predefined storage pool (`System.Pool_Size`) that ensures that all space for the pool is automatically reclaimed on exit from the scope in which the type is declared.

A special case recognized by the compiler is the specification of a `Storage_Size` of zero for an access type. This means that no items can be allocated from the pool, and this is recognized at compile time, and all the overhead normally associated with maintaining a fixed size storage pool is eliminated. Consider the following example:

```
procedure p is
  type R is array (Natural) of Character;
  type P is access all R;
  for P'Storage_Size use 0;
  -- Above access type intended only for interfacing purposes

  y : P;

  procedure g (m : P);
  pragma Import (C, g);

  -- ...

begin
  -- ...
  y := new R;
end;
```

As indicated in this example, these dummy storage pools are often useful in connection with interfacing where no object will ever be allocated. If you compile the above example, you get the warning:

```
p.adb:16:09: warning: allocation from empty storage pool
p.adb:16:09: warning: Storage_Error will be raised at run time
```

Of course in practice, there will not be any explicit allocators in the case of such an access declaration.

6.4 Size of Variant Record Objects

In the case of variant record objects, there is a question whether `Size` gives information about a particular variant, or the maximum size required for any variant. Consider the following program

```
with Text_IO; use Text_IO;
procedure q is
  type R1 (A : Boolean := False) is record
    case A is
      when True  => X : Character;
      when False => null;
    end case;
  end record;
```

```

V1 : R1 (False);
V2 : R1;

begin
  Put_Line (Integer'Image (V1'Size));
  Put_Line (Integer'Image (V2'Size));
end q;
```

Here we are dealing with a variant record, where the True variant requires 16 bits, and the False variant requires 8 bits. In the above example, both V1 and V2 contain the False variant, which is only 8 bits long. However, the result of running the program is:

```

8
16
```

The reason for the difference here is that the discriminant value of V1 is fixed, and will always be False. It is not possible to assign a True variant value to V1, therefore 8 bits is sufficient. On the other hand, in the case of V2, the initial discriminant value is False (from the default), but it is possible to assign a True variant value to V2, therefore 16 bits must be allocated for V2 in the general case, even fewer bits may be needed at any particular point during the program execution.

As can be seen from the output of this program, the 'Size attribute applied to such an object in GNAT gives the actual allocated size of the variable, which is the largest size of any of the variants. The Ada Reference Manual is not completely clear on what choice should be made here, but the GNAT behavior seems most consistent with the language in the RM.

In some cases, it may be desirable to obtain the size of the current variant, rather than the size of the largest variant. This can be achieved in GNAT by making use of the fact that in the case of a subprogram parameter, GNAT does indeed return the size of the current variant (because a subprogram has no way of knowing how much space is actually allocated for the actual).

Consider the following modified version of the above program:

```

with Text_IO; use Text_IO;
procedure q is
  type R1 (A : Boolean := False) is record
    case A is
      when True => X : Character;
      when False => null;
    end case;
  end record;

  V2 : R1;

  function Size (V : R1) return Integer is
  begin
    return V'Size;
  end Size;

begin
  Put_Line (Integer'Image (V2'Size));
  Put_Line (Integer'Image (Size (V2)));
  V2 := (True, 'x');
  Put_Line (Integer'Image (V2'Size));
  Put_Line (Integer'Image (Size (V2)));
end q;
```

The output from this program is

```

16
8
16
16
```


Here we see that while the `'Size` attribute always returns the maximum size, regardless of the current variant value, the `Size` function does indeed return the size of the current variant value.

6.5 Biased Representation

In the case of scalars with a range starting at other than zero, it is possible in some cases to specify a size smaller than the default minimum value, and in such cases, GNAT uses an unsigned biased representation, in which zero is used to represent the lower bound, and successive values represent successive values of the type.

For example, suppose we have the declaration:

```
type Small is range -7 .. -4;
for Small'Size use 2;
```

Although the default size of type `Small` is 4, the `Size` clause is accepted by GNAT and results in the following representation scheme:

```
-7 is represented as 2#00#
-6 is represented as 2#01#
-5 is represented as 2#10#
-4 is represented as 2#11#
```

Biased representation is only used if the specified `Size` clause cannot be accepted in any other manner. These reduced sizes that force biased representation can be used for all discrete types except for enumeration types for which a representation clause is given.

6.6 Value_Size and Object_Size Clauses

In Ada 95 and Ada 2005, `T'Size` for a type `T` is the minimum number of bits required to hold values of type `T`. Although this interpretation was allowed in Ada 83, it was not required, and this requirement in practice can cause some significant difficulties. For example, in most Ada 83 compilers, `Natural'Size` was 32. However, in Ada 95 and Ada 2005, `Natural'Size` is typically 31. This means that code may change in behavior when moving from Ada 83 to Ada 95 or Ada 2005. For example, consider:

```
type Rec is record;
  A : Natural;
  B : Natural;
end record;

for Rec use record
  at 0 range 0 .. Natural'Size - 1;
  at 0 range Natural'Size .. 2 * Natural'Size - 1;
end record;
```

In the above code, since the typical size of `Natural` objects is 32 bits and `Natural'Size` is 31, the above code can cause unexpected inefficient packing in Ada 95 and Ada 2005, and in general there are cases where the fact that the object size can exceed the size of the type causes surprises.

To help get around this problem GNAT provides two implementation defined attributes, `Value_Size` and `Object_Size`. When applied to a type, these attributes yield the size of the type (corresponding to the RM defined size attribute), and the size of objects of the type respectively.

The `Object_Size` is used for determining the default size of objects and components. This size value can be referred to using the `Object_Size` attribute. The phrase “is used” here means that it is the basis of the determination of the size. The backend is free to pad this up if necessary for efficiency, e.g. an 8-bit stand-alone character might be stored in 32 bits on a machine with no efficient byte access instructions such as the Alpha.

The default rules for the value of `Object_Size` for discrete types are as follows:

- The `Object_Size` for base subtypes reflect the natural hardware size in bits (run the compiler with ‘-gnatS’ to find those values for numeric types). Enumeration types and fixed-point base subtypes have 8, 16, 32 or 64 bits for this size, depending on the range of values to be stored.
- The `Object_Size` of a subtype is the same as the `Object_Size` of the type from which it is obtained.
- The `Object_Size` of a derived base type is copied from the parent base type, and the `Object_Size` of a derived first subtype is copied from the parent first subtype.

The `Value_Size` attribute is the (minimum) number of bits required to store a value of the type. This value is used to determine how tightly to pack records or arrays with components of this type, and also affects the semantics of unchecked conversion (unchecked conversions where the `Value_Size` values differ generate a warning, and are potentially target dependent).

The default rules for the value of `Value_Size` are as follows:

- The `Value_Size` for a base subtype is the minimum number of bits required to store all values of the type (including the sign bit only if negative values are possible).
- If a subtype statically matches the first subtype of a given type, then it has by default the same `Value_Size` as the first subtype. This is a consequence of RM 13.1(14) (“if two subtypes statically match, then their subtype-specific aspects are the same”).
- All other subtypes have a `Value_Size` corresponding to the minimum number of bits required to store all values of the subtype. For dynamic bounds, it is assumed that the value can range down or up to the corresponding bound of the ancestor

The RM defined attribute `Size` corresponds to the `Value_Size` attribute.

The `Size` attribute may be defined for a first-named subtype. This sets the `Value_Size` of the first-named subtype to the given value, and the `Object_Size` of this first-named subtype to the given value padded up to an appropriate boundary. It is a consequence of the default rules above that this `Object_Size` will apply to all further subtypes. On the other hand, `Value_Size` is affected only for the first subtype, any dynamic subtypes obtained from it directly, and any statically matching subtypes. The `Value_Size` of any other static subtypes is not affected.

`Value_Size` and `Object_Size` may be explicitly set for any subtype using an attribute definition clause. Note that the use of these attributes can cause the RM 13.1(14) rule to be violated. If two access types reference aliased objects whose subtypes have differing `Object_Size` values as a result of explicit attribute definition clauses, then it is erroneous to convert from one access subtype to the other.

At the implementation level, `Esize` stores the `Object_Size` and the `RM.Size` field stores the `Value_Size` (and hence the value of the `Size` attribute, which, as noted above, is equivalent to `Value_Size`).

To get a feel for the difference, consider the following examples (note that in each case the base is `Short_Short_Integer` with a size of 8):

	<code>Object_Size</code>	<code>Value_Size</code>
<code>type x1 is range 0 .. 5;</code>	8	3
<code>type x2 is range 0 .. 5;</code> <code>for x2'size use 12;</code>	16	12
<code>subtype x3 is x2 range 0 .. 3;</code>	16	2
<code>subtype x4 is x2'base range 0 .. 10;</code>	8	4
<code>subtype x5 is x2 range 0 .. dynamic;</code>	16	3*

```
subtype x6 is x2'base range 0 .. dynamic;    8                3*
```

Note: the entries marked “3*” are not actually specified by the Ada Reference Manual, but it seems in the spirit of the RM rules to allocate the minimum number of bits (here 3, given the range for x2) known to be large enough to hold the given range of values.

So far, so good, but GNAT has to obey the RM rules, so the question is under what conditions must the **RM Size** be used. The following is a list of the occasions on which the **RM Size** must be used:

- Component size for packed arrays or records
- Value of the attribute **Size** for a type
- Warning about sizes not matching for unchecked conversion

For record types, the **Object_Size** is always a multiple of the alignment of the type (this is true for all types). In some cases the **Value_Size** can be smaller. Consider:

```
type R is record
  X : Integer;
  Y : Character;
end record;
```

On a typical 32-bit architecture, the X component will be four bytes, and require four-byte alignment, and the Y component will be one byte. In this case **R'Value_Size** will be 40 (bits) since this is the minimum size required to store a value of this type, and for example, it is permissible to have a component of type R in an outer array whose component size is specified to be 48 bits. However, **R'Object_Size** will be 64 (bits), since it must be rounded up so that this value is a multiple of the alignment (4 bytes = 32 bits).

For all other types, the **Object_Size** and **Value_Size** are the same (and equivalent to the RM attribute **Size**). Only **Size** may be specified for such types.

6.7 Component_Size Clauses

Normally, the value specified in a component size clause must be consistent with the subtype of the array component with regard to size and alignment. In other words, the value specified must be at least equal to the size of this subtype, and must be a multiple of the alignment value.

In addition, component size clauses are allowed which cause the array to be packed, by specifying a smaller value. A first case is for component size values in the range 1 through 63. The value specified must not be smaller than the Size of the subtype. GNAT will accurately honor all packing requests in this range. For example, if we have:

```
type r is array (1 .. 8) of Natural;
for r'Component_Size use 31;
```

then the resulting array has a length of 31 bytes (248 bits = 8 * 31). Of course access to the components of such an array is considerably less efficient than if the natural component size of 32 is used. A second case is when the subtype of the component is a record type padded because of its default alignment. For example, if we have:

```
type r is record
  i : Integer;
  j : Integer;
  b : Boolean;
end record;

type a is array (1 .. 8) of r;
for a'Component_Size use 72;
```

then the resulting array has a length of 72 bytes, instead of 96 bytes if the alignment of the record (4) was obeyed.

Note that there is no point in giving both a component size clause and a pragma **Pack** for the same array type. If such duplicate clauses are given, the pragma **Pack** will be ignored.

6.8 Bit_Order Clauses

For record subtypes, GNAT permits the specification of the `Bit_Order` attribute. The specification may either correspond to the default bit order for the target, in which case the specification has no effect and places no additional restrictions, or it may be for the non-standard setting (that is the opposite of the default).

In the case where the non-standard value is specified, the effect is to renumber bits within each byte, but the ordering of bytes is not affected. There are certain restrictions placed on component clauses as follows:

- Components fitting within a single storage unit. These are unrestricted, and the effect is merely to renumber bits. For example if we are on a little-endian machine with `Low_Order_First` being the default, then the following two declarations have exactly the same effect:

```

type R1 is record
  A : Boolean;
  B : Integer range 1 .. 120;
end record;

for R1 use record
  A at 0 range 0 .. 0;
  B at 0 range 1 .. 7;
end record;

type R2 is record
  A : Boolean;
  B : Integer range 1 .. 120;
end record;

for R2'Bit_Order use High_Order_First;

for R2 use record
  A at 0 range 7 .. 7;
  B at 0 range 0 .. 6;
end record;
```

The useful application here is to write the second declaration with the `Bit_Order` attribute definition clause, and know that it will be treated the same, regardless of whether the target is little-endian or big-endian.

- Components occupying an integral number of bytes. These are components that exactly fit in two or more bytes. Such component declarations are allowed, but have no effect, since it is important to realize that the `Bit_Order` specification does not affect the ordering of bytes. In particular, the following attempt at getting an endian-independent integer does not work:

```

type R2 is record
  A : Integer;
end record;

for R2'Bit_Order use High_Order_First;

for R2 use record
  A at 0 range 0 .. 31;
end record;
```

This declaration will result in a little-endian integer on a little-endian machine, and a big-endian integer on a big-endian machine. If byte flipping is required for interoperability between big- and little-endian machines, this must be explicitly programmed. This capability is not provided by `Bit_Order`.

- Components that are positioned across byte boundaries but do not occupy an integral number of bytes. Given that bytes are not reordered, such fields would occupy a non-

contiguous sequence of bits in memory, requiring non-trivial code to reassemble. They are for this reason not permitted, and any component clause specifying such a layout will be flagged as illegal by GNAT.

Since the misconception that `Bit_Order` automatically deals with all endian-related incompatibilities is a common one, the specification of a component field that is an integral number of bytes will always generate a warning. This warning may be suppressed using `pragma Warnings (Off)` if desired. The following section contains additional details regarding the issue of byte ordering.

6.9 Effect of `Bit_Order` on Byte Ordering

In this section we will review the effect of the `Bit_Order` attribute definition clause on byte ordering. Briefly, it has no effect at all, but a detailed example will be helpful. Before giving this example, let us review the precise definition of the effect of defining `Bit_Order`. The effect of a non-standard bit order is described in section 15.5.3 of the Ada Reference Manual:

2 A bit ordering is a method of interpreting the meaning of the storage place attributes.

To understand the precise definition of storage place attributes in this context, we visit section 13.5.1 of the manual:

13 A `record_representation_clause` (without the `mod_clause`) specifies the layout. The storage place attributes (see 13.5.2) are taken from the values of the `position`, `first_bit`, and `last_bit` expressions after normalizing those values so that `first_bit` is less than `Storage_Unit`.

The critical point here is that storage places are taken from the values after normalization, not before. So the `Bit_Order` interpretation applies to normalized values. The interpretation is described in the later part of the 15.5.3 paragraph:

2 A bit ordering is a method of interpreting the meaning of the storage place attributes. `High_Order_First` (known in the vernacular as “big endian”) means that the first bit of a storage element (bit 0) is the most significant bit (interpreting the sequence of bits that represent a component as an unsigned integer value). `Low_Order_First` (known in the vernacular as “little endian”) means the opposite: the first bit is the least significant.

Note that the numbering is with respect to the bits of a storage unit. In other words, the specification affects only the numbering of bits within a single storage unit.

We can make the effect clearer by giving an example.

Suppose that we have an external device which presents two bytes, the first byte presented, which is the first (low addressed byte) of the two byte record is called Master, and the second byte is called Slave.

The left most (most significant bit is called Control for each byte, and the remaining 7 bits are called V1, V2, . . . V7, where V7 is the rightmost (least significant) bit.

On a big-endian machine, we can write the following representation clause

```
type Data is record
  Master_Control : Bit;
  Master_V1      : Bit;
  Master_V2      : Bit;
  Master_V3      : Bit;
  Master_V4      : Bit;
  Master_V5      : Bit;
  Master_V6      : Bit;
  Master_V7      : Bit;
  Slave_Control  : Bit;
  Slave_V1       : Bit;
```

```

    Slave_V2      : Bit;
    Slave_V3      : Bit;
    Slave_V4      : Bit;
    Slave_V5      : Bit;
    Slave_V6      : Bit;
    Slave_V7      : Bit;
end record;

for Data use record
    Master_Control at 0 range 0 .. 0;
    Master_V1      at 0 range 1 .. 1;
    Master_V2      at 0 range 2 .. 2;
    Master_V3      at 0 range 3 .. 3;
    Master_V4      at 0 range 4 .. 4;
    Master_V5      at 0 range 5 .. 5;
    Master_V6      at 0 range 6 .. 6;
    Master_V7      at 0 range 7 .. 7;
    Slave_Control at 1 range 0 .. 0;
    Slave_V1      at 1 range 1 .. 1;
    Slave_V2      at 1 range 2 .. 2;
    Slave_V3      at 1 range 3 .. 3;
    Slave_V4      at 1 range 4 .. 4;
    Slave_V5      at 1 range 5 .. 5;
    Slave_V6      at 1 range 6 .. 6;
    Slave_V7      at 1 range 7 .. 7;
end record;

```

Now if we move this to a little endian machine, then the bit ordering within the byte is backwards, so we have to rewrite the record rep clause as:

```

for Data use record
    Master_Control at 0 range 7 .. 7;
    Master_V1      at 0 range 6 .. 6;
    Master_V2      at 0 range 5 .. 5;
    Master_V3      at 0 range 4 .. 4;
    Master_V4      at 0 range 3 .. 3;
    Master_V5      at 0 range 2 .. 2;
    Master_V6      at 0 range 1 .. 1;
    Master_V7      at 0 range 0 .. 0;
    Slave_Control at 1 range 7 .. 7;
    Slave_V1      at 1 range 6 .. 6;
    Slave_V2      at 1 range 5 .. 5;
    Slave_V3      at 1 range 4 .. 4;
    Slave_V4      at 1 range 3 .. 3;
    Slave_V5      at 1 range 2 .. 2;
    Slave_V6      at 1 range 1 .. 1;
    Slave_V7      at 1 range 0 .. 0;
end record;

```

It is a nuisance to have to rewrite the clause, especially if the code has to be maintained on both machines. However, this is a case that we can handle with the `Bit_Order` attribute if it is implemented. Note that the implementation is not required on byte addressed machines, but it is indeed implemented in GNAT. This means that we can simply use the first record clause, together with the declaration

```
for Data'Bit_Order use High_Order_First;
```

and the effect is what is desired, namely the layout is exactly the same, independent of whether the code is compiled on a big-endian or little-endian machine.

The important point to understand is that byte ordering is not affected. A `Bit_Order` attribute definition never affects which byte a field ends up in, only where it ends up in that byte. To make this clear, let us rewrite the record rep clause of the previous example as:

```

for Data'Bit_Order use High_Order_First;
for Data use record
    Master_Control at 0 range 0 .. 0;

```

```

Master_V1      at 0 range 1 .. 1;
Master_V2      at 0 range 2 .. 2;
Master_V3      at 0 range 3 .. 3;
Master_V4      at 0 range 4 .. 4;
Master_V5      at 0 range 5 .. 5;
Master_V6      at 0 range 6 .. 6;
Master_V7      at 0 range 7 .. 7;
Slave_Control  at 0 range 8 .. 8;
Slave_V1       at 0 range 9 .. 9;
Slave_V2       at 0 range 10 .. 10;
Slave_V3       at 0 range 11 .. 11;
Slave_V4       at 0 range 12 .. 12;
Slave_V5       at 0 range 13 .. 13;
Slave_V6       at 0 range 14 .. 14;
Slave_V7       at 0 range 15 .. 15;
end record;

```

This is exactly equivalent to saying (a repeat of the first example):

```

for Data'Bit_Order use High_Order_First;
for Data use record
  Master_Control at 0 range 0 .. 0;
  Master_V1      at 0 range 1 .. 1;
  Master_V2      at 0 range 2 .. 2;
  Master_V3      at 0 range 3 .. 3;
  Master_V4      at 0 range 4 .. 4;
  Master_V5      at 0 range 5 .. 5;
  Master_V6      at 0 range 6 .. 6;
  Master_V7      at 0 range 7 .. 7;
  Slave_Control  at 1 range 0 .. 0;
  Slave_V1       at 1 range 1 .. 1;
  Slave_V2       at 1 range 2 .. 2;
  Slave_V3       at 1 range 3 .. 3;
  Slave_V4       at 1 range 4 .. 4;
  Slave_V5       at 1 range 5 .. 5;
  Slave_V6       at 1 range 6 .. 6;
  Slave_V7       at 1 range 7 .. 7;
end record;

```

Why are they equivalent? Well take a specific field, the `Slave_V2` field. The storage place attributes are obtained by normalizing the values given so that the `First_Bit` value is less than 8. After normalizing the values (0,10,10) we get (1,2,2) which is exactly what we specified in the other case.

Now one might expect that the `Bit_Order` attribute might affect bit numbering within the entire record component (two bytes in this case, thus affecting which byte fields end up in), but that is not the way this feature is defined, it only affects numbering of bits, not which byte they end up in.

Consequently it never makes sense to specify a starting bit number greater than 7 (for a byte addressable field) if an attribute definition for `Bit_Order` has been given, and indeed it may be actively confusing to specify such a value, so the compiler generates a warning for such usage.

If you do need to control byte ordering then appropriate conditional values must be used. If in our example, the slave byte came first on some machines we might write:

```

Master_Byte_First constant Boolean := ...;

Master_Byte : constant Natural :=
  1 - Boolean'Pos (Master_Byte_First);
Slave_Byte  : constant Natural :=
  Boolean'Pos (Master_Byte_First);

for Data'Bit_Order use High_Order_First;
for Data use record
  Master_Control at Master_Byte range 0 .. 0;

```



```

Master_V1      at Master_Byte range 1 .. 1;
Master_V2      at Master_Byte range 2 .. 2;
Master_V3      at Master_Byte range 3 .. 3;
Master_V4      at Master_Byte range 4 .. 4;
Master_V5      at Master_Byte range 5 .. 5;
Master_V6      at Master_Byte range 6 .. 6;
Master_V7      at Master_Byte range 7 .. 7;
Slave_Control  at Slave_Byte  range 0 .. 0;
Slave_V1       at Slave_Byte  range 1 .. 1;
Slave_V2       at Slave_Byte  range 2 .. 2;
Slave_V3       at Slave_Byte  range 3 .. 3;
Slave_V4       at Slave_Byte  range 4 .. 4;
Slave_V5       at Slave_Byte  range 5 .. 5;
Slave_V6       at Slave_Byte  range 6 .. 6;
Slave_V7       at Slave_Byte  range 7 .. 7;
end record;
```

Now to switch between machines, all that is necessary is to set the boolean constant `Master_Byte_First` in an appropriate manner.

6.10 Pragma Pack for Arrays

Pragma `Pack` applied to an array has no effect unless the component type is packable. For a component type to be packable, it must be one of the following cases:

- Any scalar type
- Any type whose size is specified with a size clause
- Any packed array type with a static size
- Any record type padded because of its default alignment

For all these cases, if the component subtype size is in the range 1 through 63, then the effect of the pragma `Pack` is exactly as though a component size were specified giving the component subtype size. For example if we have:

```

type r is range 0 .. 17;

type ar is array (1 .. 8) of r;
pragma Pack (ar);
```

Then the component size of `ar` will be set to 5 (i.e. to `r'size`, and the size of the array `ar` will be exactly 40 bits.

Note that in some cases this rather fierce approach to packing can produce unexpected effects. For example, in Ada 95 and Ada 2005, subtype `Natural` typically has a size of 31, meaning that if you pack an array of `Natural`, you get 31-bit close packing, which saves a few bits, but results in far less efficient access. Since many other Ada compilers will ignore such a packing request, GNAT will generate a warning on some uses of pragma `Pack` that it guesses might not be what is intended. You can easily remove this warning by using an explicit `Component_Size` setting instead, which never generates a warning, since the intention of the programmer is clear in this case.

GNAT treats packed arrays in one of two ways. If the size of the array is known at compile time and is less than 64 bits, then internally the array is represented as a single modular type, of exactly the appropriate number of bits. If the length is greater than 63 bits, or is not known at compile time, then the packed array is represented as an array of bytes, and the length is always a multiple of 8 bits.

Note that to represent a packed array as a modular type, the alignment must be suitable for the modular type involved. For example, on typical machines a 32-bit packed array will be represented by a 32-bit modular integer with an alignment of four bytes. If you explicitly override the default alignment with an alignment clause that is too small, the modular representation cannot be used. For example, consider the following set of declarations:


```

type R is range 1 .. 3;
type S is array (1 .. 31) of R;
for S'Component_Size use 2;
for S'Size use 62;
for S'Alignment use 1;

```

If the alignment clause were not present, then a 62-bit modular representation would be chosen (typically with an alignment of 4 or 8 bytes depending on the target). But the default alignment is overridden with the explicit alignment clause. This means that the modular representation cannot be used, and instead the array of bytes representation must be used, meaning that the length must be a multiple of 8. Thus the above set of declarations will result in a diagnostic rejecting the size clause and noting that the minimum size allowed is 64.

One special case that is worth noting occurs when the base type of the component size is 8/16/32 and the subtype is one bit less. Notably this occurs with subtype **Natural**. Consider:

```

type Arr is array (1 .. 32) of Natural;
pragma Pack (Arr);

```

In all commonly used Ada 83 compilers, this pragma Pack would be ignored, since typically **Natural'Size** is 32 in Ada 83, and in any case most Ada 83 compilers did not attempt 31 bit packing.

In Ada 95 and Ada 2005, **Natural'Size** is required to be 31. Furthermore, GNAT really does pack 31-bit subtype to 31 bits. This may result in a substantial unintended performance penalty when porting legacy Ada 83 code. To help prevent this, GNAT generates a warning in such cases. If you really want 31 bit packing in a case like this, you can set the component size explicitly:

```

type Arr is array (1 .. 32) of Natural;
for Arr'Component_Size use 31;

```

Here 31-bit packing is achieved as required, and no warning is generated, since in this case the programmer intention is clear.

6.11 Pragma Pack for Records

Pragma Pack applied to a record will pack the components to reduce wasted space from alignment gaps and by reducing the amount of space taken by components. We distinguish between *packable* components and *non-packable* components. Components of the following types are considered packable:

- All primitive types are packable.
- Small packed arrays, whose size does not exceed 64 bits, and where the size is statically known at compile time, are represented internally as modular integers, and so they are also packable.

All packable components occupy the exact number of bits corresponding to their **Size** value, and are packed with no padding bits, i.e. they can start on an arbitrary bit boundary.

All other types are non-packable, they occupy an integral number of storage units, and are placed at a boundary corresponding to their alignment requirements.

For example, consider the record

```

type Rb1 is array (1 .. 13) of Boolean;
pragma Pack (rb1);

type Rb2 is array (1 .. 65) of Boolean;
pragma Pack (rb2);

type x2 is record
  l1 : Boolean;
  l2 : Duration;
  l3 : Float;

```

```

    14 : Boolean;
    15 : Rb1;
    16 : Rb2;
  end record;
  pragma Pack (x2);

```

The representation for the record x2 is as follows:

```

  for x2'Size use 224;
  for x2 use record
    11 at 0 range 0 .. 0;
    12 at 0 range 1 .. 64;
    13 at 12 range 0 .. 31;
    14 at 16 range 0 .. 0;
    15 at 16 range 1 .. 13;
    16 at 18 range 0 .. 71;
  end record;

```

Studying this example, we see that the packable fields 11 and 12 are of length equal to their sizes, and placed at specific bit boundaries (and not byte boundaries) to eliminate padding. But 13 is of a non-packable float type, so it is on the next appropriate alignment boundary.

The next two fields are fully packable, so 14 and 15 are minimally packed with no gaps. However, type Rb2 is a packed array that is longer than 64 bits, so it is itself non-packable. Thus the 16 field is aligned to the next byte boundary, and takes an integral number of bytes, i.e. 72 bits.

6.12 Record Representation Clauses

Record representation clauses may be given for all record types, including types obtained by record extension. Component clauses are allowed for any static component. The restrictions on component clauses depend on the type of the component.

For all components of an elementary type, the only restriction on component clauses is that the size must be at least the 'Size value of the type (actually the Value_Size). There are no restrictions due to alignment, and such components may freely cross storage boundaries.

Packed arrays with a size up to and including 64 bits are represented internally using a modular type with the appropriate number of bits, and thus the same lack of restriction applies. For example, if you declare:

```

  type R is array (1 .. 49) of Boolean;
  pragma Pack (R);
  for R'Size use 49;

```

then a component clause for a component of type R may start on any specified bit boundary, and may specify a value of 49 bits or greater.

For packed bit arrays that are longer than 64 bits, there are two cases. If the component size is a power of 2 (1,2,4,8,16,32 bits), including the important case of single bits or boolean values, then there are no limitations on placement of such components, and they may start and end at arbitrary bit boundaries.

If the component size is not a power of 2 (e.g. 3 or 5), then an array of this type longer than 64 bits must always be placed on a storage unit (byte) boundary and occupy an integral number of storage units (bytes). Any component clause that does not meet this requirement will be rejected.

Any aliased component, or component of an aliased type, must have its normal alignment and size. A component clause that does not meet this requirement will be rejected.

The tag field of a tagged type always occupies an address sized field at the start of the record. No component clause may attempt to overlay this tag. When a tagged type appears as a component, the tag field must have proper alignment

In the case of a record extension T1, of a type T, no component clause applied to the type T1 can specify a storage location that would overlap the first T'Size bytes of the record.

For all other component types, including non-bit-packed arrays, the component can be placed at an arbitrary bit boundary, so for example, the following is permitted:

```
type R is array (1 .. 10) of Boolean;
for R'Size use 80;

type Q is record
  G, H : Boolean;
  L, M : R;
end record;

for Q use record
  G at 0 range 0 .. 0;
  H at 0 range 1 .. 1;
  L at 0 range 2 .. 81;
  R at 0 range 82 .. 161;
end record;
```

Note: the above rules apply to recent releases of GNAT 5. In GNAT 3, there are more severe restrictions on larger components. For non-primitive types, including packed arrays with a size greater than 64 bits, component clauses must respect the alignment requirement of the type, in particular, always starting on a byte boundary, and the length must be a multiple of the storage unit.

6.13 Enumeration Clauses

The only restriction on enumeration clauses is that the range of values must be representable. For the signed case, if one or more of the representation values are negative, all values must be in the range:

```
System.Min_Int .. System.Max_Int
```

For the unsigned case, where all values are nonnegative, the values must be in the range:

```
0 .. System.Max_Binary_Modulus;
```

A *confirming* representation clause is one in which the values range from 0 in sequence, i.e. a clause that confirms the default representation for an enumeration type. Such a confirming representation is permitted by these rules, and is specially recognized by the compiler so that no extra overhead results from the use of such a clause.

If an array has an index type which is an enumeration type to which an enumeration clause has been applied, then the array is stored in a compact manner. Consider the declarations:

```
type r is (A, B, C);
for r use (A => 1, B => 5, C => 10);
type t is array (r) of Character;
```

The array type t corresponds to a vector with exactly three elements and has a default size equal to 3*Character'Size. This ensures efficient use of space, but means that accesses to elements of the array will incur the overhead of converting representation values to the corresponding positional values, (i.e. the value delivered by the Pos attribute).

6.14 Address Clauses

The reference manual allows a general restriction on representation clauses, as found in RM 13.1(22):

An implementation need not support representation items containing nonstatic expressions, except that an implementation should support a representation item for a given entity if each nonstatic expression in the representation item is a name that statically denotes a constant declared before the entity.

In practice this is applicable only to address clauses, since this is the only case in which a non-static expression is permitted by the syntax. As the AARM notes in sections 13.1 (22.a-22.h):

22.a Reason: This is to avoid the following sort of thing:

```
22.b      X : Integer := F(...);
          Y : Address := G(...);
          for X'Address use Y;
```

22.c In the above, we have to evaluate the initialization expression for X before we know where to put the result. This seems like an unreasonable implementation burden.

22.d The above code should instead be written like this:

```
22.e      Y : constant Address := G(...);
          X : Integer := F(...);
          for X'Address use Y;
```

22.f This allows the expression “Y” to be safely evaluated before X is created.

22.g The constant could be a formal parameter of mode in.

22.h An implementation can support other nonstatic expressions if it wants to. Expressions of type Address are hardly ever static, but their value might be known at compile time anyway in many cases.

GNAT does indeed permit many additional cases of non-static expressions. In particular, if the type involved is elementary there are no restrictions (since in this case, holding a temporary copy of the initialization value, if one is present, is inexpensive). In addition, if there is no implicit or explicit initialization, then there are no restrictions. GNAT will reject only the case where all three of these conditions hold:

- The type of the item is non-elementary (e.g. a record or array).
- There is explicit or implicit initialization required for the object. Note that access values are always implicitly initialized, and also in GNAT, certain bit-packed arrays (those having a dynamic length or a length greater than 64) will also be implicitly initialized to zero.
- The address value is non-static. Here GNAT is more permissive than the RM, and allows the address value to be the address of a previously declared stand-alone variable, as long as it does not itself have an address clause.

```
Anchor  : Some_Initialized_Type;
Overlay : Some_Initialized_Type;
for Overlay'Address use Anchor'Address;
```

However, the prefix of the address clause cannot be an array component, or a component of a discriminated record.

As noted above in section 22.h, address values are typically non-static. In particular the To_Address function, even if applied to a literal value, is a non-static function call. To avoid this minor annoyance, GNAT provides the implementation defined attribute 'To_Address. The following two expressions have identical values:

```
To_Address (16#1234_0000#)
System'To_Address (16#1234_0000#);
```

except that the second form is considered to be a static expression, and thus when used as an address clause value is always permitted.

Additionally, GNAT treats as static an address clause that is an unchecked_conversion of a static integer value. This simplifies the porting of legacy code, and provides a portable equivalent to the GNAT attribute `To_Address`.

Another issue with address clauses is the interaction with alignment requirements. When an address clause is given for an object, the address value must be consistent with the alignment of the object (which is usually the same as the alignment of the type of the object). If an address clause is given that specifies an inappropriately aligned address value, then the program execution is erroneous.

Since this source of erroneous behavior can have unfortunate effects, GNAT checks (at compile time if possible, generating a warning, or at execution time with a run-time check) that the alignment is appropriate. If the run-time check fails, then `Program_Error` is raised. This run-time check is suppressed if range checks are suppressed, or if the special GNAT check `Alignment_Check` is suppressed, or if `pragma Restrictions (No_Elaboration_Code)` is in effect.

Finally, GNAT does not permit overlaying of objects of controlled types or composite types containing a controlled component. In most cases, the compiler can detect an attempt at such overlays and will generate a warning at compile time and a `Program_Error` exception at run time.

An address clause cannot be given for an exported object. More understandably the real restriction is that objects with an address clause cannot be exported. This is because such variables are not defined by the Ada program, so there is no external object to export.

It is permissible to give an address clause and a `pragma Import` for the same object. In this case, the variable is not really defined by the Ada program, so there is no external symbol to be linked. The link name and the external name are ignored in this case. The reason that we allow this combination is that it provides a useful idiom to avoid unwanted initializations on objects with address clauses.

When an address clause is given for an object that has implicit or explicit initialization, then by default initialization takes place. This means that the effect of the object declaration is to overwrite the memory at the specified address. This is almost always not what the programmer wants, so GNAT will output a warning:

```
with System;
package G is
  type R is record
    M : Integer := 0;
  end record;

  Ext : R;
  for Ext'Address use System'To_Address (16#1234_1234#);
  |
>>> warning: implicit initialization of "Ext" may
      modify overlaid storage
>>> warning: use pragma Import for "Ext" to suppress
      initialization (RM B(24))

end G;
```

As indicated by the warning message, the solution is to use a (dummy) `pragma Import` to suppress this initialization. The `pragma` tell the compiler that the object is declared and initialized elsewhere. The following package compiles without warnings (and the initialization is suppressed):

```

with System;
package G is
  type R is record
    M : Integer := 0;
  end record;

  Ext : R;
  for Ext'Address use System'To_Address (16#1234_1234#);
  pragma Import (Ada, Ext);
end G;

```

A final issue with address clauses involves their use for overlaying variables, as in the following example:

```

A : Integer;
B : Integer;
for B'Address use A'Address;

```

or alternatively, using the form recommended by the RM:

```

A      : Integer;
Addr   : constant Address := A'Address;
B      : Integer;
for B'Address use Addr;

```

In both of these cases, A and B become aliased to one another via the address clause. This use of address clauses to overlay variables, achieving an effect similar to unchecked conversion was erroneous in Ada 83, but in Ada 95 and Ada 2005 the effect is implementation defined. Furthermore, the Ada RM specifically recommends that in a situation like this, B should be subject to the following implementation advice (RM 13.3(19)):

19 If the Address of an object is specified, or it is imported or exported, then the implementation should not perform optimizations based on assumptions of no aliases.

GNAT follows this recommendation, and goes further by also applying this recommendation to the overlaid variable (A in the above example) in this case. This means that the overlay works "as expected", in that a modification to one of the variables will affect the value of the other.

6.15 Effect of Convention on Representation

Normally the specification of a foreign language convention for a type or an object has no effect on the chosen representation. In particular, the representation chosen for data in GNAT generally meets the standard system conventions, and for example records are laid out in a manner that is consistent with C. This means that specifying convention C (for example) has no effect.

There are four exceptions to this general rule:

- **Convention Fortran and array subtypes** If pragma `Convention Fortran` is specified for an array subtype, then in accordance with the implementation advice in section 3.6.2(11) of the Ada Reference Manual, the array will be stored in a Fortran-compatible column-major manner, instead of the normal default row-major order.
- **Convention C and enumeration types** GNAT normally stores enumeration types in 8, 16, or 32 bits as required to accommodate all values of the type. For example, for the enumeration type declared by:

```
type Color is (Red, Green, Blue);
```

8 bits is sufficient to store all values of the type, so by default, objects of type `Color` will be represented using 8 bits. However, normal C convention is to use 32 bits for all enum values in C, since enum values are essentially of type `int`. If pragma `Convention C` is specified for an Ada enumeration type, then the size is modified as necessary (usually to 32 bits) to be consistent with the C convention for enum values.

Note that this treatment applies only to types. If Convention C is given for an enumeration object, where the enumeration type is not Convention C, then `Object_Size` bits are allocated. For example, for a normal enumeration type, with less than 256 elements, only 8 bits will be allocated for the object. Since this may be a surprise in terms of what C expects, GNAT will issue a warning in this situation. The warning can be suppressed by giving an explicit size clause specifying the desired size.

- **Convention C/Fortran and Boolean types** In C, the usual convention for boolean values, that is values used for conditions, is that zero represents false, and nonzero values represent true. In Ada, the normal convention is that two specific values, typically 0/1, are used to represent false/true respectively.

Fortran has a similar convention for `LOGICAL` values (any nonzero value represents true).

To accommodate the Fortran and C conventions, if a pragma Convention specifies C or Fortran convention for a derived Boolean, as in the following example:

```
type C_Switch is new Boolean;
pragma Convention (C, C_Switch);
```

then the GNAT generated code will treat any nonzero value as true. For truth values generated by GNAT, the conventional value 1 will be used for True, but when one of these values is read, any nonzero value is treated as True.

- **Access types on OpenVMS** For 64-bit OpenVMS systems, access types (other than those for unconstrained arrays) are 64-bits long. An exception to this rule is for the case of C-convention access types where there is no explicit size clause present (or inherited for derived types). In this case, GNAT chooses to make these pointers 32-bits, which provides an easier path for migration of 32-bit legacy code. size clause specifying 64-bits must be used to obtain a 64-bit pointer.

6.16 Determining the Representations chosen by GNAT

Although the descriptions in this section are intended to be complete, it is often easier to simply experiment to see what GNAT accepts and what the effect is on the layout of types and objects.

As required by the Ada RM, if a representation clause is not accepted, then it must be rejected as illegal by the compiler. However, when a representation clause or pragma is accepted, there can still be questions of what the compiler actually does. For example, if a partial record representation clause specifies the location of some components and not others, then where are the non-specified components placed? Or if pragma `Pack` is used on a record, then exactly where are the resulting fields placed? The section on pragma `Pack` in this chapter can be used to answer the second question, but it is often easier to just see what the compiler does.

For this purpose, GNAT provides the option ‘`-gnatR`’. If you compile with this option, then the compiler will output information on the actual representations chosen, in a format similar to source representation clauses. For example, if we compile the package:

```
package q is
  type r (x : boolean) is tagged record
    case x is
      when True => S : String (1 .. 100);
      when False => null;
    end case;
  end record;

  type r2 is new r (false) with record
    y2 : integer;
  end record;

  for r2 use record
    y2 at 16 range 0 .. 31;
  end record;
```



```

type x is record
  y : character;
end record;

type x1 is array (1 .. 10) of x;
for x1'component_size use 11;

type ia is access integer;

type Rb1 is array (1 .. 13) of Boolean;
pragma Pack (rb1);

type Rb2 is array (1 .. 65) of Boolean;
pragma Pack (rb2);

type x2 is record
  l1 : Boolean;
  l2 : Duration;
  l3 : Float;
  l4 : Boolean;
  l5 : Rb1;
  l6 : Rb2;
end record;
pragma Pack (x2);
end q;

```

using the switch ‘-gnatR’ we obtain the following output:

Representation information for unit q

```

for r'Size use ??;
for r'Alignment use 4;
for r use record
  x      at 4 range 0 .. 7;
  _tag   at 0 range 0 .. 31;
  s      at 5 range 0 .. 799;
end record;

for r2'Size use 160;
for r2'Alignment use 4;
for r2 use record
  x      at 4 range 0 .. 7;
  _tag   at 0 range 0 .. 31;
  _parent at 0 range 0 .. 63;
  y2     at 16 range 0 .. 31;
end record;

for x'Size use 8;
for x'Alignment use 1;
for x use record
  y at 0 range 0 .. 7;
end record;

for x1'Size use 112;
for x1'Alignment use 1;
for x1'Component_Size use 11;

for rb1'Size use 13;
for rb1'Alignment use 2;
for rb1'Component_Size use 1;

for rb2'Size use 72;
for rb2'Alignment use 1;
for rb2'Component_Size use 1;

```



```
for x2'Size use 224;
for x2'Alignment use 4;
for x2 use record
  11 at 0 range 0 .. 0;
  12 at 0 range 1 .. 64;
  13 at 12 range 0 .. 31;
  14 at 16 range 0 .. 0;
  15 at 16 range 1 .. 13;
  16 at 18 range 0 .. 71;
end record;
```

The Size values are actually the `Object_Size`, i.e. the default size that will be allocated for objects of the type. The `??` size for type `r` indicates that we have a variant record, and the actual size of objects will depend on the discriminant value.

The Alignment values show the actual alignment chosen by the compiler for each record or array type.

The record representation clause for type `r` shows where all fields are placed, including the compiler generated tag field (whose location cannot be controlled by the programmer).

The record representation clause for the type extension `r2` shows all the fields present, including the parent field, which is a copy of the fields of the parent type of `r2`, i.e. `r1`.

The component size and size clauses for types `rb1` and `rb2` show the exact effect of pragma `Pack` on these arrays, and the record representation clause for type `x2` shows how pragma `Pack` affects this record type.

In some cases, it may be useful to cut and paste the representation clauses generated by the compiler into the original source to fix and guarantee the actual representation to be used.

7 Standard Library Routines

The Ada Reference Manual contains in Annex A a full description of an extensive set of standard library routines that can be used in any Ada program, and which must be provided by all Ada compilers. They are analogous to the standard C library used by C programs.

GNAT implements all of the facilities described in annex A, and for most purposes the description in the Ada Reference Manual, or appropriate Ada text book, will be sufficient for making use of these facilities.

In the case of the input-output facilities, See [Chapter 8 \[The Implementation of Standard I/O\], page 151](#), gives details on exactly how GNAT interfaces to the file system. For the remaining packages, the Ada Reference Manual should be sufficient. The following is a list of the packages included, together with a brief description of the functionality that is provided.

For completeness, references are included to other predefined library routines defined in other sections of the Ada Reference Manual (these are cross-indexed from Annex A).

Ada (A.2) This is a parent package for all the standard library packages. It is usually included implicitly in your program, and itself contains no useful data or routines.

Ada.Calendar (9.6)

Calendar provides time of day access, and routines for manipulating times and durations.

Ada.Characters (A.3.1)

This is a dummy parent package that contains no useful entities

Ada.Characters.Handling (A.3.2)

This package provides some basic character handling capabilities, including classification functions for classes of characters (e.g. test for letters, or digits).

Ada.Characters.Latin_1 (A.3.3)

This package includes a complete set of definitions of the characters that appear in type **CHARACTER**. It is useful for writing programs that will run in international environments. For example, if you want an upper case E with an acute accent in a string, it is often better to use the definition of **UC_E_Acute** in this package. Then your program will print in an understandable manner even if your environment does not support these extended characters.

Ada.Command_Line (A.15)

This package provides access to the command line parameters and the name of the current program (analogous to the use of **argc** and **argv** in C), and also allows the exit status for the program to be set in a system-independent manner.

Ada.Decimal (F.2)

This package provides constants describing the range of decimal numbers implemented, and also a decimal divide routine (analogous to the COBOL verb **DIVIDE ... GIVING ... REMAINDER ...**)

Ada.Direct_IO (A.8.4)

This package provides input-output using a model of a set of records of fixed-length, containing an arbitrary definite Ada type, indexed by an integer record number.

Ada.Dynamic_Priorities (D.5)

This package allows the priorities of a task to be adjusted dynamically as the task is running.

Ada.Exceptions (11.4.1)

This package provides additional information on exceptions, and also contains facilities for treating exceptions as data objects, and raising exceptions with associated messages.

Ada.Finalization (7.6)

This package contains the declarations and subprograms to support the use of controlled types, providing for automatic initialization and finalization (analogous to the constructors and destructors of C++)

Ada.Interrupts (C.3.2)

This package provides facilities for interfacing to interrupts, which includes the set of signals or conditions that can be raised and recognized as interrupts.

Ada.Interrupts.Names (C.3.2)

This package provides the set of interrupt names (actually signal or condition names) that can be handled by GNAT.

Ada.IO_Exceptions (A.13)

This package defines the set of exceptions that can be raised by use of the standard IO packages.

Ada.Numerics

This package contains some standard constants and exceptions used throughout the numerics packages. Note that the constants pi and e are defined here, and it is better to use these definitions than rolling your own.

Ada.Numerics.Complex_Elementary_Functions

Provides the implementation of standard elementary functions (such as log and trigonometric functions) operating on complex numbers using the standard `Float` and the `Complex` and `Imaginary` types created by the package `Numerics.Complex_Types`.

Ada.Numerics.Complex_Types

This is a predefined instantiation of `Numerics.Generic_Complex_Types` using `Standard.Float` to build the type `Complex` and `Imaginary`.

Ada.Numerics.Discrete_Random

This generic package provides a random number generator suitable for generating uniformly distributed values of a specified discrete subtype.

Ada.Numerics.Float_Random

This package provides a random number generator suitable for generating uniformly distributed floating point values in the unit interval.

Ada.Numerics.Generic_Complex_Elementary_Functions

This is a generic version of the package that provides the implementation of standard elementary functions (such as log and trigonometric functions) for an arbitrary complex type.

The following predefined instantiations of this package are provided:

`Short_Float`

`Ada.Numerics.Short_Complex_Elementary_Functions`

`Float`

`Ada.Numerics.Complex_Elementary_Functions`

`Long_Float`

`Ada.Numerics.Long_Complex_Elementary_Functions`

Ada.Numerics.Generic_Complex_Types

This is a generic package that allows the creation of complex types, with associated complex arithmetic operations.

The following predefined instantiations of this package exist

Short_Float

Ada.Numerics.Short_Complex_Complex_Types

Float

Ada.Numerics.Complex_Complex_Types

Long_Float

Ada.Numerics.Long_Complex_Complex_Types

Ada.Numerics.Generic_Elementary_Functions

This is a generic package that provides the implementation of standard elementary functions (such as log and trigonometric functions) for an arbitrary float type.

The following predefined instantiations of this package exist

Short_Float

Ada.Numerics.Short_Elementary_Functions

Float

Ada.Numerics.Elementary_Functions

Long_Float

Ada.Numerics.Long_Elementary_Functions

Ada.Real_Time (D.8)

This package provides facilities similar to those of **Calendar**, but operating with a finer clock suitable for real time control. Note that annex D requires that there be no backward clock jumps, and GNAT generally guarantees this behavior, but of course if the external clock on which the GNAT runtime depends is deliberately reset by some external event, then such a backward jump may occur.

Ada.Sequential_IO (A.8.1)

This package provides input-output facilities for sequential files, which can contain a sequence of values of a single type, which can be any Ada type, including indefinite (unconstrained) types.

Ada.Storage_IO (A.9)

This package provides a facility for mapping arbitrary Ada types to and from a storage buffer. It is primarily intended for the creation of new IO packages.

Ada.Streams (13.13.1)

This is a generic package that provides the basic support for the concept of streams as used by the stream attributes (**Input**, **Output**, **Read** and **Write**).

Ada.Streams.Stream_IO (A.12.1)

This package is a specialization of the type **Streams** defined in package **Streams** together with a set of operations providing **Stream_IO** capability. The **Stream_IO** model permits both random and sequential access to a file which can contain an arbitrary set of values of one or more Ada types.

Ada.Strings (A.4.1)

This package provides some basic constants used by the string handling packages.

Ada.Strings.Bounded (A.4.4)

This package provides facilities for handling variable length strings. The bounded model requires a maximum length. It is thus somewhat more limited than the unbounded model, but avoids the use of dynamic allocation or finalization.

Ada.Strings.Fixed (A.4.3)

This package provides facilities for handling fixed length strings.

Ada.Strings.Maps (A.4.2)

This package provides facilities for handling character mappings and arbitrarily defined subsets of characters. For instance it is useful in defining specialized translation tables.

Ada.Strings.Maps.Constants (A.4.6)

This package provides a standard set of predefined mappings and predefined character sets. For example, the standard upper to lower case conversion table is found in this package. Note that upper to lower case conversion is non-trivial if you want to take the entire set of characters, including extended characters like E with an acute accent, into account. You should use the mappings in this package (rather than adding 32 yourself) to do case mappings.

Ada.Strings.Unbounded (A.4.5)

This package provides facilities for handling variable length strings. The unbounded model allows arbitrary length strings, but requires the use of dynamic allocation and finalization.

Ada.Strings.Wide_Bounded (A.4.7)**Ada.Strings.Wide_Fixed (A.4.7)****Ada.Strings.Wide_Maps (A.4.7)****Ada.Strings.Wide_Maps.Constants (A.4.7)****Ada.Strings.Wide_Unbounded (A.4.7)**

These packages provide analogous capabilities to the corresponding packages without ‘Wide_’ in the name, but operate with the types `Wide_String` and `Wide_Character` instead of `String` and `Character`.

Ada.Strings.Wide_Wide_Bounded (A.4.7)**Ada.Strings.Wide_Wide_Fixed (A.4.7)****Ada.Strings.Wide_Wide_Maps (A.4.7)****Ada.Strings.Wide_Wide_Maps.Constants (A.4.7)****Ada.Strings.Wide_Wide_Unbounded (A.4.7)**

These packages provide analogous capabilities to the corresponding packages without ‘Wide_’ in the name, but operate with the types `Wide_Wide_String` and `Wide_Wide_Character` instead of `String` and `Character`.

Ada.Synchronous_Task_Control (D.10)

This package provides some standard facilities for controlling task communication in a synchronous manner.

Ada.Tags This package contains definitions for manipulation of the tags of tagged values.

Ada.Task_Attributes

This package provides the capability of associating arbitrary task-specific data with separate tasks.

Ada.Text_IO

This package provides basic text input-output capabilities for character, string and numeric data. The subpackages of this package are listed next.

Ada.Text_IO.Decimal_IO

Provides input-output facilities for decimal fixed-point types

Ada.Text_IO.Enumeration_IO

Provides input-output facilities for enumeration types.

Ada.Text_IO.Fixed_IO

Provides input-output facilities for ordinary fixed-point types.

Ada.Text_IO.Float_IO

Provides input-output facilities for float types. The following predefined instantiations of this generic package are available:

Short_Float

Short_Float_Text_IO

Float

Float_Text_IO

Long_Float

Long_Float_Text_IO

Ada.Text_IO.Integer_IO

Provides input-output facilities for integer types. The following predefined instantiations of this generic package are available:

Short_Short_Integer

Ada.Short_Short_Integer_Text_IO

Short_Integer

Ada.Short_Integer_Text_IO

Integer

Ada.Integer_Text_IO

Long_Integer

Ada.Long_Integer_Text_IO

Long_Long_Integer

Ada.Long_Long_Integer_Text_IO

Ada.Text_IO.Modular_IO

Provides input-output facilities for modular (unsigned) types

Ada.Text_IO.Complex_IO (G.1.3)

This package provides basic text input-output capabilities for complex data.

Ada.Text_IO.Editing (F.3.3)

This package contains routines for edited output, analogous to the use of pictures in COBOL. The picture formats used by this package are a close copy of the facility in COBOL.

Ada.Text_IO.Text_Streams (A.12.2)

This package provides a facility that allows Text_IO files to be treated as streams, so that the stream attributes can be used for writing arbitrary data, including binary data, to Text_IO files.

Ada.Unchecked_Conversion (13.9)

This generic package allows arbitrary conversion from one type to another of the same size, providing for breaking the type safety in special circumstances.

If the types have the same Size (more accurately the same Value_Size), then the effect is simply to transfer the bits from the source to the target type without any modification. This usage is well defined, and for simple types whose representation is typically the same across all implementations, gives a portable method of performing such conversions.

If the types do not have the same size, then the result is implementation defined, and thus may be non-portable. The following describes how GNAT handles such unchecked conversion cases.

If the types are of different sizes, and are both discrete types, then the effect is of a normal type conversion without any constraint checking. In particular if the result type has a larger size, the result will be zero or sign extended. If the result type has a smaller size, the result will be truncated by ignoring high order bits.

If the types are of different sizes, and are not both discrete types, then the conversion works as though pointers were created to the source and target, and the pointer value is converted. The effect is that bits are copied from successive low order storage units and bits of the source up to the length of the target type.

A warning is issued if the lengths differ, since the effect in this case is implementation dependent, and the above behavior may not match that of some other compiler.

A pointer to one type may be converted to a pointer to another type using unchecked conversion. The only case in which the effect is undefined is when one or both pointers are pointers to unconstrained array types. In this case, the bounds information may get incorrectly transferred, and in particular, GNAT uses double size pointers for such types, and it is meaningless to convert between such pointer types. GNAT will issue a warning if the alignment of the target designated type is more strict than the alignment of the source designated type (since the result may be unaligned in this case).

A pointer other than a pointer to an unconstrained array type may be converted to and from `System.Address`. Such usage is common in Ada 83 programs, but note that `Ada.Address_To_Access_Conversions` is the preferred method of performing such conversions in Ada 95 and Ada 2005. Neither unchecked conversion nor `Ada.Address_To_Access_Conversions` should be used in conjunction with pointers to unconstrained objects, since the bounds information cannot be handled correctly in this case.

`Ada.Unchecked_Deallocation` (13.11.2)

This generic package allows explicit freeing of storage previously allocated by use of an allocator.

`Ada.Wide_Text_IO` (A.11)

This package is similar to `Ada.Text_IO`, except that the external file supports wide character representations, and the internal types are `Wide_Character` and `Wide_String` instead of `Character` and `String`. It contains generic subpackages listed next.

`Ada.Wide_Text_IO.Decimal_IO`

Provides input-output facilities for decimal fixed-point types

`Ada.Wide_Text_IO.Enumeration_IO`

Provides input-output facilities for enumeration types.

`Ada.Wide_Text_IO.Fixed_IO`

Provides input-output facilities for ordinary fixed-point types.

`Ada.Wide_Text_IO.Float_IO`

Provides input-output facilities for float types. The following predefined instantiations of this generic package are available:

`Short_Float`

`Short_Float_Wide_Text_IO`

`Float`

`Float_Wide_Text_IO`

`Long_Float`

`Long_Float_Wide_Text_IO`

Ada.Wide_Text_IO.Integer_IO

Provides input-output facilities for integer types. The following predefined instantiations of this generic package are available:

```
Short_Short_Integer
    Ada.Short_Short_Integer_Wide_Text_IO

Short_Integer
    Ada.Short_Integer_Wide_Text_IO

Integer    Ada.Integer_Wide_Text_IO

Long_Integer
    Ada.Long_Integer_Wide_Text_IO

Long_Long_Integer
    Ada.Long_Long_Integer_Wide_Text_IO
```

Ada.Wide_Text_IO.Modular_IO

Provides input-output facilities for modular (unsigned) types

Ada.Wide_Text_IO.Complex_IO (G.1.3)

This package is similar to `Ada.Text_IO.Complex_IO`, except that the external file supports wide character representations.

Ada.Wide_Text_IO.Editing (F.3.4)

This package is similar to `Ada.Text_IO.Editing`, except that the types are `Wide_Character` and `Wide_String` instead of `Character` and `String`.

Ada.Wide_Text_IO.Streams (A.12.3)

This package is similar to `Ada.Text_IO.Streams`, except that the types are `Wide_Character` and `Wide_String` instead of `Character` and `String`.

Ada.Wide_Wide_Text_IO (A.11)

This package is similar to `Ada.Text_IO`, except that the external file supports wide character representations, and the internal types are `Wide_Character` and `Wide_String` instead of `Character` and `String`. It contains generic subpackages listed next.

Ada.Wide_Wide_Text_IO.Decimal_IO

Provides input-output facilities for decimal fixed-point types

Ada.Wide_Wide_Text_IO.Enumeration_IO

Provides input-output facilities for enumeration types.

Ada.Wide_Wide_Text_IO.Fixed_IO

Provides input-output facilities for ordinary fixed-point types.

Ada.Wide_Wide_Text_IO.Float_IO

Provides input-output facilities for float types. The following predefined instantiations of this generic package are available:

```
Short_Float
    Short_Float_Wide_Wide_Text_IO

Float    Float_Wide_Wide_Text_IO

Long_Float
    Long_Float_Wide_Wide_Text_IO
```

Ada.Wide_Wide_Text_IO.Integer_IO

Provides input-output facilities for integer types. The following predefined instantiations of this generic package are available:

Short_Short_Integer
 Ada.Short_Short_Integer_Wide_Wide_Text_IO

Short_Integer
 Ada.Short_Integer_Wide_Wide_Text_IO

Integer Ada.Integer_Wide_Wide_Text_IO

Long_Integer
 Ada.Long_Integer_Wide_Wide_Text_IO

Long_Long_Integer
 Ada.Long_Long_Integer_Wide_Wide_Text_IO

Ada.Wide_Wide_Text_IO.Modular_IO
 Provides input-output facilities for modular (unsigned) types

Ada.Wide_Wide_Text_IO.Complex_IO (G.1.3)
 This package is similar to Ada.Text_IO.Complex_IO, except that the external file supports wide character representations.

Ada.Wide_Wide_Text_IO.Editing (F.3.4)
 This package is similar to Ada.Text_IO.Editing, except that the types are Wide_Character and Wide_String instead of Character and String.

Ada.Wide_Wide_Text_IO.Streams (A.12.3)
 This package is similar to Ada.Text_IO.Streams, except that the types are Wide_Character and Wide_String instead of Character and String.

8 The Implementation of Standard I/O

GNAT implements all the required input-output facilities described in A.6 through A.14. These sections of the Ada Reference Manual describe the required behavior of these packages from the Ada point of view, and if you are writing a portable Ada program that does not need to know the exact manner in which Ada maps to the outside world when it comes to reading or writing external files, then you do not need to read this chapter. As long as your files are all regular files (not pipes or devices), and as long as you write and read the files only from Ada, the description in the Ada Reference Manual is sufficient.

However, if you want to do input-output to pipes or other devices, such as the keyboard or screen, or if the files you are dealing with are either generated by some other language, or to be read by some other language, then you need to know more about the details of how the GNAT implementation of these input-output facilities behaves.

In this chapter we give a detailed description of exactly how GNAT interfaces to the file system. As always, the sources of the system are available to you for answering questions at an even more detailed level, but for most purposes the information in this chapter will suffice.

Another reason that you may need to know more about how input-output is implemented arises when you have a program written in mixed languages where, for example, files are shared between the C and Ada sections of the same program. GNAT provides some additional facilities, in the form of additional child library packages, that facilitate this sharing, and these additional facilities are also described in this chapter.

8.1 Standard I/O Packages

The Standard I/O packages described in Annex A for

- Ada.Text_IO
- Ada.Text_IO.Complex_IO
- Ada.Text_IO.Text_Streams
- Ada.Wide_Text_IO
- Ada.Wide_Text_IO.Complex_IO
- Ada.Wide_Text_IO.Text_Streams
- Ada.Wide_Wide_Text_IO
- Ada.Wide_Wide_Text_IO.Complex_IO
- Ada.Wide_Wide_Text_IO.Text_Streams
- Ada.Stream_IO
- Ada.Sequential_IO
- Ada.Direct_IO

are implemented using the C library streams facility; where

- All files are opened using `fopen`.
- All input/output operations use `fread/fwrite`.

There is no internal buffering of any kind at the Ada library level. The only buffering is that provided at the system level in the implementation of the library routines that support streams. This facilitates shared use of these streams by mixed language programs. Note though that system level buffering is explicitly enabled at elaboration of the standard I/O packages and that can have an impact on mixed language programs, in particular those using I/O before calling the Ada elaboration routine (e.g. `adainit`). It is recommended to call the Ada elaboration routine before performing any I/O or when impractical, flush the common I/O streams and in particular `Standard_Output` before elaborating the Ada code.

8.2 FORM Strings

The format of a FORM string in GNAT is:

```
"keyword=value,keyword=value,...,keyword=value"
```

where letters may be in upper or lower case, and there are no spaces between values. The order of the entries is not important. Currently the following keywords defined.

```
TEXT_TRANSLATION=[YES|NO]
SHARED=[YES|NO]
WCEM=[n|h|u|s|e|8|b]
ENCODING=[UTF8|8BITS]
```

The use of these parameters is described later in this section.

8.3 Direct_IO

Direct_IO can only be instantiated for definite types. This is a restriction of the Ada language, which means that the records are fixed length (the length being determined by `type'Size`, rounded up to the next storage unit boundary if necessary).

The records of a Direct_IO file are simply written to the file in index sequence, with the first record starting at offset zero, and subsequent records following. There is no control information of any kind. For example, if 32-bit integers are being written, each record takes 4-bytes, so the record at index K starts at offset $(K-1)*4$.

There is no limit on the size of Direct_IO files, they are expanded as necessary to accommodate whatever records are written to the file.

8.4 Sequential_IO

Sequential_IO may be instantiated with either a definite (constrained) or indefinite (unconstrained) type.

For the definite type case, the elements written to the file are simply the memory images of the data values with no control information of any kind. The resulting file should be read using the same type, no validity checking is performed on input.

For the indefinite type case, the elements written consist of two parts. First is the size of the data item, written as the memory image of a `Interfaces.C.size_t` value, followed by the memory image of the data value. The resulting file can only be read using the same (unconstrained) type. Normal assignment checks are performed on these read operations, and if these checks fail, `Data_Error` is raised. In particular, in the array case, the lengths must match, and in the variant record case, if the variable for a particular read operation is constrained, the discriminants must match.

Note that it is not possible to use Sequential_IO to write variable length array items, and then read the data back into different length arrays. For example, the following will raise `Data_Error`:

```
package IO is new Sequential_IO (String);
F : IO.File_Type;
S : String (1..4);
...
IO.Create (F)
IO.Write (F, "hello!")
IO.Reset (F, Mode=>In_File);
IO.Read (F, S);
Put_Line (S);
```

On some Ada implementations, this will print `hell`, but the program is clearly incorrect, since there is only one element in the file, and that element is the string `hello!`.

In Ada 95 and Ada 2005, this kind of behavior can be legitimately achieved using `Stream_IO`, and this is the preferred mechanism. In particular, the above program fragment rewritten to use `Stream_IO` will work correctly.

8.5 Text_IO

`Text_IO` files consist of a stream of characters containing the following special control characters:

LF (line feed, 16#0A#) Line Mark
FF (form feed, 16#0C#) Page Mark

A canonical `Text_IO` file is defined as one in which the following conditions are met:

- The character LF is used only as a line mark, i.e. to mark the end of the line.
- The character FF is used only as a page mark, i.e. to mark the end of a page and consequently can appear only immediately following a LF (line mark) character.
- The file ends with either LF (line mark) or LF-FF (line mark, page mark). In the former case, the page mark is implicitly assumed to be present.

A file written using `Text_IO` will be in canonical form provided that no explicit LF or FF characters are written using `Put` or `Put_Line`. There will be no FF character at the end of the file unless an explicit `New_Page` operation was performed before closing the file.

A canonical `Text_IO` file that is a regular file (i.e., not a device or a pipe) can be read using any of the routines in `Text_IO`. The semantics in this case will be exactly as defined in the Ada Reference Manual, and all the routines in `Text_IO` are fully implemented.

A text file that does not meet the requirements for a canonical `Text_IO` file has one of the following:

- The file contains FF characters not immediately following a LF character.
- The file contains LF or FF characters written by `Put` or `Put_Line`, which are not logically considered to be line marks or page marks.
- The file ends in a character other than LF or FF, i.e. there is no explicit line mark or page mark at the end of the file.

`Text_IO` can be used to read such non-standard text files but subprograms to do with line or page numbers do not have defined meanings. In particular, a FF character that does not follow a LF character may or may not be treated as a page mark from the point of view of page and line numbering. Every LF character is considered to end a line, and there is an implied LF character at the end of the file.

8.5.1 Stream Pointer Positioning

`Ada.Text_IO` has a definition of current position for a file that is being read. No internal buffering occurs in `Text_IO`, and usually the physical position in the stream used to implement the file corresponds to this logical position defined by `Text_IO`. There are two exceptions:

- After a call to `End_Of_Page` that returns `True`, the stream is positioned past the LF (line mark) that precedes the page mark. `Text_IO` maintains an internal flag so that subsequent read operations properly handle the logical position which is unchanged by the `End_Of_Page` call.
- After a call to `End_Of_File` that returns `True`, if the `Text_IO` file was positioned before the line mark at the end of file before the call, then the logical position is unchanged, but the stream is physically positioned right at the end of file (past the line mark, and past a possible page mark following the line mark). Again `Text_IO` maintains internal flags so that subsequent read operations properly handle the logical position.

These discrepancies have no effect on the observable behavior of `Text_IO`, but if a single Ada stream is shared between a C program and Ada program, or shared (using `'shared=yes'` in the form string) between two Ada files, then the difference may be observable in some situations.

8.5.2 Reading and Writing Non-Regular Files

A non-regular file is a device (such as a keyboard), or a pipe. Text_IO can be used for reading and writing. Writing is not affected and the sequence of characters output is identical to the normal file case, but for reading, the behavior of Text_IO is modified to avoid undesirable look-ahead as follows:

An input file that is not a regular file is considered to have no page marks. Any `Ascii.FF` characters (the character normally used for a page mark) appearing in the file are considered to be data characters. In particular:

- `Get_Line` and `Skip_Line` do not test for a page mark following a line mark. If a page mark appears, it will be treated as a data character.
- This avoids the need to wait for an extra character to be typed or entered from the pipe to complete one of these operations.
- `End_Of_Page` always returns `False`
- `End_Of_File` will return `False` if there is a page mark at the end of the file.

Output to non-regular files is the same as for regular files. Page marks may be written to non-regular files using `New_Page`, but as noted above they will not be treated as page marks on input if the output is piped to another Ada program.

Another important discrepancy when reading non-regular files is that the end of file indication is not “sticky”. If an end of file is entered, e.g. by pressing the EOT key, then end of file is signaled once (i.e. the test `End_Of_File` will yield `True`, or a read will raise `End_Error`), but then reading can resume to read data past that end of file indication, until another end of file indication is entered.

8.5.3 Get_Immediate

`Get_Immediate` returns the next character (including control characters) from the input file. In particular, `Get_Immediate` will return LF or FF characters used as line marks or page marks. Such operations leave the file positioned past the control character, and it is thus not treated as having its normal function. This means that page, line and column counts after this kind of `Get_Immediate` call are set as though the mark did not occur. In the case where a `Get_Immediate` leaves the file positioned between the line mark and page mark (which is not normally possible), it is undefined whether the FF character will be treated as a page mark.

8.5.4 Treating Text_IO Files as Streams

The package `Text_IO.Streams` allows a Text_IO file to be treated as a stream. Data written to a Text_IO file in this stream mode is binary data. If this binary data contains bytes `16#0A#` (LF) or `16#0C#` (FF), the resulting file may have non-standard format. Similarly if read operations are used to read from a Text_IO file treated as a stream, then LF and FF characters may be skipped and the effect is similar to that described above for `Get_Immediate`.

8.5.5 Text_IO Extensions

A package `GNAT.IO.Aux` in the GNAT library provides some useful extensions to the standard `Text_IO` package:

- function `File_Exists (Name : String)` return Boolean; Determines if a file of the given name exists.
- function `Get_Line` return String; Reads a string from the standard input file. The value returned is exactly the length of the line that was read.
- function `Get_Line (File : Ada.Text_IO.File_Type)` return String; Similar, except that the parameter `File` specifies the file from which the string is to be read.

8.5.6 Text_IO Facilities for Unbounded Strings

The package `Ada.Strings.Unbounded.Text_IO` in library files `a-suteio.ads/adb` contains some GNAT-specific subprograms useful for Text_IO operations on unbounded strings:

- function `Get_Line (File : File_Type)` return `Unbounded_String`; Reads a line from the specified file and returns the result as an unbounded string.
- procedure `Put (File : File_Type; U : Unbounded_String)`; Writes the value of the given unbounded string to the specified file Similar to the effect of `Put (To_String (U))` except that an extra copy is avoided.
- procedure `Put_Line (File : File_Type; U : Unbounded_String)`; Writes the value of the given unbounded string to the specified file, followed by a `New_Line`. Similar to the effect of `Put_Line (To_String (U))` except that an extra copy is avoided.

In the above procedures, `File` is of type `Ada.Text_IO.File_Type` and is optional. If the parameter is omitted, then the standard input or output file is referenced as appropriate.

The package `Ada.Strings.Wide_Unbounded.Wide_Text_IO` in library files `'a-swuwti.ads'` and `'a-swuwti.adb'` provides similar extended `Wide_Text_IO` functionality for unbounded wide strings.

The package `Ada.Strings.Wide_Wide_Unbounded.Wide_Wide_Text_IO` in library files `'a-szuzti.ads'` and `'a-szuzti.adb'` provides similar extended `Wide_Wide_Text_IO` functionality for unbounded wide wide strings.

8.6 Wide_Text_IO

`Wide_Text_IO` is similar in most respects to `Text_IO`, except that both input and output files may contain special sequences that represent wide character values. The encoding scheme for a given file may be specified using a FORM parameter:

`WCEM=x`

as part of the FORM string (`WCEM` = wide character encoding method), where `x` is one of the following characters

<code>'h'</code>	Hex ESC encoding
<code>'u'</code>	Upper half encoding
<code>'s'</code>	Shift-JIS encoding
<code>'e'</code>	EUC Encoding
<code>'g'</code>	UTF-8 encoding
<code>'b'</code>	Brackets encoding

The encoding methods match those that can be used in a source program, but there is no requirement that the encoding method used for the source program be the same as the encoding method used for files, and different files may use different encoding methods.

The default encoding method for the standard files, and for opened files for which no `WCEM` parameter is given in the FORM string matches the wide character encoding specified for the main program (the default being brackets encoding if no coding method was specified with `-gnatW`).

Hex Coding

In this encoding, a wide character is represented by a five character sequence:

`ESC a b c d`

where `a`, `b`, `c`, `d` are the four hexadecimal characters (using upper case letters) of the wide character code. For example, `ESC A345` is used to represent the wide

character with code `16#A345#`. This scheme is compatible with use of the full `Wide_Character` set.

Upper Half Coding

The wide character with encoding `16#abcd#`, where the upper bit is on (i.e. `a` is in the range 8-F) is represented as two bytes `16#ab#` and `16#cd#`. The second byte may never be a format control character, but is not required to be in the upper half. This method can be also used for shift-JIS or EUC where the internal coding matches the external coding.

Shift JIS Coding

A wide character is represented by a two character sequence `16#ab#` and `16#cd#`, with the restrictions described for upper half encoding as described above. The internal character code is the corresponding JIS character according to the standard algorithm for Shift-JIS conversion. Only characters defined in the JIS code set table can be used with this encoding method.

EUC Coding

A wide character is represented by a two character sequence `16#ab#` and `16#cd#`, with both characters being in the upper half. The internal character code is the corresponding JIS character according to the EUC encoding algorithm. Only characters defined in the JIS code set table can be used with this encoding method.

UTF-8 Coding

A wide character is represented using UCS Transformation Format 8 (UTF-8) as defined in Annex R of ISO 10646-1/Am.2. Depending on the character value, the representation is a one, two, or three byte sequence:

```
16#0000#-16#007f#: 2#0xxxxxxx#
16#0080#-16#07ff#: 2#110xxxxx# 2#10xxxxxx#
16#0800#-16#ffff#: 2#1110xxxx# 2#10xxxxxx# 2#10xxxxxx#
```

where the `xxx` bits correspond to the left-padded bits of the 16-bit character value. Note that all lower half ASCII characters are represented as ASCII bytes and all upper half characters and other wide characters are represented as sequences of upper-half (The full UTF-8 scheme allows for encoding 31-bit characters as 6-byte sequences, but in this implementation, all UTF-8 sequences of four or more bytes length will raise a `Constraint_Error`, as will all invalid UTF-8 sequences.)

Brackets Coding

In this encoding, a wide character is represented by the following eight character sequence:

```
[ " a b c d " ]
```

where `a`, `b`, `c`, `d` are the four hexadecimal characters (using uppercase letters) of the wide character code. For example, `["A345"]` is used to represent the wide character with code `16#A345#`. This scheme is compatible with use of the full `Wide_Character` set. On input, brackets coding can also be used for upper half characters, e.g. `["C1"]` for lower case `a`. However, on output, brackets notation is only used for wide characters with a code greater than `16#FF#`.

Note that brackets coding is not normally used in the context of `Wide_Text_IO` or `Wide_Wide_Text_IO`, since it is really just designed as a portable way of encoding source files. In the context of `Wide_Text_IO` or `Wide_Wide_Text_IO`, it can only be used if the file does not contain any instance of the left bracket character other than to encode wide character values using the brackets encoding method. In practice it is expected that some standard wide character encoding method such as UTF-8 will be used for text input output.

If brackets notation is used, then any occurrence of a left bracket in the input file which is not the start of a valid wide character sequence will cause `Constraint_Error` to be raised. It is possible to encode a left bracket as `["5B"]` and `Wide_Text_IO` and `Wide_Wide_Text_IO` input will interpret this as a left bracket.

However, when a left bracket is output, it will be output as a left bracket and not as `["5B"]`. We make this decision because for normal use of `Wide_Text_IO` for outputting messages, it is unpleasant to clobber left brackets. For example, if we write:

```
Put_Line ("Start of output [first run]");
```

we really do not want to have the left bracket in this message clobbered so that the output reads:

```
Start of output ["5B"]first run]
```

In practice brackets encoding is reasonably useful for normal `Put_Line` use since we won't get confused between left brackets and wide character sequences in the output. But for input, or when files are written out and read back in, it really makes better sense to use one of the standard encoding methods such as UTF-8.

For the coding schemes other than UTF-8, Hex, or Brackets encoding, not all wide character values can be represented. An attempt to output a character that cannot be represented using the encoding scheme for the file causes `Constraint_Error` to be raised. An invalid wide character sequence on input also causes `Constraint_Error` to be raised.

8.6.1 Stream Pointer Positioning

`Ada.Wide_Text_IO` is similar to `Ada.Text_IO` in its handling of stream pointer positioning (see [Section 8.5 \[Text_IO\], page 153](#)). There is one additional case:

If `Ada.Wide_Text_IO.Look_Ahead` reads a character outside the normal lower ASCII set (i.e. a character in the range:

```
Wide_Character'Val (16#0080#) .. Wide_Character'Val (16#FFFF#)
```

then although the logical position of the file pointer is unchanged by the `Look_Ahead` call, the stream is physically positioned past the wide character sequence. Again this is to avoid the need for buffering or backup, and all `Wide_Text_IO` routines check the internal indication that this situation has occurred so that this is not visible to a normal program using `Wide_Text_IO`. However, this discrepancy can be observed if the wide text file shares a stream with another file.

8.6.2 Reading and Writing Non-Regular Files

As in the case of `Text_IO`, when a non-regular file is read, it is assumed that the file contains no page marks (any form characters are treated as data characters), and `End_Of_Page` always returns `False`. Similarly, the end of file indication is not sticky, so it is possible to read beyond an end of file.

8.7 Wide_Wide_Text_IO

`Wide_Wide_Text_IO` is similar in most respects to `Text_IO`, except that both input and output files may contain special sequences that represent wide wide character values. The encoding scheme for a given file may be specified using a FORM parameter:

```
WCEM=x
```

as part of the FORM string (WCEM = wide character encoding method), where `x` is one of the following characters

'h'	Hex ESC encoding
'u'	Upper half encoding

's'	Shift-JIS encoding
'e'	EUC Encoding
'8'	UTF-8 encoding
'b'	Brackets encoding

The encoding methods match those that can be used in a source program, but there is no requirement that the encoding method used for the source program be the same as the encoding method used for files, and different files may use different encoding methods.

The default encoding method for the standard files, and for opened files for which no WCEM parameter is given in the FORM string matches the wide character encoding specified for the main program (the default being brackets encoding if no coding method was specified with -gnatW).

UTF-8 Coding

A wide character is represented using UCS Transformation Format 8 (UTF-8) as defined in Annex R of ISO 10646-1/Am.2. Depending on the character value, the representation is a one, two, three, or four byte sequence:

```
16#000000#-16#00007f#: 2#0xxxxxxx#
16#000080#-16#0007ff#: 2#110xxxxx# 2#10xxxxxx#
16#000800#-16#00ffff#: 2#1110xxxx# 2#10xxxxxx# 2#10xxxxxx#
16#010000#-16#10ffff#: 2#11110xxx# 2#10xxxxxx# 2#10xxxxxx# 2#10xxxxxx#
```

where the xxx bits correspond to the left-padded bits of the 21-bit character value. Note that all lower half ASCII characters are represented as ASCII bytes and all upper half characters and other wide characters are represented as sequences of upper-half characters.

Brackets Coding

In this encoding, a wide wide character is represented by the following eight character sequence if is in wide character range

```
[ " a b c d " ]
```

and by the following ten character sequence if not

```
[ " a b c d e f " ]
```

where a, b, c, d, e, and f are the four or six hexadecimal characters (using upper-case letters) of the wide wide character code. For example, ["01A345"] is used to represent the wide wide character with code 16#01A345#.

This scheme is compatible with use of the full Wide_Wide_Character set. On input, brackets coding can also be used for upper half characters, e.g. ["C1"] for lower case a. However, on output, brackets notation is only used for wide characters with a code greater than 16#FF#.

If is also possible to use the other Wide_Character encoding methods, such as Shift-JIS, but the other schemes cannot support the full range of wide wide characters. An attempt to output a character that cannot be represented using the encoding scheme for the file causes Constraint_Error to be raised. An invalid wide character sequence on input also causes Constraint_Error to be raised.

8.7.1 Stream Pointer Positioning

Ada.Wide_Wide_Text_IO is similar to Ada.Text_IO in its handling of stream pointer positioning (see [Section 8.5 \[Text_IO\]](#), [page 153](#)). There is one additional case:

If Ada.Wide_Wide_Text_IO.Look_Ahead reads a character outside the normal lower ASCII set (i.e. a character in the range:

```
Wide_Wide_Character'Val (16#0080#) .. Wide_Wide_Character'Val (16#10FFFF#)
```

then although the logical position of the file pointer is unchanged by the `Look_Ahead` call, the stream is physically positioned past the wide character sequence. Again this is to avoid the need for buffering or backup, and all `Wide_Wide_Text_IO` routines check the internal indication that this situation has occurred so that this is not visible to a normal program using `Wide_Wide_Text_IO`. However, this discrepancy can be observed if the wide text file shares a stream with another file.

8.7.2 Reading and Writing Non-Regular Files

As in the case of `Text_IO`, when a non-regular file is read, it is assumed that the file contains no page marks (any form characters are treated as data characters), and `End_Of_Page` always returns `False`. Similarly, the end of file indication is not sticky, so it is possible to read beyond an end of file.

8.8 Stream_IO

A stream file is a sequence of bytes, where individual elements are written to the file as described in the Ada Reference Manual. The type `Stream_Element` is simply a byte. There are two ways to read or write a stream file.

- The operations `Read` and `Write` directly read or write a sequence of stream elements with no control information.
- The stream attributes applied to a stream file transfer data in the manner described for stream attributes.

8.9 Text Translation

'`Text_Translation=xxx`' may be used as the `Form` parameter passed to `Text_IO.Create` and `Text_IO.Open`: '`Text_Translation=Yes`' is the default, which means to translate LF to/from CR/LF on Windows systems. '`Text_Translation=No`' disables this translation; i.e. it uses binary mode. For output files, '`Text_Translation=No`' may be used to create Unix-style files on Windows. '`Text_Translation=xxx`' has no effect on Unix systems.

8.10 Shared Files

Section A.14 of the Ada Reference Manual allows implementations to provide a wide variety of behavior if an attempt is made to access the same external file with two or more internal files.

To provide a full range of functionality, while at the same time minimizing the problems of portability caused by this implementation dependence, GNAT handles file sharing as follows:

- In the absence of a '`shared=xxx`' form parameter, an attempt to open two or more files with the same full name is considered an error and is not supported. The exception `Use_Error` will be raised. Note that a file that is not explicitly closed by the program remains open until the program terminates.
- If the form parameter '`shared=no`' appears in the form string, the file can be opened or created with its own separate stream identifier, regardless of whether other files sharing the same external file are opened. The exact effect depends on how the C stream routines handle multiple accesses to the same external files using separate streams.
- If the form parameter '`shared=yes`' appears in the form string for each of two or more files opened using the same full name, the same stream is shared between these files, and the semantics are as described in Ada Reference Manual, Section A.14.

When a program that opens multiple files with the same name is ported from another Ada compiler to GNAT, the effect will be that `Use_Error` is raised.

The documentation of the original compiler and the documentation of the program should then be examined to determine if file sharing was expected, and ‘**shared=xxx**’ parameters added to **Open** and **Create** calls as required.

When a program is ported from GNAT to some other Ada compiler, no special attention is required unless the ‘**shared=xxx**’ form parameter is used in the program. In this case, you must examine the documentation of the new compiler to see if it supports the required file sharing semantics, and form strings modified appropriately. Of course it may be the case that the program cannot be ported if the target compiler does not support the required functionality. The best approach in writing portable code is to avoid file sharing (and hence the use of the ‘**shared=xxx**’ parameter in the form string) completely.

One common use of file sharing in Ada 83 is the use of instantiations of **Sequential_IO** on the same file with different types, to achieve heterogeneous input-output. Although this approach will work in GNAT if ‘**shared=yes**’ is specified, it is preferable in Ada to use **Stream_IO** for this purpose (using the stream attributes)

8.11 Filenames encoding

An encoding form parameter can be used to specify the filename encoding ‘**encoding=xxx**’.

- If the form parameter ‘**encoding=utf8**’ appears in the form string, the filename must be encoded in UTF-8.
- If the form parameter ‘**encoding=8bits**’ appears in the form string, the filename must be a standard 8bits string.

In the absence of a ‘**encoding=xxx**’ form parameter, the encoding is controlled by the ‘**GNAT_CODE_PAGE**’ environment variable. And if not set ‘**utf8**’ is assumed.

‘**CP_ACP**’ The current system Windows ANSI code page.

‘**CP_UTF8**’ UTF-8 encoding

This encoding form parameter is only supported on the Windows platform. On the other Operating Systems the run-time is supporting UTF-8 natively.

8.12 Open Modes

Open and **Create** calls result in a call to **fopen** using the mode shown in the following table:

	Open and Create Call Modes	
	OPEN	CREATE
Append_File	"r+"	"w+"
In_File	"r"	"w+"
Out_File (Direct_IO)	"r+"	"w"
Out_File (all other cases)	"w"	"w"
Inout_File	"r+"	"w+"

If text file translation is required, then either ‘**b**’ or ‘**t**’ is added to the mode, depending on the setting of **Text**. Text file translation refers to the mapping of CR/LF sequences in an external file to LF characters internally. This mapping only occurs in DOS and DOS-like systems, and is not relevant to other systems.

A special case occurs with **Stream_IO**. As shown in the above table, the file is initially opened in ‘**r**’ or ‘**w**’ mode for the **In_File** and **Out_File** cases. If a **Set_Mode** operation subsequently requires switching from reading to writing or vice-versa, then the file is reopened in ‘**r+**’ mode to permit the required operation.

8.13 Operations on C Streams

The package `Interfaces.C_Streams` provides an Ada program with direct access to the C library functions for operations on C streams:

```
package Interfaces.C_Streams is
  -- Note: the reason we do not use the types that are in
  -- Interfaces.C is that we want to avoid dragging in the
  -- code in this unit if possible.
  subtype chars is System.Address;
  -- Pointer to null-terminated array of characters
  subtype FILEs is System.Address;
  -- Corresponds to the C type FILE*
  subtype voids is System.Address;
  -- Corresponds to the C type void*
  subtype int is Integer;
  subtype long is Long_Integer;
  -- Note: the above types are subtypes deliberately, and it
  -- is part of this spec that the above correspondences are
  -- guaranteed. This means that it is legitimate to, for
  -- example, use Integer instead of int. We provide these
  -- synonyms for clarity, but in some cases it may be
  -- convenient to use the underlying types (for example to
  -- avoid an unnecessary dependency of a spec on the spec
  -- of this unit).
  type size_t is mod 2 ** Standard'Address_Size;
  NULL_Stream : constant FILEs;
  -- Value returned (NULL in C) to indicate an
  -- fdopen/fopen/tmpfile error
  -----
  -- Constants Defined in stdio.h --
  -----
  EOF : constant int;
  -- Used by a number of routines to indicate error or
  -- end of file
  IOFBF : constant int;
  IOLBF : constant int;
  IONBF : constant int;
  -- Used to indicate buffering mode for setvbuf call
  SEEK_CUR : constant int;
  SEEK_END : constant int;
  SEEK_SET : constant int;
  -- Used to indicate origin for fseek call
  function stdin return FILEs;
  function stdout return FILEs;
  function stderr return FILEs;
  -- Streams associated with standard files
  -----
  -- Standard C functions --
  -----
  -- The functions selected below are ones that are
  -- available in UNIX (but not necessarily in ANSI C).
  -- These are very thin interfaces
  -- which copy exactly the C headers. For more
  -- documentation on these functions, see the Microsoft C
  -- "Run-Time Library Reference" (Microsoft Press, 1990,
  -- ISBN 1-55615-225-6), which includes useful information
  -- on system compatibility.
  procedure clearerr (stream : FILEs);
  function fclose (stream : FILEs) return int;
  function fdopen (handle : int; mode : chars) return FILEs;
  function feof (stream : FILEs) return int;
  function ferror (stream : FILEs) return int;
  function fflush (stream : FILEs) return int;
  function fgetc (stream : FILEs) return int;
```

```

function fgets (strng : chars; n : int; stream : FILES)
  return chars;
function fileno (stream : FILES) return int;
function fopen (filename : chars; Mode : chars)
  return FILES;
-- Note: to maintain target independence, use
-- text_translation_required, a boolean variable defined in
-- a-sysdep.c to deal with the target dependent text
-- translation requirement. If this variable is set,
-- then b/t should be appended to the standard mode
-- argument to set the text translation mode off or on
-- as required.
function fputc (C : int; stream : FILES) return int;
function fputs (Strng : chars; Stream : FILES) return int;
function fread
  (buffer : voids;
   size : size_t;
   count : size_t;
   stream : FILES)
  return size_t;
function freopen
  (filename : chars;
   mode : chars;
   stream : FILES)
  return FILES;
function fseek
  (stream : FILES;
   offset : long;
   origin : int)
  return int;
function ftell (stream : FILES) return long;
function fwrite
  (buffer : voids;
   size : size_t;
   count : size_t;
   stream : FILES)
  return size_t;
function isatty (handle : int) return int;
procedure mktemp (template : chars);
-- The return value (which is just a pointer to template)
-- is discarded
procedure rewind (stream : FILES);
function rmtmp return int;
function setvbuf
  (stream : FILES;
   buffer : chars;
   mode : int;
   size : size_t)
  return int;

function tmpfile return FILES;
function ungetc (c : int; stream : FILES) return int;
function unlink (filename : chars) return int;
-----
-- Extra functions --
-----
-- These functions supply slightly thicker bindings than
-- those above. They are derived from functions in the
-- C Run-Time Library, but may do a bit more work than
-- just directly calling one of the Library functions.
function is_regular_file (handle : int) return int;
-- Tests if given handle is for a regular file (result 1)
-- or for a non-regular file (pipe or device, result 0).
-----
-- Control of Text/Binary Mode --

```

```

-----
-- If text_translation_required is true, then the following
-- functions may be used to dynamically switch a file from
-- binary to text mode or vice versa. These functions have
-- no effect if text_translation_required is false (i.e. in
-- normal UNIX mode). Use fileno to get a stream handle.
procedure set_binary_mode (handle : int);
procedure set_text_mode (handle : int);
-----
-- Full Path Name support --
-----

procedure full_name (nam : chars; buffer : chars);
-- Given a NUL terminated string representing a file
-- name, returns in buffer a NUL terminated string
-- representing the full path name for the file name.
-- On systems where it is relevant the drive is also
-- part of the full path name. It is the responsibility
-- of the caller to pass an actual parameter for buffer
-- that is big enough for any full path name. Use
-- max_path_len given below as the size of buffer.
max_path_len : integer;
-- Maximum length of an allowable full path name on the
-- system, including a terminating NUL character.
end Interfaces.C_Streams;

```

8.14 Interfacing to C Streams

The packages in this section permit interfacing Ada files to C Stream operations.

```

with Interfaces.C_Streams;
package Ada.Sequential_IO.C_Streams is
  function C_Stream (F : File_Type)
    return Interfaces.C_Streams.FILES;
  procedure Open
    (File : in out File_Type;
     Mode : in File_Mode;
     C_Stream : in Interfaces.C_Streams.FILES;
     Form : in String := "");
end Ada.Sequential_IO.C_Streams;

with Interfaces.C_Streams;
package Ada.Direct_IO.C_Streams is
  function C_Stream (F : File_Type)
    return Interfaces.C_Streams.FILES;
  procedure Open
    (File : in out File_Type;
     Mode : in File_Mode;
     C_Stream : in Interfaces.C_Streams.FILES;
     Form : in String := "");
end Ada.Direct_IO.C_Streams;

with Interfaces.C_Streams;
package Ada.Text_IO.C_Streams is
  function C_Stream (F : File_Type)
    return Interfaces.C_Streams.FILES;
  procedure Open
    (File : in out File_Type;
     Mode : in File_Mode;
     C_Stream : in Interfaces.C_Streams.FILES;
     Form : in String := "");
end Ada.Text_IO.C_Streams;

with Interfaces.C_Streams;
package Ada.Wide_Text_IO.C_Streams is
  function C_Stream (F : File_Type)

```

```

        return Interfaces.C_Streams.FILES;
    procedure Open
      (File : in out File_Type;
       Mode : in File_Mode;
       C_Stream : in Interfaces.C_Streams.FILES;
       Form : in String := "");
end Ada.Wide_Text_IO.C_Streams;

with Interfaces.C_Streams;
package Ada.Wide_Wide_Text_IO.C_Streams is
  function C_Stream (F : File_Type)
    return Interfaces.C_Streams.FILES;
  procedure Open
    (File : in out File_Type;
     Mode : in File_Mode;
     C_Stream : in Interfaces.C_Streams.FILES;
     Form : in String := "");
end Ada.Wide_Wide_Text_IO.C_Streams;

with Interfaces.C_Streams;
package Ada.Stream_IO.C_Streams is
  function C_Stream (F : File_Type)
    return Interfaces.C_Streams.FILES;
  procedure Open
    (File : in out File_Type;
     Mode : in File_Mode;
     C_Stream : in Interfaces.C_Streams.FILES;
     Form : in String := "");
end Ada.Stream_IO.C_Streams;

```

In each of these six packages, the `C_Stream` function obtains the `FILE` pointer from a currently opened Ada file. It is then possible to use the `Interfaces.C_Streams` package to operate on this stream, or the stream can be passed to a C program which can operate on it directly. Of course the program is responsible for ensuring that only appropriate sequences of operations are executed.

One particular use of relevance to an Ada program is that the `setvbuf` function can be used to control the buffering of the stream used by an Ada file. In the absence of such a call the standard default buffering is used.

The `Open` procedures in these packages open a file giving an existing C Stream instead of a file name. Typically this stream is imported from a C program, allowing an Ada file to operate on an existing C file.

9 The GNAT Library

The GNAT library contains a number of general and special purpose packages. It represents functionality that the GNAT developers have found useful, and which is made available to GNAT users. The packages described here are fully supported, and upwards compatibility will be maintained in future releases, so you can use these facilities with the confidence that the same functionality will be available in future releases.

The chapter here simply gives a brief summary of the facilities available. The full documentation is found in the spec file for the package. The full sources of these library packages, including both spec and body, are provided with all GNAT releases. For example, to find out the full specifications of the SPITBOL pattern matching capability, including a full tutorial and extensive examples, look in the ‘g-spipat.ads’ file in the library.

For each entry here, the package name (as it would appear in a `with` clause) is given, followed by the name of the corresponding spec file in parentheses. The packages are children in four hierarchies, `Ada`, `Interfaces`, `System`, and `GNAT`, the latter being a GNAT-specific hierarchy.

Note that an application program should only use packages in one of these four hierarchies if the package is defined in the Ada Reference Manual, or is listed in this section of the GNAT Programmers Reference Manual. All other units should be considered internal implementation units and should not be directly `with`’ed by application code. The use of a `with` statement that references one of these internal implementation units makes an application potentially dependent on changes in versions of GNAT, and will generate a warning message.

9.1 `Ada.Characters.Latin_9` (‘a-chlat9.ads’)

This child of `Ada.Characters` provides a set of definitions corresponding to those in the RM-defined package `Ada.Characters.Latin_1` but with the few modifications required for `Latin_9`. The provision of such a package is specifically authorized by the Ada Reference Manual (RM A.3.3(27)).

9.2 `Ada.Characters.Wide_Latin_1` (‘a-cwila1.ads’)

This child of `Ada.Characters` provides a set of definitions corresponding to those in the RM-defined package `Ada.Characters.Latin_1` but with the types of the constants being `Wide_Character` instead of `Character`. The provision of such a package is specifically authorized by the Ada Reference Manual (RM A.3.3(27)).

9.3 `Ada.Characters.Wide_Latin_9` (‘a-cwila1.ads’)

This child of `Ada.Characters` provides a set of definitions corresponding to those in the GNAT defined package `Ada.Characters.Latin_9` but with the types of the constants being `Wide_Character` instead of `Character`. The provision of such a package is specifically authorized by the Ada Reference Manual (RM A.3.3(27)).

9.4 `Ada.Characters.Wide_Wide_Latin_1` (‘a-chzla1.ads’)

This child of `Ada.Characters` provides a set of definitions corresponding to those in the RM-defined package `Ada.Characters.Latin_1` but with the types of the constants being `Wide_Wide_Character` instead of `Character`. The provision of such a package is specifically authorized by the Ada Reference Manual (RM A.3.3(27)).

9.5 Ada.Characters.Wide_Wide_Latin_9 ('a-chzla9.ads')

This child of `Ada.Characters` provides a set of definitions corresponding to those in the GNAT defined package `Ada.Characters.Latin_9` but with the types of the constants being `Wide_Wide_Character` instead of `Character`. The provision of such a package is specifically authorized by the Ada Reference Manual (RM A.3.3(27)).

9.6 Ada.Command_Line.Environment ('a-colien.ads')

This child of `Ada.Command_Line` provides a mechanism for obtaining environment values on systems where this concept makes sense.

9.7 Ada.Command_Line.Remove ('a-colire.ads')

This child of `Ada.Command_Line` provides a mechanism for logically removing arguments from the argument list. Once removed, an argument is not visible to further calls on the subprograms in `Ada.Command_Line` will not see the removed argument.

9.8 Ada.Command_Line.Response_File ('a-clrefi.ads')

This child of `Ada.Command_Line` provides a mechanism facilities for getting command line arguments from a text file, called a "response file". Using a response file allow passing a set of arguments to an executable longer than the maximum allowed by the system on the command line.

9.9 Ada.Direct_IO.C_Streams ('a-diocst.ads')

This package provides subprograms that allow interfacing between C streams and `Direct_IO`. The stream identifier can be extracted from a file opened on the Ada side, and an Ada file can be constructed from a stream opened on the C side.

9.10 Ada.Exceptions.Is_Null_Occurrence ('a-einuoc.ads')

This child subprogram provides a way of testing for the null exception occurrence (`Null_Occurrence`) without raising an exception.

9.11 Ada.Exceptions.Last_Chance_Handler ('a-elchha.ads')

This child subprogram is used for handling otherwise unhandled exceptions (hence the name last chance), and perform clean ups before terminating the program. Note that this subprogram never returns.

9.12 Ada.Exceptions.Traceback ('a-exctra.ads')

This child package provides the subprogram (`Tracebacks`) to give a traceback array of addresses based on an exception occurrence.

9.13 Ada.Sequential_IO.C_Streams ('a-siocst.ads')

This package provides subprograms that allow interfacing between C streams and `Sequential_IO`. The stream identifier can be extracted from a file opened on the Ada side, and an Ada file can be constructed from a stream opened on the C side.

9.14 Ada.Streams.Stream_IO.C_Streams ('a-ssicst.ads')

This package provides subprograms that allow interfacing between C streams and `Stream_IO`. The stream identifier can be extracted from a file opened on the Ada side, and an Ada file can be constructed from a stream opened on the C side.

9.15 Ada.Strings.Unbounded.Text_IO ('a-suteio.ads')

This package provides subprograms for `Text_IO` for unbounded strings, avoiding the necessity for an intermediate operation with ordinary strings.

9.16 Ada.Strings.Wide_Unbounded.Wide_Text_IO ('a-swuwti.ads')

This package provides subprograms for `Text_IO` for unbounded wide strings, avoiding the necessity for an intermediate operation with ordinary wide strings.

9.17 Ada.Strings.Wide_Wide_Unbounded.Wide_Wide_Text_IO ('a-szuzti.ads')

This package provides subprograms for `Text_IO` for unbounded wide wide strings, avoiding the necessity for an intermediate operation with ordinary wide wide strings.

9.18 Ada.Text_IO.C_Streams ('a-tiocst.ads')

This package provides subprograms that allow interfacing between C streams and `Text_IO`. The stream identifier can be extracted from a file opened on the Ada side, and an Ada file can be constructed from a stream opened on the C side.

9.19 Ada.Text_IO.Reset_Standard_Files ('a-tirsfi.ads')

This procedure is used to reset the status of the standard files used by `Ada.Text_IO`. This is useful in a situation (such as a restart in an embedded application) where the status of the files may change during execution (for example a standard input file may be redefined to be interactive).

9.20 Ada.Wide_Characters.Unicode ('a-wichun.ads')

This package provides subprograms that allow categorization of `Wide_Character` values according to Unicode categories.

9.21 Ada.Wide_Text_IO.C_Streams ('a-wtcstr.ads')

This package provides subprograms that allow interfacing between C streams and `Wide_Text_IO`. The stream identifier can be extracted from a file opened on the Ada side, and an Ada file can be constructed from a stream opened on the C side.

9.22 Ada.Wide_Text_IO.Reset_Standard_Files ('a-wrstfi.ads')

This procedure is used to reset the status of the standard files used by `Ada.Wide_Text_IO`. This is useful in a situation (such as a restart in an embedded application) where the status of the files may change during execution (for example a standard input file may be redefined to be interactive).

9.23 Ada.Wide_Wide_Characters.Unicode ('a-zchuni.ads')

This package provides subprograms that allow categorization of `Wide_Wide_Character` values according to Unicode categories.

9.24 Ada.Wide_Wide_Text_IO.C_Streams ('a-ztcstr.ads')

This package provides subprograms that allow interfacing between C streams and `Wide_Wide_Text_IO`. The stream identifier can be extracted from a file opened on the Ada side, and an Ada file can be constructed from a stream opened on the C side.

9.25 Ada.Wide_Wide_Text_IO.Reset_Standard_Files ('a-zrstfi.ads')

This procedure is used to reset the status of the standard files used by `Ada.Wide_Wide_Text_IO`. This is useful in a situation (such as a restart in an embedded application) where the status of the files may change during execution (for example a standard input file may be redefined to be interactive).

9.26 GNAT.Altivec ('g-active.ads')

This is the root package of the GNAT Altivec binding. It provides definitions of constants and types common to all the versions of the binding.

9.27 GNAT.Altivec.Conversions ('g-altcon.ads')

This package provides the Vector/View conversion routines.

9.28 GNAT.Altivec.Vector_Operations ('g-alveop.ads')

This package exposes the Ada interface to the Altivec operations on vector objects. A soft emulation is included by default in the GNAT library. The hard binding is provided as a separate package. This unit is common to both bindings.

9.29 GNAT.Altivec.Vector_Types ('g-alvety.ads')

This package exposes the various vector types part of the Ada binding to Altivec facilities.

9.30 GNAT.Altivec.Vector_Views ('g-alvevi.ads')

This package provides public 'View' data types from/to which private vector representations can be converted via `GNAT.Altivec.Conversions`. This allows convenient access to individual vector elements and provides a simple way to initialize vector objects.

9.31 GNAT.Array_Split ('g-arrspl.ads')

Useful array-manipulation routines: given a set of separators, split an array wherever the separators appear, and provide direct access to the resulting slices.

9.32 GNAT.AWK ('g-awk.ads')

Provides AWK-like parsing functions, with an easy interface for parsing one or more files containing formatted data. The file is viewed as a database where each record is a line and a field is a data element in this line.

9.33 GNAT.Bounded_Buffers ('g-boubuf.ads')

Provides a concurrent generic bounded buffer abstraction. Instances are useful directly or as parts of the implementations of other abstractions, such as mailboxes.

9.34 GNAT.Bounded-Mailboxes ('g-boumai.ads')

Provides a thread-safe asynchronous intertask mailbox communication facility.

9.35 GNAT.Bubble_Sort ('g-bubsort.ads')

Provides a general implementation of bubble sort usable for sorting arbitrary data items. Exchange and comparison procedures are provided by passing access-to-procedure values.

9.36 GNAT.Bubble_Sort_A ('g-busora.ads')

Provides a general implementation of bubble sort usable for sorting arbitrary data items. Move and comparison procedures are provided by passing access-to-procedure values. This is an older version, retained for compatibility. Usually GNAT.Bubble_Sort will be preferable.

9.37 GNAT.Bubble_Sort_G ('g-busorg.ads')

Similar to Bubble_Sort_A except that the move and sorting procedures are provided as generic parameters, this improves efficiency, especially if the procedures can be inlined, at the expense of duplicating code for multiple instantiations.

9.38 GNAT.Byte_Order_Mark ('g-byorma.ads')

Provides a routine which given a string, reads the start of the string to see whether it is one of the standard byte order marks (BOM's) which signal the encoding of the string. The routine includes detection of special XML sequences for various UCS input formats.

9.39 GNAT.Byte_Swapping ('g-bytswa.ads')

General routines for swapping the bytes in 2-, 4-, and 8-byte quantities. Machine-specific implementations are available in some cases.

9.40 GNAT.Calendar ('g-calend.ads')

Extends the facilities provided by Ada.Calendar to include handling of days of the week, an extended Split and Time_Of capability. Also provides conversion of Ada.Calendar.Time values to and from the C timeval format.

9.41 GNAT.Calendar.Time_IO ('g-catio.ads')

9.42 GNAT.CRC32 ('g-crc32.ads')

This package implements the CRC-32 algorithm. For a full description of this algorithm see "Computation of Cyclic Redundancy Checks via Table Look-Up", *Communications of the ACM*, Vol. 31 No. 8, pp. 1008-1013, Aug. 1988. Sarwate, D.V.

9.43 GNAT.Case_Util ('g-casuti.ads')

A set of simple routines for handling upper and lower casing of strings without the overhead of the full casing tables in Ada.Characters.Handling.

9.44 GNAT.CGI ('g-cgi.ads')

This is a package for interfacing a GNAT program with a Web server via the Common Gateway Interface (CGI). Basically this package parses the CGI parameters, which are a set of key/value pairs sent by the Web server. It builds a table whose index is the key and provides some services to deal with this table.

9.45 GNAT.CGI.Cookie ('g-cgicoo.ads')

This is a package to interface a GNAT program with a Web server via the Common Gateway Interface (CGI). It exports services to deal with Web cookies (piece of information kept in the Web client software).

9.46 GNAT.CGI.Debug ('g-cgideb.ads')

This is a package to help debugging CGI (Common Gateway Interface) programs written in Ada.

9.47 GNAT.Command_Line ('g-comlin.ads')

Provides a high level interface to `Ada.Command_Line` facilities, including the ability to scan for named switches with optional parameters and expand file names using wild card notations.

9.48 GNAT.Compiler_Version ('g-comver.ads')

Provides a routine for obtaining the version of the compiler used to compile the program. More accurately this is the version of the binder used to bind the program (this will normally be the same as the version of the compiler if a consistent tool set is used to compile all units of a partition).

9.49 GNAT.Ctrl_C ('g-ctrl_c.ads')

Provides a simple interface to handle Ctrl-C keyboard events.

9.50 GNAT.Current_Exception ('g-curexc.ads')

Provides access to information on the current exception that has been raised without the need for using the Ada 95 / Ada 2005 exception choice parameter specification syntax. This is particularly useful in simulating typical facilities for obtaining information about exceptions provided by Ada 83 compilers.

9.51 GNAT.Debug_Pools ('g-debpoo.ads')

Provide a debugging storage pools that helps tracking memory corruption problems. See [Section "The GNAT Debug Pool Facility" in *GNAT User's Guide*](#).

9.52 GNAT.Debug_Utility ('g-debuti.ads')

Provides a few useful utilities for debugging purposes, including conversion to and from string images of address values. Supports both C and Ada formats for hexadecimal literals.

9.53 GNAT.Decode_String ('g-decstr.ads')

A generic package providing routines for decoding wide character and wide wide character strings encoded as sequences of 8-bit characters using a specified encoding method. Includes validation routines, and also routines for stepping to next or previous encoded character in an encoded string. Useful in conjunction with Unicode character coding. Note there is a preinstantiation for UTF-8. See next entry.

9.54 GNAT.Decode_UTF8_String ('g-deutst.ads')

A preinstantiation of `GNAT.Decode_Strings` for UTF-8 encoding.

9.55 GNAT.Directory_Operations ('g-dirope.ads')

Provides a set of routines for manipulating directories, including changing the current directory, making new directories, and scanning the files in a directory.

9.56 GNAT.Directory_Operations.Iteration ('g-diopit.ads')

A child unit of GNAT.Directory_Operations providing additional operations for iterating through directories.

9.57 GNAT.Dynamic_HTables ('g-dynhta.ads')

A generic implementation of hash tables that can be used to hash arbitrary data. Provided in two forms, a simple form with built in hash functions, and a more complex form in which the hash function is supplied.

This package provides a facility similar to that of GNAT.HTable, except that this package declares a type that can be used to define dynamic instances of the hash table, while an instantiation of GNAT.HTable creates a single instance of the hash table.

9.58 GNAT.Dynamic_Tables ('g-dyntab.ads')

A generic package providing a single dimension array abstraction where the length of the array can be dynamically modified.

This package provides a facility similar to that of GNAT.Table, except that this package declares a type that can be used to define dynamic instances of the table, while an instantiation of GNAT.Table creates a single instance of the table type.

9.59 GNAT.Encode_String ('g-encstr.ads')

A generic package providing routines for encoding wide character and wide wide character strings as sequences of 8-bit characters using a specified encoding method. Useful in conjunction with Unicode character coding. Note there is a preinstantiation for UTF-8. See next entry.

9.60 GNAT.Encode_UTF8_String ('g-enutst.ads')

A preinstantiation of GNAT.Encode_Strings for UTF-8 encoding.

9.61 GNAT.Exception_Actions ('g-excact.ads')

Provides callbacks when an exception is raised. Callbacks can be registered for specific exceptions, or when any exception is raised. This can be used for instance to force a core dump to ease debugging.

9.62 GNAT.Exception_Traces ('g-exctra.ads')

Provides an interface allowing to control automatic output upon exception occurrences.

9.63 GNAT.Exceptions ('g-expect.ads')

Normally it is not possible to raise an exception with a message from a subprogram in a pure package, since the necessary types and subprograms are in Ada.Exceptions which is not a pure unit. GNAT.Exceptions provides a facility for getting around this limitation for a few predefined exceptions, and for example allow raising Constraint_Error with a message from a pure subprogram.

9.64 GNAT.Expect ('g-expect.ads')

Provides a set of subprograms similar to what is available with the standard Tcl Expect tool. It allows you to easily spawn and communicate with an external process. You can send commands or inputs to the process, and compare the output with some expected regular expression. Currently GNAT.Expect is implemented on all native GNAT ports except for OpenVMS. It is not implemented for cross ports, and in particular is not implemented for VxWorks or LynxOS.

9.65 GNAT.Float_Control ('g-flocon.ads')

Provides an interface for resetting the floating-point processor into the mode required for correct semantic operation in Ada. Some third party library calls may cause this mode to be modified, and the Reset procedure in this package can be used to reestablish the required mode.

9.66 GNAT.Heap_Sort ('g-heasor.ads')

Provides a general implementation of heap sort usable for sorting arbitrary data items. Exchange and comparison procedures are provided by passing access-to-procedure values. The algorithm used is a modified heap sort that performs approximately $N \cdot \log(N)$ comparisons in the worst case.

9.67 GNAT.Heap_Sort_A ('g-hesora.ads')

Provides a general implementation of heap sort usable for sorting arbitrary data items. Move and comparison procedures are provided by passing access-to-procedure values. The algorithm used is a modified heap sort that performs approximately $N \cdot \log(N)$ comparisons in the worst case. This differs from GNAT.Heap_Sort in having a less convenient interface, but may be slightly more efficient.

9.68 GNAT.Heap_Sort_G ('g-hesorg.ads')

Similar to Heap_Sort_A except that the move and sorting procedures are provided as generic parameters, this improves efficiency, especially if the procedures can be inlined, at the expense of duplicating code for multiple instantiations.

9.69 GNAT.HTable ('g-htable.ads')

A generic implementation of hash tables that can be used to hash arbitrary data. Provides two approaches, one a simple static approach, and the other allowing arbitrary dynamic hash tables.

9.70 GNAT.IO ('g-io.ads')

A simple preelaborable input-output package that provides a subset of simple Text_IO functions for reading characters and strings from Standard_Input, and writing characters, strings and integers to either Standard_Output or Standard_Error.

9.71 GNAT.IO_Aux ('g-io_aux.ads')

Provides some auxiliary functions for use with Text_IO, including a test for whether a file exists, and functions for reading a line of text.

9.72 GNAT.Lock_Files ('g-locfil.ads')

Provides a general interface for using files as locks. Can be used for providing program level synchronization.

9.73 GNAT.MBBS_Discrete_Random ('g-mbdira.ads')

The original implementation of `Ada.Numerics.Discrete_Random`. Uses a modified version of the Blum-Blum-Shub generator.

9.74 GNAT.MBBS_Float_Random ('g-mbflra.ads')

The original implementation of `Ada.Numerics.Float_Random`. Uses a modified version of the Blum-Blum-Shub generator.

9.75 GNAT.MD5 ('g-md5.ads')

Implements the MD5 Message-Digest Algorithm as described in RFC 1321.

9.76 GNAT.Memory_Dump ('g-memdum.ads')

Provides a convenient routine for dumping raw memory to either the standard output or standard error files. Uses `GNAT.IO` for actual output.

9.77 GNAT.Most_Recent_Exception ('g-moreex.ads')

Provides access to the most recently raised exception. Can be used for various logging purposes, including duplicating functionality of some Ada 83 implementation dependent extensions.

9.78 GNAT.OS_Lib ('g-os_lib.ads')

Provides a range of target independent operating system interface functions, including time/date management, file operations, subprocess management, including a portable spawn procedure, and access to environment variables and error return codes.

9.79 GNAT.Perfect_Hash_Generators ('g-pehage.ads')

Provides a generator of static minimal perfect hash functions. No collisions occur and each item can be retrieved from the table in one probe (perfect property). The hash table size corresponds to the exact size of the key set and no larger (minimal property). The key set has to be known in advance (static property). The hash functions are also order preserving. If `w2` is inserted after `w1` in the generator, their hashcode are in the same order. These hashing functions are very convenient for use with realtime applications.

9.80 GNAT.Random_Numbers ('g-rannum.ads')

Provides random number capabilities which extend those available in the standard Ada library and are more convenient to use.

9.81 GNAT.Regexp ('g-regexp.ads')

A simple implementation of regular expressions, using a subset of regular expression syntax copied from familiar Unix style utilities. This is the simplest of the three pattern matching packages provided, and is particularly suitable for "file globbing" applications.

9.82 GNAT.Registry ('g-regist.ads')

This is a high level binding to the Windows registry. It is possible to do simple things like reading a key value, creating a new key. For full registry API, but at a lower level of abstraction, refer to the `Win32.Winreg` package provided with the `Win32Ada` binding.

9.83 GNAT.Regpat ('g-regpat.ads')

A complete implementation of Unix-style regular expression matching, copied from the original V7 style regular expression library written in C by Henry Spencer (and binary compatible with this C library).

9.84 GNAT.Secondary_Stack_Info ('g-sestin.ads')

Provide the capability to query the high water mark of the current task's secondary stack.

9.85 GNAT.Semaphores ('g-semaph.ads')

Provides classic counting and binary semaphores using protected types.

9.86 GNAT.Serial_Communications ('g-sercom.ads')

Provides a simple interface to send and receive data over a serial port. This is only supported on GNU/Linux and Windows.

9.87 GNAT.SHA1 ('g-sha1.ads')

Implements the SHA-1 Secure Hash Algorithm as described in FIPS PUB 180-3 and RFC 3174.

9.88 GNAT.SHA224 ('g-sha224.ads')

Implements the SHA-224 Secure Hash Algorithm as described in FIPS PUB 180-3.

9.89 GNAT.SHA256 ('g-sha256.ads')

Implements the SHA-256 Secure Hash Algorithm as described in FIPS PUB 180-3.

9.90 GNAT.SHA384 ('g-sha384.ads')

Implements the SHA-384 Secure Hash Algorithm as described in FIPS PUB 180-3.

9.91 GNAT.SHA512 ('g-sha512.ads')

Implements the SHA-512 Secure Hash Algorithm as described in FIPS PUB 180-3.

9.92 GNAT.Signals ('g-signal.ads')

Provides the ability to manipulate the blocked status of signals on supported targets.

9.93 GNAT.Sockets ('g-socket.ads')

A high level and portable interface to develop sockets based applications. This package is based on the sockets thin binding found in GNAT.Sockets.Thin. Currently GNAT.Sockets is implemented on all native GNAT ports except for OpenVMS. It is not implemented for the LynxOS cross port.

9.94 GNAT.Source_Info ('g-souinf.ads')

Provides subprograms that give access to source code information known at compile time, such as the current file name and line number.

9.95 GNAT.Spelling_Checker ('g-speche.ads')

Provides a function for determining whether one string is a plausible near misspelling of another string.

9.96 GNAT.Spelling_Checker_Generic ('g-spchge.ads')

Provides a generic function that can be instantiated with a string type for determining whether one string is a plausible near misspelling of another string.

9.97 GNAT.Spitbol.Patterns ('g-spiPAT.ads')

A complete implementation of SNOBOL4 style pattern matching. This is the most elaborate of the pattern matching packages provided. It fully duplicates the SNOBOL4 dynamic pattern construction and matching capabilities, using the efficient algorithm developed by Robert Dewar for the SPITBOL system.

9.98 GNAT.Spitbol ('g-spitbo.ads')

The top level package of the collection of SPITBOL-style functionality, this package provides basic SNOBOL4 string manipulation functions, such as Pad, Reverse, Trim, Substr capability, as well as a generic table function useful for constructing arbitrary mappings from strings in the style of the SNOBOL4 TABLE function.

9.99 GNAT.Spitbol.Table_Boolean ('g-sptabo.ads')

A library level of instantiation of GNAT.Spitbol.Patterns.Table for type `Standard.Boolean`, giving an implementation of sets of string values.

9.100 GNAT.Spitbol.Table_Integer ('g-sptain.ads')

A library level of instantiation of GNAT.Spitbol.Patterns.Table for type `Standard.Integer`, giving an implementation of maps from string to integer values.

9.101 GNAT.Spitbol.Table_VString ('g-sptavs.ads')

A library level of instantiation of GNAT.Spitbol.Patterns.Table for a variable length string type, giving an implementation of general maps from strings to strings.

9.102 GNAT.SSE ('g-sse.ads')

Root of a set of units aimed at offering Ada bindings to a subset of the Intel(r) Streaming SIMD Extensions with GNAT on the x86 family of targets. It exposes vector component types together with a general introduction to the binding contents and use.

9.103 GNAT.SSE.Vector_Types ('g-ssvety.ads')

SSE vector types for use with SSE related intrinsics.

9.104 GNAT.Strings ('g-string.ads')

Common String access types and related subprograms. Basically it defines a string access and an array of string access types.

9.105 GNAT.String_Split ('g-strspl.ads')

Useful string manipulation routines: given a set of separators, split a string wherever the separators appear, and provide direct access to the resulting slices. This package is instantiated from GNAT.Array_Split.

9.106 GNAT.Table ('g-table.ads')

A generic package providing a single dimension array abstraction where the length of the array can be dynamically modified.

This package provides a facility similar to that of `GNAT.Dynamic_Tables`, except that this package declares a single instance of the table type, while an instantiation of `GNAT.Dynamic_Tables` creates a type that can be used to define dynamic instances of the table.

9.107 GNAT.Task_Lock ('g-tasloc.ads')

A very simple facility for locking and unlocking sections of code using a single global task lock. Appropriate for use in situations where contention between tasks is very rarely expected.

9.108 GNAT.Time_Stamp ('g-timsta.ads')

Provides a simple function that returns a string YYYY-MM-DD HH:MM:SS.SS that represents the current date and time in ISO 8601 format. This is a very simple routine with minimal code and there are no dependencies on any other unit.

9.109 GNAT.Threads ('g-thread.ads')

Provides facilities for dealing with foreign threads which need to be known by the GNAT run-time system. Consult the documentation of this package for further details if your program has threads that are created by a non-Ada environment which then accesses Ada code.

9.110 GNAT.Traceback ('g-traceb.ads')

Provides a facility for obtaining non-symbolic traceback information, useful in various debugging situations.

9.111 GNAT.Traceback.Symbolic ('g-trasym.ads')

9.112 GNAT.UTF_32 ('g-table.ads')

This is a package intended to be used in conjunction with the `Wide_Character` type in Ada 95 and the `Wide_Wide_Character` type in Ada 2005 (available in GNAT in Ada 2005 mode). This package contains Unicode categorization routines, as well as lexical categorization routines corresponding to the Ada 2005 lexical rules for identifiers and strings, and also a lower case to upper case fold routine corresponding to the Ada 2005 rules for identifier equivalence.

9.113 GNAT.Wide_Spelling_Checker ('g-u3spch.ads')

Provides a function for determining whether one wide wide string is a plausible near misspelling of another wide wide string, where the strings are represented using the `UTF_32_String` type defined in `System.Wch_Cnv`.

9.114 GNAT.Wide_Spelling_Checker ('g-wispch.ads')

Provides a function for determining whether one wide string is a plausible near misspelling of another wide string.

9.115 GNAT.Wide_String_Split ('g-wistsp.ads')

Useful wide string manipulation routines: given a set of separators, split a wide string whenever the separators appear, and provide direct access to the resulting slices. This package is instantiated from `GNAT.Array_Split`.

9.116 GNAT.Wide_Wide_Spelling_Checker ('g-zspche.ads')

Provides a function for determining whether one wide wide string is a plausible near misspelling of another wide wide string.

9.117 GNAT.Wide_Wide_String_Split ('g-zistsp.ads')

Useful wide wide string manipulation routines: given a set of separators, split a wide wide string wherever the separators appear, and provide direct access to the resulting slices. This package is instantiated from GNAT.Array_Split.

9.118 Interfaces.C.Extensions ('i-cexten.ads')

This package contains additional C-related definitions, intended for use with either manually or automatically generated bindings to C libraries.

9.119 Interfaces.C.Streams ('i-cstrea.ads')

This package is a binding for the most commonly used operations on C streams.

9.120 Interfaces.CPP ('i-cpp.ads')

This package provides facilities for use in interfacing to C++. It is primarily intended to be used in connection with automated tools for the generation of C++ interfaces.

9.121 Interfaces.Packed_Decimal ('i-pacdec.ads')

This package provides a set of routines for conversions to and from a packed decimal format compatible with that used on IBM mainframes.

9.122 Interfaces.VxWorks ('i-vxwork.ads')

This package provides a limited binding to the VxWorks API. In particular, it interfaces with the VxWorks hardware interrupt facilities.

9.123 Interfaces.VxWorks.IO ('i-vxwoio.ads')

This package provides a binding to the ioctl (IO/Control) function of VxWorks, defining a set of option values and function codes. A particular use of this package is to enable the use of Get_Immediate under VxWorks.

9.124 System.Address_Image ('s-addima.ads')

This function provides a useful debugging function that gives an (implementation dependent) string which identifies an address.

9.125 System.Assertions ('s-assert.ads')

This package provides the declaration of the exception raised by an run-time assertion failure, as well as the routine that is used internally to raise this assertion.

9.126 System.Memory ('s-memory.ads')

This package provides the interface to the low level routines used by the generated code for allocation and freeing storage for the default storage pool (analogous to the C routines malloc and free. It also provides a reallocation interface analogous to the C routine realloc. The body of this unit may be modified to provide alternative allocation mechanisms for the default pool,

and in addition, direct calls to this unit may be made for low level allocation uses (for example see the body of `GNAT.Tables`).

9.127 `System.Partition_Interface` ('s-parint.ads')

This package provides facilities for partition interfacing. It is used primarily in a distribution context when using Annex E with `GLADE`.

9.128 `System.Pool_Global` ('s-pooglo.ads')

This package provides a storage pool that is equivalent to the default storage pool used for access types for which no pool is specifically declared. It uses `malloc/free` to allocate/free and does not attempt to do any automatic reclamation.

9.129 `System.Pool_Local` ('s-pooloc.ads')

This package provides a storage pool that is intended for use with locally defined access types. It uses `malloc/free` for allocate/free, and maintains a list of allocated blocks, so that all storage allocated for the pool can be freed automatically when the pool is finalized.

9.130 `System.Restrictions` ('s-restri.ads')

This package provides facilities for accessing at run time the status of restrictions specified at compile time for the partition. Information is available both with regard to actual restrictions specified, and with regard to compiler determined information on which restrictions are violated by one or more packages in the partition.

9.131 `System.Rident` ('s-rident.ads')

This package provides definitions of the restrictions identifiers supported by GNAT, and also the format of the restrictions provided in package `System.Restrictions`. It is not normally necessary to with this generic package since the necessary instantiation is included in package `System.Restrictions`.

9.132 `System.Strings.Stream_Ops` ('s-ststop.ads')

This package provides a set of stream subprograms for standard string types. It is intended primarily to support implicit use of such subprograms when stream attributes are applied to string types, but the subprograms in this package can be used directly by application programs.

9.133 `System.Task_Info` ('s-tasinf.ads')

This package provides target dependent functionality that is used to support the `Task_Info` pragma

9.134 `System.Wch_Cnv` ('s-wchcnv.ads')

This package provides routines for converting between wide and wide wide characters and a representation as a value of type `Standard.String`, using a specified wide character encoding method. It uses definitions in package `System.Wch_Con`.

9.135 `System.Wch_Con` ('s-wchcon.ads')

This package provides definitions and descriptions of the various methods used for encoding wide characters in ordinary strings. These definitions are used by the package `System.Wch_Cnv`.

10 Interfacing to Other Languages

The facilities in annex B of the Ada Reference Manual are fully implemented in GNAT, and in addition, a full interface to C++ is provided.

10.1 Interfacing to C

Interfacing to C with GNAT can use one of two approaches:

- The types in the package `Interfaces.C` may be used.
- Standard Ada types may be used directly. This may be less portable to other compilers, but will work on all GNAT compilers, which guarantee correspondence between the C and Ada types.

Pragma `Convention C` may be applied to Ada types, but mostly has no effect, since this is the default. The following table shows the correspondence between Ada scalar types and the corresponding C types.

`Integer` `int`

`Short_Integer`
 `short`

`Short_Short_Integer`
 `signed char`

`Long_Integer`
 `long`

`Long_Long_Integer`
 `long long`

`Short_Float`
 `float`

`Float` `float`

`Long_Float`
 `double`

`Long_Long_Float`

This is the longest floating-point type supported by the hardware.

Additionally, there are the following general correspondences between Ada and C types:

- Ada enumeration types map to C enumeration types directly if pragma `Convention C` is specified, which causes them to have `int` length. Without pragma `Convention C`, Ada enumeration types map to 8, 16, or 32 bits (i.e. C types `signed char`, `short`, `int`, respectively) depending on the number of values passed. This is the only case in which pragma `Convention C` affects the representation of an Ada type.
- Ada access types map to C pointers, except for the case of pointers to unconstrained types in Ada, which have no direct C equivalent.
- Ada arrays map directly to C arrays.
- Ada records map directly to C structures.
- Packed Ada records map to C structures where all members are bit fields of the length corresponding to the `type'Size` value in Ada.

10.2 Interfacing to C++

The interface to C++ makes use of the following pragmas, which are primarily intended to be constructed automatically using a binding generator tool, although it is possible to construct them by hand. No suitable binding generator tool is supplied with GNAT though.

Using these pragmas it is possible to achieve complete inter-operability between Ada tagged types and C++ class definitions. See [Chapter 1 \[Implementation Defined Pragmas\]](#), page 3, for more details.

`pragma CPP_Class ([Entity =>] LOCAL_NAME)`

The argument denotes an entity in the current declarative region that is declared as a tagged or untagged record type. It indicates that the type corresponds to an externally declared C++ class type, and is to be laid out the same way that C++ would lay out the type.

Note: Pragma `CPP_Class` is currently obsolete. It is supported for backward compatibility but its functionality is available using pragma `Import` with `Convention = CPP`.

`pragma CPP_Constructor ([Entity =>] LOCAL_NAME)`

This pragma identifies an imported function (imported in the usual way with pragma `Import`) as corresponding to a C++ constructor.

10.3 Interfacing to COBOL

Interfacing to COBOL is achieved as described in section B.4 of the Ada Reference Manual.

10.4 Interfacing to Fortran

Interfacing to Fortran is achieved as described in section B.5 of the Ada Reference Manual. The pragma `Convention Fortran`, applied to a multi-dimensional array causes the array to be stored in column-major order as required for convenient interface to Fortran.

10.5 Interfacing to non-GNAT Ada code

It is possible to specify the convention `Ada` in a pragma `Import` or pragma `Export`. However this refers to the calling conventions used by GNAT, which may or may not be similar enough to those used by some other Ada 83 / Ada 95 / Ada 2005 compiler to allow interoperation.

If arguments types are kept simple, and if the foreign compiler generally follows system calling conventions, then it may be possible to integrate files compiled by other Ada compilers, provided that the elaboration issues are adequately addressed (for example by eliminating the need for any load time elaboration).

In particular, GNAT running on VMS is designed to be highly compatible with the DEC Ada 83 compiler, so this is one case in which it is possible to import foreign units of this type, provided that the data items passed are restricted to simple scalar values or simple record types without variants, or simple array types with fixed bounds.

11 Specialized Needs Annexes

Ada 95 and Ada 2005 define a number of Specialized Needs Annexes, which are not required in all implementations. However, as described in this chapter, GNAT implements all of these annexes:

Systems Programming (Annex C)

The Systems Programming Annex is fully implemented.

Real-Time Systems (Annex D)

The Real-Time Systems Annex is fully implemented.

Distributed Systems (Annex E)

Stub generation is fully implemented in the GNAT compiler. In addition, a complete compatible PCS is available as part of the GLADE system, a separate product. When the two products are used in conjunction, this annex is fully implemented.

Information Systems (Annex F)

The Information Systems annex is fully implemented.

Numerics (Annex G)

The Numerics Annex is fully implemented.

Safety and Security / High-Integrity Systems (Annex H)

The Safety and Security Annex (termed the High-Integrity Systems Annex in Ada 2005) is fully implemented.

12 Implementation of Specific Ada Features

This chapter describes the GNAT implementation of several Ada language facilities.

12.1 Machine Code Insertions

Package `Machine_Code` provides machine code support as described in the Ada Reference Manual in two separate forms:

- Machine code statements, consisting of qualified expressions that fit the requirements of RM section 13.8.
- An intrinsic callable procedure, providing an alternative mechanism of including machine instructions in a subprogram.

The two features are similar, and both are closely related to the mechanism provided by the `asm` instruction in the GNU C compiler. Full understanding and use of the facilities in this package requires understanding the `asm` instruction, see [Section “Assembler Instructions with C Expression Operands” in *Using the GNU Compiler Collection \(GCC\)*](#).

Calls to the function `Asm` and the procedure `Asm` have identical semantic restrictions and effects as described below. Both are provided so that the procedure call can be used as a statement, and the function call can be used to form a code_statement.

The first example given in the GCC documentation is the C `asm` instruction:

```
asm ("fsinx %1 %0" : "=f" (result) : "f" (angle));
```

The equivalent can be written for GNAT as:

```
Asm ("fsinx %1 %0",
    My_Float'Asm_Output ("=f", result),
    My_Float'Asm_Input ("f", angle));
```

The first argument to `Asm` is the assembler template, and is identical to what is used in GNU C. This string must be a static expression. The second argument is the output operand list. It is either a single `Asm_Output` attribute reference, or a list of such references enclosed in parentheses (technically an array aggregate of such references).

The `Asm_Output` attribute denotes a function that takes two parameters. The first is a string, the second is the name of a variable of the type designated by the attribute prefix. The first (string) argument is required to be a static expression and designates the constraint for the parameter (e.g. what kind of register is required). The second argument is the variable to be updated with the result. The possible values for constraint are the same as those used in the RTL, and are dependent on the configuration file used to build the GCC back end. If there are no output operands, then this argument may either be omitted, or explicitly given as `No_Output_Operands`.

The second argument of `my_float'Asm_Output` functions as though it were an `out` parameter, which is a little curious, but all names have the form of expressions, so there is no syntactic irregularity, even though normally functions would not be permitted `out` parameters. The third argument is the list of input operands. It is either a single `Asm_Input` attribute reference, or a list of such references enclosed in parentheses (technically an array aggregate of such references).

The `Asm_Input` attribute denotes a function that takes two parameters. The first is a string, the second is an expression of the type designated by the prefix. The first (string) argument is required to be a static expression, and is the constraint for the parameter, (e.g. what kind of register is required). The second argument is the value to be used as the input argument. The possible values for the constant are the same as those used in the RTL, and are dependent on the configuration file used to built the GCC back end.

If there are no input operands, this argument may either be omitted, or explicitly given as `No_Input_Operands`. The fourth argument, not present in the above example, is a list of register

names, called the *clobber* argument. This argument, if given, must be a static string expression, and is a space or comma separated list of names of registers that must be considered destroyed as a result of the `Asm` call. If this argument is the null string (the default value), then the code generator assumes that no additional registers are destroyed.

The fifth argument, not present in the above example, called the *volatile* argument, is by default `False`. It can be set to the literal value `True` to indicate to the code generator that all optimizations with respect to the instruction specified should be suppressed, and that in particular, for an instruction that has outputs, the instruction will still be generated, even if none of the outputs are used. See [Section “Assembler Instructions with C Expression Operands” in *Using the GNU Compiler Collection \(GCC\)*](#), for the full description. Generally it is strongly advisable to use `Volatile` for any ASM statement that is missing either input or output operands, or when two or more ASM statements appear in sequence, to avoid unwanted optimizations. A warning is generated if this advice is not followed.

The `Asm` subprograms may be used in two ways. First the procedure forms can be used anywhere a procedure call would be valid, and correspond to what the RM calls “intrinsic” routines. Such calls can be used to intersperse machine instructions with other Ada statements. Second, the function forms, which return a dummy value of the limited private type `Asm_Insn`, can be used in code statements, and indeed this is the only context where such calls are allowed. Code statements appear as aggregates of the form:

```
Asm_Insn'(Asm (...));
Asm_Insn'(Asm_Volatile (...));
```

In accordance with RM rules, such code statements are allowed only within subprograms whose entire body consists of such statements. It is not permissible to intermix such statements with other Ada statements.

Typically the form using intrinsic procedure calls is more convenient and more flexible. The code statement form is provided to meet the RM suggestion that such a facility should be made available. The following is the exact syntax of the call to `Asm`. As usual, if named notation is used, the arguments may be given in arbitrary order, following the normal rules for use of positional and named arguments)

```
ASM_CALL ::= Asm (
    [Template =>] static_string_EXPRESSION
    [, [Outputs =>] OUTPUT_OPERAND_LIST ]
    [, [Inputs =>] INPUT_OPERAND_LIST ]
    [, [Clobber =>] static_string_EXPRESSION ]
    [, [Volatile =>] static_boolean_EXPRESSION] )
```

```
OUTPUT_OPERAND_LIST ::=
    [PREFIX.]No_Output_Operands
  | OUTPUT_OPERAND_ATTRIBUTE
  | (OUTPUT_OPERAND_ATTRIBUTE {, OUTPUT_OPERAND_ATTRIBUTE})
```

```
OUTPUT_OPERAND_ATTRIBUTE ::=
    SUBTYPE_MARK'Asm_Output (static_string_EXPRESSION, NAME)
```

```
INPUT_OPERAND_LIST ::=
    [PREFIX.]No_Input_Operands
  | INPUT_OPERAND_ATTRIBUTE
  | (INPUT_OPERAND_ATTRIBUTE {, INPUT_OPERAND_ATTRIBUTE})
```

```
INPUT_OPERAND_ATTRIBUTE ::=
    SUBTYPE_MARK'Asm_Input (static_string_EXPRESSION, EXPRESSION)
```

The identifiers `No_Input_Operands` and `No_Output_Operands` are declared in the package `Machine_Code` and must be referenced according to normal visibility rules. In particular if there is no `use` clause for this package, then appropriate package name qualification is required.

12.2 GNAT Implementation of Tasking

This chapter outlines the basic GNAT approach to tasking (in particular, a multi-layered library for portability) and discusses issues related to compliance with the Real-Time Systems Annex.

12.2.1 Mapping Ada Tasks onto the Underlying Kernel Threads

GNAT's run-time support comprises two layers:

- GNARL (GNAT Run-time Layer)
- GNULI (GNAT Low-level Library)

In GNAT, Ada's tasking services rely on a platform and OS independent layer known as GNARL. This code is responsible for implementing the correct semantics of Ada's task creation, rendezvous, protected operations etc.

GNARL decomposes Ada's tasking semantics into simpler lower level operations such as create a thread, set the priority of a thread, yield, create a lock, lock/unlock, etc. The spec for these low-level operations constitutes GNULI, the GNULI Interface. This interface is directly inspired from the POSIX real-time API.

If the underlying executive or OS implements the POSIX standard faithfully, the GNULI Interface maps as is to the services offered by the underlying kernel. Otherwise, some target dependent glue code maps the services offered by the underlying kernel to the semantics expected by GNARL.

Whatever the underlying OS (VxWorks, UNIX, Windows, etc.) the key point is that each Ada task is mapped on a thread in the underlying kernel. For example, in the case of VxWorks, one Ada task = one VxWorks task.

In addition Ada task priorities map onto the underlying thread priorities. Mapping Ada tasks onto the underlying kernel threads has several advantages:

- The underlying scheduler is used to schedule the Ada tasks. This makes Ada tasks as efficient as kernel threads from a scheduling standpoint.
- Interaction with code written in C containing threads is eased since at the lowest level Ada tasks and C threads map onto the same underlying kernel concept.
- When an Ada task is blocked during I/O the remaining Ada tasks are able to proceed.
- On multiprocessor systems Ada tasks can execute in parallel.

Some threads libraries offer a mechanism to fork a new process, with the child process duplicating the threads from the parent. GNAT does not support this functionality when the parent contains more than one task.

12.2.2 Ensuring Compliance with the Real-Time Annex

Although mapping Ada tasks onto the underlying threads has significant advantages, it does create some complications when it comes to respecting the scheduling semantics specified in the real-time annex (Annex D).

For instance the Annex D requirement for the `FIFO_Within_Priorities` scheduling policy states:

When the active priority of a ready task that is not running changes, or the setting of its base priority takes effect, the task is removed from the ready queue for its old active priority and is added at the tail of the ready queue for its new active priority, except in the case where the active priority is lowered due to the loss of inherited priority, in which case the task is added at the head of the ready queue for its new active priority.

While most kernels do put tasks at the end of the priority queue when a task changes its priority, (which respects the main `FIFO_Within_Priorities` requirement), almost none keep a thread at the beginning of its priority queue when its priority drops from the loss of inherited priority.

As a result most vendors have provided incomplete Annex D implementations.

The GNAT run-time, has a nice cooperative solution to this problem which ensures that accurate `FIFO_Within_Priorities` semantics are respected.

The principle is as follows. When an Ada task *T* is about to start running, it checks whether some other Ada task *R* with the same priority as *T* has been suspended due to the loss of priority inheritance. If this is the case, *T* yields and is placed at the end of its priority queue. When *R* arrives at the front of the queue it executes.

Note that this simple scheme preserves the relative order of the tasks that were ready to execute in the priority queue where *R* has been placed at the end.

12.3 GNAT Implementation of Shared Passive Packages

GNAT fully implements the pragma `Shared_Passive` for the purpose of designating shared passive packages. This allows the use of passive partitions in the context described in the Ada Reference Manual; i.e., for communication between separate partitions of a distributed application using the features in Annex E.

However, the implementation approach used by GNAT provides for more extensive usage as follows:

Communication between separate programs

This allows separate programs to access the data in passive partitions, using protected objects for synchronization where needed. The only requirement is that the two programs have a common shared file system. It is even possible for programs running on different machines with different architectures (e.g. different endianness) to communicate via the data in a passive partition.

Persistence between program runs

The data in a passive package can persist from one run of a program to another, so that a later program sees the final values stored by a previous run of the same program.

The implementation approach used is to store the data in files. A separate stream file is created for each object in the package, and an access to an object causes the corresponding file to be read or written.

The environment variable `SHARED_MEMORY_DIRECTORY` should be set to the directory to be used for these files. The files in this directory have names that correspond to their fully qualified names. For example, if we have the package

```
package X is
  pragma Shared_Passive (X);
  Y : Integer;
  Z : Float;
end X;
```

and the environment variable is set to `/stemp/`, then the files created will have the names:

```
/stemp/x.y
/stemp/x.z
```

These files are created when a value is initially written to the object, and the files are retained until manually deleted. This provides the persistence semantics. If no file exists, it means that no partition has assigned a value to the variable; in this case the initial value declared in the package will be used. This model ensures that there are no issues in synchronizing the

elaboration process, since elaboration of passive packages elaborates the initial values, but does not create the files.

The files are written using normal `Stream_IO` access. If you want to be able to communicate between programs or partitions running on different architectures, then you should use the XDR versions of the stream attribute routines, since these are architecture independent.

If active synchronization is required for access to the variables in the shared passive package, then as described in the Ada Reference Manual, the package may contain protected objects used for this purpose. In this case a lock file (whose name is ‘`___lock`’ (three underscores) is created in the shared memory directory. This is used to provide the required locking semantics for proper protected object synchronization.

As of January 2003, GNAT supports shared passive packages on all platforms except for OpenVMS.

12.4 Code Generation for Array Aggregates

Aggregates have a rich syntax and allow the user to specify the values of complex data structures by means of a single construct. As a result, the code generated for aggregates can be quite complex and involve loops, case statements and multiple assignments. In the simplest cases, however, the compiler will recognize aggregates whose components and constraints are fully static, and in those cases the compiler will generate little or no executable code. The following is an outline of the code that GNAT generates for various aggregate constructs. For further details, you will find it useful to examine the output produced by the `-gnatG` flag to see the expanded source that is input to the code generator. You may also want to examine the assembly code generated at various levels of optimization.

The code generated for aggregates depends on the context, the component values, and the type. In the context of an object declaration the code generated is generally simpler than in the case of an assignment. As a general rule, static component values and static subtypes also lead to simpler code.

12.4.1 Static constant aggregates with static bounds

For the declarations:

```
type One_Dim is array (1..10) of integer;
ar0 : constant One_Dim := (1, 2, 3, 4, 5, 6, 7, 8, 9, 0);
```

GNAT generates no executable code: the constant `ar0` is placed in static memory. The same is true for constant aggregates with named associations:

```
Cr1 : constant One_Dim := (4 => 16, 2 => 4, 3 => 9, 1 => 1, 5 .. 10 => 0);
Cr3 : constant One_Dim := (others => 7777);
```

The same is true for multidimensional constant arrays such as:

```
type two_dim is array (1..3, 1..3) of integer;
Unit : constant two_dim := ( (1,0,0), (0,1,0), (0,0,1));
```

The same is true for arrays of one-dimensional arrays: the following are static:

```
type ar1b is array (1..3) of boolean;
type ar_ar is array (1..3) of ar1b;
None : constant ar1b := (others => false);      -- fully static
None2 : constant ar_ar := (1..3 => None);      -- fully static
```

However, for multidimensional aggregates with named associations, GNAT will generate assignments and loops, even if all associations are static. The following two declarations generate a loop for the first dimension, and individual component assignments for the second dimension:

```
Zero1: constant two_dim := (1..3 => (1..3 => 0));
Zero2: constant two_dim := (others => (others => 0));
```

12.4.2 Constant aggregates with unconstrained nominal types

In such cases the aggregate itself establishes the subtype, so that associations with `others` cannot be used. GNAT determines the bounds for the actual subtype of the aggregate, and allocates the aggregate statically as well. No code is generated for the following:

```
type One_Unc is array (natural range <>) of integer;
Cr_Unc : constant One_Unc := (12,24,36);
```

12.4.3 Aggregates with static bounds

In all previous examples the aggregate was the initial (and immutable) value of a constant. If the aggregate initializes a variable, then code is generated for it as a combination of individual assignments and loops over the target object. The declarations

```
Cr_Var1 : One_Dim := (2, 5, 7, 11, 0, 0, 0, 0, 0, 0);
Cr_Var2 : One_Dim := (others > -1);
```

generate the equivalent of

```
Cr_Var1 (1) := 2;
Cr_Var1 (2) := 3;
Cr_Var1 (3) := 5;
Cr_Var1 (4) := 11;

for I in Cr_Var2'range loop
  Cr_Var2 (I) := -1;
end loop;
```

12.4.4 Aggregates with non-static bounds

If the bounds of the aggregate are not statically compatible with the bounds of the nominal subtype of the target, then constraint checks have to be generated on the bounds. For a multi-dimensional array, constraint checks may have to be applied to sub-arrays individually, if they do not have statically compatible subtypes.

12.4.5 Aggregates in assignment statements

In general, aggregate assignment requires the construction of a temporary, and a copy from the temporary to the target of the assignment. This is because it is not always possible to convert the assignment into a series of individual component assignments. For example, consider the simple case:

```
A := (A(2), A(1));
```

This cannot be converted into:

```
A(1) := A(2);
A(2) := A(1);
```

So the aggregate has to be built first in a separate location, and then copied into the target. GNAT recognizes simple cases where this intermediate step is not required, and the assignments can be performed in place, directly into the target. The following sufficient criteria are applied:

- The bounds of the aggregate are static, and the associations are static.
- The components of the aggregate are static constants, names of simple variables that are not renamings, or expressions not involving indexed components whose operands obey these rules.

If any of these conditions are violated, the aggregate will be built in a temporary (created either by the front-end or the code generator) and then that temporary will be copied onto the target.

12.5 The Size of Discriminated Records with Default Discriminants

If a discriminated type *T* has discriminants with default values, it is possible to declare an object of this type without providing an explicit constraint:

```
type Size is range 1..100;

type Rec (D : Size := 15) is record
  Name : String (1..D);
end T;

Word : Rec;
```

Such an object is said to be *unconstrained*. The discriminant of the object can be modified by a full assignment to the object, as long as it preserves the relation between the value of the discriminant, and the value of the components that depend on it:

```
Word := (3, "yes");

Word := (5, "maybe");

Word := (5, "no"); -- raises Constraint_Error
```

In order to support this behavior efficiently, an unconstrained object is given the maximum size that any value of the type requires. In the case above, *Word* has storage for the discriminant and for a *String* of length 100. It is important to note that unconstrained objects do not require dynamic allocation. It would be an improper implementation to place on the heap those components whose size depends on discriminants. (This improper implementation was used by some Ada83 compilers, where the *Name* component above would have been stored as a pointer to a dynamic string). Following the principle that dynamic storage management should never be introduced implicitly, an Ada compiler should reserve the full size for an unconstrained declared object, and place it on the stack.

This maximum size approach has been a source of surprise to some users, who expect the default values of the discriminants to determine the size reserved for an unconstrained object: “If the default is 15, why should the object occupy a larger size?” The answer, of course, is that the discriminant may be later modified, and its full range of values must be taken into account. This is why the declaration:

```
type Rec (D : Positive := 15) is record
  Name : String (1..D);
end record;

Too_Large : Rec;
```

is flagged by the compiler with a warning: an attempt to create *Too_Large* will raise *Storage_Error*, because the required size includes *Positive'Last* bytes. As the first example indicates, the proper approach is to declare an index type of “reasonable” range so that unconstrained objects are not too large.

One final wrinkle: if the object is declared to be *aliased*, or if it is created in the heap by means of an allocator, then it is *not* unconstrained: it is constrained by the default values of the discriminants, and those values cannot be modified by full assignment. This is because in the presence of aliasing all views of the object (which may be manipulated by different tasks, say) must be consistent, so it is imperative that the object, once created, remain invariant.

12.6 Strict Conformance to the Ada Reference Manual

The dynamic semantics defined by the Ada Reference Manual impose a set of run-time checks to be generated. By default, the GNAT compiler will insert many run-time checks into the compiled code, including most of those required by the Ada Reference Manual. However, there are three checks that are not enabled in the default mode for efficiency reasons: arithmetic

overflow checking for integer operations (including division by zero), checks for access before elaboration on subprogram calls, and stack overflow checking (most operating systems do not perform this check by default).

Strict conformance to the Ada Reference Manual can be achieved by adding three compiler options for overflow checking for integer operations (`'-gnato'`), dynamic checks for access-before-elaboration on subprogram calls and generic instantiations (`'-gnatE'`), and stack overflow checking (`'-fstack-check'`).

Note that the result of a floating point arithmetic operation in overflow and invalid situations, when the `Machine_Overflows` attribute of the result type is `False`, is to generate IEEE NaN and infinite values. This is the case for machines compliant with the IEEE floating-point standard, but on machines that are not fully compliant with this standard, such as Alpha, the `'-mieee'` compiler flag must be used for achieving IEEE confirming behavior (although at the cost of a significant performance penalty), so infinite and NaN values are properly generated.

13 Implementation of Ada 2012 Features

This chapter contains a complete list of Ada 2012 features that have been implemented as of GNAT version 6.4. Generally, these features are only available if the ‘-gnat12’ (Ada 2012 features enabled) flag is set or if the configuration pragma `Ada_2012` is used. However, new pragmas, attributes, and restrictions are unconditionally available, since the Ada 95 standard allows the addition of new pragmas, attributes, and restrictions (there are exceptions, which are documented in the individual descriptions), and also certain packages were made available in earlier versions of Ada.

An ISO date (YYYY-MM-DD) appears in parentheses on the description line. This date shows the implementation date of the feature. Any wavefront subsequent to this date will contain the indicated feature, as will any subsequent releases. A date of 0000-00-00 means that GNAT has always implemented the feature, or implemented it as soon as it appeared as a binding interpretation.

Each feature corresponds to an Ada Issue (“AI”) approved by the Ada standardization group (ISO/IEC JTC1/SC22/WG9) for inclusion in Ada 2012. The features are ordered based on the relevant sections of the Ada Reference Manual (“RM”). When a given AI relates to multiple points in the RM, the earliest is used.

A complete description of the AIs may be found in www.ada-auth.org/ai05-summary.html.

- *AI-0176 Quantified expressions (2010-09-29)*

Both universally and existentially quantified expressions are implemented. They use the new syntax for iterators proposed in AI05-139-2, as well as the standard Ada loop syntax.

RM References: 1.01.04 (12) 2.09 (2/2) 4.04 (7) 4.05.09 (0)

- *AI-0079 Allow other_format characters in source (2010-07-10)*

Wide characters in the unicode category *other_format* are now allowed in source programs between tokens, but not within a token such as an identifier.

RM References: 2.01 (4/2) 2.02 (7)

- *AI-0091 Do not allow other_format in identifiers (0000-00-00)*

Wide characters in the unicode category *other_format* are not permitted within an identifier, since this can be a security problem. The error message for this case has been improved to be more specific, but GNAT has never allowed such characters to appear in identifiers.

RM References: 2.03 (3.1/2) 2.03 (4/2) 2.03 (5/2) 2.03 (5.1/2) 2.03 (5.2/2) 2.03 (5.3/2) 2.09 (2/2)

- *AI-0100 Placement of pragmas (2010-07-01)*

This AI is an earlier version of AI-163. It simplifies the rules for legal placement of pragmas. In the case of lists that allow pragmas, if the list may have no elements, then the list may consist solely of pragmas.

RM References: 2.08 (7)

- *AI-0163 Pragmas in place of null (2010-07-01)*

A statement sequence may be composed entirely of pragmas. It is no longer necessary to add a dummy `null` statement to make the sequence legal.

RM References: 2.08 (7) 2.08 (16)

- *AI-0080 “View of” not needed if clear from context (0000-00-00)*

This is an editorial change only, described as non-testable in the AI.

RM References: 3.01 (7)

- *AI-0183 Aspect specifications (2010-08-16)*

Aspect specifications have been fully implemented except for pre and post- conditions, and type invariants, which have their own separate AI's. All forms of declarations listed in the AI are supported. The following is a list of the aspects supported (with GNAT implementation aspects marked)

Ada_2005	– GNAT
Ada_2012	– GNAT
Address	
Alignment	
Atomic	
Atomic_Components	
Bit_Order	
Component_Size	
Discard_Names	
External_Tag	
Favor_Top_Level	– GNAT
Inline	
Inline_Always	– GNAT
Invariant	
Machine_Radix	
No_Return	
Object_Size	– GNAT
Pack	
Persistent_BSS	– GNAT
Post	
Pre	
Predicate	
Preelaborable_Initialization	
Pure_Function	– GNAT
Shared	– GNAT
Size	
Storage_Pool	
Storage_Size	
Stream_Size	
Suppress	
Suppress_Debug_Info	– GNAT
Unchecked_Union	
Universal_Aliasing	– GNAT
Unmodified	– GNAT
Unreferenced	– GNAT
Unreferenced_Objects	– GNAT
Unsuppress	
Value_Size	– GNAT
Volatile	
Volatile_Components	
Warnings	– GNAT

Note that for aspects with an expression, e.g. **Size**, the expression is treated like a default expression (visibility is analyzed at the point of occurrence of the aspect, but evaluation of the expression occurs at the freeze point of the entity involved).

RM References: 3.02.01 (3) 3.02.02 (2) 3.03.01 (2/2) 3.08 (6) 3.09.03 (1.1/2) 6.01 (2/2) 6.07 (2/2) 9.05.02 (2/2) 7.01 (3) 7.03 (2) 7.03 (3) 9.01 (2/2) 9.01 (3/2) 9.04 (2/2) 9.04

(3/2) 9.05.02 (2/2) 11.01 (2) 12.01 (3) 12.03 (2/2) 12.04 (2/2) 12.05 (2) 12.06 (2.1/2) 12.06 (2.2/2) 12.07 (2) 13.01 (0.1/2) 13.03 (5/1) 13.03.01 (0)

- *AI-0128 Inequality is a primitive operation (0000-00-00)*

If an equality operator ("=") is declared for a type, then the implicitly declared inequality operator ("<=") is a primitive operation of the type. This is the only reasonable interpretation, and is the one always implemented by GNAT, but the RM was not entirely clear in making this point.

RM References: 3.02.03 (6) 6.06 (6)

- *AI-0003 Qualified expressions as names (2010-07-11)*

In Ada 2012, a qualified expression is considered to be syntactically a name, meaning that constructs such as `A'(F(X)).B` are now legal. This is useful in disambiguating some cases of overloading.

RM References: 3.03 (11) 3.03 (21) 4.01 (2) 4.04 (7) 4.07 (3) 5.04 (7)

- *AI-0120 Constant instance of protected object (0000-00-00)*

This is an RM editorial change only. The section that lists objects that are constant failed to include the current instance of a protected object within a protected function. This has always been treated as a constant in GNAT.

RM References: 3.03 (21)

- *AI-0008 General access to constrained objects (0000-00-00)*

The wording in the RM implied that if you have a general access to a constrained object, it could be used to modify the discriminants. This was obviously not intended. `Constraint_Error` should be raised, and GNAT has always done so in this situation.

RM References: 3.03 (23) 3.10.02 (26/2) 4.01 (9) 6.04.01 (17) 8.05.01 (5/2)

- *AI-0093 Additional rules use immutably limited (0000-00-00)*

This is an editorial change only, to make more widespread use of the Ada 2012 “immutably limited”.

RM References: 3.03 (23.4/3)

- *AI-0096 Deriving from formal private types (2010-07-20)*

In general it is illegal for a type derived from a formal limited type to be nonlimited. This AI makes an exception to this rule: derivation is legal if it appears in the private part of the generic, and the formal type is not tagged. If the type is tagged, the legality check must be applied to the private part of the package.

RM References: 3.04 (5.1/2) 6.02 (7)

- *AI-0181 Soft hyphen is a non-graphic character (2010-07-23)*

From Ada 2005 on, soft hyphen is considered a non-graphic character, which means that it has a special name (`SOFT_HYPHEN`) in conjunction with the `Image` and `Value` attributes for the character types. Strictly speaking this is an inconsistency with Ada 95, but in practice the use of these attributes is so obscure that it will not cause problems.

RM References: 3.05.02 (2/2) A.01 (35/2) A.03.03 (21)

- *AI-0182 Additional forms for `Character'Value` (0000-00-00)*

This AI allows `Character'Value` to accept the string `'??'` where `?` is any character including non-graphic control characters. GNAT has always accepted such strings. It also allows strings such as `HEX_00000041` to be accepted, but GNAT does not take advantage of this permission and raises `Constraint_Error`, as is certainly still permitted.

RM References: 3.05 (56/2)

- *AI-0214 Defaulted discriminants for limited tagged (2010-10-01)*
Ada 2012 relaxes the restriction that forbids discriminants of tagged types to have default expressions by allowing them when the type is limited. It is often useful to define a default value for a discriminant even though it can't be changed by assignment.
RM References: 3.07 (9.1/2) 3.07.02 (3)
- *AI-0102 Some implicit conversions are illegal (0000-00-00)*
It is illegal to assign an anonymous access constant to an anonymous access variable. The RM did not have a clear rule to prevent this, but GNAT has always generated an error for this usage.
RM References: 3.07 (16) 3.07.01 (9) 6.04.01 (6) 8.06 (27/2)
- *AI-0158 Generalizing membership tests (2010-09-16)*
This AI extends the syntax of membership tests to simplify complex conditions that can be expressed as membership in a subset of values of any type. It introduces syntax for a list of expressions that may be used in loop contexts as well.
RM References: 3.08.01 (5) 4.04 (3) 4.05.02 (3) 4.05.02 (5) 4.05.02 (27)
- *AI-0173 Testing if tags represent abstract types (2010-07-03)*
The function `Ada.Tags.Type_Is_Abstract` returns `True` if invoked with the tag of an abstract type, and `False` otherwise.
RM References: 3.09 (7.4/2) 3.09 (12.4/2)
- *AI-0076 function with controlling result (0000-00-00)*
This is an editorial change only. The RM defines calls with controlling results, but uses the term “function with controlling result” without an explicit definition.
RM References: 3.09.02 (2/2)
- *AI-0126 Dispatching with no declared operation (0000-00-00)*
This AI clarifies dispatching rules, and simply confirms that dispatching executes the operation of the parent type when there is no explicitly or implicitly declared operation for the descendant type. This has always been the case in all versions of GNAT.
RM References: 3.09.02 (20/2) 3.09.02 (20.1/2) 3.09.02 (20.2/2)
- *AI-0097 Treatment of abstract null extension (2010-07-19)*
The RM as written implied that in some cases it was possible to create an object of an abstract type, by having an abstract extension inherit a non- abstract constructor from its parent type. This mistake has been corrected in GNAT and in the RM, and this construct is now illegal.
RM References: 3.09.03 (4/2)
- *AI-0203 Extended return cannot be abstract (0000-00-00)*
A `return_subtype_indication` cannot denote an abstract subtype. GNAT has never permitted such usage.
RM References: 3.09.03 (8/3)
- *AI-0198 Inheriting abstract operators (0000-00-00)*
This AI resolves a conflict between two rules involving inherited abstract operations and predefined operators. If a derived numeric type inherits an abstract operator, it overrides the predefined one. This interpretation was always the one implemented in GNAT.
RM References: 3.09.03 (4/3)
- *AI-0073 Functions returning abstract types (2010-07-10)*
This AI covers a number of issues regarding returning abstract types. In particular generic functions cannot have abstract result types or access result types designated an abstract

type. There are some other cases which are detailed in the AI. Note that this binding interpretation has not been retrofitted to operate before Ada 2012 mode, since it caused a significant number of regressions.

RM References: 3.09.03 (8) 3.09.03 (10) 6.05 (8/2)

- *AI-0070 Elaboration of interface types (0000-00-00)*

This is an editorial change only, there are no testable consequences short of checking for the absence of generated code for an interface declaration.

RM References: 3.09.04 (18/2)

- *AI-0208 Characteristics of incomplete views (0000-00-00)*

The wording in the Ada 2005 RM concerning characteristics of incomplete views was incorrect and implied that some programs intended to be legal were now illegal. GNAT had never considered such programs illegal, so it has always implemented the intent of this AI.

RM References: 3.10.01 (2.4/2) 3.10.01 (2.6/2)

- *AI-0162 Incomplete type completed by partial view (2010-09-15)*

Incomplete types are made more useful by allowing them to be completed by private types and private extensions.

RM References: 3.10.01 (2.5/2) 3.10.01 (2.6/2) 3.10.01 (3) 3.10.01 (4/2)

- *AI-0098 Anonymous subprogram access restrictions (0000-00-00)*

An unintentional omission in the RM implied some inconsistent restrictions on the use of anonymous access to subprogram values. These restrictions were not intentional, and have never been enforced by GNAT.

RM References: 3.10.01 (6) 3.10.01 (9.2/2)

- *AI-0199 Aggregate with anonymous access components (2010-07-14)*

A choice list in a record aggregate can include several components of (distinct) anonymous access types as long as they have matching designated subtypes.

RM References: 4.03.01 (16)

- *AI-0220 Needed components for aggregates (0000-00-00)*

This AI addresses a wording problem in the RM that appears to permit some complex cases of aggregates with non-static discriminants. GNAT has always implemented the intended semantics.

RM References: 4.03.01 (17)

- *AI-0147 Conditional expressions (2009-03-29)*

Conditional expressions are permitted. The form of such an expression is:

(if *expr* then *expr* {elsif *expr* then *expr*} [else *expr*])

The parentheses can be omitted in contexts where parentheses are present anyway, such as subprogram arguments and pragma arguments. If the **else** clause is omitted, **else True** is assumed; thus (if **A** then **B**) is a way to conveniently represent (*A implies B*) in standard logic.

RM References: 4.03.03 (15) 4.04 (1) 4.04 (7) 4.05.07 (0) 4.07 (2) 4.07 (3) 4.09 (12) 4.09 (33) 5.03 (3) 5.03 (4) 7.05 (2.1/2)

- *AI-0037 Out-of-range box associations in aggregate (0000-00-00)*

This AI confirms that an association of the form **Indx => <>** in an array aggregate must raise **Constraint_Error** if **Indx** is out of range. The RM specified a range check on other associations, but not when the value of the association was defaulted. GNAT has always inserted a constraint check on the index value.

RM References: 4.03.03 (29)

- *AI-0123 Composability of equality (2010-04-13)*

Equality of untagged record composes, so that the predefined equality for a composite type that includes a component of some untagged record type *R* uses the equality operation of *R* (which may be user-defined or predefined). This makes the behavior of untagged records identical to that of tagged types in this respect.

This change is an incompatibility with previous versions of Ada, but it corrects a non-uniformity that was often a source of confusion. Analysis of a large number of industrial programs indicates that in those rare cases where a composite type had an untagged record component with a user-defined equality, either there was no use of the composite equality, or else the code expected the same composability as for tagged types, and thus had a bug that would be fixed by this change.

RM References: 4.05.02 (9.7/2) 4.05.02 (14) 4.05.02 (15) 4.05.02 (24) 8.05.04 (8)

- *AI-0088 The value of exponentiation (0000-00-00)*

This AI clarifies the equivalence rule given for the dynamic semantics of exponentiation: the value of the operation can be obtained by repeated multiplication, but the operation can be implemented otherwise (for example using the familiar divide-by-two-and-square algorithm, even if this is less accurate), and does not imply repeated reads of a volatile base.

RM References: 4.05.06 (11)

- *AI-0188 Case expressions (2010-01-09)*

Case expressions are permitted. This allows use of constructs such as:

```
X := (case Y is when 1 => 2, when 2 => 3, when others => 31)
```

RM References: 4.05.07 (0) 4.05.08 (0) 4.09 (12) 4.09 (33)

- *AI-0104 Null exclusion and uninitialized allocator (2010-07-15)*

The assignment `Ptr := new not null Some_Ptr;` will raise `Constraint_Error` because the default value of the allocated object is `null`. This useless construct is illegal in Ada 2012.

RM References: 4.08 (2)

- *AI-0157 Allocation/Deallocation from empty pool (2010-07-11)*

Allocation and Deallocation from an empty storage pool (i.e. allocation or deallocation of a pointer for which a static storage size clause of zero has been given) is now illegal and is detected as such. GNAT previously gave a warning but not an error.

RM References: 4.08 (5.3/2) 13.11.02 (4) 13.11.02 (17)

- *AI-0179 Statement not required after label (2010-04-10)*

It is not necessary to have a statement following a label, so a label can appear at the end of a statement sequence without the need for putting a null statement afterwards, but it is not allowable to have only labels and no real statements in a statement sequence.

RM References: 5.01 (2)

- *AI-139-2 Syntactic sugar for iterators (2010-09-29)*

The new syntax for iterating over arrays and containers is now implemented. Iteration over containers is for now limited to read-only iterators. Only default iterators are supported, with the syntax: `for Elem of C`.

RM References: 5.05

- *AI-0134 Profiles must match for full conformance (0000-00-00)*

For full conformance, the profiles of anonymous-access-to-subprogram parameters must match. GNAT has always enforced this rule.

RM References: 6.03.01 (18)

- *AI-0207 Mode conformance and access constant (0000-00-00)*
This AI confirms that `access_to_constant` indication must match for mode conformance. This was implemented in GNAT when the qualifier was originally introduced in Ada 2005.
RM References: 6.03.01 (16/2)
- *AI-0046 Null exclusion match for full conformance (2010-07-17)*
For full conformance, in the case of access parameters, the null exclusion must match (either both or neither must have **not null**).
RM References: 6.03.02 (18)
- *AI-0118 The association of parameter associations (0000-00-00)*
This AI clarifies the rules for named associations in subprogram calls and generic instantiations. The rules have been in place since Ada 83.
RM References: 6.04.01 (2) 12.03 (9)
- *AI-0196 Null exclusion tests for out parameters (0000-00-00)*
Null exclusion checks are not made for **out** parameters when evaluating the actual parameters. GNAT has never generated these checks.
RM References: 6.04.01 (13)
- *AI-0015 Constant return objects (0000-00-00)*
The return object declared in an *extended_return_statement* may be declared constant. This was always intended, and GNAT has always allowed it.
RM References: 6.05 (2.1/2) 3.03 (10/2) 3.03 (21) 6.05 (5/2) 6.05 (5.7/2)
- *AI-0032 Extended return for class-wide functions (0000-00-00)*
If a function returns a class-wide type, the object of an extended return statement can be declared with a specific type that is covered by the class-wide type. This has been implemented in GNAT since the introduction of extended returns. Note AI-0103 complements this AI by imposing matching rules for constrained return types.
RM References: 6.05 (5.2/2) 6.05 (5.3/2) 6.05 (5.6/2) 6.05 (5.8/2) 6.05 (8/2)
- *AI-0103 Static matching for extended return (2010-07-23)*
If the return subtype of a function is an elementary type or a constrained type, the subtype indication in an extended return statement must match statically this return subtype.
RM References: 6.05 (5.2/2)
- *AI-0058 Abnormal completion of an extended return (0000-00-00)*
The RM had some incorrect wording implying wrong treatment of abnormal completion in an extended return. GNAT has always implemented the intended correct semantics as described by this AI.
RM References: 6.05 (22/2)
- *AI-0050 Raising Constraint_Error early for function call (0000-00-00)*
The implementation permissions for raising **Constraint_Error** early on a function call when it was clear an exception would be raised were over-permissive and allowed mishandling of discriminants in some cases. GNAT did not take advantage of these incorrect permissions in any case.
RM References: 6.05 (24/2)
- *AI-0125 Nonoverridable operations of an ancestor (2010-09-28)*
In Ada 2012, the declaration of a primitive operation of a type extension or private extension can also override an inherited primitive that is not visible at the point of this declaration.
RM References: 7.03.01 (6) 8.03 (23) 8.03.01 (5/2) 8.03.01 (6/2)

- *AI-0062 Null exclusions and deferred constants (0000-00-00)*
A full constant may have a null exclusion even if its associated deferred constant does not. GNAT has always allowed this.
RM References: 7.04 (6/2) 7.04 (7.1/2)
- *AI-0178 Incomplete views are limited (0000-00-00)*
This AI clarifies the role of incomplete views and plugs an omission in the RM. GNAT always correctly restricted the use of incomplete views and types.
RM References: 7.05 (3/2) 7.05 (6/2)
- *AI-0087 Actual for formal nonlimited derived type (2010-07-15)*
The actual for a formal nonlimited derived type cannot be limited. In particular, a formal derived type that extends a limited interface but which is not explicitly limited cannot be instantiated with a limited type.
RM References: 7.05 (5/2) 12.05.01 (5.1/2)
- *AI-0099 Tag determines whether finalization needed (0000-00-00)*
This AI clarifies that “needs finalization” is part of dynamic semantics, and therefore depends on the run-time characteristics of an object (i.e. its tag) and not on its nominal type. As the AI indicates: “we do not expect this to affect any implementation”.
RM References: 7.06.01 (6) 7.06.01 (7) 7.06.01 (8) 7.06.01 (9/2)
- *AI-0064 Redundant finalization rule (0000-00-00)*
This is an editorial change only. The intended behavior is already checked by an existing ACATS test, which GNAT has always executed correctly.
RM References: 7.06.01 (17.1/1)
- *AI-0026 Missing rules for Unchecked_Union (2010-07-07)*
Record representation clauses concerning Unchecked_Union types cannot mention the discriminant of the type. The type of a component declared in the variant part of an Unchecked_Union cannot be controlled, have controlled components, nor have protected or task parts. If an Unchecked_Union type is declared within the body of a generic unit or its descendants, then the type of a component declared in the variant part cannot be a formal private type or a formal private extension declared within the same generic unit.
RM References: 7.06 (9.4/2) B.03.03 (9/2) B.03.03 (10/2)
- *AI-0205 Extended return declares visible name (0000-00-00)*
This AI corrects a simple omission in the RM. Return objects have always been visible within an extended return statement.
RM References: 8.03 (17)
- *AI-0042 Overriding versus implemented-by (0000-00-00)*
This AI fixes a wording gap in the RM. An operation of a synchronized interface can be implemented by a protected or task entry, but the abstract operation is not being overridden in the usual sense, and it must be stated separately that this implementation is legal. This has always been the case in GNAT.
RM References: 9.01 (9.2/2) 9.04 (11.1/2)
- *AI-0030 Requeue on synchronized interfaces (2010-07-19)*
Requeue is permitted to a protected, synchronized or task interface primitive providing it is known that the overriding operation is an entry. Otherwise the requeue statement has the same effect as a procedure call. Use of pragma **Implemented** provides a way to impose a static requirement on the overriding operation by adhering to one of the implementation kinds: entry, protected procedure or any of the above.

RM References: 9.05 (9) 9.05.04 (2) 9.05.04 (3) 9.05.04 (5) 9.05.04 (6) 9.05.04 (7) 9.05.04 (12)

- *AI-0201 Independence of atomic object components (2010-07-22)*

If an Atomic object has a pragma **Pack** or a **Component_Size** attribute, then individual components may not be addressable by independent tasks. However, if the representation clause has no effect (is confirming), then independence is not compromised. Furthermore, in GNAT, specification of other appropriately addressable component sizes (e.g. 16 for 8-bit characters) also preserves independence. GNAT now gives very clear warnings both for the declaration of such a type, and for any assignment to its components.

RM References: 9.10 (1/3) C.06 (22/2) C.06 (23/2)

- *AI-0009 Pragma Independent[_Components] (2010-07-23)*

This AI introduces the new pragmas **Independent** and **Independent_Components**, which control guaranteeing independence of access to objects and components. The AI also requires independence not unaffected by confirming rep clauses.

RM References: 9.10 (1) 13.01 (15/1) 13.02 (9) 13.03 (13) C.06 (2) C.06 (4) C.06 (6) C.06 (9) C.06 (13) C.06 (14)

- *AI-0072 Task signalling using 'Terminated' (0000-00-00)*

This AI clarifies that task signalling for reading **'Terminated** only occurs if the result is True. GNAT semantics has always been consistent with this notion of task signalling.

RM References: 9.10 (6.1/1)

- *AI-0108 Limited incomplete view and discriminants (0000-00-00)*

This AI confirms that an incomplete type from a limited view does not have discriminants. This has always been the case in GNAT.

RM References: 10.01.01 (12.3/2)

- *AI-0129 Limited views and incomplete types (0000-00-00)*

This AI clarifies the description of limited views: a limited view of a package includes only one view of a type that has an incomplete declaration and a full declaration (there is no possible ambiguity in a client package). This AI also fixes an omission: a nested package in the private part has no limited view. GNAT always implemented this correctly.

RM References: 10.01.01 (12.2/2) 10.01.01 (12.3/2)

- *AI-0077 Limited withs and scope of declarations (0000-00-00)*

This AI clarifies that a declaration does not include a context clause, and confirms that it is illegal to have a context in which both a limited and a nonlimited view of a package are accessible. Such double visibility was always rejected by GNAT.

RM References: 10.01.02 (12/2) 10.01.02 (21/2) 10.01.02 (22/2)

- *AI-0122 Private with and children of generics (0000-00-00)*

This AI clarifies the visibility of private children of generic units within instantiations of a parent. GNAT has always handled this correctly.

RM References: 10.01.02 (12/2)

- *AI-0040 Limited with clauses on descendant (0000-00-00)*

This AI confirms that a limited with clause in a child unit cannot name an ancestor of the unit. This has always been checked in GNAT.

RM References: 10.01.02 (20/2)

- *AI-0132 Placement of library unit pragmas (0000-00-00)*

This AI fills a gap in the description of library unit pragmas. The pragma clearly must apply to a library unit, even if it does not carry the name of the enclosing unit. GNAT has always enforced the required check.

RM References: 10.01.05 (7)

- *AI-0034 Categorization of limited views (0000-00-00)*

The RM makes certain limited with clauses illegal because of categorization considerations, when the corresponding normal with would be legal. This is not intended, and GNAT has always implemented the recommended behavior.

RM References: 10.02.01 (11/1) 10.02.01 (17/2)

- *AI-0035 Inconsistencies with Pure units (0000-00-00)*

This AI remedies some inconsistencies in the legality rules for Pure units. Derived access types are legal in a pure unit (on the assumption that the rule for a zero storage pool size has been enforced on the ancestor type). The rules are enforced in generic instances and in subunits. GNAT has always implemented the recommended behavior.

RM References: 10.02.01 (15.1/2) 10.02.01 (15.4/2) 10.02.01 (15.5/2) 10.02.01 (17/2)

- *AI-0219 Pure permissions and limited parameters (2010-05-25)*

This AI refines the rules for the cases with limited parameters which do not allow the implementations to omit “redundant”. GNAT now properly conforms to the requirements of this binding interpretation.

RM References: 10.02.01 (18/2)

- *AI-0043 Rules about raising exceptions (0000-00-00)*

This AI covers various omissions in the RM regarding the raising of exceptions. GNAT has always implemented the intended semantics.

RM References: 11.04.01 (10.1/2) 11 (2)

- *AI-0200 Mismatches in formal package declarations (0000-00-00)*

This AI plugs a gap in the RM which appeared to allow some obviously intended illegal instantiations. GNAT has never allowed these instantiations.

RM References: 12.07 (16)

- *AI-0112 Detection of duplicate pragmas (2010-07-24)*

This AI concerns giving names to various representation aspects, but the practical effect is simply to make the use of duplicate `Atomic[_Components]`, `Volatile[_Components]` and `Independent[_Components]` pragmas illegal, and GNAT now performs this required check.

RM References: 13.01 (8)

- *AI-0106 No representation pragmas on generic formals (0000-00-00)*

The RM appeared to allow representation pragmas on generic formal parameters, but this was not intended, and GNAT has never permitted this usage.

RM References: 13.01 (9.1/1)

- *AI-0012 Pack/Component_Size for aliased/atomic (2010-07-15)*

It is now illegal to give an inappropriate component size or a pragma `Pack` that attempts to change the component size in the case of atomic or aliased components. Previously GNAT ignored such an attempt with a warning.

RM References: 13.02 (6.1/2) 13.02 (7) C.06 (10) C.06 (11) C.06 (21)

- *AI-0039 Stream attributes cannot be dynamic (0000-00-00)*

The RM permitted the use of dynamic expressions (such as `ptr.all`) for stream attributes, but these were never useful and are now illegal. GNAT has always regarded such expressions as illegal.

RM References: 13.03 (4) 13.03 (6) 13.13.02 (38/2)

- *AI-0095 Address of intrinsic subprograms (0000-00-00)*
 The prefix of 'Address cannot statically denote a subprogram with convention `Intrinsic`. The use of the `Address` attribute raises `Program_Error` if the prefix denotes a subprogram with convention `Intrinsic`.
 RM References: 13.03 (11/1)
- *AI-0116 Alignment of class-wide objects (0000-00-00)*
 This AI requires that the alignment of a class-wide object be no greater than the alignment of any type in the class. GNAT has always followed this recommendation.
 RM References: 13.03 (29) 13.11 (16)
- *AI-0146 Type invariants (2009-09-21)*
 Type invariants may be specified for private types using the aspect notation. Aspect `Invariant` may be specified for any private type, `Invariant'Class` can only be specified for tagged types, and is inherited by any descendent of the tagged types. The invariant is a boolean expression that is tested for being true in the following situations: conversions to the private type, object declarations for the private type that are default initialized, and `[in] out` parameters and returned result on return from any primitive operation for the type that is visible to a client.
 RM References: 13.03.03 (00)
- *AI-0078 Relax Unchecked_Conversion alignment rules (0000-00-00)*
 In Ada 2012, compilers are required to support unchecked conversion where the target alignment is a multiple of the source alignment. GNAT always supported this case (and indeed all cases of differing alignments, doing copies where required if the alignment was reduced).
 RM References: 13.09 (7)
- *AI-0195 Invalid value handling is implementation defined (2010-07-03)*
 The handling of invalid values is now designated to be implementation defined. This is a documentation change only, requiring Annex M in the GNAT Reference Manual to document this handling. In GNAT, checks for invalid values are made only when necessary to avoid erroneous behavior. Operations like assignments which cannot cause erroneous behavior ignore the possibility of invalid values and do not do a check. The date given above applies only to the documentation change, this behavior has always been implemented by GNAT.
 RM References: 13.09.01 (10)
- *AI-0193 Alignment of allocators (2010-09-16)*
 This AI introduces a new attribute `Max_Alignment_For_Allocation`, analogous to `Max_Size_In_Storage_Elements`, but for alignment instead of size.
 RM References: 13.11 (16) 13.11 (21) 13.11.01 (0) 13.11.01 (1) 13.11.01 (2) 13.11.01 (3)
- *AI-0177 Parameterized expressions (2010-07-10)*
 The new Ada 2012 notion of parameterized expressions is implemented. The form is:
 `function specification is (expression)`
 This is exactly equivalent to the corresponding function body that returns the expression, but it can appear in a package spec. Note that the expression must be parenthesized.
 RM References: 13.11.01 (3/2)
- *AI-0033 Attach/Interrupt_Handler in generic (2010-07-24)*
 Neither of these two pragmas may appear within a generic template, because the generic might be instantiated at other than the library level.
 RM References: 13.11.02 (16) C.03.01 (7/2) C.03.01 (8/2)

- *AI-0161 Restriction No_Default_Stream_Attributes (2010-09-11)*

A new restriction `No_Default_Stream_Attributes` prevents the use of any of the default stream attributes for elementary types. If this restriction is in force, then it is necessary to provide explicit subprograms for any stream attributes used.

RM References: 13.12.01 (4/2) 13.13.02 (40/2) 13.13.02 (52/2)

- *AI-0194 Value of Stream_Size attribute (0000-00-00)*

The `Stream_Size` attribute returns the default number of bits in the stream representation of the given type. This value is not affected by the presence of stream subprogram attributes for the type. GNAT has always implemented this interpretation.

RM References: 13.13.02 (1.2/2)

- *AI-0109 Redundant check in S'Class'Input (0000-00-00)*

This AI is an editorial change only. It removes the need for a tag check that can never fail.

RM References: 13.13.02 (34/2)

- *AI-0007 Stream read and private scalar types (0000-00-00)*

The RM as written appeared to limit the possibilities of declaring read attribute procedures for private scalar types. This limitation was not intended, and has never been enforced by GNAT.

RM References: 13.13.02 (50/2) 13.13.02 (51/2)

- *AI-0065 Remote access types and external streaming (0000-00-00)*

This AI clarifies the fact that all remote access types support external streaming. This fixes an obvious oversight in the definition of the language, and GNAT always implemented the intended correct rules.

RM References: 13.13.02 (52/2)

- *AI-0019 Freezing of primitives for tagged types (0000-00-00)*

The RM suggests that primitive subprograms of a specific tagged type are frozen when the tagged type is frozen. This would be an incompatible change and is not intended. GNAT has never attempted this kind of freezing and its behavior is consistent with the recommendation of this AI.

RM References: 13.14 (2) 13.14 (3/1) 13.14 (8.1/1) 13.14 (10) 13.14 (14) 13.14 (15.1/2)

- *AI-0017 Freezing and incomplete types (0000-00-00)*

So-called “Taft-amendment types” (i.e., types that are completed in package bodies) are not frozen by the occurrence of bodies in the enclosing declarative part. GNAT always implemented this properly.

RM References: 13.14 (3/1)

- *AI-0060 Extended definition of remote access types (0000-00-00)*

This AI extends the definition of remote access types to include access to limited, synchronized, protected or task class-wide interface types. GNAT already implemented this extension.

RM References: A (4) E.02.02 (9/1) E.02.02 (9.2/1) E.02.02 (14/2) E.02.02 (18)

- *AI-0114 Classification of letters (0000-00-00)*

The code points 170 (FEMININE ORDINAL INDICATOR), 181 (MICRO SIGN), and 186 (MASCULINE ORDINAL INDICATOR) are technically considered lower case letters by Unicode. However, they are not allowed in identifiers, and they return `False` to `Ada.Characters.Handling.Is_Letter/Is_Lower`. This behavior is consistent with that defined in Ada 95.

RM References: A.03.02 (59) A.04.06 (7)

- *AI-0185 Ada.Wide_[Wide_]Characters.Handling (2010-07-06)*
Two new packages `Ada.Wide_[Wide_]Characters.Handling` provide classification functions for `Wide_Character` and `Wide_Wide_Character`, as well as providing case folding routines for `Wide_[Wide_]Character` and `Wide_[Wide_]String`.
RM References: A.03.05 (0) A.03.06 (0)
- *AI-0031 Add From parameter to Find-Token (2010-07-25)*
A new version of `Find-Token` is added to all relevant string packages, with an extra parameter `From`. Instead of starting at the first character of the string, the search for a matching Token starts at the character indexed by the value of `From`. These procedures are available in all versions of Ada but if used in versions earlier than Ada 2012 they will generate a warning that an Ada 2012 subprogram is being used.
RM References: A.04.03 (16) A.04.03 (67) A.04.03 (68/1) A.04.04 (51) A.04.05 (46)
- *AI-0056 Index on null string returns zero (0000-00-00)*
The wording in the Ada 2005 RM implied an incompatible handling of the `Index` functions, resulting in raising an exception instead of returning zero in some situations. This was not intended and has been corrected. GNAT always returned zero, and is thus consistent with this AI.
RM References: A.04.03 (56.2/2) A.04.03 (58.5/2)
- *AI-0137 String encoding package (2010-03-25)*
The packages `Ada.Strings.UTF_Encoding`, together with its child packages, `Conversions`, `Strings`, `Wide_Strings`, and `Wide_Wide_Strings` have been implemented. These packages (whose documentation can be found in the spec files ‘a-stuten.ads’, ‘a-suenco.ads’, ‘a-suenst.ads’, ‘a-suewst.ads’, ‘a-suezst.ads’) allow encoding and decoding of `String`, `Wide_String`, and `Wide_Wide_String` values using UTF coding schemes (including UTF-8, UTF-16LE, UTF-16BE, and UTF-16), as well as conversions between the different UTF encodings. With the exception of `Wide_Wide_Strings`, these packages are available in Ada 95 and Ada 2005 mode as well as Ada 2012 mode. The `Wide_Wide_Strings` package is available in Ada 2005 mode as well as Ada 2012 mode (but not in Ada 95 mode since it uses `Wide_Wide_Character`).
RM References: A.04.11
- *AI-0038 Minor errors in Text_IO (0000-00-00)*
These are minor errors in the description on three points. The intent on all these points has always been clear, and GNAT has always implemented the correct intended semantics.
RM References: A.10.05 (37) A.10.07 (8/1) A.10.07 (10) A.10.07 (12) A.10.08 (10) A.10.08 (24)
- *AI-0044 Restrictions on container instantiations (0000-00-00)*
This AI places restrictions on allowed instantiations of generic containers. These restrictions are not checked by the compiler, so there is nothing to change in the implementation. This affects only the RM documentation.
RM References: A.18 (4/2) A.18.02 (231/2) A.18.03 (145/2) A.18.06 (56/2) A.18.08 (66/2) A.18.09 (79/2) A.18.26 (5/2) A.18.26 (9/2)
- *AI-0127 Adding Locale Capabilities (2010-09-29)*
This package provides an interface for identifying the current locale.
RM References: A.19 A.19.01 A.19.02 A.19.03 A.19.05 A.19.06 A.19.07 A.19.08 A.19.09 A.19.10 A.19.11 A.19.12 A.19.13
- *AI-0002 Export C with unconstrained arrays (0000-00-00)*
The compiler is not required to support exporting an Ada subprogram with convention C if there are parameters or a return type of an unconstrained array type (such as `String`).

GNAT allows such declarations but generates warnings. It is possible, but complicated, to write the corresponding C code and certainly such code would be specific to GNAT and non-portable.

RM References: B.01 (17) B.03 (62) B.03 (71.1/2)

- *AI-0216 No_Task_Hierarchy forbids local tasks (0000-00-00)*

It is clearly the intention that `No_Task_Hierarchy` is intended to forbid tasks declared locally within subprograms, or functions returning task objects, and that is the implementation that GNAT has always provided. However the language in the RM was not sufficiently clear on this point. Thus this is a documentation change in the RM only.

RM References: D.07 (3/3)

- *AI-0211 No_Relative_Delays forbids Set_Handler use (2010-07-09)*

The restriction `No_Relative_Delays` forbids any calls to the subprogram `Ada.Real_Time.Timing_Events.Set_Handler`.

RM References: D.07 (5) D.07 (10/2) D.07 (10.4/2) D.07 (10.7/2)

- *AI-0190 pragma Default_Storage_Pool (2010-09-15)*

This AI introduces a new pragma `Default_Storage_Pool`, which can be used to control storage pools globally. In particular, you can force every access type that is used for allocation (**new**) to have an explicit storage pool, or you can declare a pool globally to be used for all access types that lack an explicit one.

RM References: D.07 (8)

- *AI-0189 No_Allocators_After_Elaboration (2010-01-23)*

This AI introduces a new restriction `No_Allocators_After_Elaboration`, which says that no dynamic allocation will occur once elaboration is completed. In general this requires a run-time check, which is not required, and which GNAT does not attempt. But the static cases of allocators in a task body or in the body of the main program are detected and flagged at compile or bind time.

RM References: D.07 (19.1/2) H.04 (23.3/2)

- *AI-0171 Pragma CPU and Ravenscar Profile (2010-09-24)*

A new package `System.Multiprocessors` is added, together with the definition of pragma `CPU` for controlling task affinity. A new no dependence restriction, on `System.Multiprocessors.Dispatching_Domains`, is added to the Ravenscar profile.

RM References: D.13.01 (4/2) D.16

- *AI-0210 Correct Timing_Events metric (0000-00-00)*

This is a documentation only issue regarding wording of metric requirements, that does not affect the implementation of the compiler.

RM References: D.15 (24/2)

- *AI-0206 Remote types packages and preelaborate (2010-07-24)*

Remote types packages are now allowed to depend on preelaborated packages. This was formerly considered illegal.

RM References: E.02.02 (6)

- *AI-0152 Restriction No_Anonymous_Allocators (2010-09-08)*

Restriction `No_Anonymous_Allocators` prevents the use of allocators where the type of the returned value is an anonymous access type.

RM References: H.04 (8/1)

14 Obsolescent Features

This chapter describes features that are provided by GNAT, but are considered obsolescent since there are preferred ways of achieving the same effect. These features are provided solely for historical compatibility purposes.

14.1 `pragma No_Run_Time`

The `pragma No_Run_Time` is used to achieve an affect similar to the use of the "Zero Foot Print" configurable run time, but without requiring a specially configured run time. The result of using this pragma, which must be used for all units in a partition, is to restrict the use of any language features requiring run-time support code. The preferred usage is to use an appropriately configured run-time that includes just those features that are to be made accessible.

14.2 `pragma Ravenscar`

The `pragma Ravenscar` has exactly the same effect as `pragma Profile (Ravenscar)`. The latter usage is preferred since it is part of the new Ada 2005 standard.

14.3 `pragma Restricted_Run_Time`

The `pragma Restricted_Run_Time` has exactly the same effect as `pragma Profile (Restricted)`. The latter usage is preferred since the Ada 2005 `pragma Profile` is intended for this kind of implementation dependent addition.

GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.

<http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “publisher” means any person or entity that distributes copies of the Document to the public.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document’s license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both

covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its

Title Page, then add an item describing the Modified Version as stated in the previous sentence.

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the “History” section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled “Acknowledgements” or “Dedications”, Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled “Endorsements”. Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled “Endorsements” or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.  
Permission is granted to copy, distribute and/or modify this document  
under the terms of the GNU Free Documentation License, Version 1.3  
or any later version published by the Free Software Foundation;  
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover  
Texts. A copy of the license is included in the section entitled ‘‘GNU  
Free Documentation License’’.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with  
the Front-Cover Texts being list, and with the Back-Cover Texts  
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Index

-	
'-gnat12' option	191
'-gnatR' switch	139
-	
'__lock' file (for shared passive packages)	187
A	
Abort_Defer	3
Abort_Signal	57
Access values, testing for	60
Access, unrestricted	66
Accuracy requirements	89
Accuracy, complex arithmetic	89
Ada 2005 Language Reference Manual	2
Ada 2012 implementation status	191
Ada 83 attributes	59, 60, 61, 64
Ada 95 Language Reference Manual	2
Ada Extensions	17
Ada.Characters.Handling	78
Ada.Characters.Latin_9 ('a-chlat9.ads')	165
Ada.Characters.Wide_Latin_1 ('a-cwilal.ads')	165
Ada.Characters.Wide_Latin_9 ('a-cwilal.ads')	165
Ada.Characters.Wide_Wide_Latin_1 ('a-chzla1.ads')	165
Ada.Characters.Wide_Wide_Latin_9 ('a-chzla9.ads')	166
Ada.Command_Line.Environment ('a-colien.ads')	166
Ada.Command_Line.Remove ('a-colire.ads')	166
Ada.Command_Line.Response_File ('a-clrefi.ads')	166
Ada.Direct_IO.C_Streams ('a-diocst.ads')	166
Ada.Exceptions.Is_Null_Occurrence ('a-einuoc.ads')	166
Ada.Exceptions.Last_Chance_Handler ('a-elchha.ads')	166
Ada.Exceptions.Traceback ('a-extra.ads')	166
Ada.Sequential_IO.C_Streams ('a-siocst.ads')	166
Ada.Streams.Stream_IO.C_Streams ('a-ssicst.ads')	167
Ada.Strings.Unbounded.Text_IO ('a-suteio.ads')	167
Ada.Strings.Wide_Unbounded.Wide_Text_IO ('a-swuwti.ads')	167
Ada.Strings.Wide_Wide_Unbounded.Wide_Wide_Text_IO ('a-szuzti.ads')	167
Ada.Text_IO.C_Streams ('a-tiocst.ads')	167
Ada.Text_IO.Reset_Standard_Files ('a-tirstfi.ads')	167
Ada.Wide_Characters.Unicode ('a-wichun.ads')	167
Ada.Wide_Text_IO.C_Streams ('a-wtcstr.ads')	167
Ada.Wide_Text_IO.Reset_Standard_Files ('a-wrstfi.ads')	167
Ada.Wide_Wide_Characters.Unicode ('a-zchuni.ads')	167
Ada.Wide_Wide_Text_IO.C_Streams ('a-ztcstr.ads')	168
Ada.Wide_Wide_Text_IO.Reset_Standard_Files ('a-zrstfi.ads')	168
Ada_05	4
Ada_12	4
Ada_2005	4
Ada_2012 configuration pragma	191
Ada_83	3
Ada_95	3
Address Clause	135
Address clauses	72
Address image	177
Address of subprogram code	58
Address, as private type	76
Address, operations of	76
Address_Size	57
AI-0002 (Ada 2012 feature)	203
AI-0003 (Ada 2012 feature)	193
AI-0007 (Ada 2012 feature)	202
AI-0008 (Ada 2012 feature)	193
AI-0009 (Ada 2012 feature)	199
AI-0012 (Ada 2012 feature)	200
AI-0015 (Ada 2012 feature)	197
AI-0017 (Ada 2012 feature)	202
AI-0019 (Ada 2012 feature)	202
AI-0026 (Ada 2012 feature)	198
AI-0030 (Ada 2012 feature)	198
AI-0031 (Ada 2012 feature)	203
AI-0032 (Ada 2012 feature)	197
AI-0033 (Ada 2012 feature)	201
AI-0034 (Ada 2012 feature)	200
AI-0035 (Ada 2012 feature)	200
AI-0037 (Ada 2012 feature)	195
AI-0038 (Ada 2012 feature)	203
AI-0039 (Ada 2012 feature)	200
AI-0040 (Ada 2012 feature)	199
AI-0042 (Ada 2012 feature)	198
AI-0043 (Ada 2012 feature)	200
AI-0044 (Ada 2012 feature)	203
AI-0046 (Ada 2012 feature)	197
AI-0050 (Ada 2012 feature)	197
AI-0056 (Ada 2012 feature)	203
AI-0058 (Ada 2012 feature)	197
AI-0060 (Ada 2012 feature)	202
AI-0062 (Ada 2012 feature)	198
AI-0064 (Ada 2012 feature)	198
AI-0065 (Ada 2012 feature)	202
AI-0070 (Ada 2012 feature)	195
AI-0072 (Ada 2012 feature)	199
AI-0073 (Ada 2012 feature)	194
AI-0076 (Ada 2012 feature)	194
AI-0077 (Ada 2012 feature)	199
AI-0078 (Ada 2012 feature)	201
AI-0079 (Ada 2012 feature)	191
AI-0080 (Ada 2012 feature)	191
AI-0087 (Ada 2012 feature)	198

AI-0088 (Ada 2012 feature)	196	AI-0211 (Ada 2012 feature)	204
AI-0091 (Ada 2012 feature)	191	AI-0214 (Ada 2012 feature)	194
AI-0093 (Ada 2012 feature)	193	AI-0216 (Ada 2012 feature)	204
AI-0095 (Ada 2012 feature)	201	AI-0219 (Ada 2012 feature)	200
AI-0096 (Ada 2012 feature)	193	AI-0220 (Ada 2012 feature)	195
AI-0097 (Ada 2012 feature)	194	AI-139-2 (Ada 2012 feature)	196
AI-0098 (Ada 2012 feature)	195	Alignment Clause	121
AI-0099 (Ada 2012 feature)	198	Alignment clauses	73
AI-0100 (Ada 2012 feature)	191	Alignment, default	122
AI-0102 (Ada 2012 feature)	194	Alignment, default settings	34
AI-0103 (Ada 2012 feature)	197	Alignment, maximum	62
AI-0104 (Ada 2012 feature)	196	Alignments of components	9
AI-0106 (Ada 2012 feature)	200	Alternative Character Sets	68
AI-0108 (Ada 2012 feature)	199	Altivec	168
AI-0109 (Ada 2012 feature)	202	Annex E	186
AI-0112 (Ada 2012 feature)	200	Annotate	4
AI-0114 (Ada 2012 feature)	202	Argument passing mechanisms	14
AI-0116 (Ada 2012 feature)	201	Array packing	21
AI-0118 (Ada 2012 feature)	197	Array splitter	168
AI-0120 (Ada 2012 feature)	193	Arrays, extendable	171, 176
AI-0122 (Ada 2012 feature)	199	Arrays, multidimensional	70
AI-0123 (Ada 2012 feature)	196	Asm_Input	57
AI-0125 (Ada 2012 feature)	197	Asm_Output	57
AI-0126 (Ada 2012 feature)	194	Assert	4
AI-0127 (Ada 2012 feature)	203	Assert_Failure, exception	177
AI-0128 (Ada 2012 feature)	193	Assertions	6, 177
AI-0129 (Ada 2012 feature)	199	Assertions, control	7
AI-0132 (Ada 2012 feature)	199	Assume_No_Invalid_Values	5
AI-0134 (Ada 2012 feature)	196	Ast_Entry	6
AI-0137 (Ada 2012 feature)	203	AST_Entry	57
AI-0146 (Ada 2012 feature)	201	Attribute	136
AI-0147 (Ada 2012 feature)	195	AWK	168
AI-0152 (Ada 2012 feature)	204		
AI-0157 (Ada 2012 feature)	196		
AI-0158 (Ada 2012 feature)	194		
AI-0161 (Ada 2012 feature)	202		
AI-0162 (Ada 2012 feature)	195		
AI-0163 (Ada 2012 feature)	191		
AI-0171 (Ada 2012 feature)	204		
AI-0173 (Ada 2012 feature)	194		
AI-0176 (Ada 2012 feature)	191		
AI-0177 (Ada 2012 feature)	201		
AI-0178 (Ada 2012 feature)	198		
AI-0179 (Ada 2012 feature)	196		
AI-0181 (Ada 2012 feature)	193		
AI-0182 (Ada 2012 feature)	193		
AI-0183 (Ada 2012 feature)	192		
AI-0185 (Ada 2012 feature)	203		
AI-0188 (Ada 2012 feature)	196		
AI-0189 (Ada 2012 feature)	204		
AI-0190 (Ada 2012 feature)	204		
AI-0193 (Ada 2012 feature)	201		
AI-0194 (Ada 2012 feature)	202		
AI-0195 (Ada 2012 feature)	201		
AI-0196 (Ada 2012 feature)	197		
AI-0198 (Ada 2012 feature)	194		
AI-0199 (Ada 2012 feature)	195		
AI-0200 (Ada 2012 feature)	200		
AI-0201 (Ada 2012 feature)	199		
AI-0203 (Ada 2012 feature)	194		
AI-0205 (Ada 2012 feature)	198		
AI-0206 (Ada 2012 feature)	204		
AI-0207 (Ada 2012 feature)	197		
AI-0208 (Ada 2012 feature)	195		
AI-0210 (Ada 2012 feature)	204		
		B	
		Biased representation	125
		Big endian	59
		Bit	58
		bit ordering	128
		Bit ordering	76
		Bit_Order Clause	128
		Bit_Position	58
		Bounded Buffers	168
		Bounded errors	67
		Bounded-length strings	79
		Bubble sort	169
		byte ordering	129
		Byte swapping	169
		C	
		C streams, interfacing	177
		C Streams, Interfacing with Direct_IO	166
		C Streams, Interfacing with Sequential_IO	166
		C Streams, Interfacing with Stream_IO	167
		C Streams, Interfacing with Text_IO	167
		C Streams, Interfacing with Wide_Text_IO	167
		C Streams, Interfacing with Wide_Wide_Text_IO	168
		C++ interfacing	177
		C, interfacing with	80
		C_Pass_By_Copy	6
		Calendar	169
		Capturing Old values	63

Casing of External names	18
Casing utilities	169
CGI (Common Gateway Interface)	169
CGI (Common Gateway Interface) cookie support	170
CGI (Common Gateway Interface) debugging ...	170
Character handling (GNAT.Case_Util)	169
Character Sets	68
Check	6, 7
Check names, defining	7
Check pragma control	7
Check_Name	7
Checks, postconditions	37
Checks, preconditions	39
Checks, suppression of	71
Child Units	67
COBOL support	87
COBOL, interfacing with	82
Code_Address	58
Command line	170
Command line, argument removal	166
Command line, handling long command lines ...	166
Command line, response file	166
Comment	8
Common_Object	8
Compile_Time_Error	8
Compile_Time_Warning	8
Compiler Version	170
Compiler_Unit	9
Compiler_Version	58
Complete_Representation	9
Complex arithmetic accuracy	89
Complex elementary functions	88
Complex types	87
Complex_Representation	9
Component Clause	134
Component_Alignment	9
Component_Size	9
Component_Size Clause	127
Component_Size clauses	74
Component_Size_4	10
configuration pragma Ada_2012	191
Controlling assertions	7
Convention, effect on representation	138
Convention_Identifier	10
Conventions, synonyms	10
Conventions, typographical	2
Cookie support in CGI	170
CPP_Class	11
CPP_Constructor	11
CPP_Virtual	12
CPP_Vtable	12
CRC32	169
Current exception	170
Current time	176
Cyclic Redundancy Check	169

D

Debug	12
Debug pools	170
Debug_Policy	12
Debugging	170, 171
debugging with Initialize Scalars	24

Dec Ada 83	17
Dec Ada 83 casing compatibility	18
Decimal radix support	87
Decoding strings	170
Decoding UTF-8 strings	170
Default_Bit_Order	59
Deferring aborts	3
Defining check names	7
Detect_Blocking	12
Directory operations	171
Directory operations iteration	171
Discriminants, testing for	61
Distribution Systems Annex	186
Dump Memory	173
Duration'Small	70

E

Elab_Body	59
Elab_Spec	59
Elaborated	59
Elaboration control	12
Elaboration_Checks	12
Eliminate	13
Elimination of unused subprograms	13
Emax	59
Enabled	59
Enclosing_Entity	117
Encoding strings	171
Encoding UTF-8 strings	171
Endian	169
Entry queuing policies	85
Enum_Rep	59
Enum_Val	60
Enumeration representation clauses	75
Enumeration values	69
Environment entries	166
Epsilon	60
Error detection	67
Exception actions	171
Exception information	71
Exception retrieval	170
Exception traces	171
Exception, obtaining most recent	173
Exception_Information'	117
Exception_Message	117
Exception_Name	118
Exceptions, Pure	171
Export	79, 137
Export_Exception	13
Export_Function	14
Export_Object	15
Export_Procedure	15
Export_Value	16
Export_Valued_Procedure	16
Extend_System	17
Extensions_Allowed	17
External	18
External Names, casing	18
External_Name_Casing	18

F

Fast_Math	19
-----------------	----

Favor_Top_Level	19
FDL, GNU Free Documentation License.....	207
File.....	118
File locking.....	172
Finalize_Storage_Only	19
Fixed_Value.....	60
Float types.....	69
Float_Representation.....	20
Floating-Point Processor.....	172
Foreign threads.....	176
Forking a new process.....	185
Fortran, interfacing with.....	82

G

Get_Immediate.....	79
Get_Immediate	154
Get_Immediate, VxWorks.....	177
Global storage pool.....	178
GNAT Extensions.....	17
GNAT.Altivec ('g-altive.ads').....	168
GNAT.Altivec.Conversions ('g-altcon.ads') ..	168
GNAT.Altivec.Vector_Operations ('g-alveop.ads')	168
GNAT.Altivec.Vector_Types ('g-alvety.ads') ..	168
GNAT.Altivec.Vector_Views ('g-alvevi.ads') ..	168
GNAT.Array_Split ('g-arrspl.ads').....	168
GNAT.AWK ('g-awk.ads').....	168
GNAT.Bounded_Buffers ('g-boubuf.ads').....	168
GNAT.Bounded-Mailboxes ('g-boumai.ads').....	168
GNAT.Bubble_Sort ('g-bubsor.ads').....	169
GNAT.Bubble_Sort_A ('g-busora.ads').....	169
GNAT.Bubble_Sort_G ('g-busorg.ads').....	169
GNAT.Byte_Order_Mark ('g-byorma.ads').....	169
GNAT.Byte_Swapping ('g-bytswa.ads').....	169
GNAT.Calendar ('g-calend.ads').....	169
GNAT.Calendar.Time_IO ('g-catiio.ads').....	169
GNAT.Case_Util ('g-casuti.ads').....	169
GNAT.CGI ('g-cgi.ads').....	169
GNAT.CGI.Cookie ('g-cgicoo.ads').....	170
GNAT.CGI.Debug ('g-cgideb.ads').....	170
GNAT.Command_Line ('g-comlin.ads').....	170
GNAT.Compiler_Version ('g-comver.ads').....	170
GNAT.CRC32 ('g-crc32.ads').....	169
GNAT.Ctrl_C ('g-ctrl_c.ads').....	170
GNAT.Current_Exception ('g-curexc.ads').....	170
GNAT.Debug_Pools ('g-debpoo.ads').....	170
GNAT.Debug_Uutilities ('g-debuti.ads').....	170
GNAT.Decode_String ('g-decstr.ads').....	170
GNAT.Decode_UTF8_String ('g-deutst.ads') ..	170
GNAT.Directory_Operations ('g-dirope.ads') ..	171
GNAT.Directory_Operations.Iteration ('g-diopit.ads').....	171
GNAT.Dynamic_HTables ('g-dynhta.ads').....	171
GNAT.Dynamic_Tables ('g-dyntab.ads').....	171
GNAT.Encode_String ('g-encstr.ads').....	171
GNAT.Encode_UTF8_String ('g-enutst.ads') ..	171
GNAT.Exception_Actions ('g-excact.ads').....	171
GNAT.Exception_Traces ('g-exctra.ads').....	171
GNAT.Exceptions ('g-expect.ads').....	171
GNAT.Expect ('g-expect.ads').....	172
GNAT.Float_Control ('g-flocon.ads').....	172
GNAT.Heap_Sort ('g-heasor.ads').....	172
GNAT.Heap_Sort_A ('g-hesora.ads').....	172

GNAT.Heap_Sort_G ('g-hesorg.ads').....	172
GNAT.HTable ('g-htable.ads').....	172
GNAT.IO ('g-io.ads').....	172
GNAT.IO_Aux ('g-io_aux.ads').....	172
GNAT.Lock_Files ('g-locfil.ads').....	172
GNAT.MBBS_Discrete_Random ('g-mbdira.ads') ..	173
GNAT.MBBS_Float_Random ('g-mbflra.ads').....	173
GNAT.MD5 ('g-md5.ads').....	173
GNAT.Memory_Dump ('g-memdum.ads').....	173
GNAT.Most_Recent_Exception ('g-moreex.ads')	173
GNAT.OS_Lib ('g-os_lib.ads').....	173
GNAT.Perfect_Hash_Generators ('g-pehage.ads')	173
GNAT.Random_Numbers ('g-rannum.ads').....	173
GNAT.Regexp ('g-regexp.ads').....	173
GNAT.Registry ('g-regist.ads').....	173
GNAT.Regpat ('g-regpat.ads').....	174
GNAT.Secondary_Stack_Info ('g-sestin.ads') ..	174
GNAT.Semaphores ('g-semaph.ads').....	174
GNAT.Serial_Communications ('g-sercom.ads')	174
GNAT.SHA1 ('g-sha1.ads').....	174
GNAT.SHA224 ('g-sha224.ads').....	174
GNAT.SHA256 ('g-sha256.ads').....	174
GNAT.SHA384 ('g-sha384.ads').....	174
GNAT.SHA512 ('g-sha512.ads').....	174
GNAT.Signals ('g-signal.ads').....	174
GNAT.Sockets ('g-socket.ads').....	174
GNAT.Source_Info ('g-souinf.ads').....	174
GNAT.Spelling_Checker ('g-speche.ads').....	174
GNAT.Spelling_Checker_Generic ('g-spchge.ads')	175
GNAT.Spitbol ('g-spitbo.ads').....	175
GNAT.Spitbol.Patterns ('g-spipat.ads').....	175
GNAT.Spitbol.Table_Boolean ('g-sptabo.ads')	175
GNAT.Spitbol.Table_Integer ('g-sptain.ads')	175
GNAT.Spitbol.Table_VString ('g-sptavs.ads')	175
GNAT.SSE ('g-sse.ads').....	175
GNAT.SSE.Vector_Types ('g-ssvety.ads').....	175
GNAT.String_Split ('g-strspl.ads').....	175
GNAT.Strings ('g-string.ads').....	175
GNAT.Table ('g-table.ads').....	176
GNAT.Task_Lock ('g-tasloc.ads').....	176
GNAT.Threads ('g-thread.ads').....	176
GNAT.Time_Stamp ('g-timsta.ads').....	176
GNAT.Traceback ('g-traceb.ads').....	176
GNAT.Traceback.Symbolic ('g-trasym.ads') ..	176
GNAT.UTF_32 ('g-table.ads').....	176
GNAT.Wide_Spelling_Checker ('g-u3spch.ads')	176
GNAT.Wide_Spelling_Checker ('g-wispch.ads')	176
GNAT.Wide_String_Split ('g-wistsp.ads').....	176
GNAT.Wide_Wide_Spelling_Checker ('g-zspche.ads').....	177
GNAT.Wide_Wide_String_Split ('g-zistsp.ads')	177

H

Has_Access_Values	60
-------------------------	----

Has_Discriminants 61
 Hash functions 173
 Hash tables 171, 172
 Heap usage, implicit 77

I

IBM Packed Format 177
 Ident 20
 Image, of an address 177
 Img 61
 Implementation-dependent features 1
 Implemented 20
 Implicit_Packing 21
 Import 137
 Import_Exception 21
 Import_Function 22
 Import_Object 23
 Import_Procedure 23
 Import_Valued_Procedure 24
 Initialization, suppression of 48
 Initialize_Scalars 24
 Inline_Always 25
 Inline_Generic 25
 Input/Output facilities 172
 Integer maps 175
 Integer types 69
 Integer_Value 61
 Interface 25
 Interface_Name 26
 Interfaces 80
 Interfaces.C.Extensions ('i-cexten.ads') 177
 Interfaces.C.Streams ('i-cstrea.ads') 177
 Interfaces.CPP ('i-cpp.ads') 177
 Interfaces.Packed_Decimal ('i-pacdec.ads') 177
 Interfaces.VxWorks ('i-vxwork.ads') 177
 Interfaces.VxWorks.IO ('i-vxwoio.ads') 177
 Interfacing to C++ 12
 Interfacing to VxWorks 177
 Interfacing to VxWorks' I/O 177
 Interfacing with C++ 11, 12
 Interfacing, to C++ 177
 Interrupt 170
 Interrupt priority, maximum 61
 Interrupt support 84
 Interrupt_Handler 26
 Interrupt_State 26
 Interrupts 84
 Intrinsic operator 117
 Intrinsic Subprograms 117
 Invalid representations 5
 Invalid values 5
 Invalid_Value 61
 Invariant 27

K

Keep_Names 28

L

Large 61
 Latin_1 constants for Wide_Character 165
 Latin_1 constants for Wide_Wide_Character 165

Latin_9 constants for Character 165
 Latin_9 constants for Wide_Character 165
 Latin_9 constants for Wide_Wide_Character 166
 License 28
 License checking 28
 Line 118
 Link_With 29
 Linker_Alias 29
 Linker_Constructor 29
 Linker_Destructor 30
 Linker_Section 30
 Little endian 59
 Local storage pool 178
 Locking 176
 Locking Policies 85
 Locking using files 172
 Long_Float 31

M

Machine Code insertions 183
 Machine operations 83
 Machine_Attribute 31
 Machine_Size 61
 Mailboxes 168
 Main 31
 Main_Storage 31
 Mantissa 61
 Maps 175
 Max_Entry_Queue_Length 99
 Max_Interrupt_Priority 61
 Max_Priority 62
 Maximum_Alignment 62
 Maximum_Alignment attribute 121
 Mechanism_Code 62
 Memory allocation 177
 Memory corruption debugging 170
 Message Digest MD5 173
 Multidimensional arrays 70

N

Named assertions 6, 7
 Named numbers, representation of 66
 No_Body 32
 No_Calendar 99
 No_Default_Initialization 99
 No_Direct_Boolean_Operators 99
 No_Dispatching_Calls 100
 No_Dynamic_Attachment 100
 No_Elaboration_Code 103
 No_Entry_Calls_In_Elaboration_Code 100
 No_Entry_Queue 104
 No_Enumeration_Maps 100
 No_Exception_Handlers 101
 No_Exception_Propagation 101
 No_Exception_Registration 101
 No_Implementation_Attributes 104
 No_Implementation_Pragmas 104
 No_Implementation_Restrictions 104
 No_Implicit_Conditionals 101
 No_Implicit_Dynamic_Code 101
 No_Implicit_Loops 102
 No_Initialize_Scalars 102

No_Local_Protected_Objects.....	102
No_Protected_Type_Allocators.....	102
No_Return.....	32
No_Secondary_Stack.....	102
No_Select_Statements.....	102
No_Standard_Storage_Pools.....	102
No_Streams.....	102
No_Strict_Aliasing.....	32
No_Task_Attributes_Package.....	102
No_Task_Termination.....	103
No_Tasking.....	103
No_Wide_Characters.....	104
Normalize_Scalars.....	32
Null_Occurrence, testing for.....	166
Null_Parameter.....	62
Numerics.....	87

O

Object_Size.....	62, 125
Obsolescent.....	33
OpenVMS....	6, 10, 13, 15, 16, 17, 20, 21, 22, 31, 50, 57, 62
Operating System interface.....	173
Operations, on Address.....	76
Optimize_Alignment.....	34
Ordered.....	35
ordering, of bits.....	128
ordering, of bytes.....	129
Overlaying of objects.....	138

P

Package Interfaces.....	80
Package Interrupts.....	84
Package Task_Attributes.....	85
Packed Decimal.....	177
Packed types.....	72
Parameters, passing mechanism.....	62
Parameters, when passed by reference.....	63
Parsing.....	168
Partition communication subsystem.....	87
Partition interfacing functions.....	178
Passed_By_Reference.....	63
Passing by copy.....	6
Passing by descriptor.....	15, 16, 17, 22
Passive.....	36
Pattern matching.....	173, 174, 175
PCS.....	87
Persistent_BSS.....	36
Polling.....	37
Pool_Address.....	63
Portability.....	1
Postconditions.....	37
Postconditions.....	63
pragma Ada_2012.....	191
pragma Ordered.....	35
Pragma Pack (for arrays).....	132
Pragma Pack (for records).....	133
Pragma Pack (for type Natural).....	133
Pragma Pack warning.....	133
pragma Shared_Passive.....	186
Pragma, representation.....	121
Pragmas.....	67

Pre-elaboration requirements.....	85
Preconditions.....	39
Preemptive abort.....	86
Priority, maximum.....	62
Protected procedure handlers.....	84
Psect_Object.....	42
Pure.....	43
Pure packages, exceptions.....	171
Pure_Function.....	42

R

Random number generation.....	79, 173
Range_Length.....	64
Ravenscar.....	39
Read attribute.....	78
Real-Time Systems Annex compliance.....	185
Record Representation Clause.....	134
Record representation clauses.....	75
Ref.....	64
Regular expressions.....	173, 174
Removing command line arguments.....	166
Representation Clause.....	121
Representation clauses.....	71
Representation Clauses.....	121
Representation clauses, enumeration.....	75
Representation clauses, records.....	75
Representation of enums.....	59, 60
Representation of wide characters.....	178
Representation Pragma.....	121
Representation, determination of.....	139
Response file for command line.....	166
Restricted Run Time.....	42
Restriction_Warnings.....	43
Restrictions definitions.....	178
Result.....	64
Return values, passing mechanism.....	62
Rotate_Left.....	118
Rotate_Right.....	118
Run-time restrictions access.....	178

S

Safe_Emax.....	64
Safe_Large.....	64
Secondary Stack Info.....	174
Secure Hash Algorithm SHA-1.....	174
Secure Hash Algorithm SHA-224.....	174
Secure Hash Algorithm SHA-256.....	174
Secure Hash Algorithm SHA-384.....	174
Secure Hash Algorithm SHA-512.....	174
Semaphores.....	174
Serial_Communications.....	174
Sets of strings.....	175
Shared.....	43
Shared passive packages.....	186
SHARED_MEMORY_DIRECTORY environment variable.....	186
Shift_Left.....	118
Shift_Right.....	118
Shift_Right_Arithmetic.....	118
Short_Circuit_And_Or.....	43
Short_Descriptors.....	44
Signals.....	174
Simple I/O.....	172

Simple_Barriers 99
 Size Clause 122
 Size clauses 73
 Size for biased representation 125
 Size of **Address** 57
 Size, of objects 125
Size, setting for not-first subtype 66
 Size, used for objects 62
Size, VADS compatibility 53, 66
 Size, variant record objects 123
Small 64
 Sockets 174
 Sorting 169, 172
 Source Information 174
Source_File_Name 44
Source_File_Name_Project 45
Source_Location 119
Source_Reference 45
 Spawn capability 173
 Spell checking 174, 175, 176, 177
 SPITBOL interface 175
 SPITBOL pattern matching 175
 SPITBOL Tables 175
Static_Priorities 103
Static_Storage_Size 103
 Storage place attributes 76
 Storage pool, global 178
 Storage pool, local 178
Storage_Size Clause 122
Storage_Unit 10, 64
 Stream files 154
 Stream operations 178
 Stream oriented attributes 78
Stream_Convert 45
 String decoding 170
 String encoding 171
 String maps 175
 String splitter 175
 String stream operations 178
Stub_Type 64
Style_Checks 46
 Subprogram address 58
 Subtitle 47
Suppress 47
Suppress_All 47
Suppress_Exception_Locations 48
Suppress_Initialization 48
 Suppressing external name 15, 16, 17
 Suppressing initialization 48
 Suppression of checks 71
system, extending 17
System.Address_Image ('s-addima.ads') 177
System.Assertions ('s-assert.ads') 177
System.Memory ('s-memory.ads') 177
System.Partition_Interface ('s-parint.ads') 178
System.Pool_Global ('s-pooglo.ads') 178
System.Pool_Local ('s-pooloc.ads') 178
System.Restrictions ('s-restri.ads') 178
System.Rident ('s-rident.ads') 178
System.Strings.Stream_Ops ('s-ststop.ads') .. 178
System.Task_Info ('s-tasinf.ads') 178
System.Wch_Cnv ('s-wchcnv.ads') 178
System.Wch_Con ('s-wchcon.ads') 178

T

Table implementation 171, 176
Target_Name 65
 Task locking 176
 Task specific storage 49
 Task synchronization 176
Task_Attributes 85
Task_Info 48
Task_Info pragma 178
Task_Name 48
Task_Storage 49
 Tasking restrictions 86
Text_IO 172
Text_IO extensions 154
Text_IO for unbounded strings 155
Text_IO resetting standard files 167
Text_IO, extensions for unbounded strings 167
Text_IO, extensions for unbounded wide strings .. 167
Text_IO, extensions for unbounded wide wide strings 167
Thread_Local_Storage 49
 Threads, foreign 176
 Tick 65
 Time 169
 Time stamp 176
 Time, monotonic 86
Time_Slice 49
Title 50
 TLS (Thread Local Storage) 49
To_Address 65, 136
 Trace back facilities 176
 Traceback for Exception Occurrence 166
 trampoline 101
Type_Class 65
 Typographical conventions 2

U

UET_Address 65
Unbounded_String, IO support 167
Unbounded_String, **Text_IO** operations 155
Unbounded_Wide_String, IO support 167
Unbounded_Wide_Wide_String, IO support 167
 Unchecked conversion 77
 Unchecked deallocation 78
Unchecked_Union 50
Unconstrained_Array 65
 Unicode 170, 171
 Unicode categorization, **Wide_Character** 167
 Unicode categorization, **Wide_Wide_Character** .. 167
Unimplemented_Unit 50
 Unions in C 50
Universal_Aliasing 50
Universal_Data 51
Universal_Literal_String 66
 Unmodified 51
 Unreferenced 51
Unreferenced_Objects 52
Unreserve_All_Interrupts 52
Unrestricted_Access 66
Unsuppress 52
Use_VADS_Size 53
 UTF-8 170, 171
 UTF-8 representation 169

UTF-8 string decoding	170
UTF-8 string encoding	171

V

VADS_Size	66
Validity_Checks	53
Value_Size	66, 125
Variant record objects, size	123
Version, of compiler	170
Volatile	53
VxWorks, Get_Immediate	177
VxWorks, I/O interfacing	177
VxWorks, interfacing	177

W

Warnings	54
Warnings, unmodified	51
Warnings, unreferenced	51, 52
Wchar_T_Size	66
Weak_External	55

Wide character representations	169
Wide character codes	176
Wide character decoding	170
Wide character encoding	170, 171
Wide Character, Representation	178
Wide String, Conversion	178
Wide_Character_Encoding	55
Wide_String splitter	176
Wide_Text_IO resetting standard files	167
Wide_Wide_String splitter	177
Wide_Wide_Text_IO resetting standard files	168
Windows Registry	173
Word_Size	66
Write attribute	78

X

XDR representation	78
--------------------------	----

Z

Zero address, passing	62
-----------------------------	----

Table of Contents

About This Guide	1
What This Reference Manual Contains	1
Conventions	2
Related Information	2
1 Implementation Defined Pragas	3
Pragma Abort_Defer	3
Pragma Ada_83	3
Pragma Ada_95	3
Pragma Ada_05	4
Pragma Ada_2005	4
Pragma Ada_12	4
Pragma Ada_2012	4
Pragma Annotate	4
Pragma Assert	4
Pragma Assume_No_Invalid_Values	5
Pragma Ast_Entry	6
Pragma C_Pass_By_Copy	6
Pragma Check	6
Pragma Check_Name	7
Pragma Check_Policy	7
Pragma Comment	8
Pragma Common_Object	8
Pragma Compile_Time_Error	8
Pragma Compile_Time_Warning	8
Pragma Compiler_Unit	9
Pragma Complete_Representation	9
Pragma Complex_Representation	9
Pragma Component_Alignment	9
Pragma Convention_Identifier	10
Pragma CPP_Class	11
Pragma CPP_Constructor	11
Pragma CPP_Virtual	12
Pragma CPP_Vtable	12
Pragma Debug	12
Pragma Debug_Policy	12
Pragma Detect_Blocking	12
Pragma Elaboration_Checks	12
Pragma Eliminate	13
Pragma Export_Exception	13
Pragma Export_Function	14
Pragma Export_Object	15
Pragma Export_Procedure	15
Pragma Export_Value	16
Pragma Export_Valued_Procedure	16
Pragma Extend_System	17
Pragma Extensions_Allowed	17
Pragma External	18

Pragma External_Name_Casing	18
Pragma Fast_Math	19
Pragma Favor_Top_Level	19
Pragma Finalize_Storage_Only	19
Pragma Float_Representation	20
Pragma Ident	20
Pragma Implemented	20
Pragma Implicit_Packing	21
Pragma Import_Exception	21
Pragma Import_Function	22
Pragma Import_Object	23
Pragma Import_Procedure	23
Pragma Import_Valued_Procedure	24
Pragma Initialize_Scalars	24
Pragma Inline_Always	25
Pragma Inline_Generic	25
Pragma Interface	25
Pragma Interface_Name	26
Pragma Interrupt_Handler	26
Pragma Interrupt_State	26
Pragma Invariant	27
Pragma Keep_Names	28
Pragma License	28
Pragma Link_With	29
Pragma Linker_Alias	29
Pragma Linker_Constructor	29
Pragma Linker_Destructor	30
Pragma Linker_Section	30
Pragma Long_Float	31
Pragma Machine_Attribute	31
Pragma Main	31
Pragma Main_Storage	31
Pragma No_Body	32
Pragma No_Return	32
Pragma No_Strict_Aliasing	32
Pragma Normalize_Scalars	32
Pragma Obsolescent	33
Pragma Optimize_Alignment	34
Pragma Ordered	35
Pragma Passive	36
Pragma Persistent_BSS	36
Pragma Polling	37
Pragma Postcondition	37
Pragma Precondition	39
Pragma Profile (Ravenscar)	39
Pragma Profile (Restricted)	42
Pragma Psect_Object	42
Pragma Pure_Function	42
Pragma Restriction_Warnings	43
Pragma Shared	43
Pragma Short_Circuit_And_Or	43
Pragma Short_Descriptors	44
Pragma Source_File_Name	44
Pragma Source_File_Name_Project	45

Pragma Source_Reference	45
Pragma Stream_Convert	45
Pragma Style_Checks	46
Pragma Subtitle	47
Pragma Suppress	47
Pragma Suppress_All	47
Pragma Suppress_Exception_Locations	48
Pragma Suppress_Initialization	48
Pragma Task_Info	48
Pragma Task_Name	48
Pragma Task_Storage	49
Pragma Thread_Local_Storage	49
Pragma Time_Slice	49
Pragma Title	50
Pragma Unchecked_Union	50
Pragma Unimplemented_Unit	50
Pragma Universal_Aliasing	50
Pragma Universal_Data	51
Pragma Unmodified	51
Pragma Unreferenced	51
Pragma Unreferenced_Objects	52
Pragma Unreserve_All_Interrupts	52
Pragma Unsuppress	52
Pragma Use_VADS_Size	53
Pragma Validity_Checks	53
Pragma Volatile	53
Pragma Warnings	54
Pragma Weak_External	55
Pragma Wide_Character_Encoding	55
2 Implementation Defined Attributes	57
Abort_Signal	57
Address_Size	57
Asm_Input	57
Asm_Output	57
AST_Entry	57
Bit	58
Bit_Position	58
Compiler_Version	58
Code_Address	58
Default_Bit_Order	59
Elaborated	59
Elab_Body	59
Elab_Spec	59
Emax	59
Enabled	59
Enum_Rep	59
Enum_Val	60
Epsilon	60
Fixed_Value	60
Has_Access_Values	60
Has_Discriminants	61
Img	61
Integer_Value	61

Invalid_Value	61
Large	61
Machine_Size	61
Mantissa	61
Max_Interrupt_Priority	61
Max_Priority	62
Maximum_Alignment	62
Mechanism_Code	62
Null_Parameter	62
Object_Size	62
Old	63
Passed_By_Reference	63
Pool_Address	63
Range_Length	64
Ref.	64
Result	64
Safe_Emax	64
Safe_Large	64
Small	64
Storage_Unit	64
Stub_Type	64
Target_Name	65
Tick	65
To_Address	65
Type_Class	65
UET_Address	65
Unconstrained_Array	65
Universal_Literal_String	66
Unrestricted_Access	66
VADS_Size	66
Value_Size	66
Wchar_T_Size	66
Word_Size	66
3 Implementation Advice	67
1.1.3(20): Error Detection	67
1.1.3(31): Child Units	67
1.1.5(12): Bounded Errors	67
2.8(16): Pragmas	68
2.8(17-19): Pragmas	68
3.5.2(5): Alternative Character Sets	69
3.5.4(28): Integer Types	69
3.5.4(29): Integer Types	69
3.5.5(8): Enumeration Values	69
3.5.7(17): Float Types	70
3.6.2(11): Multidimensional Arrays	70
9.6(30-31): Duration'Small	70
10.2.1(12): Consistent Representation	70
11.4.1(19): Exception Information	71
11.5(28): Suppression of Checks	71
13.1 (21-24): Representation Clauses	71
13.2(6-8): Packed Types	72
13.3(14-19): Address Clauses	72
13.3(29-35): Alignment Clauses	73

13.3(42-43): Size Clauses	74
13.3(50-56): Size Clauses	74
13.3(71-73): Component Size Clauses	74
13.4(9-10): Enumeration Representation Clauses	75
13.5.1(17-22): Record Representation Clauses	75
13.5.2(5): Storage Place Attributes	76
13.5.3(7-8): Bit Ordering	76
13.7(37): Address as Private	76
13.7.1(16): Address Operations	76
13.9(14-17): Unchecked Conversion	77
13.11(23-25): Implicit Heap Usage	77
13.11.2(17): Unchecked De-allocation	78
13.13.2(17): Stream Oriented Attributes	78
A.1(52): Names of Predefined Numeric Types	78
A.3.2(49): <code>Ada.Characters.Handling</code>	79
A.4.4(106): Bounded-Length String Handling	79
A.5.2(46-47): Random Number Generation	79
A.10.7(23): <code>Get_Immediate</code>	79
B.1(39-41): <code>Pragma Export</code>	80
B.2(12-13): <code>Package Interfaces</code>	80
B.3(63-71): Interfacing with C	81
B.4(95-98): Interfacing with COBOL	82
B.5(22-26): Interfacing with Fortran	82
C.1(3-5): Access to Machine Operations	83
C.1(10-16): Access to Machine Operations	83
C.3(28): Interrupt Support	84
C.3.1(20-21): Protected Procedure Handlers	84
C.3.2(25): <code>Package Interrupts</code>	85
C.4(14): Pre-elaboration Requirements	85
C.5(8): <code>Pragma Discard_Names</code>	85
C.7.2(30): The Package <code>Task_Attributes</code>	85
D.3(17): Locking Policies	85
D.4(16): Entry Queuing Policies	86
D.6(9-10): Preemptive Abort	86
D.7(21): Tasking Restrictions	86
D.8(47-49): Monotonic Time	86
E.5(28-29): Partition Communication Subsystem	87
F(7): COBOL Support	87
F.1(2): Decimal Radix Support	87
G: Numerics	87
G.1.1(56-58): Complex Types	88
G.1.2(49): Complex Elementary Functions	89
G.2.4(19): Accuracy Requirements	89
G.2.6(15): Complex Arithmetic Accuracy	89
4 Implementation Defined Characteristics	91

5	Intrinsic Subprograms	117
5.1	Intrinsic Operators	117
5.2	Enclosing_Entity	117
5.3	Exception_Information	117
5.4	Exception_Message	117
5.5	Exception_Name	118
5.6	File	118
5.7	Line	118
5.8	Rotate_Left	118
5.9	Rotate_Right	118
5.10	Shift_Left	118
5.11	Shift_Right	118
5.12	Shift_Right_Arithmetic	118
5.13	Source_Location	119
6	Representation Clauses and Pragmas	121
6.1	Alignment Clauses	121
6.2	Size Clauses	122
6.3	Storage_Size Clauses	122
6.4	Size of Variant Record Objects	123
6.5	Biased Representation	125
6.6	Value_Size and Object_Size Clauses	125
6.7	Component_Size Clauses	127
6.8	Bit_Order Clauses	128
6.9	Effect of Bit_Order on Byte Ordering	129
6.10	Pragma Pack for Arrays	132
6.11	Pragma Pack for Records	133
6.12	Record Representation Clauses	134
6.13	Enumeration Clauses	135
6.14	Address Clauses	135
6.15	Effect of Convention on Representation	138
6.16	Determining the Representations chosen by GNAT	139
7	Standard Library Routines	143
8	The Implementation of Standard I/O	151
8.1	Standard I/O Packages	151
8.2	FORM Strings	152
8.3	Direct_IO	152
8.4	Sequential_IO	152
8.5	Text_IO	153
8.5.1	Stream Pointer Positioning	153
8.5.2	Reading and Writing Non-Regular Files	154
8.5.3	Get_Immediate	154
8.5.4	Treating Text_IO Files as Streams	154
8.5.5	Text_IO Extensions	154
8.5.6	Text_IO Facilities for Unbounded Strings	155
8.6	Wide_Text_IO	155
8.6.1	Stream Pointer Positioning	157
8.6.2	Reading and Writing Non-Regular Files	157
8.7	Wide_Wide_Text_IO	157
8.7.1	Stream Pointer Positioning	158
8.7.2	Reading and Writing Non-Regular Files	159

8.8	Stream_IO	159
8.9	Text Translation	159
8.10	Shared Files	159
8.11	Filenames encoding	160
8.12	Open Modes	160
8.13	Operations on C Streams	161
8.14	Interfacing to C Streams	163
9	The GNAT Library	165
9.1	Ada.Characters.Latin_9 ('a-chlat9.ads')	165
9.2	Ada.Characters.Wide_Latin_1 ('a-cwila1.ads')	165
9.3	Ada.Characters.Wide_Latin_9 ('a-cwila1.ads')	165
9.4	Ada.Characters.Wide_Wide_Latin_1 ('a-chzla1.ads')	165
9.5	Ada.Characters.Wide_Wide_Latin_9 ('a-chzla9.ads')	166
9.6	Ada.Command_Line.Environment ('a-colien.ads')	166
9.7	Ada.Command_Line.Remove ('a-colire.ads')	166
9.8	Ada.Command_Line.Response_File ('a-clrefi.ads')	166
9.9	Ada.Direct_IO.C_Streams ('a-diocst.ads')	166
9.10	Ada.Exceptions.Is_Null_Occurrence ('a-einuoc.ads')	166
9.11	Ada.Exceptions.Last_Chance_Handler ('a-elchha.ads')	166
9.12	Ada.Exceptions.Traceback ('a-extra.ads')	166
9.13	Ada.Sequential_IO.C_Streams ('a-siocst.ads')	166
9.14	Ada.Streams.Stream_IO.C_Streams ('a-ssicst.ads')	167
9.15	Ada.Strings.Unbounded.Text_IO ('a-suteio.ads')	167
9.16	Ada.Strings.Wide_Unbounded.Wide_Text_IO ('a-swuwti.ads')	167
9.17	Ada.Strings.Wide_Wide_Unbounded.Wide_Wide_Text_IO ('a-szuzti.ads')	167
9.18	Ada.Text_IO.C_Streams ('a-tiocst.ads')	167
9.19	Ada.Text_IO.Reset_Standard_Files ('a-tirsfi.ads')	167
9.20	Ada.Wide_Characters.Unicode ('a-wichun.ads')	167
9.21	Ada.Wide_Text_IO.C_Streams ('a-wtcstr.ads')	167
9.22	Ada.Wide_Text_IO.Reset_Standard_Files ('a-wrstfi.ads')	167
9.23	Ada.Wide_Wide_Characters.Unicode ('a-zchuni.ads')	167
9.24	Ada.Wide_Wide_Text_IO.C_Streams ('a-ztcstr.ads')	168
9.25	Ada.Wide_Wide_Text_IO.Reset_Standard_Files ('a-zrstfi.ads')	168
9.26	GNAT.Alivec ('g-alive.ads')	168
9.27	GNAT.Alivec.Conversions ('g-altcon.ads')	168
9.28	GNAT.Alivec.Vector_Operations ('g-alveop.ads')	168
9.29	GNAT.Alivec.Vector_Types ('g-alvety.ads')	168
9.30	GNAT.Alivec.Vector_Views ('g-alvevi.ads')	168
9.31	GNAT.Array_Split ('g-arrspl.ads')	168
9.32	GNAT.AWK ('g-awk.ads')	168
9.33	GNAT.Bounded_Buffers ('g-boubuf.ads')	168
9.34	GNAT.Bounded-Mailboxes ('g-boumai.ads')	168
9.35	GNAT.Bubble_Sort ('g-bubsor.ads')	169
9.36	GNAT.Bubble_Sort_A ('g-busora.ads')	169
9.37	GNAT.Bubble_Sort_G ('g-busorg.ads')	169
9.38	GNAT.Byte_Order_Mark ('g-byorma.ads')	169
9.39	GNAT.Byte_Swapping ('g-bytswa.ads')	169
9.40	GNAT.Calendar ('g-calend.ads')	169
9.41	GNAT.Calendar.Time_IO ('g-catiio.ads')	169
9.42	GNAT.CRC32 ('g-crc32.ads')	169
9.43	GNAT.Case_Util ('g-casuti.ads')	169
9.44	GNAT.CGI ('g-cgi.ads')	169
9.45	GNAT.CGI.Cookie ('g-cgicoo.ads')	170

9.46	GNAT.CGI.Debug ('g-cgideb.ads')	170
9.47	GNAT.Command_Line ('g-comlin.ads')	170
9.48	GNAT.Compiler_Version ('g-comver.ads')	170
9.49	GNAT.Ctrl_C ('g-ctrl_c.ads')	170
9.50	GNAT.Current_Exception ('g-curexc.ads')	170
9.51	GNAT.Debug_Pools ('g-debpoo.ads')	170
9.52	GNAT.Debug_Uutilities ('g-debuti.ads')	170
9.53	GNAT.Decode_String ('g-decstr.ads')	170
9.54	GNAT.Decode_UTF8_String ('g-deutst.ads')	170
9.55	GNAT.Directory_Operations ('g-dirope.ads')	171
9.56	GNAT.Directory_Operations.Iteration ('g-diopit.ads')	171
9.57	GNAT.Dynamic_HTables ('g-dynhta.ads')	171
9.58	GNAT.Dynamic_Tables ('g-dyntab.ads')	171
9.59	GNAT.Encode_String ('g-encstr.ads')	171
9.60	GNAT.Encode_UTF8_String ('g-enutst.ads')	171
9.61	GNAT.Exception_Actions ('g-excact.ads')	171
9.62	GNAT.Exception_Traces ('g-extra.ads')	171
9.63	GNAT.Exceptions ('g-expect.ads')	171
9.64	GNAT.Expect ('g-expect.ads')	172
9.65	GNAT.Float_Control ('g-flocon.ads')	172
9.66	GNAT.Heap_Sort ('g-heasor.ads')	172
9.67	GNAT.Heap_Sort_A ('g-hesora.ads')	172
9.68	GNAT.Heap_Sort_G ('g-hesorg.ads')	172
9.69	GNAT.HTable ('g-htable.ads')	172
9.70	GNAT.IO ('g-io.ads')	172
9.71	GNAT.IO_Aux ('g-io_aux.ads')	172
9.72	GNAT.Lock_Files ('g-locfil.ads')	172
9.73	GNAT.MBBS_Discrete_Random ('g-mbdira.ads')	173
9.74	GNAT.MBBS_Float_Random ('g-mbflra.ads')	173
9.75	GNAT.MD5 ('g-md5.ads')	173
9.76	GNAT.Memory_Dump ('g-memdum.ads')	173
9.77	GNAT.Most_Recent_Exception ('g-moreex.ads')	173
9.78	GNAT.OS_Lib ('g-os_lib.ads')	173
9.79	GNAT.Perfect_Hash_Generators ('g-pehage.ads')	173
9.80	GNAT.Random_Numbers ('g-rannum.ads')	173
9.81	GNAT.Regexp ('g-regexp.ads')	173
9.82	GNAT.Registry ('g-regist.ads')	173
9.83	GNAT.Regpat ('g-regpat.ads')	174
9.84	GNAT.Secondary_Stack_Info ('g-sestin.ads')	174
9.85	GNAT.Semaphores ('g-semaph.ads')	174
9.86	GNAT.Serial_Communications ('g-sercom.ads')	174
9.87	GNAT.SHA1 ('g-sha1.ads')	174
9.88	GNAT.SHA224 ('g-sha224.ads')	174
9.89	GNAT.SHA256 ('g-sha256.ads')	174
9.90	GNAT.SHA384 ('g-sha384.ads')	174
9.91	GNAT.SHA512 ('g-sha512.ads')	174
9.92	GNAT.Signals ('g-signal.ads')	174
9.93	GNAT.Sockets ('g-socket.ads')	174
9.94	GNAT.Source_Info ('g-souinf.ads')	174
9.95	GNAT.Spelling_Checker ('g-speche.ads')	174
9.96	GNAT.Spelling_Checker_Generic ('g-spchge.ads')	175
9.97	GNAT.Spitbol.Patterns ('g-spipat.ads')	175
9.98	GNAT.Spitbol ('g-spitbo.ads')	175
9.99	GNAT.Spitbol.Table_Boolean ('g-sptabo.ads')	175

9.100	GNAT.Spitbol.Table_Integer ('g-sptain.ads')	175
9.101	GNAT.Spitbol.Table_VString ('g-sptavs.ads')	175
9.102	GNAT.SSE ('g-sse.ads')	175
9.103	GNAT.SSE.Vector_Types ('g-ssvety.ads')	175
9.104	GNAT.Strings ('g-string.ads')	175
9.105	GNAT.String_Split ('g-strspl.ads')	175
9.106	GNAT.Table ('g-table.ads')	176
9.107	GNAT.Task_Lock ('g-tasloc.ads')	176
9.108	GNAT.Time_Stamp ('g-timsta.ads')	176
9.109	GNAT.Threads ('g-thread.ads')	176
9.110	GNAT.Traceback ('g-traceb.ads')	176
9.111	GNAT.Traceback.Symbolic ('g-trasym.ads')	176
9.112	GNAT.UTF_32 ('g-table.ads')	176
9.113	GNAT.Wide_Spelling_Checker ('g-u3spch.ads')	176
9.114	GNAT.Wide_Spelling_Checker ('g-wispch.ads')	176
9.115	GNAT.Wide_String_Split ('g-wistsp.ads')	176
9.116	GNAT.Wide_Wide_Spelling_Checker ('g-zspche.ads')	177
9.117	GNAT.Wide_Wide_String_Split ('g-zistsp.ads')	177
9.118	Interfaces.C.Extensions ('i-cexten.ads')	177
9.119	Interfaces.C.Streams ('i-cstrea.ads')	177
9.120	Interfaces.CPP ('i-cpp.ads')	177
9.121	Interfaces.Packed_Decimal ('i-pacdec.ads')	177
9.122	Interfaces.VxWorks ('i-vxwork.ads')	177
9.123	Interfaces.VxWorks.IO ('i-vxwoio.ads')	177
9.124	System.Address_Image ('s-addima.ads')	177
9.125	System.Assertions ('s-assert.ads')	177
9.126	System.Memory ('s-memory.ads')	177
9.127	System.Partition_Interface ('s-parint.ads')	178
9.128	System.Pool_Global ('s-pooglo.ads')	178
9.129	System.Pool_Local ('s-pooloc.ads')	178
9.130	System.Restrictions ('s-restri.ads')	178
9.131	System.Rident ('s-rident.ads')	178
9.132	System.Strings.Stream_Ops ('s-ststop.ads')	178
9.133	System.Task_Info ('s-tasinf.ads')	178
9.134	System.Wch_Cnv ('s-wchcnv.ads')	178
9.135	System.Wch_Con ('s-wchcon.ads')	178
10	Interfacing to Other Languages	179
10.1	Interfacing to C	179
10.2	Interfacing to C++	180
10.3	Interfacing to COBOL	180
10.4	Interfacing to Fortran	180
10.5	Interfacing to non-GNAT Ada code	180
11	Specialized Needs Annexes	181

12	Implementation of Specific Ada Features	183
12.1	Machine Code Insertions	183
12.2	GNAT Implementation of Tasking	185
12.2.1	Mapping Ada Tasks onto the Underlying Kernel Threads	185
12.2.2	Ensuring Compliance with the Real-Time Annex	185
12.3	GNAT Implementation of Shared Passive Packages	186
12.4	Code Generation for Array Aggregates	187
12.4.1	Static constant aggregates with static bounds	187
12.4.2	Constant aggregates with unconstrained nominal types	188
12.4.3	Aggregates with static bounds	188
12.4.4	Aggregates with non-static bounds	188
12.4.5	Aggregates in assignment statements	188
12.5	The Size of Discriminated Records with Default Discriminants	189
12.6	Strict Conformance to the Ada Reference Manual	189
13	Implementation of Ada 2012 Features	191
14	Obsolescent Features	205
14.1	pragma No_Run_Time	205
14.2	pragma Ravenscar	205
14.3	pragma Restricted_Run_Time	205
	GNU Free Documentation License	207
	ADDENDUM: How to use this License for your documents	213
	Index	215